



Center for Applied Scientific Computing (CASC), LLNL
Department of Mathematics and Statistics, University of New Mexico

This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344. This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes. LLNL-SM-660398

Copyright (c) 2013, Lawrence Livermore National Security, LLC. Produced at the Lawrence Livermore National Laboratory. Written by the XBraid team. LLNL-CODE-660355. All rights reserved.

This file is part of XBraid. Please see the COPYRIGHT and LICENSE file for the copyright notice, disclaimer, and the GNU Lesser General Public License. For support, post issues to the XBraid Github page.

XBraid is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License (as published by the Free Software Foundation) version 2.1 dated February 1999.

XBraid is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the IMPLIED WARRANTY OF MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the terms and conditions of the GNU General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111- 1307 USA

Contents

1 Abstract	2
2 XBraid Quickstart, User Advice, and License	2
3 Introduction	4
3.1 Overview of the XBraid Algorithm	4
3.1.1 Two-Grid Algorithm	9
3.1.2 Summary	9
3.2 Overview of the XBraid Code	10
3.2.1 Parallel decomposition and memory	11
3.2.2 Cycling and relaxation strategies	12
3.2.3 Overlapping communication and computation	13
3.2.4 Configuring the XBraid Hierarchy	13
3.2.5 Halting tolerance	14
3.2.6 Debugging XBraid	15
3.3 Computing Derivatives with XBraid_Adjoint	16
3.3.1 Short Introduction to Adjoint-based Sensitivity Computation	16
3.3.2 Overview of the XBraid_Adjoint Algorithm	17
3.3.3 Overview of the XBraid_Adjoint Code	18
3.4 Citing XBraid	20
3.5 Summary	20
4 Examples	21
4.1 The Simplest Example	21
4.1.1 Running XBraid for the Simplest Example	24
4.2 Some Advanced Features	25
4.3 Simplest example expanded	28
4.4 One-Dimensional Heat Equation	29
4.5 Two-Dimensional Heat Equation	29
4.5.1 Scaling Study with this Example	33
4.6 Simplest XBraid_Adjoint example	34
4.7 Optimization with the Simplest Example	38
4.8 A Simple Optimal Control Problem	39
4.9 Running and Testing XBraid	40
4.10 Fortran90 Interface, C++ Interface, Python Interface, and More Complicated Examples	40

5	Examples: compiling and running	41
6	Drivers: compiling and running	42
7	Coding Style	44
8	File naming conventions	44
9	Using Doxygen	44
10	Regression Testing	46
11	Module Index	50
11.1	Modules	50
12	Data Structure Index	51
12.1	Data Structures	51
13	File Index	52
13.1	File List	52
14	Module Documentation	52
14.1	Fortran 90 interface options	52
14.1.1	Detailed Description	53
14.1.2	Macro Definition Documentation	53
14.2	Error Codes	54
14.2.1	Detailed Description	54
14.2.2	Macro Definition Documentation	54
14.3	User-written routines	55
14.3.1	Detailed Description	55
14.3.2	Typedef Documentation	55
14.4	User-written routines for XBraid_Adjoint	60
14.4.1	Detailed Description	60

14.4.2 Typedef Documentation	60
14.5 User interface routines	62
14.5.1 Detailed Description	62
14.6 General Interface routines	63
14.6.1 Detailed Description	64
14.6.2 Macro Definition Documentation	64
14.6.3 Typedef Documentation	64
14.6.4 Function Documentation	64
14.7 Interface routines for XBraid_Adjoint	82
14.7.1 Detailed Description	82
14.7.2 Function Documentation	82
14.8 XBraid status structures	87
14.9 XBraid status routines	88
14.9.1 Detailed Description	88
14.9.2 Function Documentation	89
14.10 Inherited XBraid status routines	102
14.10.1 Detailed Description	103
14.10.2 Function Documentation	103
14.11 XBraid status macros	114
14.11.1 Detailed Description	114
14.11.2 Macro Definition Documentation	114
14.12 XBraid test routines	115
14.12.1 Detailed Description	115
14.12.2 Function Documentation	115

15 Data Structure Documentation	123
15.1 <code>_braid_Action</code> Struct Reference	123
15.1.1 Detailed Description	123
15.1.2 Field Documentation	123
15.2 <code>_braid_CommHandle</code> Struct Reference	125
15.2.1 Detailed Description	126
15.2.2 Field Documentation	126
15.3 <code>_braid_Core</code> Struct Reference	127
15.3.1 Detailed Description	129
15.3.2 Field Documentation	129
15.4 <code>_braid_Grid</code> Struct Reference	143
15.4.1 Detailed Description	143
15.4.2 Field Documentation	143
15.5 <code>_braid_Status</code> Struct Reference	146
15.5.1 Detailed Description	146
15.5.2 Field Documentation	147
15.6 <code>_braid_Tape</code> Struct Reference	147
15.6.1 Detailed Description	147
15.6.2 Field Documentation	147
15.7 <code>braid_AccessStatus</code> Struct Reference	148
15.7.1 Detailed Description	148
15.7.2 Field Documentation	148
15.8 <code>braid_BaseVector</code> Struct Reference	148
15.8.1 Detailed Description	148
15.8.2 Field Documentation	149
15.9 <code>braid_BufferStatus</code> Struct Reference	149
15.9.1 Detailed Description	149
15.9.2 Field Documentation	149

15.10	braid_CoarsenRefStatus Struct Reference	150
15.10.1	Detailed Description	150
15.10.2	Field Documentation	150
15.11	braid_ObjectiveStatus Struct Reference	150
15.11.1	Detailed Description	150
15.11.2	Field Documentation	150
15.12	braid_Optim Struct Reference	151
15.12.1	Detailed Description	151
15.12.2	Field Documentation	151
15.13	braid_StepStatus Struct Reference	153
15.13.1	Detailed Description	153
15.13.2	Field Documentation	154
15.14	braid_SyncStatus Struct Reference	154
15.14.1	Detailed Description	154
15.14.2	Field Documentation	154
15.15	braid_VectorBar Struct Reference	154
15.15.1	Detailed Description	155
15.15.2	Field Documentation	155
16	File Documentation	155
16.1	_braid.h File Reference	155
16.1.1	Detailed Description	157
16.1.2	Macro Definition Documentation	158
16.1.3	Function Documentation	161
16.1.4	Variable Documentation	171
16.2	adjoint.h File Reference	172
16.2.1	Detailed Description	172
16.2.2	Function Documentation	172

16.3	base.h File Reference	174
16.3.1	Detailed Description	175
16.3.2	Function Documentation	175
16.4	braid.h File Reference	186
16.4.1	Detailed Description	188
16.5	braid_defs.h File Reference	188
16.5.1	Detailed Description	188
16.5.2	Macro Definition Documentation	188
16.5.3	Typedef Documentation	189
16.6	braid_status.h File Reference	190
16.6.1	Detailed Description	192
16.6.2	Macro Definition Documentation	192
16.7	braid_test.h File Reference	194
16.7.1	Detailed Description	195
16.8	mpistubs.h File Reference	195
16.8.1	Detailed Description	195
16.9	status.h File Reference	195
16.9.1	Detailed Description	196
16.9.2	Macro Definition Documentation	196
16.9.3	Function Documentation	196
16.10	tape.h File Reference	199
16.10.1	Detailed Description	200
16.10.2	Enumeration Type Documentation	200
16.10.3	Function Documentation	201
16.11	util.h File Reference	203
16.11.1	Detailed Description	203
16.11.2	Function Documentation	203

1 Abstract

This package implements an optimal-scaling multigrid solver for the (non)linear systems that arise from the discretization of problems with evolutionary behavior. Typically, solution algorithms for evolution equations are based on a time-marching approach, solving sequentially for one time step after the other. Parallelism in these traditional time-integration techniques is limited to spatial parallelism. However, current trends in computer architectures are leading towards systems with more, but not faster, processors, i.e., clock speeds are stagnate. Therefore, faster overall runtimes must come from greater parallelism. One approach to achieve parallelism in time is with multigrid, but extending classical multigrid methods for elliptic operators to this setting is a significant achievement. In this software, we implement a non-intrusive, optimal-scaling time-parallel method based on multigrid reduction techniques. The examples in the package demonstrate optimality of our multigrid-reduction-in-time algorithm (MGRIT) for solving a variety of equations in two and three spatial dimensions. These examples can also be used to show that MGRIT can achieve significant speedup in comparison to sequential time marching on modern architectures.

It is **strongly recommended** that you also read [Parallel Time Integration with Multigrid](#) after reading the [Overview of the XBraid Algorithm](#). It is a more in depth discussion of the algorithm and associated experiments.

2 XBraid Quickstart, User Advice, and License

What is XBraid?

XBraid is a parallel-in-time software package. It implements an optimal-scaling multigrid solver for the (non)linear systems that arise from the discretization of problems with evolutionary behavior.

This code and associated algorithms are developed at [Lawrence Livermore National Laboratory](#), and at collaborating [academic institutions](#).

For our publication list, please go [here](#). There you will papers on XBraid and various application areas where XBraid has been applied, e.g., fluid dynamics, machine learning, parabolic equations, Burgers' equation, powergrid systems, etc.

About XBraid

Typically, solution algorithms for evolution equations are based on a time-marching approach, solving sequentially for one time step after the other. Parallelism in these traditional time-integration techniques is limited to spatial parallelism. However, current trends in computer architectures are leading towards systems with more, but not faster, processors, i.e., clock speeds are stagnate. Therefore, faster overall runtimes must come from greater parallelism. Our approach to achieve such parallelism in time is with multigrid.

In this software, we implement a non-intrusive, optimal-scaling time-parallel method based on multigrid reduction techniques (multigrid-reduction-in-time or MGRIT). A few important points about XBraid are as follows.

- The algorithm enables a scalable parallel-in-time approach by applying multigrid to the time dimension.

- It is designed to be nonintrusive. That is, users apply their existing sequential time-stepping code according to our interface, and then XBraid does the rest. Users have spent years, sometimes decades, developing the right time-stepping scheme for their problem. XBraid allows users to keep their schemes, but enjoy parallelism in the time dimension.
- XBraid solves exactly the same problem that the existing sequential time-stepping scheme does.
- XBraid is flexible, allowing for a variety of time stepping, relaxation, and temporal and spatial coarsening options.
- The full approximation scheme multigrid approach is used to accommodate nonlinear problems.
- XBraid written in MPI/C with C++, Fortran 90, and Python interfaces.
- XBraid is released under LGPL 2.1.

Documentation

- For examples of using XBraid, see the [examples/](#) and [drivers/](#) directories, and in particular [examples/ex-01-*](#)
- See the [release](#) page for links to precompiled documentation PDFs that go through, step-by-step, how to use XBraid.
- For tutorials, see the bottom of our [publications page](#).
- For citing XBraid, see [here](#).

Advice to Users

The field of parallel-in-time methods is in many ways under development, and success has been shown primarily for problems with some parabolic character. While there are ongoing projects (here and elsewhere) looking at varied applications such as hyperbolic problems, computational fluid dynamics, power grids, medical applications, and so on, expectations should take this fact into account. That being said, we strongly encourage new users to try our code for their application. Every new application has its own issues to address and this will help us to improve both the algorithm and the software. Please see our project publications website for our recent [publications](#) concerning some of these varied applications.

For bug reporting, please use the issue tracker here on Github. Please include as much relevant information as possible, including all the information in the "VERSION" file located in the bottom most XBraid directory. For compile and runtime problems, please also include the machine type, operating system, MPI implementation, compiler, and any error messages produced.

Building XBraid

- To specify the compilers, flags and options for your machine, edit `makefile.inc`. For now, we keep it simple and avoid using `configure` or `cmake`.
- To make the library, `libbraid.a`,

```
$ make
```

- To make the examples

```
$ make all
```

- The makefile lets you pass some parameters like debug with

```
$ make debug=yes
```

or

```
$ make all debug=yes
```

It would also be easy to add additional parameters, e.g., to compile with insure.

- To set compilers and library locations, look in makefile.inc where you can set up an option for your machine to define simple stuff like

```
CC = mpicc
MPICC = mpicc
MPICXX = mpiCC
LFLAGS = -lm
```

Meaning of the name

We chose the package name XBraid to stand for Time-Braid, where X is the first letter in the Greek word for time, Chronos. The algorithm braids together time-grids of different granularity in order to create a multigrid method and achieve parallelism in the time dimension.

License

This project is released under the LGPL v2.1 license. See files COPYRIGHT and LICENSE file for full details.

LLNL Release Number: LLNL-CODE-660355

3 Introduction

3.1 Overview of the XBraid Algorithm

The goal of XBraid is to solve a problem faster than a traditional time marching algorithm. Instead of sequential time marching, XBraid solves the problem iteratively by simultaneously updating a space-time solution guess over all time values. The initial solution guess can be anything, even a random function over space-time. The iterative updates to the solution guess are done by constructing a hierarchy of temporal grids, where the finest grid contains all of the time values for the simulation. Each subsequent grid is a coarser grid with fewer time values. The coarsest grid has a trivial number of time steps and can be quickly solved exactly. The effect is that solutions to the time marching problem on the coarser (i.e., cheaper) grids can be used to correct the original finest grid solution. Analogous to spatial multigrid, the coarse grid correction only *corrects* and *accelerates* convergence to the finest grid solution. The coarse grid does not need to represent an accurate time discretization in its own right. Thus, a problem with many time steps (thousands, tens of thousands or more) can be solved with 10 or 15 XBraid iterations, and the overall time to solution can be greatly sped up. However, this is achieved at the cost of more computational resources.

To understand how XBraid differs from traditional time marching, consider the simple linear advection equation, $u_t = -cu_x$. The next figure depicts how one would typically evolve a solution here with sequential time stepping. The initial condition is a wave, and this wave propagates sequentially across space as time increases.

XBraid instead begins with a solution guess over all of space-time, which for demonstration, we let be random. An XBraid iteration does




Figure 1 Sequential time stepping.

1. Relaxation on the fine grid, i.e., the grid that contains all of the desired time values. Relaxation is just a local application of the time stepping scheme, e.g., backward Euler.
2. Restriction to the first coarse grid, i.e., interpolate the problem to a grid that contains fewer time values, say every second or every third time value.
3. Relaxation on the first coarse grid
4. Restriction to the second coarse grid and so on...
5. When a coarse grid of trivial size (say 2 time steps) is reached, it is solved exactly.
6. The solution is then interpolated from the coarsest grid to the finest grid

One XBraid iteration is called a *cycle* and these cycles continue until the solution is accurate enough. This is depicted in the next figure, where only a few iterations are required for this simple problem.




Figure 2 XBraid iterations.

There are a few important points to make.

- The coarse time grids allow for global propagation of information across space-time with only one XBraid iteration. This is visible in the above figure by observing how the solution is updated from iteration 0 to iteration 1.
- Using coarser (cheaper) grids to correct the fine grid is analogous to spatial multigrid.

- Only a few XBraid iterations are required to find the solution over 1024 time steps. Therefore if enough processors are available to parallelize XBraid, we can see a speedup over traditional time stepping (more on this later).
- This is a simple example, with evenly spaced time steps. XBraid is structured to handle variable time step sizes and adaptive time step sizes.

To firm up our understanding, let's do a little math. Assume that you have a general system of ordinary differential equations (ODEs),

$$\mathbf{u}'(t) = \mathbf{f}(t, \mathbf{u}(t)), \quad \mathbf{u}(0) = \mathbf{u}_0, \quad t \in [0, T].$$

Next, let $t_i = i\delta t, i = 0, 1, \dots, N$ be a temporal mesh with spacing $\delta t = T/N$, and u_i be an approximation to $u(t_i)$. A general one-step time discretization is now given by

$$\begin{aligned} \mathbf{u}_0 &= \mathbf{g}_0 \\ \mathbf{u}_i &= \Phi_i(\mathbf{u}_{i-1}) + \mathbf{g}_i, \quad i = 1, 2, \dots, N. \end{aligned}$$

Traditional time marching would first solve for $i = 1$, then solve for $i = 2$, and so on. For linear time propagators $\{\Phi_i\}$, this can also be expressed as applying a direct solver (a forward solve) to the following system:

$$A\mathbf{u} \equiv \begin{pmatrix} I & & & & \\ -\Phi_1 & I & & & \\ & \ddots & \ddots & & \\ & & & -\Phi_N & I \end{pmatrix} \begin{pmatrix} \mathbf{u}_0 \\ \mathbf{u}_1 \\ \vdots \\ \mathbf{u}_N \end{pmatrix} = \begin{pmatrix} \mathbf{g}_0 \\ \mathbf{g}_1 \\ \vdots \\ \mathbf{g}_N \end{pmatrix} \equiv \mathbf{g}$$

or

$$A\mathbf{u} = \mathbf{g}.$$

This process is optimal and $O(N)$, but it is sequential. XBraid achieves parallelism in time by replacing this sequential solve with an optimal multigrid reduction iterative method¹ applied to only the time dimension. This approach is

- nonintrusive, in that it coarsens only in time and the user defines Φ . Thus, users can continue using existing time stepping codes by wrapping them into our framework.
- optimal and $O(N)$, but $O(N)$ with a higher constant than time stepping. Thus with enough computational resources, XBraid will outperform sequential time stepping.
- highly parallel


We now describe the two-grid process in more detail, with the multilevel analogue being a recursive application of the process. We also assume that Φ is constant for notational simplicity. XBraid coarsens in the time dimension with factor $m > 1$ to yield a coarse time grid with $N_\Delta = N/m$ points and time step $\Delta T = m\delta t$. The corresponding coarse grid problem,

$$A_\Delta = \begin{pmatrix} I & & & & \\ -\Phi_\Delta & I & & & \\ & \ddots & \ddots & & \\ & & & -\Phi_\Delta & I \end{pmatrix},$$

is obtained by defining coarse grid propagators $\{\Phi_\Delta\}$ which are at least as cheap to apply as the fine scale propagators $\{\Phi\}$. The matrix A_Δ has fewer rows and columns than A , e.g., if we are coarsening in time by 2, A_Δ has one half as many rows and columns.

This coarse time grid induces a partition of the fine grid into C-points (associated with coarse grid points) and F-points, as visualized next. C-points exist on both the fine and coarse time grid, but F-points exist only on the fine time scale.

¹ Ries, Manfred, Ulrich Trottenberg, and Gerd Winter. "A note on MGR methods." *Linear Algebra and its Applications* 49 (1983): 1-26.



Every multigrid algorithm requires a relaxation method and an approach to transfer values between grids. Our relaxation scheme alternates between so-called F-relaxation and C-relaxation as illustrated next. F-relaxation updates the F-point values $\{u_j\}$ on interval (T_i, T_{i+1}) by simply propagating the C-point value u_{m_i} across the interval using the time propagator $\{\Phi\}$. While this is a sequential process, each F-point interval update is independent from the others and can be computed in parallel. Similarly, C-relaxation updates the C-point value u_{m_i} based on the F-point value u_{m_i-1} and these updates can also be computed in parallel. This approach to relaxation can be thought of as line relaxation in space in that the residual is set to 0 for an entire time step.

The F updates are done simultaneously in parallel, as depicted next.




Figure 3 Update all F-point intervals in parallel, using the time propagator Φ .

Following the F sweep, the C updates are also done simultaneously in parallel, as depicted next.





Figure 4 Update all C-points in parallel, using the time propagator Φ .

- XBraid convergence will depend heavily on how well Φ_{Δ} approximates Φ^m , that is how well a time step size of $m\delta t = \Delta T$ will approximate m applications of the same time integrator for a time step size of δt . This is a subject of research, but this approximation need not capture fine scale behavior, which is instead captured by relaxation on the fine grid.
- The coarsest grid is solved exactly, i.e., sequentially, which can be a bottleneck for two-level methods like Parareal, ² but not for a multilevel scheme like XBraid where the coarsest grid is of trivial size.
- By forming the coarse grid to have the same sparsity structure and time stepper as the fine grid, the algorithm can recur easily and efficiently.
- Interpolation is ideal or exact, in that an application of interpolation leaves a zero residual at all F-points.
- The process is applied recursively until a trivially sized temporal grid is reached, e.g., 2 or 3 time points. Thus, the coarsening rate m determines how many levels there are in the hierarchy. For instance in this figure, a 3 level hierarchy is shown. Three levels are chosen because there are six time points, $m = 2$ and $m^2 < 6 \leq m^3$. If the coarsening rate had been $m = 4$ then there would only be two levels because there would be no more points to coarsen!




By default, XBraid will subdivide the time domain into evenly sized time steps. XBraid is structured to handle variable time step sizes and adaptive time step sizes.

3.2 Overview of the XBraid Code

XBraid is designed to run in conjunction with an existing application code that can be wrapped per our interface. This application code will implement some time marching simulation like fluid flow. Essentially, the user has to take their application code and extract a stand-alone time-stepping function Φ that can evolve a solution from one time value to another, regardless of time step size. After this is done, the XBraid code takes care of the parallelism in the time dimension.


XBraid

- is written in C and can easily interface with Fortran, C++, and Python
- uses MPI for parallelism
- self documents through comments in the source code and through *.md files
- functions and structures are prefixed by *braid*
 - User routines are prefixed by `braid_`
 - Developer routines are prefixed by `_braid_`



3.2.1 Parallel decomposition and memory

- XBraid decomposes the problem in parallel as depicted next. As you can see, traditional time stepping only stores one time step at a time, but only enjoys a spatial data decomposition and spatial parallelism. On the other hand, XBraid stores multiple time steps simultaneously and each processor holds a space-time chunk reflecting both the spatial and temporal parallelism.
- XBraid only handles temporal parallelism and is agnostic to the spatial decomposition. See [braid_Split](#) and [Commworld](#). Each processor owns a certain number of CF intervals of points. In the following figure, processor 1 and processor 2 each own 2 CF intervals. XBraid distributes intervals evenly on the finest grid.




- XBraid increases the parallelism significantly, but now several time steps need to be stored, requiring more memory. XBraid employs two strategies to address the increased memory costs.
 - First, one need not solve the whole problem at once. Storing only one space-time slab is advisable. That is, solve for as many time steps (say k time steps) as you have available memory for. Then move on to the next k time steps.
 - Second, XBraid provides support for storing only C-points. Whenever an F-point is needed, it is generated by F-relaxation. More precisely, only the red C-point time values in the previous figure are stored. Coarsening is usually aggressive with $m = 8, 16, 32, \dots$, so the storage requirements of XBraid are significantly reduced when compared to storing all of the time values.

Overall, the memory multiplier per processor when using XBraid is $O(1)$ if space-time coarsening (see [The Simplest Example](#)) is used and $O(\log_m N)$ for time-only coarsening. The time-only coarsening option is the default and requires no user-written spatial interpolation/restriction routines (which is the case for space-time coarsening). We note that the base of the logarithm is m , which can be quite large.


² Lions, J., Yvon Maday, and Gabriel Turinici. "A"parareal" in time discretization of PDE's." *Comptes Rendus de l'Academie des Sciences Series I Mathematics* 332.7 (2001): 661-668.

3.2.2 Cycling and relaxation strategies

There are two main cycling strategies available in XBraid, F- and V-cycles. These two cycles differ in how often and the order in which coarse levels are visited. A V-cycle is depicted next, and is a simple recursive application of the [Two-Grid Algorithm](#).



An F-cycle visits coarse grids more frequently and in a different order. Essentially, an F-cycle uses a V-cycle as the post-smoother, which is an expensive choice for relaxation. But, this extra work gives you a closer approximation to a two-grid cycle, and a faster convergence rate at the extra expense of more work. The effectiveness of a V-cycle as a relaxation scheme can be seen in [Figure 2](#), where one V-cycle globally propagates and *smooths* the error. The cycling strategy of an F-cycle is depicted next.



Next, we make a few points about F- versus V-cycles.

- One V-cycle iteration is cheaper than one F-cycle iteration.
- But, F-cycles often converge more quickly. For some test cases, this difference can be quite large. The cycle choice for the best time to solution will be problem dependent. See [Scaling Study with this Example](#) for a case study of cycling strategies.
- For exceptionally strong F-cycles, the option `braid_SetNFMGVcyc` can be set to use multiple V-cycles as relaxation. This has proven useful for some problems with a strongly advective nature.

The number of FC relaxation sweeps is another important algorithmic setting. Note that at least one F-relaxation sweep is always done on a level. A few summary points about relaxation are as follows.

- Using FCF, FCFCF, or FCFCFCF relaxation corresponds to passing `braid_SetNRelax` a value of 1, 2 or 3 respectively, and will result in an XBraid cycle that converges more quickly as the number of relaxations grows.
- But as the number of relaxations grows, each XBraid cycle becomes more expensive. The optimal relaxation strategy for the best time to solution will be problem dependent.
- However, a good first step is to try FCF on all levels (i.e., `braid_SetNRelax(core, -1, 1)`).
- A common optimization is to first set FCF on all levels (i.e., `braid_setnrelax(core, -1, 1)`), but then overwrite the FCF option on level 0 so that only F-relaxation is done on level 0, (i.e., `braid_setnrelax(core, 0, 1)`). Another strategy is to use F-relaxation on all levels together with F-cycles.
- See [Scaling Study with this Example](#) for a case study of relaxation strategies.


There is also a weighted relaxation option, which applies weighted-Jacobi at the C-points during the C-relaxation. Experiments with the 1D heat equation and 1D advection showed iteration gains of 10-25% for V-cycles when the experimentally optimal weight was used.

- For the heat equation, a weight of around 1.3 was experimentally optimal
- For the advection equation, weights between 1.4 and 1.8 were experimentally optimal
- Set this option with `braid_SetCRelaxWt`, which allows you to set a global relaxation weight, or an individual weight for each level. In general, under-relaxation (weight < 1.0) never improved performance, but over-relaxation (1.0 < weight < 2.0) often offered some improvement.

Last, `Parallel Time Integration with Multigrid` has a more in depth case study of cycling and relaxation strategies

3.2.3 Overlapping communication and computation

XBraid effectively overlaps communication and computation. The main computational kernel of XBraid is one relaxation sweep touching all the CF intervals. At the start of a relaxation sweep, each process first posts a non-blocking receive at its left-most point. It then carries out F-relaxation in each interval, starting with the right-most interval to send the data to the neighboring process as soon as possible. If each process has multiple CF intervals at this XBraid level, the strategy allows for complete overlap.



3.2.4 Configuring the XBraid Hierarchy

Some of the more basic XBraid function calls allow you to control aspects discussed here.

- `braid_SetFMG`: switches between using F- and V-cycles.
- `braid_SetMaxIter`: sets the maximum number of XBraid iterations
- `braid_SetCFactor`: sets the coarsening factor for any (or all levels)
- `braid_SetNRelax`: sets the number of CF-relaxation sweeps for any (or all levels)
- `braid_SetRelTol`, `braid_SetAbsTol`: sets the stopping tolerance
- `braid_SetMinCoarse`: sets the minimum possible coarse grid size
- `braid_SetMaxLevels`: sets the maximum number of levels in the XBraid hierarchy

3.2.5 Halting tolerance

Another important configuration aspect regards setting a residual halting tolerance. Setting a tolerance involves these three XBraid options:

1. [braid_PtFcnSpatialNorm](#)

This user-defined function carries out a spatial norm by taking the norm of a `braid_Vector`. A common choice is the standard Euclidean norm (2-norm), but many other choices are possible, such as an L2-norm based on a finite element space.

2. [braid_SetTemporalNorm](#)

This option determines how to obtain a global space-time residual norm. That is, this decides how to combine the spatial norms returned by [braid_PtFcnSpatialNorm](#) at each time step to obtain a global norm over space and time. It is this global norm that then controls halting.

There are three *tnorm* options supported by [braid_SetTemporalNorm](#). We let the summation index *i* be over all C-point values on the fine time grid, *k* refer to the current XBraid iteration, *r* be residual values, *space_time* norms be a norm over the entire space-time domain and *spatial_norm* be the user-defined spatial norm from [braid_PtFcnSpatialNorm](#). Thus, r_i is the residual at the *i*th C-point, and $r^{(k)}$ is the residual at the *k*th XBraid iteration. The three options are then defined as,

- *tnorm=1*: One-norm summation of spatial norms

$$\|r^{(k)}\|_{\text{space_time}} = \sum_i \|r_i^{(k)}\|_{\text{spatial_norm}}$$

If [braid_PtFcnSpatialNorm](#) is the one-norm over space, then this is equivalent to the one-norm of the global space-time residual vector.

- *tnorm=2*: Two-norm summation of spatial norms

$$\|r^{(k)}\|_{\text{space_time}} = \left(\sum_i \|r_i^{(k)}\|_{\text{spatial_norm}}^2 \right)^{1/2}$$

If [braid_PtFcnSpatialNorm](#) is the Euclidean norm (two-norm) over space, then this is equivalent to the Euclidean-norm of the global space-time residual vector.

- *tnorm=3*: Infinity-norm combination of spatial norms

$$\|r^{(k)}\|_{\text{space_time}} = \max_i \|r_i^{(k)}\|_{\text{spatial_norm}}$$

If [braid_PtFcnSpatialNorm](#) is the infinity-norm over space, then this is equivalent to the infinity-norm of the global space-time residual vector.

The default choice is *tnorm=2*

3. [braid_SetAbsTol](#), [braid_SetRelTol](#)

- If an absolute tolerance is used, then

$$\|r^{(k)}\|_{\text{space_time}} < \text{tol}$$

defines when to halt.

- If a relative tolerance is used, then

$$\frac{\|r^{(k)}\|_{\text{space_time}}}{\|r^{(0)}\|_{\text{space_time}}} < \text{tol}$$

defines when to halt. That is, the current *k*th residual is scaled by the initial residual before comparison to the halting tolerance. This is similar to typical relative residual halting tolerances used in spatial multigrid, but can be a dangerous choice in this setting.

Care should be practiced when choosing a halting tolerance. For instance, if a relative tolerance is used, then issues can arise when the initial guess is zero for large numbers of time steps. Taking the case where the initial guess (defined by `braid_PtFcnInit`) is 0 for all time values $t > 0$, the initial residual norm will essentially only be nonzero at the first time value,

$$\|r^{(0)}\|_{\text{space_time}} \approx \|r_1^{(k)}\|_{\text{spatial_norm}}$$

This will skew the relative halting tolerance, especially if the number of time steps increases, but the initial residual norm does not.

A better strategy is to choose an absolute tolerance that takes your space-time domain size into account, as in Section [Scaling Study with this Example](#), or to use an infinity-norm temporal norm option.

3.2.6 Debugging XBraid

Wrapping and debugging a code with XBraid typically follows a few steps.

- Test your wrapped functions with XBraid test functions, e.g., `braid_TestClone` or `braid_TestSum`.
- Set max levels to 1 (`braid_SetMaxLevels`) and run an XBraid simulation. You should get the exact same answer as that achieved with sequential time stepping. If you make sure that the time-grids used by XBraid and by sequential time stepping are bit-wise the same (by using the user-defined time grid option `braid_SetTimeGrid`), then the agreement of their solutions should be bit-wise the same.
- Continue with max levels equal to 1, but switch to two processors in time. Check that the answer again exactly matches sequential time stepping. This test checks that the information in `braid_Vector` is sufficient to correctly start the simulation on the second processor in time.
- Set max levels to 2, halting tolerance to 0.0 (`braid_SetAbsTol`), max iterations to 3 (`braid_SetMaxIter`) and turn on the option `braid_SetSeqSoln`. This will use the solution from sequential time-stepping as the initial guess for XBraid and then run 3 iterations. The residual should be exactly 0 each iteration, verifying the fixed-point nature of XBraid and a (hopefully!) correct implementation. The residual may be on the order of machine epsilon (or smaller). Repeat this test for multiple processors in time (and space if possible).
- A similar test turns on debug level printing by passing a print level of 3 to `braid_SetPrintLevel`. This will print out the residual norm at each C-point. XBraid with FCF-relaxation has the property that the exact solution is propagated forward two C-points each iteration. Thus, this should be reflected by numerically zero residual values for the first so many time points. Repeat this test for multiple processors in time (and space if possible).
- Finally, run some multilevel tests, making sure that the XBraid results are within the halting tolerance of the solutions generated by sequential time-stepping. Repeat this test for multiple processors in time (and space if possible).
- Congratulations! Your code is now verified.

3.3 Computing Derivatives with XBraid_Adjoint

XBraid_Adjoint has been developed in collaboration with the Scientific Computing group at TU Kaiserslautern, Germany, and in particular with Dr. Stefanie Guenther and Prof. Nicolas Gauger.

In many application scenarios, the ODE system is driven by some independent design parameters ρ . These can be any time-dependent or time-independent parameters that uniquely determine the solution of the ODE (e.g. a boundary condition, material coefficients, etc.). In a discretized ODE setting, the user's time-stepping routine might then be written as

$$u_i = \Phi_i(u_{i-1}, \rho), \quad \forall i = 1, \dots, N,$$

where the time-stepper Φ_i , which propagates a state u_{i-1} at a time t_{i-1} to the next time step at t_i , now also depends on the design parameters ρ . In order to quantify the simulation output for the given design, a real-valued objective function can then be set up that measures the quality of the ODE solution:

$$J(\mathbf{u}, \rho) \in \mathbb{R}.$$

Here, $\mathbf{u} = (u_0, \dots, u_N)$ denotes the space-time state solution for a given design.

XBraid_Adjoint is a consistent discrete time-parallel adjoint solver for XBraid which provides sensitivity information of the output quantity J with respect to the user-defined design parameters ρ . The ability to compute sensitivities can greatly improve and enhance the simulation tool, for example for solving

- Design optimization problems,
- Optimal control problems,
- Parameter estimation for validation and verification purposes,
- Error estimation,
- Uncertainty quantification techniques.

XBraid_Adjoint is non-intrusive with respect to the adjoint time-stepping scheme so that existing time-serial adjoint codes can be integrated easily through an extended user-interface.

3.3.1 Short Introduction to Adjoint-based Sensitivity Computation

Adjoint-based sensitivities compute the total derivative of J with respect to changes in the design parameters ρ by solving additional so-called adjoint equations. We will briefly introduce the idea in the following. You can skip this section, if you are familiar with adjoint sensitivity computation in general and move to [Overview of the XBraid_Adjoint Algorithm](#) immediately. Information on the adjoint method can be found in [Giles, Pierce, 2000]³ amongst many others.

Consider an augmented (so-called *Lagrange*) function

$$L(\mathbf{u}, \rho) = J(\mathbf{u}, \rho) + \bar{\mathbf{u}}^T A(\mathbf{u}, \rho)$$

where the discretized time-stepping ODE equations in

$$A(\mathbf{u}, \rho) := \begin{pmatrix} \Phi_1(u_0, \rho) - u_1 \\ \vdots \\ \Phi_N(u_{N-1}, \rho) - u_N \end{pmatrix}$$

³ Giles, M.B., Pierce, N.A.: "An introduction to the adjoint approach to design." Flow, Turbulence and Combustion 65(3), 393–415 (2000)

have been added to the objective function, and multiplied with so-called *adjoint* variables $\bar{\mathbf{u}} = (\bar{u}_1, \dots, \bar{u}_N)$. Since the added term is zero for all design and state variables that satisfy the discrete ODE equations, the total derivative of J and L with respect to the design match. Using the chain rule of differentiation, this derivative can be expressed as

$$\frac{dJ}{d\rho} = \frac{dL}{d\rho} = \frac{\partial J}{\partial \mathbf{u}} \frac{d\mathbf{u}}{d\rho} + \frac{\partial J}{\partial \rho} + \bar{\mathbf{u}}^T \left(\frac{\partial A}{\partial \mathbf{u}} \frac{d\mathbf{u}}{d\rho} + \frac{\partial A}{\partial \rho} \right)$$

where ∂ denotes partial derivatives – in contrast to the total derivative (i.e. the sensitivity) denoted by d .

When computing this derivative, the terms in red are the ones that are computationally most expensive. In fact, the cost for computing these sensitivities scale linearly with the number of design parameters, i.e. the dimension of ρ . These costs can grow quickly. For example, consider a finite differencing setting, where a re-computation of the entire space-time state would be necessary for each design variable, because a perturbation of the design must be computed in all the unit directions of the design space. In order to avoid these costs, the adjoint method aims to set the adjoint variable $\bar{\mathbf{u}}$ such that these red terms add up to zero in the above expression. Hence, if we solve first for

$$\left(\frac{\partial J}{\partial \mathbf{u}} \right)^T + \left(\frac{\partial A}{\partial \mathbf{u}} \right)^T \bar{\mathbf{u}} = 0$$

for the adjoint variable $\bar{\mathbf{u}}$, then the so-called *reduced gradient* of J , which is the transpose of the total derivative of J with respect to the design, is given by

$$\left(\frac{dJ}{d\rho} \right)^T = \left(\frac{\partial J}{\partial \rho} \right)^T + \left(\frac{\partial A}{\partial \rho} \right)^T \bar{\mathbf{u}}$$

The advantage of this strategy is, that in order to compute the sensitivity of J with respect to ρ , only one additional space-time equation (adjoint) for $\bar{\mathbf{u}}$ has to be solved, in addition to evaluating the partial derivatives. The computational cost for computing $dJ/d\rho$ therefore does not scale in this setting with the number of design parameters.

For the time-dependent discrete ODE problem, the adjoint equation from above reads

$$\text{unsteady adjoint:} \quad \bar{u}_i = \partial_{u_i} J(\mathbf{u}, \rho)^T + (\partial_{u_i} \Phi_{i+1}(u_i, \rho))^T \bar{u}_{i+1} \quad \forall i = N \dots, 1$$

using the terminal condition $u_{N+1} := 0$. The reduced gradient is given by

$$\text{reduced gradient:} \quad \left(\frac{\partial J}{\partial \rho} \right)^T = \partial_{\rho} J(\mathbf{u}, \rho)^T + \sum_{i=1}^N (\partial_{\rho} \Phi_i(u_{i-1}, \rho))^T \bar{u}_i$$

3.3.2 Overview of the XBraid_Adjoint Algorithm

The *unsteady adjoint* equations can in principle be solved “backwards in time” in a time-serial manner, starting from the terminal condition $\bar{u}_{N+1} = 0$. However, the parallel-in-time XBraid_Adjoint solver offers speedup by distributing the backwards-in-time phase onto multiple processors along the time domain. Its implementation is based on techniques of the reverse-mode of Automatic Differentiation applied to one primal XBraid iteration. To that end, each primal iteration is augmented by an objective function evaluation, followed by updates for the space-time adjoint variable $\bar{\mathbf{u}}$, as well as evaluation of the reduced gradient denoted by $\bar{\rho}$. In particular, the following so-called *piggy-back* iteration is performed:

1. **XBraid**: update the state and evaluate the objective function

$$\mathbf{u}^{(k+1)} \leftarrow \text{XBraid}(\mathbf{u}^{(k)}, \rho), \quad J \leftarrow J(\mathbf{u}^{(k)}, \rho)$$

2. **XBraid_Adjoint**: update the adjoint and evaluate the reduced gradient

$$\bar{\mathbf{u}}^{(k+1)} \leftarrow \text{XBraid_Adjoint}(\mathbf{u}^{(k)}, \bar{\mathbf{u}}^{(k)}, \rho), \quad \bar{\rho} \leftarrow \left(\frac{dJ(\mathbf{u}^{(k)}, \rho)}{d\rho} \right)^T$$

Each `XBraid_Adjoint` iteration moves backwards through the primal `XBraid` multigrid cycle. It collects local partial derivatives of the elemental `XBraid` operations in reverse order and concatenates them using the chain rule of differentiation. This is the basic idea of the reverse mode of Automatic Differentiation (AD). This yields a consistent discrete time-parallel adjoint solver that inherits the parallel scaling properties of the primal `XBraid` solver.

Further, `XBraid_Adjoint` is non-intrusive for existing adjoint methods based on sequential time marching schemes. It adds additional user-defined routines to the primal `XBraid` interface, in order to define the propagation of sensitivities of the forward time stepper backwards-in-time and the evaluation of partial derivatives of the local objective function at each time step. In cases where a time-serial unsteady adjoint solver is already available, this backwards time stepping capability can be easily wrapped according to the adjoint user interface with little extra coding.

The adjoint solve in the above piggy-back iteration converges at the same convergence rate as the primal state variables. However since the adjoint equations depend on the state solution, the adjoint convergence will slightly lag behind the convergence of the state. More information on convergence results and implementational details for `XBraid_Adjoint` can be found in [Gunther, Gauger, Schroder, 2017].⁴

3.3.3 Overview of the `XBraid_Adjoint` Code

`XBraid_Adjoint` offers a non-intrusive approach for time-parallelization of existing time-serial adjoint codes. To that end, an extended user-interface allows the user to wrap their existing code for evaluating the objective function and performing a backwards-in-time adjoint step into routines according to the `XBraid_Adjoint` interface.

3.3.3.1 Objective function evaluation

The user-interface for `XBraid_Adjoint` allows for objective functions of the following type:

$$J = F \left(\int_{t_0}^{t_1} f(u(t), \rho) dt \right).$$

This involves a time-integral part of some time-dependent quantity of interest f as well as a *postprocessing* function F . The time-interval boundaries t_0, t_1 can be set using the options `braid_SetTStartObjective` and `braid_SetTStopObjective`, otherwise the entire time domain will be considered. Note that these options can be used for objective functions that are only evaluated at one specific time instance by setting $t_0 = t_1$ (e.g. in cases where only the last time step is of interest). The postprocessing function F offers the possibility to further modify the time-integral, e.g. for setting up a tracking-type objective function (subtract a target value and square), or for adding relaxation or penalty terms. While defining f is mandatory for `XBraid_Adjoint`, the postprocessing routine F is optional and is passed to `XBraid_Adjoint` through the optional `braid_SetPostprocessObjective` and `braid_SetPostprocessObjective_diff` routines. `XBraid_Adjoint` will perform the time-integration by summing up the f evaluations in the given time-domain

$$I \leftarrow \sum_{i=i_0}^{i_1} f(u_i, \rho)$$

followed by a call to the postprocessing function F , if set:

$$J \leftarrow F(I, \rho).$$

Note that any integration rule for computing I , e.g. for scaling contributions from $f()$, must be done by the user.

⁴ Günther, S., Gauger, N.R. and Schroder, J.B. "A Non-Intrusive Parallel-in-Time Adjoint Solver with the `XBraid` Library." *Computing and Visualization in Science*, Springer, (accepted), (2017)

Partial derivatives of user-routines

The user needs to provide the derivatives of the time-stepper Φ and function evaluation f (and potentially F) for $X \leftarrow$ Braid_Adjoint. Those are provided in terms of transposed matrix-vector products in the following way:

1. Derivatives of the objective function J :

- **Time-dependent part f** : The user provides a routine that evaluates the following transposed partial derivatives of f multiplied with the scalar input \bar{F} :

$$\bar{u}_i \leftarrow \left(\frac{\partial f(u_i, \rho)}{\partial u_i} \right)^T \bar{F}$$

$$\bar{\rho} \leftarrow \bar{\rho} + \left(\frac{\partial f(u_i, \rho)}{\partial \rho} \right)^T \bar{F}$$

The scalar input \bar{F} equals 1.0, if no postprocessing function F has been set.

- **Postprocessing F** : If the postprocessing routine has been set, the user needs to provide it's transposed partial derivatives in the following way:

$$\bar{F} \leftarrow \frac{\partial F(I, \rho)}{\partial I}$$

$$\bar{\rho} \leftarrow \bar{\rho} + \frac{\partial F(I, \rho)}{\partial \rho}$$

- #### 2. Derivatives of the time-stepper Φ_i :
- The user provides a routine that computes the following transposed partial derivatives of Φ_i multiplied with the adjoint input vector \bar{u}_i :

$$\bar{u}_i \leftarrow \left(\frac{\partial \Phi(u_i, \rho)}{\partial u_i} \right)^T \bar{u}_i$$

$$\bar{\rho} \leftarrow \bar{\rho} + \left(\frac{\partial \Phi(u_i, \rho)}{\partial \rho} \right)^T \bar{u}_i$$

Note that the partial derivatives with respect to ρ always *update* the reduced gradient $\bar{\rho}$ instead of overwriting it (i.e. they are a plus-equal operation, $+ =$). Therefore, the gradient needs to be reset to zero before each iteration of $X \leftarrow$ Braid_Adjoint, which is taken care of by XBraid_Adjoint calling an additional user-defined routine [braid_PtFcnResetGradient](#).

Depending on the nature of the design variables, it is necessary to gather gradient information in $\bar{\rho}$ from all time-processors after XBraid_Adjoint has finished. It is the user's responsibility to do that, if needed, e.g. through a call to `MPI_Allreduce`.

Halting tolerance

Similar to the primal XBraid algorithm, the user can choose a halting tolerance for XBraid_Adjoint which is based on the adjoint residual norm. An absolute tolerance ([braid_SetAbsTolAdjoint](#))

$$\|\bar{\mathbf{u}}^{(k)} - \bar{\mathbf{u}}^{(k-1)}\|_{\text{space_time}} < \text{tol_adjoint}$$

or a relative tolerance ([braid_SetRelTolAdjoint](#))

$$\frac{\|\bar{\mathbf{u}}^{(k)} - \bar{\mathbf{u}}^{(k-1)}\|_{\text{space_time}}}{\|\bar{\mathbf{u}}^{(1)} - \bar{\mathbf{u}}^{(0)}\|_{\text{space_time}}} < \text{tol_adjoint}$$

can be chosen.

Finite Difference Testing

You can verify the gradient computed from `XBraid_Adjoint` using Finite Differences. Let e_i denote the i -th unit vector in the design space, then the i -th entry of the gradient should match with

$$i\text{-th Finite Difference: } \frac{J(\mathbf{u}_{\rho+he_i}, \rho + he_i) - J(\mathbf{u}, \rho)}{h}$$

for a small perturbation $h > 0$. Here, $\mathbf{u}_{\rho+he_i}$ denotes the new state solution for the perturbed design variable. Keep in mind, that round-off errors have to be considered when computing the Finite Differences for very small perturbations $h \rightarrow 0$. Hence, you should vary the parameter to find the best fit.

In order to save some computational work while computing the perturbed objective function value, `XBraid_Adjoint` can run in `ObjectiveOnly` mode, see `braid_SetObjectiveOnly`. When in this mode, `XBraid_Adjoint` will only solve the ODE system and evaluate the objective function, without actually computing its derivative. This option might also be useful within an optimization framework e.g. for implementing a line-search procedure.

Getting started

- Look at the simple example [Simplest XBraid_Adjoint example](#) in order to get started. This example is in `examples/ex-01-adjoint.c`, which implements `XBraid_Adjoint` sensitivity computation for a scalar ODE.

3.4 Citing XBraid

To cite `XBraid`, please state in your text the version number from the `VERSION` file, and please cite the project website in your bibliography as

[1] `XBraid`: Parallel multigrid in time. <http://llnl.gov/casc/xbraid>.

The corresponding BibTeX entry is

```
@misc{xbraid-package,
  title = {{XB}raid: Parallel multigrid in time},
  howpublished = {\url{http://llnl.gov/casc/xbraid}}
}
```

3.5 Summary

- `XBraid` applies multigrid to the time dimension.
 - This exposes concurrency in the time dimension.
 - The potential for speedup is large, 10x, 100x, ...
- This is a non-intrusive approach, with an unchanged time discretization defined by user.
- Parallel time integration is only useful beyond some scale. This is evidenced by the experimental results below. For smaller numbers of cores sequential time stepping is faster, but at larger core counts `XBraid` is much faster.
- The more time steps that you can parallelize over, the better your speedup will be.
- `XBraid` is optimal for a variety of parabolic problems (see the examples directory).
- `XBraid_Adjoint` provides time-parallel adjoint-based sensitivities of output quantities with respect to user-defined design variables
 - It is non-intrusive with respect to existing adjoint time-marching schemes
 - It inherits parallel scaling properties from `XBraid`

4 Examples

This section is the chief *tutorial* of XBraid, illustrating how to use it through a sequence of progressively more sophisticated examples.

4.1 The Simplest Example

User Defined Structures and Wrappers

The user must wrap their existing time stepping routine per the XBraid interface. To do this, the user must define two data structures and some wrapper routines. To make the idea more concrete, we now give these function definitions from `examples/ex-01`, which implements a scalar ODE,

$$u_t = \lambda u.$$

The two data structures are:

1. **App:** This holds a wide variety of information and is *global* in that it is passed to every function. This structure holds everything that the user will need to carry out a simulation. Here for illustration, this is just an integer storing a processor's rank.

```
typedef struct _braid_App_struct
{
    int      rank;
} my_App;
```

2. **Vector:** this defines (roughly) a state vector at a certain time value. It could also contain any other information related to this vector which is needed to evolve the vector to the next time value, like mesh information. Here, the vector is just a scalar double.

```
typedef struct _braid_Vector_struct
{
    double value;
} my_Vector;
```

The user must also define a few wrapper routines. Note, that the *app* structure is the first argument to every function.

1. **Step:** This function tells XBraid how to take a time step, and is the core user routine. The user must advance the vector u from time $tstart$ to time $tstop$. Note how the time values are given to the user through the *status* structure and associated *Get* routine. **Important note:** the g_i function from [Overview of the XBraid Algorithm](#) must be incorporated into *Step*, so that the following equation is solved by default.

$$\Phi(u_i) = 0.$$

The $ustop$ parameter serves as an approximation to the solution at time $tstop$ and is not needed here. It can be useful for implicit schemes that require an initial guess for a linear or nonlinear solver. The use of $fstop$ is an advanced parameter (not required) and forms the the right-hand side of the nonlinear problem on the given time grid. This value is only nonzero when providing a residual with [braid_SetResidual](#). More information on how to use this optional feature is given below.

Here advancing the solution just involves the scalar λ .

```

int
my_Step(braid_App      app,
        braid_Vector  ustop,
        braid_Vector  fstop,
        braid_Vector  u,
        braid_StepStatus status)
{
    double tstart;          /* current time */
    double tstop;          /* evolve to this time*/
    braid_StepStatusGetTstartTstop(status, &tstart, &tstop);

    /* Use backward Euler to propagate solution */
    (u->value) = 1./(1. + tstop-tstart)*(u->value);

    return 0;
}

```

2. **Init:** This function tells XBraid how to initialize a vector at time t . Here that is just allocating and setting a scalar on the heap.

```

int
my_Init(braid_App      app,
        double         t,
        braid_Vector *u_ptr)
{
    my_Vector *u;

    u = (my_Vector *) malloc(sizeof(my_Vector));
    if (t == 0.0) /* Initial condition */
    {
        (u->value) = 1.0;
    }
    else /* All other time points set to arbitrary value */
    {
        (u->value) = 0.456;
    }
    *u_ptr = u;

    return 0;
}

```

3. **Clone:** This function tells XBraid how to clone a vector into a new vector.

```

int
my_Clone(braid_App      app,
         braid_Vector  u,
         braid_Vector *v_ptr)
{
    my_Vector *v;

    v = (my_Vector *) malloc(sizeof(my_Vector));
    (v->value) = (u->value);
    *v_ptr = v;

    return 0;
}

```

4. **Free:** This function tells XBraid how to free a vector.

```

int
my_Free(braid_App      app,
        braid_Vector u)
{
    free(u);

    return 0;
}

```

5. **Sum:** This function tells XBraid how to sum two vectors (AXPY operation).

```
int
my_Sum(braid_App    app,
       double      alpha,
       braid_Vector x,
       double      beta,
       braid_Vector y)
{
    (y->value) = alpha*(x->value) + beta*(y->value);

    return 0;
}
```

6. **SpatialNorm:** This function tells XBraid how to take the norm of a *braid_Vector* and is used for halting. This norm is only over space. A common norm choice is the standard Euclidean norm, but many other choices are possible, such as an L2-norm based on a finite element space. The norm choice should be based on what makes sense for your problem. How to accumulate spatial norm values to obtain a global space-time residual norm for halting decisions is controlled by [braid_SetTemporalNorm](#).

```
int
my_SpatialNorm(braid_App    app,
               braid_Vector u,
               double        *norm_ptr)
{
    double dot;

    dot = (u->value)*(u->value);
    *norm_ptr = sqrt(dot);

    return 0;
}
```

7. **Access:** This function allows the user access to XBraid and the current solution vector at time t . This is most commonly used to print solution(s) to screen, file, etc... The user defines what is appropriate output. Notice how you are told the time value t of the vector u and even more information in *astatus*. This lets you tailor the output to only certain time values at certain XBraid iterations. Querying *astatus* for such information is done through [braid_AccessStatusGet**\(..\)](#) routines.

The frequency of the calls to *access* is controlled through [braid_SetAccessLevel](#). For instance, if *access_level* is set to 2, then *access* is called every XBraid iteration and on every XBraid level. In this case, querying *astatus* to determine the current XBraid level and iteration will be useful. This scenario allows for even more detailed tracking of the simulation. The default *access_level* is 1 and gives the user access only after the simulation ends and only on the finest time-grid.

Eventually, this routine will allow for broader access to XBraid and computational steering.

See [examples/ex-03](#) and [drivers/drive-diffusion](#) for more advanced uses of the *access* function. In [drive-diffusion](#), *access* is used to write solution vectors to a GLVIS visualization port, and [ex-03](#) uses *access* to write to .vtu files.

```
int
my_Access(braid_App    app,
          braid_Vector u,
          braid_AccessStatus astatus)
{
    int    index;
    char    filename[255];
    FILE    *file;

    braid_AccessStatusGetTIndex(astatus, &index);
    sprintf(filename, "%s.%04d.%03d", "ex-01.out", index, app->rank);
}
```

```

    file = fopen(filename, "w");
    fprintf(file, "%.14e\n", (u->value));
    fflush(file);
    fclose(file);

    return 0;
}

```

8. **BufSize, BufPack, BufUnpack:** These three routines tell XBraid how to communicate vectors between processors. *BufPack* packs a vector into a `void * buffer` for MPI and then *BufUnPack* unpacks the `void * buffer` into a vector. Here doing that for a scalar is trivial. *BufSize* computes the upper bound for the size of an arbitrary vector.

Note how *BufPack* also sets the size in *bstatus*. This value is optional, but if set it should be the exact number of bytes packed, while *BufSize* should provide only an upper-bound on a possible buffer size. This flexibility allows for the buffer to be allocated the fewest possible times, but smaller messages to be sent when needed. For instance, this occurs when using variable spatial grid sizes. **To avoid MPI issues, it is very important that BufSize be pessimistic, provide an upper bound, and return the same value across processors.**

In general, the buffer should be self-contained. The receiving processor should be able to pull all necessary information from the buffer in order to properly interpret and unpack the buffer.

```

int
my_BufSize(braid_App      app,
           int            *size_ptr,
           braid_BufferStatus bstatus)
{
    *size_ptr = sizeof(double);
    return 0;
}

int
my_BufPack(braid_App      app,
           braid_Vector   u,
           void           *buffer,
           braid_BufferStatus bstatus)
{
    double *dbuffer = buffer;

    dbuffer[0] = (u->value);
    braid_BufferStatusSetSize( bstatus, sizeof(double) );

    return 0;
}

int
my_BufUnpack(braid_App      app,
             void           *buffer,
             braid_Vector   *u_ptr,
             braid_BufferStatus bstatus)
{
    double *dbuffer = buffer;
    my_Vector *u;

    u = (my_Vector *) malloc(sizeof(my_Vector));
    (u->value) = dbuffer[0];
    *u_ptr = u;

    return 0;
}

```

4.1.1 Running XBraid for the Simplest Example

A typical flow of events in the *main* function is to first initialize the *app* structure.

```
/* set up app structure */
app = (my_App *) malloc(sizeof(my_App));
(app->rank) = rank;
```

Then, the data structure definitions and wrapper routines are passed to XBraid. The core structure is used by XBraid for internal data structures.

```
braid_Core core;
braid_Init(MPI_COMM_WORLD, comm, tstart, tstop, ntime, app,
          my_Step, my_Init, my_Clone, my_Free, my_Sum, my_SpatialNorm,
          my_Access, my_BufSize, my_BufPack, my_BufUnpack, &core);
```

Then, XBraid options are set.

```
braid_SetPrintLevel( core, 1);
braid_SetMaxLevels(core, max_levels);
braid_SetAbsTol(core, tol);
braid_SetCFactor(core, -1, cfactor);
```

Then, the simulation is run.

```
braid_Drive(core);
```

Then, we clean up.

```
braid_Destroy(core);
```

Finally, to run ex-01, type


```
ex-01
```

4.2 Some Advanced Features

We now give an overview of some *optional* advanced features that will be implemented in some of the following examples.

1. **SCoarsen, SRestrict:** These are advanced options that allow for coarsening in space while you coarsen in time. This is useful for maintaining stable explicit schemes on coarse time scales and is not needed here. See `examples/ex-02` for a simple example of this feature, and then `drivers/drive-diffusion` and `drivers/drive-diffusion-2D` for more advanced examples of this feature.

These functions allow you to vary the spatial mesh size on XBraid levels as depicted here where the spatial and temporal grid sizes are halved every level.



2. **Residual:** A user-defined residual can be provided with the function `braided_SetResidual` and can result in substantial computational savings, as explained below. However to use this advanced feature, one must first understand how XBraid measures the residual. XBraid computes residuals of this equation,

$$A_i(u_i, u_{i-1}) = f_i,$$

where $A_i(\cdot)$ evaluates one block-row of the the global space-time operator A . The forcing f_i is the XBraid forcing, which is the FAS right-hand-side term on coarse grids and 0 on the finest grid. The PDE forcing goes inside of A_i .

Since XBraid assumes one-step methods, $A_i(\cdot)$ is defined to be

$$A_i(u_i, u_{i-1}) = -\Phi(u_{i-1}) + \Psi(u_i),$$

i.e., the subdiagonal and diagonal blocks of A .

Default setting: In the default XBraid setting (no residual option used), the user only implements `Step()` and `Step()` will simply apply $\Phi(\cdot)$, because $\Psi(\cdot)$ is assumed to be the identity. Thus, XBraid can compute the residual using only the user-defined `Step()` function by combining `Step()` with the `Sum()` function, i.e.

$$r_i = f_i + \Phi(u_{i-1}) - u_i.$$

The `fstop` parameter in `Step()` corresponds to f_i , but is always passed in as NULL to the user in this setting and should be ignored. This is because XBraid can compute the contribution of f_i to the residual on its own using the `Sum()` function.

An implication of this is that the evaluation of $\Phi(\cdot)$ on the finest grid must be very accurate, or the residual will not be accurate. This leads to a nonintrusive, but expensive algorithm. The accuracy of $\Phi(\cdot)$ can be relaxed on coarser grids to save computations.

Residual setting: The alternative to the above default least-intrusive strategy is to have the user define

$$A_i(u_i, u_{i-1}) = -\Phi(u_{i-1}) + \Psi(u_i),$$

directly, which is what the `Residual` function implements (set with `braided_PtFcnResidual`). In other words, the user now defines each block-row of the space-time operator, rather than only defining $\Phi(\cdot)$. The user `Residual()` function computes $A_i(u_i, u_{i-1})$ and XBraid then subtracts this from f_i to compute r_i .

However, more care must now be taken when defining the `Step()` function. In particular, the `fstop` value (i.e., the f_i value) must be taken into account. Essentially, the definition of `Step()` changes so that it no longer defines $\Phi(\cdot)$, but instead defines a (possibly inexact) solve of the equation defined by

$$A_i(u_i, u_{i-1}) = f_i.$$

Thus, `Step()` must be compatible with `Residual()`. Expanding the previous equation, we say that `Step()` must now compute

$$u_i = \Psi^{-1}(f_i + \Phi(u_{i-1})).$$

It is clear that the *fstop* value (i.e., the f_i value) must now be given to the *Step()* function so that this equation can be solved by the user. In other words, *fstop* is now no longer NULL.

Essentially, one can think of *Residual()* as defining the equation, and *Step()* defining a preconditioner for that row of the equation, or an inexact solve for u_i .

As an example, let $\Psi = (I + \Delta t L)$, where L is a Laplacian and $\Phi = I$. The application of the residual function will only be a sparse matrix-vector multiply, as opposed to the default case where an inversion is required for $\Phi = (I + \Delta t L)^{-1}$ and $\Psi = I$. This results in considerable computational savings. Moreover, the application of *Step()* now involves an inexact inversion of Ψ , e.g., by using just one spatial multigrid V-cycle. This again results in substantial computation savings when compared with the naive approach of a full matrix inversion.

Another way to think about the compatibility between Ψ and Φ is that

$$f_i - A_i(u_i, u_{i-1}) = 0$$

must hold exactly if u_i is an exact propagation of u_{i-1} , that is,

$$f_i - A_i(\text{Step}(u_{i-1}, f_i), u_{i-1}) = 0$$

must hold. When the accuracy of the *Step()* function is reduced (as mentioned above), this exact equality with 0 is lost, but this should evaluate to something `small`. There is an XBraid test function `braid_TestResidual` that tests for this compatibility.

The residual feature is implemented in the examples `examples/ex-01-expanded.c`, `examples/ex-02.c`, and `examples/ex-03.c`.

3. **Adaptive and variable time stepping:** This feature is available by first calling the function `braid_SetRefine` in the main driver and then using `braid_StepStatusSetRFactor` in the *Step* routine to set a refinement factor for interval $[tstart, tstop]$. In this way, user-defined criteria can subdivide intervals on the fly and adaptively refine in time. For instance, returning a refinement factor of 4 in *Step* will tell XBraid to subdivide that interval into 4 evenly spaced smaller intervals for the next iteration. Refinement can only be done on the finest XBraid level.

The final time grid is constructed adaptively in an FMG-like cycle by refining the initial grid according to the requested refinement factors. Refinement stops when the requested factors are all one or when various upper bounds are reached such as the max number of time points or max number of time grid refinement levels allowed. No restriction on the refinement factors is applied within XBraid, so the user may want to apply his own upper bound on the refinement factors to avoid over-refinement. See `examples/ex-01-refinement.c` and `examples/ex-03.c` for an implementation of this.

4. **Richardson-based Error Estimation and Extrapolation:** This feature allows the user to access built-in Richardson-based error estimates and accuracy improving extrapolation. The error estimates and/or extrapolation can be turned on by using `braid_SetRichardsonEstimation`. Moreover, this feature can be used in conjunction with the above discussed function, `braid_StepStatusSetRFactor`, to achieve easy-to-use adaptive refinement in time.

Essentially, Richardson extrapolation (RE) is used to improve the accuracy of the solution at the C-points on the finest level. When the built-in error estimate option is turned on, RE is used to estimate the local truncation error at each point. These estimates can be accessed through `StepStatus` and `AccessStatus` functions.

The Richardson-based error estimates and extrapolation are only available after the first Braid iteration, in that the coarse level solution must be available to compute the error estimate and/or extrapolation. Thus, after an adaptive refinement (and new hierarchy is constructed), another iteration is again required for the error estimates to be available. If the error estimate isn't available, Braid returns a value of -1. See this example for more details

`examples/ex-06.c`

5. **Shell-vector:** This feature supports the use of multi-step methods. The strategy for BDF-K methods is to allow for the lumping of k time points into a single XBraid vector. So, if the problem had 100 time points and the time-stepper was BDF-2, then XBraid would only *see* 50 time points but each XBraid vector would contain two separate time points. By lumping 2 time points into one vector, the BDF-2 scheme remains one-step and compatible with XBraid.

However, the time-point spacing between the two points internal to the vector stays the same on all time grids, while the spacing between vectors grows on coarse time grids. This creates an irregular spacing which is problematic for BDF-k methods. Thus the shell-vector strategy lets meta-data be stored at all time points, even for F-points which are usually not stored, so that the irregular spacings can be tracked and accounted for with the BDF method. (Note, there are other possible uses for shell-vectors.)

There are many strategies for handling the coarse time-grids with BDF methods (dropping the BDF order, adjusting time-point spacings inside the lumped vectors, etc...). Prospective users are encouraged to contact the developers through the XBraid Github page and issue tracker. This area is active research.

See `examples/ex-01-expanded-bdf2.c`.

6. **Storage:** This option (see [braid_SetStorage](#)) allows the user to specify storage at all time points (C and F) or only at C-points. This extra storage is useful for implicit methods, where the solution value from the *previous XBraid iteration* for time step i can be used as the initial guess when computing step i with the implicit solver. This is often a better initial guess than using the solution value from the previous time step $i - 1$. The default is to store only C-point values, thus the better initial guess is only available at C-points in the default setting. When storage is turned on at F-points, the better initial guess becomes available everywhere.

In general, the user should always use the `ustop` parameter in `Step()` as the initial guess for an implicit solve. If storage is turned on (i.e., set to 0), then this value will always be the improved initial guess for C- and F-points. If storage is not turned on, then this will be the improved guess only for C-points. For F-points, it will equal the solution from the previous time step.

See `examples/ex-03` for an example which uses this feature.

4.3 Simplest example expanded

These examples build on [The Simplest Example](#), but still solve the scalar ODE,

$$u_t = \lambda u.$$

The goal here is to show more advanced features of XBraid.

- `examples/ex-01-expanded.c`: same as `ex-01.c` but adds more XBraid features such as the residual feature, the user defined initial time-grid and full multigrid cycling.
- `examples/ex-01-expanded-bdf2.c`: same as `ex-01-expanded.c`, but uses BDF2 instead of backward Euler. This example makes use of the advanced shell-vector feature in order to implement BDF2.
- `examples/ex-01-expanded-f.f90`: same as `ex-01-expanded.c`, but implemented in f90.
- `examples/ex-01-refinement.c`: same as `ex-01.c`, but adds the refinement feature of XBraid. The refinement can be arbitrary or based on error estimate.

4.4 One-Dimensional Heat Equation

In this example, we assume familiarity with [The Simplest Example](#). This example is a time-only parallel example that implements the 1D heat equation,

$$\delta/\delta_t u(x, t) = \Delta u(x, t) + g(x, t),$$

as opposed to [The Simplest Example](#), which implements only a scalar ODE for one degree-of-freedom in space. There is no spatial parallelism, as a serial cyclic reduction algorithm is used to invert the tri-diagonal spatial operators. The space-time discretization is the standard 3-point finite difference stencil ($[-1, 2, -1]$), scaled by mesh widths. Backward Euler is used in time.

This example consists of three files and two executables.

- `examples/ex-02-serial.c`: This file compiles into its own executable `ex-02-serial` and represents a simple example user application that does sequential time-stepping. This file represents where a new XBraid user would start, in terms of converting a sequential time-stepping code to XBraid.
- `examples/ex-02.c`: This file compiles into its own executable `ex-02` and represents a time-parallel XBraid wrapping of the user application `ex-02-serial`.
- `ex-02-lib.c`: This file contains shared functions used by the time-serial version and the time-parallel version. This file provides the basic functionality of this problem. For instance, `take_step(u, tstart, tstop, ...)` carries out a step, moving the vector `u` from time `tstart` to time `tstop`.

4.5 Two-Dimensional Heat Equation

In this example, we assume familiarity with [The Simplest Example](#) and describe the major ways in which this example differs. This example is a full space-time parallel example, as opposed to [The Simplest Example](#), which implements only a scalar ODE for one degree-of-freedom in space. We solve the heat equation in 2D,

$$\delta/\delta_t u(x, y, t) = \Delta u(x, y, t) + g(x, y, t).$$

For spatial parallelism, we rely on the `hypr` package where the `SemiStruct` interface is used to define our spatial discretization stencil and form our time stepping scheme, the backward Euler method. The spatial discretization is just the standard 5-point finite difference stencil ($[-1; -1, 4, -1; -1]$), scaled by mesh widths, and the PFMG solver is used for the solves required by backward Euler. Please see the `hypr` manual and examples for more information on the `SemiStruct` interface and PFMG. Although, the `hypr` specific calls have mostly been abstracted away for this example, and so it is not necessary to be familiar with the `SemiStruct` interface for this example.

This example consists of three files and two executables.

- `examples/ex-03-serial.c`: This file compiles into its own executable `ex-03-serial` and represents a simple example user application. This file supports only parallelism in space and represents a basic approach to doing efficient sequential time stepping with the backward Euler scheme. Note that the `hypr` solver used (PFMG) to carry out the time stepping is highly efficient.
- `examples/ex-03.c`: This file compiles into its own executable `ex-03` and represents a basic example of wrapping the user application `ex-03-serial`. We will go over the wrappers below.
- `ex-03-lib.c`: This file contains shared functions used by the time-serial version and the time-parallel version. This is where most of the `hypr` specific calls reside. This file provides the basic functionality of this problem. For instance, `take_step(u, tstart, tstop, ...)` carries out a step, moving the vector `u` from time `tstart` to time `tstop` and `setUpImplicitMatrix(...)` constructs the matrix to be inverted by PFMG for the backward Euler method.

User Defined Structures and Wrappers

We now discuss in more detail the important data structures and wrapper routines in `examples/ex-03.c`. The actual code for this example is quite simple and it is recommended to read through it after this overview.

The two data structures are:

1. **App:** This holds a wide variety of information and is *global* in that it is passed to every user function. This structure holds everything that the user will need to carry out a simulation. One important structure contained in the *app* is the *simulation_manager*. This is a structure native to the user code `ex-03-lib.c`. This structure conveniently holds the information needed by the user code to carry out a time step. For instance,

```
app->man->A
```

is the time stepping matrix,

```
app->man->solver
```

is the hypre PFMG solver object,

```
app->man->dt
```

is the current time step size. The *app* is defined as

```
typedef struct _braid_App_struct {
    MPI_Comm      comm;           /* global communicator */
    MPI_Comm      comm_t;        /* communicator for parallelizing in time */
    MPI_Comm      comm_x;        /* communicator for parallelizing in space */
    int           pt;            /* number of processors in time */
    simulation_manager *man;      /* user's simulation manager structure */
    HYPRE_SStructVector e;       /* temporary vector used for error computations */
    int           nA;            /* number of spatial matrices created */
    HYPRE_SStructMatrix *A;      /* array of spatial matrices, size nA, one per level*/
    double        *dt_A;         /* array of time step sizes, size nA, one per level*/
    HYPRE_StructSolver *solver;   /* array of PFMG solvers, size nA, one per level*/
    int           use_rand;       /* binary value, use random or zero initial guess */
    int           *runtime_max_iter; /* runtime info for number of PFMG iterations*/
    int           *max_iter_x;    /* maximum iteration limits for PFMG */
} my_App;
```

The *app* contains all the information needed to take a time step with the user code for an arbitrary time step size. See the *Step* function below for more detail.

1. **Vector:** this defines a state vector at a certain time value. Here, the vector is a structure containing a native hypre data-type, the *SStructVector*, which describes a vector over the spatial grid. Note that *my_Vector* is used to define *braid_Vector*.

```
typedef struct _braid_Vector_struct {
    HYPRE_SStructVector x;
} my_Vector;
```

The user must also define a few wrapper routines. Note, that the *app* structure is the first argument to every function.

1. **Step:** This function tells XBraid how to take a time step, and is the core user routine. This function advances the vector *u* from time *tstart* to time *tstop*. A few important things to note are as follows.
 - The time values are given to the user through the *status* structure and associated *Get* routines.

- The basic strategy is to see if a matrix and solver already exist for this dt value. If not, generate a new matrix and solver and store them in the *app* structure. If they do already exist, then re-use the data.
- To carry out a step, the user routines from `ex-03-lib.c` rely on a few crucial data members *man->dt*, *man->A* and *man->solver*. We overwrite these members with the correct information for the time step size in question. Then, we pass *man* and *u* to the user function *take_step(...)* which evolves *u*.
- The forcing term g_i is wrapped into the *take_step(...)* function. Thus, $\Phi(u_i) \rightarrow u_{i+1}$.

```
int my_Step(braid_App      app,
           braid_Vector   u,
           braid_StepStatus status)
{
    double tstart;          /* current time */
    double tstop;          /* evolve u to this time*/
    int i, A_idx;
    int iters_taken = -1;

    /* Grab status of current time step */
    braid_StepStatusGetTstartTstop(status, &tstart, &tstop);

    /* Check matrix lookup table to see if this matrix already exists*/
    A_idx = -1.0;
    for( i = 0; i < app->nA; i++ ){
        if( fabs( app->dt_A[i] - (tstop-tstart) )/(tstop-tstart) < 1e-10) {
            A_idx = i;
            break;
        }
    }

    /* We need to "trick" the user's manager with the new dt */
    app->man->dt = tstop - tstart;

    /* Set up a new matrix and solver and store in app */
    if( A_idx == -1.0 ){
        A_idx = i;
        app->nA++;
        app->dt_A[A_idx] = tstop-tstart;

        setUpImplicitMatrix( app->man );
        app->A[A_idx] = app->man->A;

        setUpStructSolver( app->man, u->x, u->x );
        app->solver[A_idx] = app->man->solver;
    }

    /* Time integration to next time point: Solve the system Ax = b.
     * First, "trick" the user's manager with the right matrix and solver */
    app->man->A = app->A[A_idx];
    app->man->solver = app->solver[A_idx];
    ...
    /* Take step */
    take_step(app->man, u->x, tstart, tstop);
    ...
    return 0;
}
```

2. There are other functions, **Init**, **Clone**, **Free**, **Sum**, **SpatialNorm**, **Access**, **BufSize**, **BufPack** and **BufUnpack**, which also must be written. These functions are all simple for this example, as for the case of [The Simplest Example](#). All we do here is standard operations on a spatial vector such as initialize, clone, take an inner-product, pack, etc... We refer the reader to `ex-03.c`.

Running XBraid for this Example

To initialize and run XBraid, the procedure is similar to [The Simplest Example](#). Only here, we have to both initialize the user code and XBraid. The code that is specific to the user's application comes directly from the existing serial

simulation code. If you compare `ex-03-serial.c` and `ex-03.c`, you will see that most of the code setting up the user's data structures and defining the wrapper functions are simply lifted from the serial simulation.

Taking excerpts from the function `main()` in `ex-03.c`, we first initialize the user's simulation manager with code like

```
...
app->man->px    = 1; /* my processor number in the x-direction */
app->man->py    = 1; /* my processor number in the y-direction */
                /* px*py=num procs in space */
app->man->nx    = 17; /* number of points in the x-dim */
app->man->ny    = 17; /* number of points in the y-dim */
app->man->nt    = 32; /* number of time steps */
...
```

We also define default XBraid parameters with code like

```
...
max_levels    = 15; /* Max levels for XBraid solver */
min_coarse    = 3; /* Minimum possible coarse grid size */
nrelax        = 1; /* Number of CF relaxation sweeps on all levels */
...
```

The XBraid app must also be initialized with code like

```
...
app->comm      = comm;
app->tstart    = tstart;
app->tstop     = tstop;
app->ntime     = ntime;
```

Then, the data structure definitions and wrapper routines are passed to XBraid.

```
braid_Core core;
braid_Init(MPI_COMM_WORLD, comm, tstart, tstop, ntime, app,
           my_Step, my_Init, my_Clone, my_Free, my_Sum, my_SpatialNorm,
           my_Access, my_BufSize, my_BufPack, my_BufUnpack, &core);
```

Then, XBraid options are set with calls like

```
...
braid_SetPrintLevel( core, 1);
braid_SetMaxLevels(core, max_levels);
braid_SetNRelax(core, -1, nrelax);
...
```

Then, the simulation is run.

```
braid_Drive(core);
```

Then, we clean up.


```
braid_Destroy(core);
```

Finally, to run `ex-03`, type

```
ex-03 -help
```

As a simple example, try the following.

```
mpirun -np 8 ex-03 -pgrid 2 2 2 -nt 256
```



4.5.1 Scaling Study with this Example

Here, we carry out a simple strong scaling study for this example. The "time stepping" data set represents sequential time stepping and was generated using `examples/ex-03-serial`. The time-parallel data set was generated using `examples/ex-03`. The problem setup is as follows.

- Backwards Euler is used as the time stepper. This is the only time stepper supported by `ex-03`.
- We used a Linux cluster with 4 cores per node, a Sandybridge Intel chipset, and a fast Infiniband interconnect.
- The space-time problem size was $129^2 \times 16,192$ over the unit cube $[0, 1] \times [0, 1] \times [0, 1]$.
- The coarsening factor was $m = 16$ on the finest level and $m = 2$ on coarser levels.
- Since 16 processors optimized the serial time stepping approach, 16 processors in space are also used for the XBraid experiments. So for instance 512 processors in the plot corresponds to 16 processors in space and 32 processors in time, $16 * 32 = 512$. Thus, each processor owns a space-time hypercube of $(129^2/16) \times (16, 192/32)$. See [Parallel decomposition and memory](#) for a depiction of how XBraid breaks the problem up.
- Various relaxation and V and F cycling strategies are experimented with.
 - *V-cycle, FCF* denotes V-cycles and FCF-relaxation on each level.
 - *V-cycle, F-FCF* denotes V-cycles and F-relaxation on the finest level and FCF-relaxation on all coarser levels.
 - *F-cycle, F* denotes F-cycles and F-relaxation on each level.
- The initial guess at time values for $t > 0$ is zero, which is typical.
- The halting tolerance corresponds to a discrete L2-norm and was

$$\text{tol} = \frac{10^{-8}}{\sqrt{(h_x)^2 h_t}},$$

where h_x and h_t are the spatial and temporal grid spacings, respectively.

This corresponds to passing `tol` to `braid_SetAbsTol`, passing 2 to `braid_SetTemporalNorm` and defining `braid_PtFcnSpatialNorm` to be the standard Euclidean 2-norm. All together, this appropriately scales the space-time residual in way that is relative to the number of space-time grid points (i.e., it approximates the L2-norm).

To re-run this scaling study, a sample run string for `ex-03` is

```
mpirun -np 64 ex-03 -pgrid 4 4 4 -nx 129 129 -nt 16129 -cf0 16 -cf 2 -nu 1 -use_rand 0
```

To re-run the baseline sequential time stepper, `ex-03-serial`, try


```
mpirun -np 64 ex-03-serial -pgrid 8 8 -nx 129 129 -nt 16129
```

For explanations of the command line parameters, type

```
ex-03-serial -help
ex-03 -help
```

Regarding the performance, we can say

- The best speedup is 10x and this would grow if more processors were available.
- Although not shown, the iteration counts here are about 10-15 XBraid iterations. See [Parallel Time Integration with Multigrid](#) for the exact iteration counts.
- At smaller core counts, serial time stepping is faster. But at about 256 processors, there is a crossover and XBraid is faster.
- You can see the impact of the cycling and relaxation strategies discussed in [Cycling and relaxation strategies](#). For instance, even though *V-cycle, F-FCF* is a weaker relaxation strategy than *V-cycle, FCF* (i.e., the XBraid convergence is slower), *V-cycle, F-FCF* has a faster time to solution than *V-cycle, FCF* because each cycle is cheaper.
- In general, one level of aggressive coarsening (here by a factor 16) followed by slower coarsening was found to be best on this machine.

Achieving the best speedup can require some tuning, and it is recommended to read [Parallel Time Integration with Multigrid](#) where this 2D heat equation example is explored in much more detail.

4.6 Simplest XBraid_Adjoint example

The file `examples/ex-01-adjoint.c` extends the simple scalar ODE example in `ex-01.c` for computing adjoint-based sensitivities. See [The Simplest Example](#). The scalar ODE is

$$u_t(t) = \lambda u(t) \quad \forall t \in (0, T),$$

where λ is considered the design variable. We consider an objective function of the form

$$J(u, \lambda) = \int_0^T \frac{1}{T} \|u(t)\|^2 dt.$$

User Defined Structures and Wrappers

The two user-defined data structures are:

1. **Vector:** This structure is unchanged from [The Simplest Example](#), and contains a single scalar representing the state at a given time.

```
typedef struct _braid_Vector_struct
{
    double value;
} my_Vector;
```

2. **App:** This structure holds two additional elements when compared to [The Simplest Example](#) : the *design* and the *reduced gradient*. This ensures that both are accessible in all user routines.

```
typedef struct _braid_App_struct
{
    int      rank;
    double   design;
    double   gradient;
} my_App;
```

The user must also define a few *additional* wrapper routines. Note, that the app structure continues to be the first argument to every function.

1. All user-defined routines from `examples/ex-01.c` stay the same, except `Step()`, which must be changed to account for the new design parameter in `app`.
2. The user's **Step** routine queries the `app` to get the design and propagates the `braid_Vector u` forward in time for one time step:

```
int
my_Step(braid_App      app,
        braid_Vector  ustop,
        braid_Vector  fstop,
        braid_Vector  u,
        braid_StepStatus status)
{
    double tstart;          /* current time */
    double tstop;          /* evolve to this time*/
    braid_StepStatusGetTstartTstop(status, &tstart, &tstop);

    /* Get the design variable from the app */
    double lambda = app->design;

    /* Use backward Euler to propagate the solution */
    (u->value) = 1./(1. - lambda * (tstop-tstart))*(u->value);

    return 0;
}
```

3. **ObjectiveT:** This new routine evaluates the time-dependent part of the objective function at a local time t_i , i.e. it returns the integrand $f(u_i, \lambda) = \frac{1}{T} \|u_i\|_2^2$.

```
int
my_ObjectiveT(braid_App      app,
              braid_Vector  u,
              braid_ObjectiveStatus ostatus,
              double        *objectiveT_ptr)
{
    /* Get the total number of time steps */
    braid_ObjectiveStatusGetNTPoints(ostatus, &ntime);

    /* Evaluate the local objective: 1/N u(t)^2 */
    objT = 1. / ntime * (u->value) * (u->value);

    *objectiveT_ptr = objT;
    return 0;
}
```

The `ObjectiveStatus` can be queried for information about the current status of XBraid (e.g., what is the current time value, time-index, number of time steps, current iteration number, etc...).

XBraid_Adjoint calls the `ObjectiveT` function on the finest time-grid level during the down-cycle of the multigrid algorithm and adds the value to a global objective function value with a simple summation. Thus, any user-specific integration formula of the objective function must be here.

4. **ObjectiveT_diff**: This new routine updates the adjoint variable u_bar and the reduced gradient with the transposed partial derivatives of `ObjectiveT` multiplied by the scalar input \bar{F} , i.e.,

$$\bar{u}_i = \frac{\partial f(u_i, \lambda)}{\partial u_i} \bar{F} \quad \text{and} \quad \bar{\rho}+ = \frac{\partial f(u_i, \lambda)}{\partial \rho} \bar{F}.$$

Note that \bar{u}_i gets overwritten ("="), whereas ρ is updated ("+=").

```
int
my_ObjectiveT_diff(braid_App      app,
                  braid_Vector    u,
                  braid_Vector    u_bar,
                  braid_Real      F_bar,
                  braid_ObjectiveStatus ostatus)
{
    int    ntime;
    double ddu;      /* Derivative wrt u */
    double ddesign;  /* Derivative wrt design */

    /* Get the total number of time steps */
    braid_ObjectiveStatusGetNTPoints(ostatus, &ntime);

    /* Partial derivative with respect to u times F_bar */
    ddu = 2. / ntime * u->value * F_bar;

    /* Partial derivative with respect to design times F_bar*/
    ddesign = 0.0 * F_bar;

    /* Update u_bar and gradient */
    u_bar->value = ddu;
    app->gradient += ddesign;

    return 0;
}
```

5. **Step_diff**: This new routine computes transposed partial derivatives of the `Step` routine multiplied with the adjoint vector u_bar (\bar{u}_i), i.e.,

$$\bar{u}_i = \left(\frac{\partial \Phi_{i+1}(u_i, \rho)}{\partial u_i} \right)^T \bar{u}_i \quad \text{and} \quad \bar{\rho}+ = \left(\frac{\partial \Phi_{i+1}(u_i, \rho)}{\partial \rho} \right)^T \bar{u}_i.$$

```
int
my_Step_diff(braid_App      app,
             braid_Vector    ustop,
             braid_Vector    u,
             braid_Vector    ustop_bar,
             braid_Vector    u_bar,
             braid_StepStatus status)
{
    double ddu;      /* Derivative wrt u */
    double ddesign;  /* Derivative wrt design */

    /* Get the time step size */
    double tstop, tstart, deltat;
    braid_StepStatusGetTstartTstop(status, &tstart, &tstop);
    deltat = tstop - tstart;

    /* Get the design from the app */
    double lambda = app->design;

    /* Transposed derivative of step wrt u times u_bar */
    ddu = 1./ (1. - lambda * deltat) * (u_bar->value);

    /* Transposed derivative of step wrt design times u_bar */
    ddesign = (deltat * (u->value)) / pow(1. - deltat*lambda,2) * (u_bar->value);
}
```

```

/* Update u_bar and gradient */
u_bar->value      = ddu;
app->gradient     += ddesign;

return 0;
}

```

Important note on the usage of `ustop`: If the `Step` routine uses the input vector `ustop` instead of `u` (typically for initializing a (non-)linear solve within Φ), then `Step_diff` must update `ustop_bar` instead of `u_bar` and set `u_bar` to zero:

$$\overline{ustop} += \left(\frac{\partial \Phi_{i+1}(ustop, \rho)}{\partial ustop} \right)^T \bar{u}_i \quad \text{and} \quad \bar{u}_i = 0.0.$$

6. **ResetGradient:** This new routine sets the gradient to zero.

```

int
my_ResetGradient(braid_App app)
{
    app->gradient = 0.0;
    return 0;
}

```

XBraid_Adjoint calls this routine before each iteration such that old gradient information is removed properly.

Running XBraid_Adjoint for this example

The workflow for computing adjoint sensitivities with XBraid_Adjoint alongside the primal state computation closely follows XBraid's workflow. The user's *main* file will first set up the `app` structure, holding the additional information on an initial design and zero gradient. Then, all the setup calls done in [Running XBraid for the Simplest Example](#) will also be done.

The XBraid_Adjoint specific calls are as follows. After `braid_Init(...)` is called, the user initializes XBraid_Adjoint by calling

```

/* Initialize XBraid_Adjoint */
braid_InitAdjoint( my_ObjectiveT, my_ObjectiveT_diff, my_Step_diff, my_ResetGradient, &core);

```

Next, in addition to the usual XBraid options for controlling the multigrid iterations, the adjoint solver's accuracy is set by calling

```

braid_SetAbsTolAdjoint(core, 1e-6);

```

After that, one call to

```

/* Run simulation and adjoint-based gradient computation */
braid_Drive(core);

```

runs the multigrid iterations with additional adjoint sensitivity computations (i.e. the piggy-back iterations). After it finishes, the objective function value can be accessed by calling

```

/* Get the objective function value from XBraid */
braid_GetObjective(core, &objective);

```

Further, the reduced gradient, which is stored in the user's `App` structure, holds the sensitivity information $dJ/d\rho$. As this information is local to all the time-processors, the user is responsible for summing up the gradients from all time-processors, if necessary. This usually involves an `MPI_Allreduce` call as in

```

/* Collect sensitivities from all processors */
double mygradient = app->gradient;
MPI_Allreduce(&mygradient, &(app->gradient), 1, MPI_DOUBLE, MPI_SUM, MPI_COMM_WORLD);

```

Lastly, the gradient computed with XBraid_Adjoint is verified using Finite Differences. See the source code `examples/ex-01-adjoint.c` for details.

4.7 Optimization with the Simplest Example

The file `examples/ex-01-optimization.c` implements a simple optimization iteration by extending `examples/ex-01-adjoint.c`, described in [Simplest XBraid_Adjoint example](#). This example solves an inverse design problem for the simple scalar ODE example:

$$\min \frac{1}{2} \left(\int_0^T \frac{1}{T} \|u(t)\|^2 dt - J_{\text{Target}} \right)^2 + \frac{\gamma}{2} \|\lambda\|^2$$

$$\text{s.t. } \frac{\partial}{\partial t} u(t) = \lambda u(t) \quad \forall t \in (0, T)$$

where J_{Target} is a fixed and precomputed target value and $\gamma > 0$ is a fixed relaxation parameter. Those fixed values are stored within the `App`.

User Defined Structures and Wrappers

In order to evaluate the time-independent part of the objective function (e.g. the postprocessing function F) and its derivative, two additional user routines are necessary. *There are no new user-defined data structures.*

1. **PostprocessObjective:** This function evaluates the tracking-type objective function and the regularization term. The input variable `integral` contains the integral-part of the objective and returns the objective that is to be minimized $F(I)$:

```
/* Evaluate the time-independent part of the objective function */
int
my_PostprocessObjective(braid_App app,
                       double     integral,
                       double     *postprocess
                       )
{
    double F;

    /* Tracking-type functional */
    F = 1./2. * pow(integral - app->target,2);

    /* Regularization term */
    F += (app->gamma) / 2. * pow(app->design,2);

    *postprocess = F;
    return 0;
}
```

1. **PostprocessObjective_diff:** This provides `XBraid_Adjoint` with the partial derivatives of the `PostprocessObjective` routine, i.e.

$$\bar{F} = \frac{\partial F(I, \lambda)}{\partial I} \quad \text{and} \quad \bar{\rho}_+ = \frac{\partial F(I, \lambda)}{\partial \lambda}$$

```
int
my_PostprocessObjective_diff(braid_App app,
                             double     integral,
                             double     *F_bar
                             )
{
    /* Derivative of tracking type function */
    *F_bar = integral - app->target;

    /* Derivative of regularization term */
    app->gradient += (app->gamma) * (app->design);
    return 0;
}
```

These routines are optional for `XBraid_Adjoint`. Therefore, they need to be passed to `XBraid_Adjoint` after the initialization with `braid_Init(...)` and `braid_InitAdjoint(...)` in the user's *main* file:

```
/* Optional: Set the tracking type objective function and derivative */
braid_SetPostprocessObjective(core, my_PostprocessObjective);
braid_SetPostprocessObjective_diff(core, my_PostprocessObjective_diff);
```

Running an Optimization Cycle with `XBraid_Adjoint`

`XBraid_Adjoint` does not natively implement any optimization algorithms. Instead, we provide examples showing how one can easily use `XBraid_Adjoint` inside an optimization cycle. Here, one iteration of the optimization cycle consists of the following steps:

1. First, we run `XBraid_Adjoint` to solve the primal and adjoint dynamics:

```
braid_Drive(core);
```

2. Get the value of the objective function with

```
braid_GetObjective(core, &objective);
```

3. Gradient information is stored in the `app` structure. Since it is local to all temporal processors, we need to invoke an `MPI_Allreduce` call which sums up the local sensitivities:

```
mygradient = app->gradient;
MPI_Allreduce(&mygradient, &app->gradient, 1, MPI_DOUBLE, MPI_SUM, MPI_COMM_WORLD);
```

Note: For time-dependent design variables, summing over all processors might not be necessary, since information is needed only locally in time. See `examples/ex-04.c` for a time-dependent design example.

4. Update the design variable using the gradient information. Here, we implement a simple steepest descent update into the direction of the negative gradient:

```
app->design -= stepsize * app->gradient;
```

Here, a fixed step size is used to update the design variable. Usually, a line-search procedure should be implemented in order to find a suitable step length that minimizes the objective function along the update direction. However to carry out a line search, we must re-evaluate the objective function for different design value(s). Thus, the option `braid_SetObjectiveOnly(core, 1)` can be used. After this option has been set, any further call to `braid_Drive(core)` will then only run a primal `XBraid` simulation and carry out an objective function evaluation. No gradients will be computed, which saves computational time. After the line search, make sure to reset `XBraid_Adjoint` for gradient computation with `braid_SetObjectiveOnly(core, 0)`.

5. The optimization iterations are stopped when the norm of the gradient is below a prescribed tolerance.

4.8 A Simple Optimal Control Problem

This example demonstrates the use of `XBraid_Adjoint` for solving an optimal control problem with time-dependent design variables:

$$\begin{aligned} \min \quad & \int_0^1 u_1(t)^2 + u_2(t)^2 + \gamma c(t)^2 dt \\ \text{s.t.} \quad & \frac{\partial}{\partial t} u_1(t) = u_2(t) \quad \forall t \in (0, 1) \\ & \frac{\partial}{\partial t} u_2(t) = -u_2(t) + c(t) \quad \forall t \in (0, 1) \end{aligned}$$

with initial condition $u_1(0) = 0, u_2(0) = -1$ and piecewise constant control (design) variable $c(t)$.

The example consists of three files, meant to indicate how one can take a time-serial implementation for an optimal control problem and create a corresponding `XBraid_Adjoint` implementation.

- `examples/ex-04-serial.c`: Compiles into its own executable `examples/ex-04-serial`, which solves the optimal control problem using time-serial forward-propagation of state variables and time-serial backward-propagation of the adjoint variables in each iteration of an outer optimization cycle.
- `examples/ex-04.c`: Compiles into `ex-04`. This solves the same optimization problem in time-parallel by replacing the forward- and backward-propagation of state and adjoint by the time-parallel XBraid and XBraid_↔ Adjoint solvers.
- `examples/ex-04-lib.c`: Contains the routines that are shared by both the serial and the time-parallel implementation. Study this file, and discover that most of the important code setting up the user-defined data structures and wrapper routines are simply lifted from the serial simulation.

4.9 Running and Testing XBraid

The best overall test for XBraid, is to set the maximum number of levels to 1 (see [braid_SetMaxLevels](#)) which will carry out a sequential time stepping test. Take the output given to you by your `Access` function and compare it to output from a non-XBraid run. Is everything OK? Once this is complete, repeat for multilevel XBraid, and check that the solution is correct (that is, it matches a serial run to within tolerance).

At a lower level, to do sanity checks of your data structures and wrapper routines, there are also XBraid test functions, which can be easily run. The test routines also take as arguments the `app` structure, spatial communicator `comm_x`, a stream like `stdout` for test output and a time step size `dt` to test. After these arguments, function pointers to wrapper routines are the rest of the arguments. Some of the tests can return a boolean variable to indicate correctness.

```

/* Test init(), access(), free() */
braid_TestInitAccess( app, comm_x, stdout, dt, my_Init, my_Access, my_Free);

/* Test clone() */
braid_TestClone( app, comm_x, stdout, dt, my_Init, my_Access, my_Free, my_Clone);

/* Test sum() */
braid_TestSum( app, comm_x, stdout, dt, my_Init, my_Access, my_Free, my_Clone, my_Sum);

/* Test spatialnorm() */
correct = braid_TestSpatialNorm( app, comm_x, stdout, dt, my_Init, my_Free, my_Clone,
                                my_Sum, my_SpatialNorm);

/* Test bufsize(), bufpack(), bufunpack() */
correct = braid_TestBuf( app, comm_x, stdout, dt, my_Init, my_Free, my_Sum, my_SpatialNorm,
                        my_BufSize, my_BufPack, my_BufUnpack);

/* Test coarsen and refine */
correct = braid_TestCoarsenRefine(app, comm_x, stdout, 0.0, dt, 2*dt, my_Init,
                                my_Access, my_Free, my_Clone, my_Sum, my_SpatialNorm,
                                my_CoarsenInjection, my_Refine);
correct = braid_TestCoarsenRefine(app, comm_x, stdout, 0.0, dt, 2*dt, my_Init,
                                my_Access, my_Free, my_Clone, my_Sum, my_SpatialNorm,
                                my_CoarsenBilinear, my_Refine);

```

4.10 Fortran90 Interface, C++ Interface, Python Interface, and More Complicated Examples

We have Fortran90, C++, and Python interfaces. For Fortran 90, see `examples/ex-01f.f90`. For C++ see `braid.hpp` and `examples/ex-01-pp.cpp` For more complicated C++ examples, see the various C++ examples in `drivers/drive-*.cpp`. For Python, see the directories `examples/ex-01-cython` and `examples/ex-01-cython-alt`.

For a discussion of more complex problems please see our project [publications website](#) for our recent publications concerning some of these varied applications.

5 Examples: compiling and running

For C/C++/Fortran examples, type

```
ex-* -help
```

for instructions on how to run. To run the C/C++/Fortran examples, type

```
mpirun -np 4 ex-* [args]
```

For the Cython examples, see the corresponding *.pyx file.

1. ex-01 is the simplest example. It implements a scalar ODE and can be compiled and run with no outside dependencies. See Section ([The Simplest Example](#)) for more discussion of this example. There are seven versions of this example,

- *ex-01.c*: simplest possible implementation, start reading this example first
- *ex-01-expanded.c*: same as ex-01.c but adds more XBraid features
- *ex-01-expanded-bdf2.c*: same as ex-01-expanded.c, but uses BDF2 instead of backward Euler
- *ex-01-expanded-f.f90*: same as ex-01-expanded.c, but implemented in f90
- *ex-01-refinement.c*: same as ex-01.c, but adds the refinement feature
- *ex-01-adjoint.c*: adds adjoint-based gradient computation to ex-01.c
- *ex-01-optimization.c*: gradient-based optimization cycle for ex-01-c
- *ex-01-cython/*: is a directory containing an example using the Braid-Cython interface defined in `braid.pyx` (`braid/braid.pyx`). It solves the same scalar ODE equation as the ex-01 series described above. This example uses a Python-like syntax, in contrast to the ex-01-cython-alt example, which uses a C-style syntax. For instructions on running and compiling, see

```
examples/ex-01-cython/ex_01.pyx
```

and

```
examples/ex-01-cython/ex_01-setup.py
```

- *ex-01-cython-alt/*: is a directory containing another example using the Braid-Cython interface defined in `braid.pyx` (`braid/braid.pyx`). It solves the same scalar ODE equation as the ex-01 series described above. This example uses a lower-level C-like syntax for most of it's code, in contrast to the ex-01-cython example, which uses a Python-style syntax.

For instructions on running and compiling, see

```
examples/ex-01-cython-alt/ex_01_alt.pyx
```

and

```
examples/ex-01-cython-alt/ex_01_alt-setup.py
```

2. ex-02 implements the 1D heat equation on a regular grid, using a very simple implementation. This is the next example to read after the various ex-01 cases.
3. ex-03 implements the 2D heat equation on a regular grid. You must have `hypre` installed and these variables in `examples/Makefile` set correctly

```
HYPRE_DIR = ../../linear_solvers/hypre
HYPRE_FLAGS = -I$(HYPRE_DIR)/include
HYPRE_LIB = -L$(HYPRE_DIR)/lib -lHYPRE
```


Only implicit time stepping (backward Euler) is supported. See Section ([Two-Dimensional Heat Equation](#)) for more discussion of this example. The driver

```
drivers/drive-diffusion
```

is a more sophisticated version of this simple example that supports explicit time stepping and spatial coarsening.

4. ex-04 solves a simple optimal control problem with time-dependent design variable using a simple steepest-descent optimization iteration.
5. Directory ex-05-cython/ solves a simple 1D heat equation using the Cython interface

```
examples/ex-05-cython/ex_05.pyx
```

and

```
examples/ex-05-cython/ex_05-setup.py
```

6. ex-06 solve a simple scalar ODE, but allows for use of the built-in Richardson-based error estimator and accuracy improving extrapolation. With the "-refinet" option, the error estimator allows for adaptive refinement in time, and with the "-richardson" option, Richardson extrapolation is used improve the solution at fine-level C-points.

The viz script,

```
examples/viz-ex-06.py
```

allows you to visualize the solution, error, and error estimate. The use of "-richardson" notably improves the accuracy of the solution.

The Richardson-based error estimates and/or extrapolation are only available after the first Braid iteration, in that the coarse level solution must be available to compute the error estimate and extrapolation. Thus, after an adaptive refinement (and new hierarchy is constructed), another iteration is again required for the error estimate to be available. If the error estimate isn't available, Braid returns a value of -1. See this example and the comments therein for more details.

6 Drivers: compiling and running

Type

```
drive-* -help
```

for instructions on how to run any driver.

To run the examples, type

```
mpirun -np 4 drive-* [args]
```

1. *drive-diffusion-2D* implements the 2D heat equation on a regular grid. You must have `hypre` installed and these variables in `examples/Makefile` set correctly

```
HYPRE_DIR = ../../linear_solvers/hypre
HYPRE_FLAGS = -I$(HYPRE_DIR)/include
HYPRE_LIB = -L$(HYPRE_DIR)/lib -lHYPRE
```

This driver also support spatial coarsening and explicit time stepping. This allows you to use explicit time stepping on each Braid level, regardless of time step size.

2. *drive-burgers-1D* implements Burger's equation (and also linear advection) in 1D using forward or backward Euler in time and Lax-Friedrichs in space. Spatial coarsening is supported, allowing for stable time stepping on coarse time-grids.

See also *viz-burgers.py* for visualizing the output.

3. *drive-lorenz* implements the Lorenz equation, with it's trademark attractors. This problem has not been researched very extensively, and XBraid's behavior is not yet well understood. Convergence stagnates, but is the solution "good enough" from a statistical point-of-view?

See also *viz-lorenz.py* for visualizing the output.

4. *drive-diffusion* is a sophisticated test bed for finite element discretizations of the heat equation. It relies on the *mfem* package to create general finite element discretizations for the spatial problem. Other packages must be installed in this order.

- Unpack and install *Metis*
- Unpack and install *hypre*
- Unpack *mfem*. Then make sure to set these variables correctly in the mfem Makefile:

```
USE_METIS_5 = YES
HYPRE_DIR = where_ever_linear_solvers_is/hypre
```

- Make the parallel version of mfem first by typing

```
make parallel
```

- Make *GLVIS*. Set these variables in the glvis makefile

```
MFEM_DIR = mfem_location
MFEM_LIB = -L$(MFEM_DIR) -lmfem
```

- Go to braid/examples and set these Makefile variables,

```
METIS_DIR = ../../metis-5.1.0/lib
MFEM_DIR = ../../mfem
MFEM_FLAGS = -I$(MFEM_DIR)
MFEM_LIB = -L$(MFEM_DIR) -lmfem -L$(METIS_DIR) -lmetis
```

then type

```
make drive-diffusion
```

- To run drive-diffusion and glvis, open two windows. In one, start a glvis session

```
./glvis
```

Then, in the other window, run drive-diffusion

```
mpirun -np ... drive-diffusion [args]
```

Glvis will listen on a port to which drive-diffusion will dump visualization information.

5. The other drive-.cpp files use MFEM to implement other PDEs

- *drive-adv-diff-DG*: implements advection(-diffusion) with a discontinuous Galerkin discretization. This driver is under developement.
- *drive-diffusion-1D-moving-mesh*: implements the 1D heat equation, but with a moving mesh that adapts to the forcing function so that the mesh equidistributes the arc-length of the solution.
- *drive-diffusion-1D-moving-mesh-serial*: implements a serial time-stepping version of the above problem.
- *drive-pLaplacian*: implements the 2D the p -Laplacian (nonlinear diffusion).
- *drive-diffusion-ben*: implements the 2D/3D diffusion equation with time-dependent coefficients. This is essentially equivalent to drive-diffusion, and could be removed, but we're keeping it around because it implements linear diffusion in the same way that the p -Laplacian driver implemented nonlinear diffusion. This makes it suitable for head-to-head timings.

- *drive-lin-elasticity*: implements time-dependent linearized elasticity and is under development.
 - *drive-nonlin-elasticity*: implements time-dependent nonlinear elasticity and is under development.
6. Directory `drive-adv-diff-1D-Cython/` solves a simple 1D advection-diffusion equation using the Cython interface and numerous spatial and temporal discretizations

```
drivers/drive-adv-diff-1D-Cython/drive_adv_diff_1D.pyx
```

and

```
drivers/drive-adv-diff-1D-Cython/drive_adv_diff_1D-setup.py
```

7 Coding Style

Code should follow the `ellement1` style. See `braid/misc/sample_c_code.c`, and for emacs and vim style files, see `braid/misc/sample.vimrc`, and `braid/misc/sample.emacs`.

8 File naming conventions

These are the general filenames conventions for Braid

User interface routines in `braid` begin with `braid_` and all other internal non-user routines begin with `_braid_`. This helps to prevent name clashes when working with other libraries and helps to clearly distinguish user routines that are supported and maintained.

To keep things somewhat organized, all user header files and implementation files should have names that begin with `braid`, for example, `braid.h`, `braid.c`, `braid_status.c`, ... There should be no user interface prototypes or implementations that appear elsewhere.

Note that it is okay to include internal prototypes and implementations in these user interface files when it makes sense (say, as supporting routines), but this should generally be avoided.

An attempt has been made to simplify header file usage as much as possible by requiring only one header file for users, `braid.h`, and one header file for developers, `_braid.h`.

9 Using Doxygen

To build the documentation, `doxygen` must be version 1.8 or greater. XBraid documentation uses a `markdown` syntax both in source file comments and in `*.md` files.

To make the documentation,

```
$ make user_manual
$ acread user_manual.pdf
```

or to make a more extensive reference manual for developers,

```
$ make developer_manual
$ acread developer_manual.pdf
```

Developers can run doxygen from a precompiled binary, which may or may not work for your machine,

```
/usr/casc/hypre/braid/share/doxygen/bin/doxygen
```

or build doxygen from

```
/usr/casc/hypre/braid/share/doxygen.tgz
```

- Compiling doxygen requires a number of dependencies like Bison, GraphViz and Flex. Configure will tell you what you're missing
- Unpack doxygen.tgz, then from the doxygen directory

```
./configure --prefix some_dir_in_your_path
make
make install
```

Documentation Strategy

- The doxygen comments are to be placed in the header files.
- A sample function declaration using the documentation approach using markdown (including typesetting equations) is in [braid.h](#) for the function [braid_Init\(\)](#)
- A sample structure documentation is in [_braid.h](#) for [_braid_Core_struct](#)
- Descriptors for files can also be added, as at the top of [braid.h](#)
- The Doxygen manual is at <http://www.stack.nl/~dimitri/doxygen/manual/index.html>

XBraid Doxygen details

The user and developer manuals are ultimately produced by Latex. The formatting of the manuals is configured according to the following.

- docs/local_doxygen.sty
 - Latex style file used
- docs/user_manual_header.tex
 - User manual title page and header info
- docs/developer_manual_header.tex
 - Developer manual title page and header info
- *.md
 - Any file ending in .md is extra documentation in markdown format, like [Introduction.md](#) or the various [Readme.md](#) files in each directory. This material can be read in plain-text or when it's compiled by Doxygen and Latex.

- docs/user_manual.conf
 - Doxygen configure file for the user manual
 - The FILE_NAMES tag is a filter to only include the user interface routines in [braid.h](#)
 - The INPUT tag orders the processing of the files and hence the section ordering
- docs/reference_manual.conf
 - Same as user_manual.conf, but the FILE_NAMES tag does not exclude any file from processing.
- docs/img
 - Contains the images
- To regenerate generic doxygen latex files, type

```
$ doxygen -w latex header.tex footer.tex doxygen.sty doxy.conf
```

If this is done, then the .conf file must be changed to use the new header file and to copy the local_doxygen.sty file to the latex directory.

10 Regression Testing

Overview

- There are three levels in the testing framework. At each level, the fine-grain output from a `testscript.sh` is dumped into a directory `testscript.dir`, with the standard out and error stored in `testscript.out` and `testscript.err`. The test `testscript.sh` passes if `testscript.err` is empty (nothing is written to standard error).
- Basic instructions: run a test with a command like

```
$ ./test.sh diffusion2D.sh
```

Then, see if `diffusion2D.err` is of size 0. If it is not, look at it's contents to see which test failed.

- To add a new regression test, create a new lowest level script like `diffusion2D.sh` and then call it from a machine script at level 2.
- Regression tests should be run before pushing code. It is recommended to run the basic (lowest level) tests like `diffusion2d.sh` or machine test like `machine-tux.sh`

Lowest Level Test Scripts

As an example, here we look at one of the lowest level tests, the `diffusion2d` test.
Files used:

- `test.sh`
- `diffusion2D.sh`
- `diffusion2D.saved`

Output:

- diffusion2D.dir
- diffusion2D.err
- diffusion2D.out

At this level, we execute

```
$ ./test.sh diffusion2D.sh
```

or just

```
$ ./diffusion2D.sh
```

The script `diffusion2D.sh` must create `diffusion2D.dir` and place all fine-grain test output in this directory. `test.sh` captures the standard out and error in `diffusion2D.out` and `diffusion2D.err`. The test `diffusion2D.sh` passes if `diffusion2D.err` is empty (nothing is written to standard error).

The strategy for low level scripts like `diffusion2D.sh` is to run a sequence of tests such as

```
$ mpirun -np 1 ../examples/ex-02 -pgrid 1 1 1 -nt 256
$ mpirun -np 4 ../examples/ex-02 -pgrid 1 1 4 -nt 256
```

The output from the first `mpirun` test must then be written to files named

```
diffusion2D.dir/unfiltered.std.out.0
diffusion2D.dir/std.out.0
diffusion2D.dir/std.err.0
```

and the second `mpirun` test similarly writes the files

```
diffusion2D.dir/unfiltered.std.out.1
diffusion2D.dir/std.out.1
diffusion2D.dir/std.err.1
```

Subsequent tests are written to higher numbered files. The `unfiltered.std.out.num` file contains all of the standard out for the test, while `std.out.num` contains filtered output (usually from a `grep` command) and could contain the output lines such as iteration numbers and number of levels. The file `std.err.num` contains the standard error output.

To see if a test ran correctly, `std.out.num` is compared to saved output in `diffusion2D.saved`. The file `diffusion2D.saved` contains the concatenated output from all the tests that `diffusion2D.sh` will run. For the above example, this file could look like

```
# Begin Test 1
number of levels      = 6
iterations            = 16
# Begin Test 2
number of levels      = 4
iterations            = 8
```

This saved output is split into an individual file for each test (using `# Begin Test` as a delimiter) and these new files are placed in `diffusion2D.dir`. So, after running these two regression tests, `diffusion2D.dir` will contain

```
diffusion2D.saved.0
diffusion2D.saved.1
unfiltered.std.out.0
std.out.0
std.err.0
unfiltered.std.out.1
std.out.1
std.err.1
```

An individual test has passed if `std.err.num` is empty. The file `std.err.num` contains a diff between `diffusion2D.save.num` and `std.out.num` (the diff ignores whitespace and the delimiter `# Begin Test`).

Last in the directory where you ran `./test.sh diffusion2d.sh`, the files

```
diffusion2D.err
diffusion2D.out
```

will be created. If all the tests passed then `diffusion2D.err` will be empty. Otherwise, it will contain the filenames of the `std.err.num` files that are non-empty, representing failed tests.

Level 2 Scripts

As an example, here we look at one of the Level 2 tests, the `machine-tux` test that Jacob runs.

Files used:

- `machine-tux.sh`

Output:

- `machine-tux.dir`
- `machine-tux.err` (only generated if `autotest.sh` is used to run `machine-tux.sh`)
- `machine-tux.out` (only generated if `autotest.sh` is used to run `machine-tux.sh`)

At this level, we execute

```
./machine-tux.sh
```

The `autotest` framework (`autotest.sh`) calls machine scripts in this way. Each machine script should be short and call lower-level scripts like `diffusion2D.sh`. The output from lower-level scripts must be moved to `machine-tux.dir` like this:

```
$ ./test.sh diffusion2D.sh
$ mv -f diffusion2D.dir machine-tux.dir
$ mv -f diffusion2D.out machine-tux.dir
$ mv -f diffusion2D.err machine-tux.dir
```

All error files from `diffusion2D.sh` will be placed in `machine-tux.dir`, so if `machine-tux.dir` has all zero `*.err` files, then the `machine-tux` test has passed.

To begin testing on a new machine, like `vulcan`, add a new machine script similar to `machine-tux.sh` and change `autotest.sh` to recognize and run the new machine test. To then use `autotest.sh` with the machine script, you'll have to set up a passwordless connection from the new machine to

```
/usr/casc/hypre/braid/testing
```

Level 3 Script

Here we look at the highest level, where `autotest.sh` runs all of the level 2 machine tests and emails out the results.

Files used:

- `autotest.sh`

Output:

- `test/autotest_finished`
- `/usr/casc/hypre/braid/testing/AUTOTEST-20**.**.*-Day`
- Email to recipients listed in `autotest.sh`

At the highest level sits `autotest.sh` and is called automatically as a cronjob. If you just want to check to see if you've broken anything with a commit, just use lower level scripts.

There are four steps to running `autotest`.

- Step 1

```
$ ./autotest.sh -init
```

will do a pull from master for the current working repository and recompile Braid. The `autotest` output files (`autotest.err` and `autotest.out`) and the output directory (`autotest_finished`) are initialized.

- Step 2

```
$ ./autotest.sh -tux343
```

will run the autotests on `tux343`. This command will look for a `machine-tux.sh`, and execute it, moving the resulting

```
machine-tux.dir
machine-tux.err
machine-tux.out
```

into `test/autotest_finished`.

- Step 3

```
$ ./autotest.sh -remote-copy
```

will copy `/test/autotest_finished/*` to a time-stamped directory such as `/usr/casc/hypre/braid/testing/AUTOTEST-2013.11.18-Mon`
Alternatively,

```
$ ./autotest.sh -remote-copy tux343
```

will ssh through `tux343` to copy to `/usr/casc`. Multiple machines may independently be running regression tests and then copy to `AUTOTEST-2013.11.18-Mon`.

- Step 4

```
$ ./autotest.sh -summary-email
```

will email everyone listed in the `$email_list` (an `autotest.sh` variable)

Cronfile

To add entries to your crontab, First, put your new cronjob lines into `cronfile`. Then see what you already have in your crontab file with

```
$ crontab -l
```

Next, append to cronfile whatever you already have

```
$ crontab -l >> cronfile
```

Finally, tell crontab to use your cronfile

```
$ crontab cronfile
```

Then make sure it took affect with

```
$ crontab -l
```

Crontab entry format uses '*' to mean "every" and '*/m' to mean "every m-th". The first five entries on each line correspond respectively to:

- minute (0-56)
- hour (0-23)
- day of month (1-31)
- month (1-12)
- day of week (0-6)(0=Sunday)

Jacob's crontab (on tux343):

```
00 01 * * * source /etc/profile; source $HOME/.bashrc; cd $HOME/joint_repos/braid/test; ./autotest.sh -init
10 01 * * * source /etc/profile; source $HOME/.bashrc; cd $HOME/joint_repos/braid/test; ./autotest.sh -tux343
40 01 * * * source /etc/profile; source $HOME/.bashrc; cd $HOME/joint_repos/braid/test; ./autotest.sh -remote-c
50 01 * * * source /etc/profile; source $HOME/.bashrc; cd $HOME/joint_repos/braid/test; ./autotest.sh -summary-
00 02 * * * source /etc/profile; source $HOME/.bashrc; cd $HOME/joint_repos/braid/test; ./autotest.sh -create-t
```

11 Module Index

11.1 Modules

Here is a list of all modules:

Fortran 90 interface options	52
Error Codes	54

User-written routines	55
User-written routines for XBraid_Adjoint	60
User interface routines	62
General Interface routines	63
Interface routines for XBraid_Adjoint	82
XBraid status structures	87
XBraid status routines	88
Inherited XBraid status routines	102
XBraid status macros	114
XBraid test routines	115

12 Data Structure Index

12.1 Data Structures

Here are the data structures with brief descriptions:

_braid_Action	123
_braid_CommHandle	125
_braid_Core	127
_braid_Grid	143
_braid_Status	146
_braid_Tape	147
braid_AccessStatus	148
braid_BaseVector	148
braid_BufferStatus	149
braid_CoarsenRefStatus	150
braid_ObjectiveStatus	150
braid_Optim	151
braid_StepStatus	153
braid_SyncStatus	154
braid_VectorBar	154

13 File Index

13.1 File List

Here is a list of all files with brief descriptions:

_braid.h	Define headers for XBraid internal (developer) routines and XBraid internal structure declarations	155
adjoint.h	Define internal XBraid headers for the adjoint feature	172
base.h	Define XBraid internal headers for wrapper routines of user-defined functions	174
braid.h	Define headers for user-interface routines	186
braid_defs.h	Definitions of braid types, error flags, etc..	188
braid_status.h	Define headers for the user-interface with the XBraid status structures, allowing the user to get/set status structure values	190
braid_test.h	Define headers for XBraid user-test routines	194
mpistubs.h	XBraid internal headers to define fake MPI stubs. This ultimately allows the user to generate purely serial codes without MPI	195
status.h	Define the XBraid internal headers for the XBraid status structure routines, and define the status structures themselves	195
tape.h	Define the XBraid internal headers for the action-tape routines (linked list for AD)	199
util.h	Define XBraid internal headers for utility routines	203

14 Module Documentation

14.1 Fortran 90 interface options

Macros

- #define [braid_FMANGLE](#) 1
- #define [braid_Fortran_SpatialCoarsen](#) 0
- #define [braid_Fortran_Residual](#) 1
- #define [braid_Fortran_TimeGrid](#) 1
- #define [braid_Fortran_Sync](#) 1

14.1.1 Detailed Description

Allows user to manually, at compile-time, turn on Fortran 90 interface options

14.1.2 Macro Definition Documentation

14.1.2.1 braid_FMANGLE

```
#define braid_FMANGLE 1
```

Define Fortran name-mangling schema, there are four supported options, see `braid_F90_iface.c`

14.1.2.2 braid_Fortran_Residual

```
#define braid_Fortran_Residual 1
```

Turn on the optional user-defined residual function

14.1.2.3 braid_Fortran_SpatialCoarsen

```
#define braid_Fortran_SpatialCoarsen 0
```

Turn on the optional user-defined spatial coarsening and refinement functions

14.1.2.4 braid_Fortran_Sync

```
#define braid_Fortran_Sync 1
```

Turn on the optional user-defined sync function

14.1.2.5 braid_Fortran_TimeGrid

```
#define braid_Fortran_TimeGrid 1
```

Turn on the optional user-defined time-grid function

14.2 Error Codes

Macros

- `#define braid_INVALID_RNORM -1`
- `#define braid_ERROR_GENERIC 1 /* generic error */`
- `#define braid_ERROR_MEMORY 2 /* unable to allocate memory */`
- `#define braid_ERROR_ARG 4 /* argument error */`

14.2.1 Detailed Description

14.2.2 Macro Definition Documentation

14.2.2.1 `braid_ERROR_ARG`

```
#define braid_ERROR_ARG 4 /* argument error */
```

14.2.2.2 `braid_ERROR_GENERIC`

```
#define braid_ERROR_GENERIC 1 /* generic error */
```

14.2.2.3 `braid_ERROR_MEMORY`

```
#define braid_ERROR_MEMORY 2 /* unable to allocate memory */
```

14.2.2.4 `braid_INVALID_RNORM`

```
#define braid_INVALID_RNORM -1
```

Value used to represent an invalid residual norm

14.3 User-written routines

Modules

- [User-written routines for XBraid_Adjoint](#)

Typedefs

- typedef struct _braid_App_struct * [braid_App](#)
- typedef struct _braid_Vector_struct * [braid_Vector](#)
- typedef [braid_Int](#)(* [braid_PtFcnStep](#)) ([braid_App](#) app, [braid_Vector](#) ustop, [braid_Vector](#) fstop, [braid_Vector](#) u, [braid_StepStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnInit](#)) ([braid_App](#) app, [braid_Real](#) t, [braid_Vector](#) *u_ptr)
- typedef [braid_Int](#)(* [braid_PtFcnClone](#)) ([braid_App](#) app, [braid_Vector](#) u, [braid_Vector](#) *v_ptr)
- typedef [braid_Int](#)(* [braid_PtFcnFree](#)) ([braid_App](#) app, [braid_Vector](#) u)
- typedef [braid_Int](#)(* [braid_PtFcnSum](#)) ([braid_App](#) app, [braid_Real](#) alpha, [braid_Vector](#) x, [braid_Real](#) beta, [braid_Vector](#) y)
- typedef [braid_Int](#)(* [braid_PtFcnSpatialNorm](#)) ([braid_App](#) app, [braid_Vector](#) u, [braid_Real](#) *norm_ptr)
- typedef [braid_Int](#)(* [braid_PtFcnAccess](#)) ([braid_App](#) app, [braid_Vector](#) u, [braid_AccessStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnSync](#)) ([braid_App](#) app, [braid_SyncStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnBufSize](#)) ([braid_App](#) app, [braid_Int](#) *size_ptr, [braid_BufferStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnBufPack](#)) ([braid_App](#) app, [braid_Vector](#) u, void *buffer, [braid_BufferStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnBufUnpack](#)) ([braid_App](#) app, void *buffer, [braid_Vector](#) *u_ptr, [braid_BufferStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnResidual](#)) ([braid_App](#) app, [braid_Vector](#) ustop, [braid_Vector](#) r, [braid_StepStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnSCoarsen](#)) ([braid_App](#) app, [braid_Vector](#) fu, [braid_Vector](#) *cu_ptr, [braid_CoarsenRefStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnSRefine](#)) ([braid_App](#) app, [braid_Vector](#) cu, [braid_Vector](#) *fu_ptr, [braid_CoarsenRefStatus](#) status)
- typedef [braid_Int](#)(* [braid_PtFcnSInit](#)) ([braid_App](#) app, [braid_Real](#) t, [braid_Vector](#) *u_ptr)
- typedef [braid_Int](#)(* [braid_PtFcnSClone](#)) ([braid_App](#) app, [braid_Vector](#) u, [braid_Vector](#) *v_ptr)
- typedef [braid_Int](#)(* [braid_PtFcnSFree](#)) ([braid_App](#) app, [braid_Vector](#) u)
- typedef [braid_Int](#)(* [braid_PtFcnTimeGrid](#)) ([braid_App](#) app, [braid_Real](#) *ta, [braid_Int](#) *ilower, [braid_Int](#) *iupper)

14.3.1 Detailed Description

These are all the user-written data structures and routines. There are two data structures ([braid_App](#) and [braid_Vector](#)) for the user to define. And, there are a variety of function interfaces (defined through function pointer declarations) that the user must implement.

14.3.2 Typedef Documentation

14.3.2.1 `braid_App`

```
typedef struct _braid_App_struct* braid_App
```

This holds a wide variety of information and is `global` in that it is passed to every function. This structure holds everything that the user will need to carry out a simulation. For a simple example, this could just hold the global MPI communicator and a few values describing the temporal domain.

14.3.2.2 `braid_PtFcnAccess`

```
typedef braid_Int (* braid_PtFcnAccess) (braid_App app, braid_Vector u, braid_AccessStatus status)
```

Gives user access to XBraid and to the current vector u at time t . Most commonly, this lets the user write the vector to screen, file, etc... The user decides what is appropriate. Note how you are told the time value t of the vector u and other information in `status`. This lets you tailor the output, e.g., for only certain time values at certain XBraid iterations. Querying status for such information is done through `braid_AccessStatusGet**(..)` routines.

The frequency of XBraid's calls to `access` is controlled through `braid_SetAccessLevel`. For instance, if `access_level` is set to 3, then `access` is called every XBraid iteration and on every XBraid level. In this case, querying `status` to determine the current XBraid level and iteration will be useful. This scenario allows for even more detailed tracking of the simulation.

Eventually, access will be broadened to allow the user to steer XBraid.

14.3.2.3 `braid_PtFcnBufPack`

```
typedef braid_Int (* braid_PtFcnBufPack) (braid_App app, braid_Vector u, void *buffer, braid_↔  
BufferStatus status)
```

This allows XBraid to send messages containing `braid_Vectors`. This routine packs a vector u into a `void * buffer` for MPI. The status structure holds information regarding the message. This is accessed through the `braid_BufferStatusGet**(..)` routines. Optionally, the user can set the message size through the status structure.

14.3.2.4 `braid_PtFcnBufSize`

```
typedef braid_Int (* braid_PtFcnBufSize) (braid_App app, braid_Int *size_ptr, braid_BufferStatus  
status)
```

This routine tells XBraid message sizes by computing an upper bound in bytes for an arbitrary `braid_Vector`. This size must be an upper bound for what `BufPack` and `BufUnPack` will assume.

14.3.2.5 `braid_PtFcnBufUnpack`

```
typedef braid_Int (* braid_PtFcnBufUnpack) (braid_App app, void *buffer, braid_Vector *u_ptr, braid_↔  
_BufferStatus status)
```

This allows XBraid to receive messages containing `braid_Vectors`. This routine unpacks a `void * buffer` from MPI into a `braid_Vector`. The status structure, contains information conveying the type of message inside the buffer. This can be accessed through the `braid_BufferStatusGet**(..)` routines.

14.3.2.6 `braid_PtFcnClone`

```
typedef braid_Int (* braid_PtFcnClone) (braid_App app, braid_Vector u, braid_Vector *v_ptr)
```

Clone *u* into *v_ptr*

14.3.2.7 `braid_PtFcnFree`

```
typedef braid_Int (* braid_PtFcnFree) (braid_App app, braid_Vector u)
```

Free and deallocate *u*

14.3.2.8 `braid_PtFcnInit`

```
typedef braid_Int (* braid_PtFcnInit) (braid_App app, braid_Real t, braid_Vector *u_ptr)
```

Initializes a vector *u_ptr* at time *t*

14.3.2.9 `braid_PtFcnResidual`

```
typedef braid_Int (* braid_PtFcnResidual) (braid_App app, braid_Vector ustop, braid_Vector r, braid_StepStatus status)
```

This function (optional) computes the residual *r* at time *tstop*. On input, *r* holds the value of *u* at *tstart*, and *ustop* is the value of *u* at *tstop*. If used, set with `braid_SetResidual`.

Query the status structure with `braid_StepStatusGetTstart(status, &tstart)` and `braid_StepStatusGetTstop(status, &tstop)` to get *tstart* and *tstop*.

14.3.2.10 `braid_PtFcnSClone`

```
typedef braid_Int (* braid_PtFcnSClone) (braid_App app, braid_Vector u, braid_Vector *v_ptr)
```

Shell clone (optional)

14.3.2.11 `braid_PtFcnSCoarsen`

```
typedef braid_Int (* braid_PtFcnSCoarsen) (braid_App app, braid_Vector fu, braid_Vector *cu_ptr, braid_CoarsenRefStatus status)
```

Spatial coarsening (optional). Allows the user to coarsen when going from a fine time grid to a coarse time grid. This function is called on every vector at each level, thus you can coarsen the entire space time domain. The action of this function should match the `braid_PtFcnSRefine` function.

The user should query the status structure at run time with `braid_CoarsenRefGet**()` calls in order to determine how to coarsen. For instance, status tells you what the current time value is, and what the time step sizes on the fine and coarse levels are.

14.3.2.12 `braid_PtFcnSFree`

```
typedef braid_Int (* braid_PtFcnSFree) (braid_App app, braid_Vector u)
```

Free the data of u , keep its shell (optional)

14.3.2.13 `braid_PtFcnSInit`

```
typedef braid_Int (* braid_PtFcnSInit) (braid_App app, braid_Real t, braid_Vector *u_ptr)
```

Shell initialization (optional)

14.3.2.14 `braid_PtFcnSpatialNorm`

```
typedef braid_Int (* braid_PtFcnSpatialNorm) (braid_App app, braid_Vector u, braid_Real *norm_ptr)
```

Carry out a spatial norm by taking the norm of a `braid_Vector` $norm_ptr = || u ||$. A common choice is the standard Euclidean norm, but many other choices are possible, such as an L2-norm based on a finite element space. See [`braid_SetTemporalNorm`](#) for information on how the spatial norm is combined over time for a global space-time residual norm. This global norm then controls halting.

14.3.2.15 `braid_PtFcnSRefine`

```
typedef braid_Int (* braid_PtFcnSRefine) (braid_App app, braid_Vector cu, braid_Vector *fu_ptr, braid_CoarsenRefStatus status)
```

Spatial refinement (optional). Allows the user to refine when going from a coarse time grid to a fine time grid. This function is called on every vector at each level, thus you can refine the entire space time domain. The action of this function should match the [`braid_PtFcnSCoarsen`](#) function.

The user should query the status structure at run time with `braid_CoarsenRefGet**()` calls in order to determine how to coarsen. For instance, status tells you what the current time value is, and what the time step sizes on the fine and coarse levels are.

14.3.2.16 `braid_PtFcnStep`

```
typedef braid_Int (* braid_PtFcnStep) (braid_App app, braid_Vector ustop, braid_Vector fstop, braid_Vector u, braid_StepStatus status)
```

Defines the central time stepping function that the user must write.

The user must advance the vector u from time $tstart$ to $tstop$. The time step is taken assuming the right-hand-side vector $fstop$ at time $tstop$. The vector $ustop$ may be the same vector as u (in the case where not all unknowns are stored). The vector $fstop$ is set to NULL to indicate a zero right-hand-side.

Query the status structure with `braid_StepStatusGetTstart(status, &tstart)` and `braid_StepStatusGetTstop(status, &tstop)` to get $tstart$ and $tstop$. The status structure also allows for steering. For example, `braid_StepStatusSetRefinementFactor(...)` allows for setting a refinement factor, which tells XBraid to refine this time interval.

14.3.2.17 `braid_PtFcnSum`

```
typedef braid_Int (* braid_PtFcnSum) (braid_App app, braid_Real alpha, braid_Vector x, braid_Real
beta, braid_Vector y)
```

AXPY, $\alpha x + \beta y \rightarrow y$

14.3.2.18 `braid_PtFcnSync`

```
typedef braid_Int (* braid_PtFcnSync) (braid_App app, braid_SyncStatus status)
```

Gives user access to XBraid and to the user's app at various points (primarily once per iteration inside FRefine and outside in the main cycle loop). This function is called once per-processor (not for every state vector stored on the processor, like access).

14.3.2.19 `braid_PtFcnTimeGrid`

```
typedef braid_Int (* braid_PtFcnTimeGrid) (braid_App app, braid_Real *ta, braid_Int *ilower, braid_←
_Int *iupper)
```

Set time values for temporal grid on level 0 (time slice per processor)

14.3.2.20 `braid_Vector`

```
typedef struct _braid_Vector_struct* braid_Vector
```

This defines (roughly) a state vector at a certain time value. It could also contain any other information related to this vector which is needed to evolve the vector to the next time value, like mesh information.

14.4 User-written routines for XBraid_Adjoint

Typedefs

- typedef `braided_Int>(* braided_PtFcnObjectiveT)` (`braided_App` app, `braided_Vector` u, `braided_ObjectiveStatus` ostatus, `braided_Real` *objectiveT_ptr)
- typedef `braided_Int(* braided_PtFcnObjectiveTDiff)` (`braided_App` app, `braided_Vector` u, `braided_Vector` u_bar, `braided_Real` F_bar, `braided_ObjectiveStatus` ostatus)
- typedef `braided_Int(* braided_PtFcnPostprocessObjective)` (`braided_App` app, `braided_Real` sum_obj, `braided_Real` *postprocess_ptr)
- typedef `braided_Int(* braided_PtFcnPostprocessObjective_diff)` (`braided_App` app, `braided_Real` sum_obj, `braided_Real` *F↔_bar_ptr)
- typedef `braided_Int(* braided_PtFcnStepDiff)` (`braided_App` app, `braided_Vector` ustop, `braided_Vector` u, `braided_Vector` ustop_bar, `braided_Vector` u_bar, `braided_StepStatus` status)
- typedef `braided_Int(* braided_PtFcnResetGradient)` (`braided_App` app)

14.4.1 Detailed Description

These are all the user-written routines needed to use XBraid_Adjoint. There are no new user-written data structures here. But, the `braided_App` structure will typically be used to store some things like optimization parameters and gradients.

14.4.2 Typedef Documentation

14.4.2.1 braided_PtFcnObjectiveT

```
typedef braided_Int (* braided_PtFcnObjectiveT) (braided_App app, braided_Vector u, braided_ObjectiveStatus ostatus, braided_Real *objectiveT_ptr)
```

This routine evaluates the time-dependent part of the objective function, at a current time t , i.e. the integrand. Query the `braided_ObjectiveStatus` structure for information about the current time and status of XBraid_Adjoint.

14.4.2.2 braided_PtFcnObjectiveTDiff

```
typedef braided_Int (* braided_PtFcnObjectiveTDiff) (braided_App app, braided_Vector u, braided_Vector u_bar, braided_Real F_bar, braided_ObjectiveStatus ostatus)
```

This is the differentiated version of the `braided_PtFcnObjectiveT` routine. It provides the derivatives of `ObjectiveT()` multiplied by the scalar input F_bar .

First output: the derivative with respect to the state vector must be returned to XBraid_Adjoint in u_bar .

Second output: The derivative with respect to the design must update the gradient, which is stored in the `braided_App`.

14.4.2.3 braid_PtFcnPostprocessObjective

```
typedef braid_Int (* braid_PtFcnPostprocessObjective) (braid_App app, braid_Real sum_obj, braid_↵
Real *postprocess_ptr)
```

(Optional) This function can be used to postprocess the time-integral objective function. For example, when inverse design problems are considered, you can use a tracking-type objective function by subtracting a target value from *postprocess_ptr*, and squaring the result. Relaxation or penalty terms can also be added to *postprocess_ptr*. For a description of the postprocessing routine, see the Section [Objective function evaluation](#) .

14.4.2.4 braid_PtFcnPostprocessObjective_diff

```
typedef braid_Int (* braid_PtFcnPostprocessObjective_diff) (braid_App app, braid_Real sum_obj,
braid_Real *F_bar_ptr)
```

(Optional) Differentiated version of the Postprocessing routine.

First output: Return the partial derivative of the [braid_PtFcnPostprocessObjective](#) routine with respect to the time-integral objective function, and placing the result in the scalar value *F_bar_ptr*

Second output: Update the gradient with the partial derivative with respect to the design. Gradients are usually stored in [braid_App](#) .

For a description of the postprocessing routine, see the Section [Objective function evaluation](#) .

14.4.2.5 braid_PtFcnResetGradient

```
typedef braid_Int (* braid_PtFcnResetGradient) (braid_App app)
```

Set the gradient to zero, which is usually stored in [braid_App](#) .

14.4.2.6 braid_PtFcnStepDiff

```
typedef braid_Int (* braid_PtFcnStepDiff) (braid_App app, braid_Vector ustop, braid_Vector u, braid_↵
_Vector ustop_bar, braid_Vector u_bar, braid_StepStatus status)
```

This is the differentiated version of the time-stepping routine. It provides the transposed derivatives of *Step()* multiplied by the adjoint input vector *u_bar* (or *ustop_bar*).

First output: the derivative with respect to the state *u* updates the adjoint vector *u_bar* (or *ustop_bar*).

Second output: The derivative with respect to the design must update the gradient, which is stored in [braid_App](#) .

14.5 User interface routines

Modules

- [General Interface routines](#)
- [Interface routines for XBraid_Adjoint](#)
- [XBraid status structures](#)
- [XBraid status routines](#)
- [Inherited XBraid status routines](#)
- [XBraid status macros](#)

14.5.1 Detailed Description

These are all the user interface routines.

14.6 General Interface routines

Macros

- `#define braid_RAND_MAX 32768`

Typedefs

- `typedef struct _braid_Core_struct * braid_Core`

Functions

- `braid_Int braid_Init` (MPI_Comm comm_world, MPI_Comm comm, `braid_Real` tstart, `braid_Real` tstop, `braid_Int` ntime, `braid_App` app, `braid_PtFcnStep` step, `braid_PtFcnInit` init, `braid_PtFcnClone` clone, `braid_PtFcnFree` free, `braid_PtFcnSum` sum, `braid_PtFcnSpatialNorm` spatialnorm, `braid_PtFcnAccess` access, `braid_PtFcnBufSize` bufsize, `braid_PtFcnBufPack` bufpack, `braid_PtFcnBufUnpack` bufunpack, `braid_Core` *core_ptr)
- `braid_Int braid_Drive` (`braid_Core` core)
- `braid_Int braid_Destroy` (`braid_Core` core)
- `braid_Int braid_PrintStats` (`braid_Core` core)
- `braid_Int braid_WriteConvHistory` (`braid_Core` core, const char *filename)
- `braid_Int braid_SetMaxLevels` (`braid_Core` core, `braid_Int` max_levels)
- `braid_Int braid_SetIncrMaxLevels` (`braid_Core` core)
- `braid_Int braid_SetSkip` (`braid_Core` core, `braid_Int` skip)
- `braid_Int braid_SetRefine` (`braid_Core` core, `braid_Int` refine)
- `braid_Int braid_SetMaxRefinements` (`braid_Core` core, `braid_Int` max_refinements)
- `braid_Int braid_SetTPointsCutoff` (`braid_Core` core, `braid_Int` tpoints_cutoff)
- `braid_Int braid_SetMinCoarse` (`braid_Core` core, `braid_Int` min_coarse)
- `braid_Int braid_SetAbsTol` (`braid_Core` core, `braid_Real` atol)
- `braid_Int braid_SetRelTol` (`braid_Core` core, `braid_Real` rtol)
- `braid_Int braid_SetNRelax` (`braid_Core` core, `braid_Int` level, `braid_Int` nrelax)
- `braid_Int braid_SetCRelaxWt` (`braid_Core` core, `braid_Int` level, `braid_Real` Cwt)
- `braid_Int braid_SetCFactor` (`braid_Core` core, `braid_Int` level, `braid_Int` cfactor)
- `braid_Int braid_SetMaxIter` (`braid_Core` core, `braid_Int` max_iter)
- `braid_Int braid_SetFMG` (`braid_Core` core)
- `braid_Int braid_SetNFMG` (`braid_Core` core, `braid_Int` k)
- `braid_Int braid_SetNFMGVcyc` (`braid_Core` core, `braid_Int` nfmg_Vcyc)
- `braid_Int braid_SetStorage` (`braid_Core` core, `braid_Int` storage)
- `braid_Int braid_SetTemporalNorm` (`braid_Core` core, `braid_Int` tnorm)
- `braid_Int braid_SetResidual` (`braid_Core` core, `braid_PtFcnResidual` residual)
- `braid_Int braid_SetFullRNormRes` (`braid_Core` core, `braid_PtFcnResidual` residual)
- `braid_Int braid_SetTimeGrid` (`braid_Core` core, `braid_PtFcnTimeGrid` tgrid)
- `braid_Int braid_SetPeriodic` (`braid_Core` core, `braid_Int` periodic)
- `braid_Int braid_SetSpatialCoarsen` (`braid_Core` core, `braid_PtFcnSCoarsen` scoarsen)
- `braid_Int braid_SetSpatialRefine` (`braid_Core` core, `braid_PtFcnSRefine` srefine)
- `braid_Int braid_SetSync` (`braid_Core` core, `braid_PtFcnSync` sync)
- `braid_Int braid_SetPrintLevel` (`braid_Core` core, `braid_Int` print_level)
- `braid_Int braid_SetFileIOLevel` (`braid_Core` core, `braid_Int` io_level)
- `braid_Int braid_SetPrintFile` (`braid_Core` core, const char *printfile_name)
- `braid_Int braid_SetDefaultPrintFile` (`braid_Core` core)

- `braid_Int braid_SetAccessLevel` (`braid_Core` core, `braid_Int` access_level)
- `braid_Int braid_SplitCommworld` (const `MPI_Comm` *comm_world, `braid_Int` px, `MPI_Comm` *comm_x, `MPI_Comm` *comm_t)
- `braid_Int braid_SetShell` (`braid_Core` core, `braid_PtFcnSInit` sinit, `braid_PtFcnSClone` sclone, `braid_PtFcnSFree` sfree)
- `braid_Int braid_GetNumIter` (`braid_Core` core, `braid_Int` *niter_ptr)
- `braid_Int braid_GetRNorms` (`braid_Core` core, `braid_Int` *nrequest_ptr, `braid_Real` *rnorms)
- `braid_Int braid_GetNLevels` (`braid_Core` core, `braid_Int` *nlevels_ptr)
- `braid_Int braid_GetSpatialAccuracy` (`braid_StepStatus` status, `braid_Real` loose_tol, `braid_Real` tight_tol, `braid_Real` *tol_ptr)
- `braid_Int braid_SetSeqSoln` (`braid_Core` core, `braid_Int` seq_soln)
- `braid_Int braid_GetMyID` (`braid_Core` core, `braid_Int` *myid_ptr)
- `braid_Int braid_Rand` (void)

14.6.1 Detailed Description

These are general interface routines, e.g., routines to initialize and run a XBraid solver, or to split a communicator into spatial and temporal components.

14.6.2 Macro Definition Documentation

14.6.2.1 `braid_RAND_MAX`

```
#define braid_RAND_MAX 32768
```

Machine independent pseudo-random number generator is defined in `Braid.c`

14.6.3 Typedef Documentation

14.6.3.1 `braid_Core`

```
typedef struct _braid_Core_struct* braid_Core
```

points to the core structure defined in `_braid.h`

14.6.4 Function Documentation

14.6.4.1 `braid_Destroy()`

```
braid_Int braid_Destroy (
    braid_Core core )
```

Clean up and destroy core.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
-------------	---

14.6.4.2 braid_Drive()

```
braid_Int braid_Drive (
    braid_Core core )
```

Carry out a simulation with XBraid. Integrate in time.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
-------------	---

14.6.4.3 braid_GetMyID()

```
braid_Int braid_GetMyID (
    braid_Core core,
    braid_Int * myid_ptr )
```

Get the processor's rank.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>myid_ptr</i>	output: rank of the processor.

14.6.4.4 braid_GetNLevels()

```
braid_Int braid_GetNLevels (
    braid_Core core,
    braid_Int * nlevels_ptr )
```

After Drive() finishes, this returns the number of XBraid levels

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>nlevels_ptr</i>	output, holds the number of XBraid levels

14.6.4.5 braid_GetNumIter()

```
braid_Int braid_GetNumIter (
    braid_Core core,
    braid_Int * niter_ptr )
```

After Drive() finishes, this returns the number of iterations taken.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>niter_ptr</i>	output, holds number of iterations taken

14.6.4.6 braid_GetRNorms()

```
braid_Int braid_GetRNorms (
    braid_Core core,
    braid_Int * nrequest_ptr,
    braid_Real * rnorms )
```

After Drive() finishes, this returns XBraid residual history. If *nrequest_ptr* is negative, return the last *nrequest_ptr* residual norms. If positive, return the first *nrequest_ptr* residual norms. Upon exit, *nrequest_ptr* holds the number of residuals actually returned.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>nrequest_ptr</i>	input/output, input: num requested resid norms, output: num actually returned
<i>rnorms</i>	output, holds residual norm history array

14.6.4.7 braid_GetSpatialAccuracy()

```
braid_Int braid_GetSpatialAccuracy (
    braid_StepStatus status,
    braid_Real loose_tol,
    braid_Real tight_tol,
    braid_Real * tol_ptr )
```

Example function to compute a tapered stopping tolerance for implicit time stepping routines, i.e., a tolerance *tol_ptr* for the spatial solves. This tapering only occurs on the fine grid.

This rule must be followed. The same tolerance must be returned over all processors, for a given XBraid and XBraid level. Different levels may have different tolerances and the same level may vary its tolerance from iteration to iteration, but for the same iteration and level, the tolerance must be constant.

This additional rule must be followed. The fine grid tolerance is never reduced (this is important for convergence)

On the fine level, the spatial stopping tolerance *tol_ptr* is interpolated from *loose_tol* to *tight_tol* based on the relationship between $rnorm / rnorm0$ and *tol*. Remember when $rnorm / rnorm0 < tol$, XBraid halts. Thus, this function lets us have a loose stopping tolerance while the Braid residual is still relatively large, and then we transition to a tight stopping tolerance as the Braid residual is reduced.

If the user has not defined a residual function, *tight_tol* is always returned.

The *loose_tol* is always used on coarse grids, excepting the above mentioned residual computations.

This function will normally be called from the user's step routine.

This function is also meant as a guide for users to develop their own routine.

Parameters

<i>status</i>	Current XBraid step status
<i>loose_tol</i>	Loosest allowed spatial solve stopping tol on fine grid
<i>tight_tol</i>	Tightest allowed spatial solve stopping tol on fine grid
<i>tol_ptr</i>	output, holds the computed spatial solve stopping tol

14.6.4.8 braid_Init()

```

braid_Int braid_Init (
    MPI_Comm comm_world,
    MPI_Comm comm,
    braid_Real tstart,
    braid_Real tstop,
    braid_Int ntime,
    braid_App app,
    braid_PtFcnStep step,
    braid_PtFcnInit init,
    braid_PtFcnClone clone,
    braid_PtFcnFree free,
    braid_PtFcnSum sum,
    braid_PtFcnSpatialNorm spatialnorm,
    braid_PtFcnAccess access,
    braid_PtFcnBufSize bufsize,
    braid_PtFcnBufPack bufpack,
    braid_PtFcnBufUnpack bufunpack,
    braid_Core * core_ptr )

```

Create a core object with the required initial data.

This core is used by XBraid for internal data structures. The output is *core_ptr* which points to the newly created *braid_Core* structure.

Parameters

<i>comm_world</i>	Global communicator for space and time
<i>comm</i>	Communicator for temporal dimension
<i>tstart</i>	start time
<i>tstop</i>	End time
<i>ntime</i>	Initial number of temporal grid values
<i>app</i>	User-defined <code>_braid_App</code> structure
<i>step</i>	User time stepping routine to advance a <code>braid_Vector</code> forward one step
<i>init</i>	Initialize a <code>braid_Vector</code> on the finest temporal grid
<i>clone</i>	Clone a <code>braid_Vector</code>
<i>free</i>	Free a <code>braid_Vector</code>
<i>sum</i>	Compute vector sum of two <code>braid_Vectors</code>
<i>spatialnorm</i>	Compute norm of a <code>braid_Vector</code> , this is a norm only over space
<i>access</i>	Allows access to <code>XBraid</code> and current <code>braid_Vector</code>
<i>bufsize</i>	Computes size for MPI buffer for one <code>braid_Vector</code>
<i>bufpack</i>	Packs MPI buffer to contain one <code>braid_Vector</code>
<i>bufunpack</i>	Unpacks MPI buffer into a <code>braid_Vector</code>
<i>core_ptr</i>	Pointer to <code>braid_Core</code> (<code>_braid_Core</code>) struct

14.6.4.9 `braid_PrintStats()`

```
braid_Int braid_PrintStats (
    braid_Core core )
```

Print statistics after a `XBraid` run.

Parameters

<i>core</i>	<code>braid_Core</code> (<code>_braid_Core</code>) struct
-------------	---

14.6.4.10 `braid_Rand()`

```
braid_Int braid_Rand (
    void )
```

Define a machine independent random number generator

14.6.4.11 `braid_SetAbsTol()`

```
braid_Int braid_SetAbsTol (
    braid_Core core,
    braid_Real atol )
```

Set absolute stopping tolerance.

Recommended option over relative tolerance

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>atol</i>	absolute stopping tolerance

14.6.4.12 `braid_SetAccessLevel()`

```
braid_Int braid_SetAccessLevel (
    braid_Core core,
    braid_Int access_level )
```

Set access level for XBraid. This controls how often the user's access routine is called.

- Level 0: Never call the user's access routine
- Level 1: Only call the user's access routine after XBraid is finished
- Level 2: Call the user's access routine every iteration and on every level. This is during `_braid_FRestrict`, during the down-cycle part of a XBraid iteration.

Default is level 1.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>access_level</i>	desired access_level

14.6.4.13 `braid_SetCFactor()`

```
braid_Int braid_SetCFactor (
    braid_Core core,
    braid_Int level,
    braid_Int cfactor )
```

Set the coarsening factor *cfactor* on grid *level* (level 0 is the finest grid). The default factor is 2 on all levels. To change the default factor, use *level* = -1.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>level</i>	<i>level</i> to set coarsening factor on
<i>cfactor</i>	desired coarsening factor

14.6.4.14 `braid_SetCRelaxWt()`

```
braid_Int braid_SetCRelaxWt (
    braid_Core core,
    braid_Int level,
    braid_Real Cwt )
```

Set the C-relaxation weight on grid *level* (level 0 is the finest grid). The default is 1.0 on all levels. To change the default factor, use *level* * = -1.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>level</i>	<i>level</i> to set <i>Cwt</i> on
<i>Cwt</i>	C-relaxation weight to use on <i>level</i>

14.6.4.15 `braid_SetDefaultPrintFile()`

```
braid_Int braid_SetDefaultPrintFile (
    braid_Core core )
```

Use default filename, *braid_runtime.out* for runtime print messages. This function is particularly useful for Fortran codes, where passing filename strings between C and Fortran is troublesome. Level of printing is controlled by [braid_SetPrintLevel](#).

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
-------------	---

14.6.4.16 `braid_SetFileIOLevel()`

```
braid_Int braid_SetFileIOLevel (
    braid_Core core,
    braid_Int io_level )
```

Set output level for XBraid. This controls how much information is saved to files .

- Level 0: no output
- Level 1: save the cycle in *braid.out.cycle*

Default is level 1.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>io_level</i>	desired output-to-file level

14.6.4.17 `braid_SetFMG()`

```
braid_Int braid_SetFMG (
    braid_Core core )
```

Once called, XBraid will use FMG (i.e., F-cycles).

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
-------------	---

14.6.4.18 `braid_SetFullRNormRes()`

```
braid_Int braid_SetFullRNormRes (
    braid_Core core,
    braid_PtFcnResidual residual )
```

Set user-defined residual routine for computing full residual norm (all C/F points).

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>residual</i>	function pointer to residual routine

14.6.4.19 `braid_SetIncrMaxLevels()`

```
braid_Int braid_SetIncrMaxLevels (
    braid_Core core )
```

Increase the max number of multigrid levels after performing a refinement.

14.6.4.20 `braid_SetMaxIter()`

```
braid_Int braid_SetMaxIter (
    braid_Core core,
    braid_Int max_iter )
```

Set max number of multigrid iterations.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>max_iter</i>	maximum iterations to allow

14.6.4.21 `braid_SetMaxLevels()`

```
braid_Int braid_SetMaxLevels (
    braid_Core core,
    braid_Int max_levels )
```

Set max number of multigrid levels.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>max_levels</i>	maximum levels to allow

14.6.4.22 `braid_SetMaxRefinements()`

```
braid_Int braid_SetMaxRefinements (
    braid_Core core,
    braid_Int max_refinements )
```

Set the max number of time grid refinement levels allowed.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>max_refinements</i>	maximum refinement levels allowed

14.6.4.23 `braid_SetMinCoarse()`

```
braid_Int braid_SetMinCoarse (
    braid_Core core,
    braid_Int min_coarse )
```

Set minimum allowed coarse grid size. XBraid stops coarsening whenever creating the next coarser grid will result in a grid smaller than `min_coarse`. The maximum possible coarse grid size will be `min_coarse*coarsening_factor`.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>min_coarse</i>	minimum coarse grid size

14.6.4.24 `braid_SetNFMG()`

```
braid_Int braid_SetNFMG (
    braid_Core core,
    braid_Int k )
```

Once called, XBraid will use FMG (i.e., F-cycles.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>k</i>	number of initial F-cycles to do before switching to V-cycles

14.6.4.25 `braid_SetNFMGVcyc()`

```
braid_Int braid_SetNFMGVcyc (
    braid_Core core,
    braid_Int nfmg_Vcyc )
```

Set number of V-cycles to use at each FMG level (standard is 1)

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>nfmg_Vcyc</i>	number of V-cycles to do each FMG level

14.6.4.26 `braid_SetNRelax()`

```
braid_Int braid_SetNRelax (
    braid_Core core,
    braid_Int level,
    braid_Int nrelax )
```

Set the number of relaxation sweeps *nrelax* on grid *level* (level 0 is the finest grid). The default is 1 on all levels. To change the default factor, use *level* = -1. One sweep is a CF relaxation sweep.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>level</i>	<i>level</i> to set <i>nrelax</i> on
<i>nrelax</i>	number of relaxations to do on <i>level</i>

14.6.4.27 `braid_SetPeriodic()`

```
braid_Int braid_SetPeriodic (
    braid_Core core,
    braid_Int periodic )
```

Set periodic time grid. The periodicity on each grid level is given by the number of points on each level. Requirements: The number of points on the finest grid level must be evenly divisible by the product of the coarsening factors between each grid level. Currently, the coarsening factors must be the same on all grid levels. Also, `braid_SetSeqSoln` must not be used.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>periodic</i>	boolean to specify if periodic

14.6.4.28 `braid_SetPrintFile()`

```
braid_Int braid_SetPrintFile (
    braid_Core core,
    const char * printfile_name )
```

Set output file for runtime print messages. Level of printing is controlled by [braid_SetPrintLevel](#). Default is stdout.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>printfile_name</i>	output file for XBraid runtime output

14.6.4.29 `braid_SetPrintLevel()`

```
braid_Int braid_SetPrintLevel (
    braid_Core core,
    braid_Int print_level )
```

Set print level for XBraid. This controls how much information is printed to the XBraid print file ([braid_SetPrintFile](#)).

- Level 0: no output
- Level 1: print runtime information like the residual history
- Level 2: level 1 output, plus post-Braid run statistics (default)
- Level 3: level 2 output, plus debug level output.

Default is level 1.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>print_level</i>	desired print level

14.6.4.30 braid_SetRefine()

```
braid_Int braid_SetRefine (
    braid_Core core,
    braid_Int refine )
```

Turn time refinement on (refine = 1) or off (refine = 0).

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>refine</i>	boolean, refine in time or not

14.6.4.31 braid_SetRelTol()

```
braid_Int braid_SetRelTol (
    braid_Core core,
    braid_Real rtol )
```

Set relative stopping tolerance, relative to the initial residual. Be careful. If your initial guess is all zero, then the initial residual may only be nonzero over one or two time values, and this will skew the relative tolerance. Absolute tolerances are recommended.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>rtol</i>	relative stopping tolerance

14.6.4.32 `braid_SetResidual()`

```
braid_Int braid_SetResidual (
    braid_Core core,
    braid_PtFcnResidual residual )
```

Set user-defined residual routine.

Parameters

<i>core</i>	braid_Core (<code>_braid_Core</code>) struct
<i>residual</i>	function pointer to residual routine

14.6.4.33 `braid_SetSeqSoln()`

```
braid_Int braid_SetSeqSoln (
    braid_Core core,
    braid_Int seq_soln )
```

Set the initial guess to XBraid as the sequential time stepping solution. This is primarily for debugging. When used with `storage=-2`, the initial residual should evaluate to exactly 0. The residual can also be 0 for other storage options if the time stepping is *exact*, e.g., the implicit solve in Step is done to full precision.

The value `seq_soln` is a Boolean

- 0: The user's `Init()` function initializes the state vector (default)
- 1: Sequential time stepping, with the user's initial condition from `Init(t=0)` initializes the state vector

Default is 0.

Parameters

<i>core</i>	braid_Core (<code>_braid_Core</code>) struct
<i>seq_soln</i>	1: Init with sequential time stepping soln, 0: Use user's <code>Init()</code>

14.6.4.34 `braid_SetShell()`

```
braid_Int braid_SetShell (
    braid_Core core,
    braid_PtFcnSInit sinit,
    braid_PtFcnSClone sclone,
    braid_PtFcnSFree sfree )
```

Activate the shell vector feature, and set the various functions that are required :

- `sinit` : create a shell vector
- `sclone` : clone the shell of a vector
- `sfree` : free the data of a vector, keeping its shell This feature should be used with storage option = -1. It allows the used to keep metadata on all points (including F-points) without storing the all vector everywhere. With these options, the vectors are fully stored on C-points, but only the vector shell is kept on F-points.

14.6.4.35 `braid_SetSkip()`

```
braid_Int braid_SetSkip (
    braid_Core core,
    braid_Int skip )
```

Set whether to skip all work on the first down cycle (`skip = 1`). On by default.

Parameters

<code>core</code>	<code>braid_Core</code> (<code>_braid_Core</code>) struct
<code>skip</code>	boolean, whether to skip all work on first down-cycle

14.6.4.36 `braid_SetSpatialCoarsen()`

```
braid_Int braid_SetSpatialCoarsen (
    braid_Core core,
    braid_PtFcnSCoarsen scoarsen )
```

Set spatial coarsening routine with user-defined routine. Default is no spatial refinement or coarsening.

Parameters

<code>core</code>	<code>braid_Core</code> (<code>_braid_Core</code>) struct
<code>scoarsen</code>	function pointer to spatial coarsening routine

14.6.4.37 `braid_SetSpatialRefine()`

```
braid_Int braid_SetSpatialRefine (
    braid_Core core,
    braid_PtFcnSRefine srefine )
```

Set spatial refinement routine with user-defined routine. Default is no spatial refinement or coarsening.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>srefine</i>	function pointer to spatial refinement routine

14.6.4.38 braid_SetStorage()

```
braid_Int braid_SetStorage (
    braid_Core core,
    braid_Int storage )
```

Sets the storage properties of the code. -1 : Default, store only C-points 0 : Full storage of C- and F-Points on all levels
 $x > 0$: Full storage on all levels $\geq x$

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>storage</i>	storage property

14.6.4.39 braid_SetSync()

```
braid_Int braid_SetSync (
    braid_Core core,
    braid_PtFcnSync sync )
```

Set sync routine with user-defined routine. Sync gives user access to XBraid and the user's app at various points (primarily once per iteration inside FRefine and outside in the main cycle loop). This function is called once per-processor (instead of for every state vector on the processor, like access). The use case is to allow the user to update their app once-per iteration based on information from XBraid, for example to maintain the space-time grid when doing time-space adaptivity. Default is no sync routine.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>sync</i>	function pointer to sync routine

14.6.4.40 braid_SetTemporalNorm()

```
braid_Int braid_SetTemporalNorm (
    braid_Core core,
    braid_Int tnorm )
```

Sets XBraid temporal norm.

This option determines how to obtain a global space-time residual norm. That is, this decides how to combine the spatial norms returned by [braid_PtFcnSpatialNorm](#) at each time step to obtain a global norm over space and time. It is this global norm that then controls halting.

There are three options for setting *tnorm*. See section [Halting tolerance](#) for a more detailed discussion (in [Introduction](#)↔[md](#)).

- *tnorm=1*: One-norm summation of spatial norms
- *tnorm=2*: Two-norm summation of spatial norms
- *tnorm=3*: Infinity-norm combination of spatial norms

The default choice is *tnorm=2*

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>tnorm</i>	choice of temporal norm

14.6.4.41 [braid_SetTimeGrid\(\)](#)

```
braid_Int braid_SetTimeGrid (
    braid_Core core,
    braid_PtFcnTimeGrid tgrid )
```

Set user-defined time points on finest grid

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>tgrid</i>	function pointer to time grid routine

14.6.4.42 [braid_SetTPointsCutoff\(\)](#)

```
braid_Int braid_SetTPointsCutoff (
    braid_Core core,
    braid_Int tpoints_cutoff )
```

Set the number of time steps, beyond which refinements stop. If `num(tpoints) > tpoints_cutoff`, then stop doing refinements.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>tpoints_cutoff</i>	cutoff for stopping refinements

14.6.4.43 `braid_SplitCommworld()`

```
braid_Int braid_SplitCommworld (
    const MPI_Comm * comm_world,
    braid_Int px,
    MPI_Comm * comm_x,
    MPI_Comm * comm_t )
```

Split MPI commworld into *comm_x* and *comm_t*, the spatial and temporal communicators. The total number of processors will equal $P_x \times P_t$, there P_x is the number of procs in space, and P_t is the number of procs in time.

Parameters

<i>comm_world</i>	Global communicator to split
<i>px</i>	Number of processors parallelizing space for a single time step
<i>comm_x</i>	Spatial communicator (written as output)
<i>comm_t</i>	Temporal communicator (written as output)

14.6.4.44 `braid_WriteConvHistory()`

```
braid_Int braid_WriteConvHistory (
    braid_Core core,
    const char * filename )
```

After `Drive()` finishes, this function can be called to write out the convergence history (residuals for each iteration) to a file

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>filename</i>	Output file name

14.7 Interface routines for XBraid_Adjoint

Functions

- `braid_Int braid_InitAdjoint` (`braid_PtFcnObjectiveT` objectiveT, `braid_PtFcnObjectiveTDiff` objectiveT_diff, `braid_PtFcnStepDiff` step_diff, `braid_PtFcnResetGradient` reset_gradient, `braid_Core` *core_ptr)
- `braid_Int braid_SetTStartObjective` (`braid_Core` core, `braid_Real` tstart_obj)
- `braid_Int braid_SetTStopObjective` (`braid_Core` core, `braid_Real` tstop_obj)
- `braid_Int braid_SetPostprocessObjective` (`braid_Core` core, `braid_PtFcnPostprocessObjective` post_fcn)
- `braid_Int braid_SetPostprocessObjective_diff` (`braid_Core` core, `braid_PtFcnPostprocessObjective_diff` post_fcn_diff)
- `braid_Int braid_SetAbsTolAdjoint` (`braid_Core` core, `braid_Real` tol_adj)
- `braid_Int braid_SetRelTolAdjoint` (`braid_Core` core, `braid_Real` rtol_adj)
- `braid_Int braid_SetObjectiveOnly` (`braid_Core` core, `braid_Int` boolean)
- `braid_Int braid_GetObjective` (`braid_Core` core, `braid_Real` *objective_ptr)
- `braid_Int braid_GetRNormAdjoint` (`braid_Core` core, `braid_Real` *rnorm_adj)
- `braid_Int braid_SetRichardsonEstimation` (`braid_Core` core, `braid_Int` est_error, `braid_Int` richardson, `braid_Int` local_order)

14.7.1 Detailed Description

These are interface routines for computing adjoint sensitivities, i.e., adjoint-based gradients. These routines initialize the XBraid_Adjoint solver, and allow the user to set XBraid_Adjoint solver parameters.

14.7.2 Function Documentation

14.7.2.1 `braid_GetObjective()`

```
braid_Int braid_GetObjective (
    braid_Core core,
    braid_Real * objective_ptr )
```

After `braid_Drive` has finished, this returns the objective function value.

Parameters

<code>core</code>	braid_Core struct
<code>objective_ptr</code>	output: value of the objective function

14.7.2.2 `braid_GetRNormAdjoint()`

```
braid_Int braid_GetRNormAdjoint (
```

```

    braid_Core core,
    braid_Real * rnorm_adj )

```

After `braid_Drive` has finished, this returns the residual norm after the last XBraid iteration.

Parameters

<code>core</code>	braid_Core struct
<code>rnorm_adj</code>	output: adjoint residual norm of last iteration

14.7.2.3 braid_InitAdjoint()

```

braid_Int braid_InitAdjoint (
    braid_PtFcnObjectiveT objectiveT,
    braid_PtFcnObjectiveTDiff objectiveT_diff,
    braid_PtFcnStepDiff step_diff,
    braid_PtFcnResetGradient reset_gradient,
    braid_Core * core_ptr )

```

Initialize the XBraid_Adjoint solver for computing adjoint sensitivities. Once this function is called, `braid_Drive` will then compute gradient information alongside the primal XBraid computations.

Parameters

<code>objectiveT</code>	user-routine: evaluates the time-dependent objective function value at time t
<code>objectiveT_diff</code>	user-routine: differentiated version of the objectiveT function
<code>step_diff</code>	user-routine: differentiated version of the step function
<code>reset_gradient</code>	user-routine: set the gradient to zero (storage location of gradient up to user)
<code>core_ptr</code>	pointer to braid_Core (<code>_braid_Core</code>) struct

14.7.2.4 braid_SetAbsTolAdjoint()

```

braid_Int braid_SetAbsTolAdjoint (
    braid_Core core,
    braid_Real tol_adj )

```

Set an absolute halting tolerance for the adjoint residuals. XBraid_Adjoint stops iterating when the adjoint residual is below this value.

Parameters

<code>core</code>	braid_Core (<code>_braid_Core</code>) struct
<code>tol_adj</code>	absolute stopping tolerance for adjoint solve

14.7.2.5 `braid_SetObjectiveOnly()`

```
braid_Int braid_SetObjectiveOnly (
    braid_Core core,
    braid_Int boolean )
```

Set this option with `boolean = 1`, and then `braid_Drive(core)` will skip the gradient computation and only compute the forward ODE solution and objective function value. Reset this option with `boolean = 0` to turn the adjoint solve and gradient computations back on.

Parameters

<code>core</code>	<code>braid_Core</code> (<code>_braid_Core</code>) struct
<code>boolean</code>	set to '1' for computing objective function only, '0' for computing objective function AND gradients

14.7.2.6 `braid_SetPostprocessObjective()`

```
braid_Int braid_SetPostprocessObjective (
    braid_Core core,
    braid_PtFcnPostprocessObjective post_fcn )
```

Pass the postprocessing objective function F to `XBraid_Adjoint`. For a description of F , see the Section [Objective function evaluation](#).

Parameters

<code>core</code>	<code>braid_Core</code> (<code>_braid_Core</code>) struct
<code>post_fcn</code>	function pointer to postprocessing routine

14.7.2.7 `braid_SetPostprocessObjective_diff()`

```
braid_Int braid_SetPostprocessObjective_diff (
    braid_Core core,
    braid_PtFcnPostprocessObjective_diff post_fcn_diff )
```

Pass the differentiated version of the postprocessing objective function F to `XBraid_Adjoint`. For a description of F , see the Section [Objective function evaluation](#).

Parameters

<code>core</code>	<code>braid_Core</code> (<code>_braid_Core</code>) struct
<code>post_fcn_diff</code>	function pointer to differentiated postprocessing routine

14.7.2.8 braid_SetRelTolAdjoint()

```
braid_Int braid_SetRelTolAdjoint (
    braid_Core core,
    braid_Real rtol_adj )
```

Set a relative stopping tolerance for adjoint residuals. XBraid_Adjoint will stop iterating when the relative residual drops below this value. Be careful when using a relative stopping criterion. The initial residual may already be close to zero, and this will skew the relative tolerance. Absolute tolerances are recommended.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>rtol_adj</i>	relative stopping tolerance for adjoint solve

14.7.2.9 braid_SetRichardsonEstimation()

```
braid_Int braid_SetRichardsonEstimation (
    braid_Core core,
    braid_Int est_error,
    braid_Int richardson,
    braid_Int local_order )
```

Turn on built-in Richardson-based error estimation and/or extrapolation with XBraid. When enabled, the Richardson extrapolation (RE) option (`richardson == 1`) is used to improve the accuracy of the solution at the C-points on the finest level. When the built-in error estimate option is turned on (`est_error == 1`), RE is used to estimate the local truncation error at each point. These estimates can be accessed through `StepStatus` and `AccessStatus` functions.

The last parameter is `local_order`, which represents the LOCAL order of the time integration scheme. e.g. `local_order = 2` for Backward Euler.

Also, the Richardson error estimate is only available after roughly 1 Braid iteration. The estimate is given a dummy value of -1.0, until an actual estimate is available. Thus after an adaptive refinement, and a new hierarchy is formed, another iteration must pass before the error estimates are available again.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>est_error</i>	Boolean, if 1 compute Richardson-based error estimates, if 0, then do not
<i>richardson</i>	Boolean, if 1 carry out Richardson-based extrapolation to enhance accuracy on the fine-grid, if 0, then do not
<i>local_order</i>	Local order of the time integration scheme, e.g., <code>local_order=2</code> for backward Euler

14.7.2.10 `braid_SetTStartObjective()`

```
braid_Int braid_SetTStartObjective (
    braid_Core core,
    braid_Real tstart_obj )
```

Set a start time for integrating the objective function over time. Default is *tstart* of the primal XBraid run.

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>tstart_obj</i>	time value for starting the time-integration of the objective function

14.7.2.11 `braid_SetTStopObjective()`

```
braid_Int braid_SetTStopObjective (
    braid_Core core,
    braid_Real tstop_obj )
```

Set the end-time for integrating the objective function over time. Default is *tstop* of the primal XBraid run

Parameters

<i>core</i>	braid_Core (_braid_Core) struct
<i>tstop_obj</i>	time value for stopping the time-integration of the objective function

14.8 XBraid status structures

Define the different status types.

14.9 XBraid status routines

Functions

- `braid_Int braid_StatusGetT` (`braid_Status` status, `braid_Real *t_ptr`)
- `braid_Int braid_StatusGetTIndex` (`braid_Status` status, `braid_Int *idx_ptr`)
- `braid_Int braid_StatusGetIter` (`braid_Status` status, `braid_Int *iter_ptr`)
- `braid_Int braid_StatusGetLevel` (`braid_Status` status, `braid_Int *level_ptr`)
- `braid_Int braid_StatusGetNLevels` (`braid_Status` status, `braid_Int *nlevels_ptr`)
- `braid_Int braid_StatusGetNRefine` (`braid_Status` status, `braid_Int *nrefine_ptr`)
- `braid_Int braid_StatusGetNTPoints` (`braid_Status` status, `braid_Int *ntpoints_ptr`)
- `braid_Int braid_StatusGetResidual` (`braid_Status` status, `braid_Real *rnorm_ptr`)
- `braid_Int braid_StatusGetDone` (`braid_Status` status, `braid_Int *done_ptr`)
- `braid_Int braid_StatusGetTIUL` (`braid_Status` status, `braid_Int *iloc_upper`, `braid_Int *iloc_lower`, `braid_Int level`)
- `braid_Int braid_StatusGetTimeValues` (`braid_Status` status, `braid_Real **tvalues_ptr`, `braid_Int i_upper`, `braid_Int i_lower`, `braid_Int level`)
- `braid_Int braid_StatusGetTILD` (`braid_Status` status, `braid_Real *t_ptr`, `braid_Int *iter_ptr`, `braid_Int *level_ptr`, `braid_Int *done_ptr`)
- `braid_Int braid_StatusGetWrapperTest` (`braid_Status` status, `braid_Int *wtest_ptr`)
- `braid_Int braid_StatusGetCallingFunction` (`braid_Status` status, `braid_Int *cfunction_ptr`)
- `braid_Int braid_StatusGetCTprior` (`braid_Status` status, `braid_Real *ctprior_ptr`)
- `braid_Int braid_StatusGetCTstop` (`braid_Status` status, `braid_Real *ctstop_ptr`)
- `braid_Int braid_StatusGetFTPprior` (`braid_Status` status, `braid_Real *ftprior_ptr`)
- `braid_Int braid_StatusGetFTstop` (`braid_Status` status, `braid_Real *ftstop_ptr`)
- `braid_Int braid_StatusGetTpriorTstop` (`braid_Status` status, `braid_Real *t_ptr`, `braid_Real *ftprior_ptr`, `braid_Real *ftstop_ptr`, `braid_Real *ctprior_ptr`, `braid_Real *ctstop_ptr`)
- `braid_Int braid_StatusGetTstop` (`braid_Status` status, `braid_Real *tstop_ptr`)
- `braid_Int braid_StatusGetTstartTstop` (`braid_Status` status, `braid_Real *tstart_ptr`, `braid_Real *tstop_ptr`)
- `braid_Int braid_StatusGetTol` (`braid_Status` status, `braid_Real *tol_ptr`)
- `braid_Int braid_StatusGetRNorms` (`braid_Status` status, `braid_Int *nrequest_ptr`, `braid_Real *rnorms_ptr`)
- `braid_Int braid_StatusGetOldFineTolx` (`braid_Status` status, `braid_Real *old_fine_tolx_ptr`)
- `braid_Int braid_StatusSetOldFineTolx` (`braid_Status` status, `braid_Real old_fine_tolx`)
- `braid_Int braid_StatusSetTightFineTolx` (`braid_Status` status, `braid_Real tight_fine_tolx`)
- `braid_Int braid_StatusSetRFactor` (`braid_Status` status, `braid_Real rfactor`)
- `braid_Int braid_StatusSetRefinementDtValues` (`braid_Status` status, `braid_Real rfactor`, `braid_Real *dtarray`)
- `braid_Int braid_StatusSetRSpace` (`braid_Status` status, `braid_Real r_space`)
- `braid_Int braid_StatusGetMessageType` (`braid_Status` status, `braid_Int *messagetype_ptr`)
- `braid_Int braid_StatusSetSize` (`braid_Status` status, `braid_Real size`)
- `braid_Int braid_StatusGetSingleErrorEstStep` (`braid_Status` status, `braid_Real *estimate`)
- `braid_Int braid_StatusGetSingleErrorEstAccess` (`braid_Status` status, `braid_Real *estimate`)
- `braid_Int braid_StatusGetNumErrorEst` (`braid_Status` status, `braid_Int *npoints`)
- `braid_Int braid_StatusGetAllErrorEst` (`braid_Status` status, `braid_Real *error_est`)

14.9.1 Detailed Description

XBraid status structures and associated Get/Set routines are what tell the user the status of the simulation when their routines (step, coarsen/refine, access) are called.

14.9.2 Function Documentation

14.9.2.1 `braid_StatusGetAllErrorEst()`

```
braid_Int braid_StatusGetAllErrorEst (
    braid_Status status,
    braid_Real * error_est )
```

Get All the Richardson based error estimates, e.g. from inside Sync. Use this function in conjunction with `GetNumErrorEst()`. Workflow: use `GetNumErrorEst()` to get the size of the needed user-array that will hold the error estimates, then pre-allocate array, then call this function to write error estimates to the user-array, then post-process array in user-code. This post-processing will often occur in the Sync function. See examples/ex-06.c.

The `error_est` array must be user-allocated.

Parameters

<i>status</i>	structure containing current simulation info
<i>error_est</i>	output, user-allocated error estimate array, written by Braid, equals -1 if not available yet (e.g., before iteration 1, or after refinement)

14.9.2.2 `braid_StatusGetCallingFunction()`

```
braid_Int braid_StatusGetCallingFunction (
    braid_Status status,
    braid_Int * cfunction_ptr )
```

Return flag indicating from which function the vector is accessed

Parameters

<i>status</i>	structure containing current simulation info
<i>cfunction_ptr</i>	output, function number (0=FInterp, 1=FRestrict, 2=FRefine, 3=FAccess, 4=FRefine after refinement, 5=Drive Top of Cycle)

14.9.2.3 `braid_StatusGetCTprior()`

```
braid_Int braid_StatusGetCTprior (
    braid_Status status,
    braid_Real * ctprior_ptr )
```

Return the **coarse grid** time value to the left of the current time value from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>ctprior_ptr</i>	output, time value to the left of current time value on coarse grid

14.9.2.4 `braid_StatusGetCTstop()`

```
braid_Int braid_StatusGetCTstop (
    braid_Status status,
    braid_Real * ctstop_ptr )
```

Return the **coarse grid** time value to the right of the current time value from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>ctstop_ptr</i>	output, time value to the right of current time value on coarse grid

14.9.2.5 `braid_StatusGetDone()`

```
braid_Int braid_StatusGetDone (
    braid_Status status,
    braid_Int * done_ptr )
```

Return whether XBraid is done for the current simulation.

done_ptr = 1 indicates that XBraid has finished iterating, (either maxiter has been reached, or the tolerance has been met).

Parameters

<i>status</i>	structure containing current simulation info
<i>done_ptr</i>	output, =1 if XBraid has finished, else =0

14.9.2.6 `braid_StatusGetFTPrior()`

```
braid_Int braid_StatusGetFTPrior (
    braid_Status status,
    braid_Real * ftprior_ptr )
```

Return the **fine grid** time value to the left of the current time value from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>ftprior_ptr</i>	output, time value to the left of current time value on fine grid

14.9.2.7 `braid_StatusGetFTstop()`

```
braid_Int braid_StatusGetFTstop (
    braid_Status status,
    braid_Real * fstop_ptr )
```

Return the **fine grid** time value to the right of the current time value from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>fstop_ptr</i>	output, time value to the right of current time value on fine grid

14.9.2.8 `braid_StatusGetIter()`

```
braid_Int braid_StatusGetIter (
    braid_Status status,
    braid_Int * iter_ptr )
```

Return the current iteration from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>iter_ptr</i>	output, current XBraid iteration number

14.9.2.9 `braid_StatusGetLevel()`

```
braid_Int braid_StatusGetLevel (
    braid_Status status,
    braid_Int * level_ptr )
```

Return the current XBraid level from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>level_ptr</i>	output, current level in XBraid

14.9.2.10 `braid_StatusGetMessageType()`

```
braid_Int braid_StatusGetMessageType (
    braid_Status status,
    braid_Int * messagetype_ptr )
```

Return the current message type from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>messagetype_ptr</i>	output, type of message, 0: for Step(), 1: for load balancing

14.9.2.11 `braid_StatusGetNLevels()`

```
braid_Int braid_StatusGetNLevels (
    braid_Status status,
    braid_Int * nlevels_ptr )
```

Return the total number of XBraid levels from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>nlevels_ptr</i>	output, number of levels in XBraid

14.9.2.12 `braid_StatusGetNRefine()`

```
braid_Int braid_StatusGetNRefine (
    braid_Status status,
    braid_Int * nrefine_ptr )
```

Return the number of refinements done.

Parameters

<i>status</i>	structure containing current simulation info
<i>nrefine_ptr</i>	output, number of refinements done

14.9.2.13 `braid_StatusGetNTPoints()`

```
braid_Int braid_StatusGetNTPoints (
    braid_Status status,
    braid_Int * ntpoints_ptr )
```

Return the global number of time points on the fine grid.

Parameters

<i>status</i>	structure containing current simulation info
<i>ntpoints_ptr</i>	output, number of time points on the fine grid

14.9.2.14 `braid_StatusGetNumErrorEst()`

```
braid_Int braid_StatusGetNumErrorEst (
    braid_Status status,
    braid_Int * npoints )
```

Get the number of local Richardson-based error estimates stored on this processor. Use this function in conjunction with `GetAllErrorEst()`. Workflow: use this function to get the size of the needed user-array that will hold the error estimates, then pre-allocate array, then call `GetAllErrorEst()` to write error estimates to the user-array, then post-process array in user-code. This post-processing will often occur in the `Sync` function. See examples/ex-06.c.

Parameters

<i>status</i>	structure containing current simulation info
<i>npoints</i>	output, number of locally stored Richardson error estimates

14.9.2.15 `braid_StatusGetOldFineTolx()`

```
braid_Int braid_StatusGetOldFineTolx (
    braid_Status status,
    braid_Real * old_fine_tolx_ptr )
```

Return the previous `old_fine_tolx` set through `braid_StatusSetOldFineTolx`. This is used especially by `*braid_Get↔SpatialAccuracy`

Parameters

<i>status</i>	structure containing current simulation info
<i>old_fine_tolx_ptr</i>	output, previous <i>old_fine_tolx</i> , set through <i>braid_StepStatusSetOldFineTolx</i>

14.9.2.16 `braid_StatusGetResidual()`

```
braid_Int braid_StatusGetResidual (
    braid_Status status,
    braid_Real * rnorm_ptr )
```

Return the current residual norm from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>rnorm_ptr</i>	output, current residual norm

14.9.2.17 `braid_StatusGetRNorms()`

```
braid_Int braid_StatusGetRNorms (
    braid_Status status,
    braid_Int * nrequest_ptr,
    braid_Real * rnorms_ptr )
```

Return the current XBraid residual history. If *nrequest_ptr* is negative, return the last *nrequest_ptr* residual norms. If positive, return the first *nrequest_ptr* residual norms. Upon exit, *nrequest_ptr* holds the number of residuals actually returned.

Parameters

<i>status</i>	structure containing current simulation info
<i>nrequest_ptr</i>	input/output, input: number of requested residual norms, output: number actually copied
<i>rnorms_ptr</i>	output, XBraid residual norm history, of length <i>nrequest_ptr</i>

14.9.2.18 `braid_StatusGetSingleErrorEstAccess()`

```
braid_Int braid_StatusGetSingleErrorEstAccess (
    braid_Status status,
    braid_Real * estimate )
```

Get the Richardson based error estimate at the single time point currently accessible from Access.

Note that Access needs specific logic distinct from Step, hence please use [braid_StepStatusGetSingleErrorEstStep](#) for the user Step() function.

Parameters

<i>status</i>	structure containing current simulation info
<i>estimate</i>	output, error estimate, equals -1 if not available yet (e.g., before iteration 1, or after refinement)

14.9.2.19 braid_StatusGetSingleErrorEstStep()

```
braid_Int braid_StatusGetSingleErrorEstStep (
    braid_Status status,
    braid_Real * estimate )
```

Get the Richardson based error estimate at the single time point currently being "Stepped", i.e., return the current error estimate for the time point at "tstart".

Note that Step needs specific logic distinct from Access, hence please use [braid_AccessStatusGetSingleErrorEstAccess](#) for the user Access() function.

Parameters

<i>status</i>	structure containing current simulation info
<i>estimate</i>	output, error estimate, equals -1 if not available yet (e.g., before iteration 1, or after refinement)

14.9.2.20 braid_StatusGetT()

```
braid_Int braid_StatusGetT (
    braid_Status status,
    braid_Real * t_ptr )
```

Return the current time from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>t_ptr</i>	output, current time

14.9.2.21 braid_StatusGetTILD()

```
braid_Int braid_StatusGetTILD (
```

```

    braid_Status status,
    braid_Real * t_ptr,
    braid_Int * iter_ptr,
    braid_Int * level_ptr,
    braid_Int * done_ptr )

```

Return XBraid status for the current simulation. Four values are returned.

TILD : time, iteration, level, done

These values are also available through individual Get routines. These individual routines are the location of detailed documentation on each parameter, e.g., see *braid_StatusGetDone* for more information on the *done* value.

Parameters

<i>status</i>	structure containing current simulation info
<i>t_ptr</i>	output, current time
<i>iter_ptr</i>	output, current XBraid iteration number
<i>level_ptr</i>	output, current level in XBraid
<i>done_ptr</i>	output, =1 if XBraid has finished, else =0

14.9.2.22 *braid_StatusGetTimeValues()*

```

braid_Int braid_StatusGetTimeValues (
    braid_Status status,
    braid_Real ** tvalues_ptr,
    braid_Int i_upper,
    braid_Int i_lower,
    braid_Int level )

```

Returns an array of time values corresponding to the given inputs. The inputs are the level you want the time values from, the upper time point index you want the value of, and the lower time point index you want the time value of. The output is then filled with all time values from the upper index to the lower index, inclusive.

The caller is responsible for allocating and managing the memory for the array. Time values are filled in so that *tvalues_ptr*[0] corresponds to the lower time index.

Parameters

<i>status</i>	structure containing current simulation info
<i>tvalues_ptr</i>	output, time point values for the requested range of indices
<i>i_upper</i>	input, upper index of the desired time value range (inclusive)
<i>i_lower</i>	input, lower index of the desired time value range (inclusive)
<i>level</i>	input, level for the desired time values

14.9.2.23 `braid_StatusGetTIndex()`

```
braid_Int braid_StatusGetTIndex (
    braid_Status status,
    braid_Int * idx_ptr )
```

Return the index value corresponding to the current time value from the Status structure.

For Step(), this corresponds to the time-index of "tstart", as this is the time-index of the input vector. That is, NOT the time-index of "tstop". For Access, this corresponds just simply to the time-index of the input vector.

Parameters

<i>status</i>	structure containing current simulation info
<i>idx_ptr</i>	output, global index value corresponding to current time value

14.9.2.24 `braid_StatusGetTIUL()`

```
braid_Int braid_StatusGetTIUL (
    braid_Status status,
    braid_Int * iloc_upper,
    braid_Int * iloc_lower,
    braid_Int level )
```

Returns upper and lower time point indices on this processor. Two values are returned. Requires the user to specify which level they want the time point indices from.

Parameters

<i>status</i>	structure containing current simulation info
<i>iloc_upper</i>	output, the upper time point index on this processor
<i>iloc_lower</i>	output, the lower time point index on this processor
<i>level</i>	input, level for the desired indices

14.9.2.25 `braid_StatusGetTol()`

```
braid_Int braid_StatusGetTol (
    braid_Status status,
    braid_Real * tol_ptr )
```

Return the current XBraid stopping tolerance

Parameters

<i>status</i>	structure containing current simulation info
<i>tol_ptr</i>	output, current XBraid stopping tolerance

14.9.2.26 `braid_StatusGetTpriorTstop()`

```
braid_Int braid_StatusGetTpriorTstop (
    braid_Status status,
    braid_Real * t_ptr,
    braid_Real * ftprior_ptr,
    braid_Real * ftstop_ptr,
    braid_Real * ctprior_ptr,
    braid_Real * ctstop_ptr )
```

Return XBraid status for the current simulation. Five values are returned, `tstart`, `f_tprior`, `f_tstop`, `c_tprior`, `c_tstop`.

These values are also available through individual Get routines. These individual routines are the location of detailed documentation on each parameter, e.g., see `braid_StatusGetCTprior` for more information on the `c_tprior` value.

Parameters

<code>status</code>	structure containing current simulation info
<code>t_ptr</code>	output, current time
<code>ftprior_ptr</code>	output, time value to the left of current time value on fine grid
<code>ftstop_ptr</code>	output, time value to the right of current time value on fine grid
<code>ctprior_ptr</code>	output, time value to the left of current time value on coarse grid
<code>ctstop_ptr</code>	output, time value to the right of current time value on coarse grid

14.9.2.27 `braid_StatusGetTstartTstop()`

```
braid_Int braid_StatusGetTstartTstop (
    braid_Status status,
    braid_Real * tstart_ptr,
    braid_Real * tstop_ptr )
```

Return XBraid status for the current simulation. Two values are returned, `tstart` and `tstop`.

These values are also available through individual Get routines. These individual routines are the location of detailed documentation on each parameter, e.g., see `braid_StatusGetTstart` for more information on the `tstart` value.

Parameters

<code>status</code>	structure containing current simulation info
<code>tstart_ptr</code>	output, current time
<code>tstop_ptr</code>	output, next time value to evolve towards

14.9.2.28 `braid_StatusGetTstop()`

```
braid_Int braid_StatusGetTstop (
    braid_Status status,
    braid_Real * tstop_ptr )
```

Return the time value to the right of the current time value from the Status structure.

Parameters

<i>status</i>	structure containing current simulation info
<i>tstop_ptr</i>	output, next time value to evolve towards

14.9.2.29 `braid_StatusGetWrapperTest()`

```
braid_Int braid_StatusGetWrapperTest (
    braid_Status status,
    braid_Int * wtest_ptr )
```

Return whether this is a wrapper test or an XBraid run

Parameters

<i>status</i>	structure containing current simulation info
<i>wtest_ptr</i>	output, =1 if this is a wrapper test, =0 if XBraid run

14.9.2.30 `braid_StatusSetOldFineTolx()`

```
braid_Int braid_StatusSetOldFineTolx (
    braid_Status status,
    braid_Real old_fine_tolx )
```

Set *old_fine_tolx*, available for retrieval through `braid_StatusGetOldFineTolx` This is used especially by `*braid_Get↔SpatialAccuracy`

Parameters

<i>status</i>	structure containing current simulation info
<i>old_fine_tolx</i>	input, the last used fine_tolx

14.9.2.31 `braid_StatusSetRefinementDtValues()`

```
braid_Int braid_StatusSetRefinementDtValues (
    braid_Status status,
    braid_Real rfactor,
    braid_Real * dtarray )
```

Set time step sizes for refining the time interval non-uniformly.

Parameters

<i>status</i>	structure containing current simulation info
<i>rfactor</i>	input, number of subintervals
<i>dtarray</i>	input, array of dt values for non-uniform refinement

14.9.2.32 `braid_StatusSetRFactor()`

```
braid_Int braid_StatusSetRFactor (
    braid_Status status,
    braid_Real rfactor )
```

Set the rfactor, a desired refinement factor for this interval. rfactor=1 indicates no refinement, otherwise, this interval is subdivided rfactor times (uniform refinement).

Parameters

<i>status</i>	structure containing current simulation info
<i>rfactor</i>	input, user-determined desired rfactor

14.9.2.33 `braid_StatusSetRSpace()`

```
braid_Int braid_StatusSetRSpace (
    braid_Status status,
    braid_Real r_space )
```

Set the `r_space` flag. When set = 1, spatial coarsening will be called, for all local time points, following the completion of the current iteration, provided rfactored are not set at any global time point. This allows for spatial refinement without temporal refinement

Parameters

<i>status</i>	structure containing current simulation info
<i>r_space</i>	input, if 1, call spatial refinement on finest grid after this iter

14.9.2.34 `braid_StatusSetSize()`

```
braid_Int braid_StatusSetSize (  
    braid_Status status,  
    braid_Real size )
```

Set the size of the buffer. If set by user, the send buffer will be "size" bytes in length. If not, BufSize is used.

Parameters

<i>status</i>	structure containing current simulation info
<i>size</i>	input, size of the send buffer

14.9.2.35 `braid_StatusSetTightFineTolx()`

```
braid_Int braid_StatusSetTightFineTolx (  
    braid_Status status,  
    braid_Real tight_fine_tolx )
```

Set *tight_fine_tolx*, boolean variable indicating whether the tightest tolerance has been used for spatial solves (implicit schemes). This value must be 1 in order for XBraid to halt (unless maxiter is reached)

Parameters

<i>status</i>	structure containing current simulation info
<i>tight_fine_tolx</i>	input, boolean indicating whether the tight tol has been used

14.10 Inherited XBraid status routines

Functions

- [braid_Int braid_AccessStatusGetT](#) (braid_AccessStatus s, [braid_Real](#) *v1)
- [braid_Int braid_AccessStatusGetTIndex](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetTIter](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetLevel](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetNLevels](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetNRefine](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetNTPoints](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetResidual](#) (braid_AccessStatus s, [braid_Real](#) *v1)
- [braid_Int braid_AccessStatusGetDone](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetTILD](#) (braid_AccessStatus s, [braid_Real](#) *v1, [braid_Int](#) *v2, [braid_Int](#) *v3, [braid_Int](#) *v4)
- [braid_Int braid_AccessStatusGetWrapperTest](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetCallingFunction](#) (braid_AccessStatus s, [braid_Int](#) *v1)
- [braid_Int braid_AccessStatusGetSingleErrorEstAccess](#) (braid_AccessStatus s, [braid_Real](#) *v1)
- [braid_Int braid_SyncStatusGetTIUL](#) (braid_SyncStatus s, [braid_Int](#) *v1, [braid_Int](#) *v2, [braid_Int](#) *v3)
- [braid_Int braid_SyncStatusGetTimeValues](#) (braid_SyncStatus s, [braid_Real](#) **v1, [braid_Int](#) *v2, [braid_Int](#) *v3, [braid_Int](#) *v4)
- [braid_Int braid_SyncStatusGetTIter](#) (braid_SyncStatus s, [braid_Int](#) *v1)
- [braid_Int braid_SyncStatusGetLevel](#) (braid_SyncStatus s, [braid_Int](#) *v1)
- [braid_Int braid_SyncStatusGetNLevels](#) (braid_SyncStatus s, [braid_Int](#) *v1)
- [braid_Int braid_SyncStatusGetNRefine](#) (braid_SyncStatus s, [braid_Int](#) *v1)
- [braid_Int braid_SyncStatusGetNTPoints](#) (braid_SyncStatus s, [braid_Int](#) *v1)
- [braid_Int braid_SyncStatusGetDone](#) (braid_SyncStatus s, [braid_Int](#) *v1)
- [braid_Int braid_SyncStatusGetCallingFunction](#) (braid_SyncStatus s, [braid_Int](#) *v1)
- [braid_Int braid_SyncStatusGetNumErrorEst](#) (braid_SyncStatus s, [braid_Int](#) *v1)
- [braid_Int braid_SyncStatusGetAllErrorEst](#) (braid_SyncStatus s, [braid_Real](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetT](#) (braid_CoarsenRefStatus s, [braid_Real](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetTIndex](#) (braid_CoarsenRefStatus s, [braid_Int](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetTIter](#) (braid_CoarsenRefStatus s, [braid_Int](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetLevel](#) (braid_CoarsenRefStatus s, [braid_Int](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetNLevels](#) (braid_CoarsenRefStatus s, [braid_Int](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetNRefine](#) (braid_CoarsenRefStatus s, [braid_Int](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetNTPoints](#) (braid_CoarsenRefStatus s, [braid_Int](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetCTprior](#) (braid_CoarsenRefStatus s, [braid_Real](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetCTstop](#) (braid_CoarsenRefStatus s, [braid_Real](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetFTprior](#) (braid_CoarsenRefStatus s, [braid_Real](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetFTstop](#) (braid_CoarsenRefStatus s, [braid_Real](#) *v1)
- [braid_Int braid_CoarsenRefStatusGetTpriorTstop](#) (braid_CoarsenRefStatus s, [braid_Real](#) *v1, [braid_Real](#) *v2, [braid_Real](#) *v3, [braid_Real](#) *v4, [braid_Real](#) *v5)
- [braid_Int braid_StepStatusGetT](#) (braid_StepStatus s, [braid_Real](#) *v1)
- [braid_Int braid_StepStatusGetTIndex](#) (braid_StepStatus s, [braid_Int](#) *v1)
- [braid_Int braid_StepStatusGetTIter](#) (braid_StepStatus s, [braid_Int](#) *v1)
- [braid_Int braid_StepStatusGetLevel](#) (braid_StepStatus s, [braid_Int](#) *v1)
- [braid_Int braid_StepStatusGetNLevels](#) (braid_StepStatus s, [braid_Int](#) *v1)
- [braid_Int braid_StepStatusGetNRefine](#) (braid_StepStatus s, [braid_Int](#) *v1)
- [braid_Int braid_StepStatusGetNTPoints](#) (braid_StepStatus s, [braid_Int](#) *v1)
- [braid_Int braid_StepStatusGetTstop](#) (braid_StepStatus s, [braid_Real](#) *v1)

- `braid_Int braid_StepStatusGetTstartTstop` (`braid_StepStatus s`, `braid_Real *v1`, `braid_Real *v2`)
- `braid_Int braid_StepStatusGetTol` (`braid_StepStatus s`, `braid_Real *v1`)
- `braid_Int braid_StepStatusGetRNorms` (`braid_StepStatus s`, `braid_Int *v1`, `braid_Real *v2`)
- `braid_Int braid_StepStatusGetOldFineTolx` (`braid_StepStatus s`, `braid_Real *v1`)
- `braid_Int braid_StepStatusSetOldFineTolx` (`braid_StepStatus s`, `braid_Real v1`)
- `braid_Int braid_StepStatusSetTightFineTolx` (`braid_StepStatus s`, `braid_Real v1`)
- `braid_Int braid_StepStatusSetRFactor` (`braid_StepStatus s`, `braid_Real v1`)
- `braid_Int braid_StepStatusSetRSpace` (`braid_StepStatus s`, `braid_Real v1`)
- `braid_Int braid_StepStatusGetSingleErrorEstStep` (`braid_StepStatus s`, `braid_Real *v1`)
- `braid_Int braid_BufferStatusGetMessageType` (`braid_BufferStatus s`, `braid_Int *v1`)
- `braid_Int braid_BufferStatusSetSize` (`braid_BufferStatus s`, `braid_Real v1`)
- `braid_Int braid_ObjectiveStatusGetT` (`braid_ObjectiveStatus s`, `braid_Real *v1`)
- `braid_Int braid_ObjectiveStatusGetTIndex` (`braid_ObjectiveStatus s`, `braid_Int *v1`)
- `braid_Int braid_ObjectiveStatusGetIter` (`braid_ObjectiveStatus s`, `braid_Int *v1`)
- `braid_Int braid_ObjectiveStatusGetLevel` (`braid_ObjectiveStatus s`, `braid_Int *v1`)
- `braid_Int braid_ObjectiveStatusGetNLevels` (`braid_ObjectiveStatus s`, `braid_Int *v1`)
- `braid_Int braid_ObjectiveStatusGetNRefine` (`braid_ObjectiveStatus s`, `braid_Int *v1`)
- `braid_Int braid_ObjectiveStatusGetNTPoints` (`braid_ObjectiveStatus s`, `braid_Int *v1`)
- `braid_Int braid_ObjectiveStatusGetTol` (`braid_ObjectiveStatus s`, `braid_Real *v1`)

14.10.1 Detailed Description

These are the 'inherited' Status Get/Set functions. See the *XBraid status routines* section for the description of each function. For example, for `braid_StepStatusGetT(...)`, you would look up `braid_StatusGetT(...)`

14.10.2 Function Documentation

14.10.2.1 `braid_AccessStatusGetCallingFunction()`

```
braid_Int braid_AccessStatusGetCallingFunction (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.2 `braid_AccessStatusGetDone()`

```
braid_Int braid_AccessStatusGetDone (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.3 `braid_AccessStatusGetIter()`

```
braid_Int braid_AccessStatusGetIter (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.4 `braid_AccessStatusGetLevel()`

```
braid_Int braid_AccessStatusGetLevel (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.5 `braid_AccessStatusGetNLevels()`

```
braid_Int braid_AccessStatusGetNLevels (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.6 `braid_AccessStatusGetNRefine()`

```
braid_Int braid_AccessStatusGetNRefine (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.7 `braid_AccessStatusGetNTPoints()`

```
braid_Int braid_AccessStatusGetNTPoints (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.8 `braid_AccessStatusGetResidual()`

```
braid_Int braid_AccessStatusGetResidual (
    braid_AccessStatus s,
    braid_Real * v1 )
```

14.10.2.9 braid_AccessStatusGetSingleErrorEstAccess()

```
braid_Int braid_AccessStatusGetSingleErrorEstAccess (
    braid_AccessStatus s,
    braid_Real * v1 )
```

14.10.2.10 braid_AccessStatusGetT()

```
braid_Int braid_AccessStatusGetT (
    braid_AccessStatus s,
    braid_Real * v1 )
```

14.10.2.11 braid_AccessStatusGetTILD()

```
braid_Int braid_AccessStatusGetTILD (
    braid_AccessStatus s,
    braid_Real * v1,
    braid_Int * v2,
    braid_Int * v3,
    braid_Int * v4 )
```

14.10.2.12 braid_AccessStatusGetTIndex()

```
braid_Int braid_AccessStatusGetTIndex (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.13 braid_AccessStatusGetWrapperTest()

```
braid_Int braid_AccessStatusGetWrapperTest (
    braid_AccessStatus s,
    braid_Int * v1 )
```

14.10.2.14 braid_BufferStatusGetMessageType()

```
braid_Int braid_BufferStatusGetMessageType (
    braid_BufferStatus s,
    braid_Int * v1 )
```


14.10.2.15 braid_BufferStatusSetSize()

```
braid_Int braid_BufferStatusSetSize (  
    braid_BufferStatus s,  
    braid_Real v1 )
```

14.10.2.16 braid_CoarsenRefStatusGetCTprior()

```
braid_Int braid_CoarsenRefStatusGetCTprior (  
    braid_CoarsenRefStatus s,  
    braid_Real * v1 )
```

14.10.2.17 braid_CoarsenRefStatusGetCTstop()

```
braid_Int braid_CoarsenRefStatusGetCTstop (  
    braid_CoarsenRefStatus s,  
    braid_Real * v1 )
```

14.10.2.18 braid_CoarsenRefStatusGetFTprior()

```
braid_Int braid_CoarsenRefStatusGetFTprior (  
    braid_CoarsenRefStatus s,  
    braid_Real * v1 )
```

14.10.2.19 braid_CoarsenRefStatusGetFTstop()

```
braid_Int braid_CoarsenRefStatusGetFTstop (  
    braid_CoarsenRefStatus s,  
    braid_Real * v1 )
```

14.10.2.20 braid_CoarsenRefStatusGetIter()

```
braid_Int braid_CoarsenRefStatusGetIter (  
    braid_CoarsenRefStatus s,  
    braid_Int * v1 )
```

14.10.2.21 braid_CoarsenRefStatusGetLevel()

```
braid_Int braid_CoarsenRefStatusGetLevel (
    braid_CoarsenRefStatus s,
    braid_Int * v1 )
```

14.10.2.22 braid_CoarsenRefStatusGetNLevels()

```
braid_Int braid_CoarsenRefStatusGetNLevels (
    braid_CoarsenRefStatus s,
    braid_Int * v1 )
```

14.10.2.23 braid_CoarsenRefStatusGetNRefine()

```
braid_Int braid_CoarsenRefStatusGetNRefine (
    braid_CoarsenRefStatus s,
    braid_Int * v1 )
```

14.10.2.24 braid_CoarsenRefStatusGetNTPoints()

```
braid_Int braid_CoarsenRefStatusGetNTPoints (
    braid_CoarsenRefStatus s,
    braid_Int * v1 )
```

14.10.2.25 braid_CoarsenRefStatusGetT()

```
braid_Int braid_CoarsenRefStatusGetT (
    braid_CoarsenRefStatus s,
    braid_Real * v1 )
```

14.10.2.26 braid_CoarsenRefStatusGetTIndex()

```
braid_Int braid_CoarsenRefStatusGetTIndex (
    braid_CoarsenRefStatus s,
    braid_Int * v1 )
```

14.10.2.27 braid_CoarsenRefStatusGetTpriorTstop()

```
braid_Int braid_CoarsenRefStatusGetTpriorTstop (
    braid_CoarsenRefStatus s,
    braid_Real * v1,
    braid_Real * v2,
    braid_Real * v3,
    braid_Real * v4,
    braid_Real * v5 )
```

14.10.2.28 braid_ObjectiveStatusGetIter()

```
braid_Int braid_ObjectiveStatusGetIter (
    braid_ObjectiveStatus s,
    braid_Int * v1 )
```

14.10.2.29 braid_ObjectiveStatusGetLevel()

```
braid_Int braid_ObjectiveStatusGetLevel (
    braid_ObjectiveStatus s,
    braid_Int * v1 )
```

14.10.2.30 braid_ObjectiveStatusGetNLevels()

```
braid_Int braid_ObjectiveStatusGetNLevels (
    braid_ObjectiveStatus s,
    braid_Int * v1 )
```

14.10.2.31 braid_ObjectiveStatusGetNRefine()

```
braid_Int braid_ObjectiveStatusGetNRefine (
    braid_ObjectiveStatus s,
    braid_Int * v1 )
```

14.10.2.32 braid_ObjectiveStatusGetNTPoints()

```
braid_Int braid_ObjectiveStatusGetNTPoints (
    braid_ObjectiveStatus s,
    braid_Int * v1 )
```

14.10.2.33 braid_ObjectiveStatusGetT()

```
braid_Int braid_ObjectiveStatusGetT (
    braid_ObjectiveStatus s,
    braid_Real * v1 )
```

14.10.2.34 braid_ObjectiveStatusGetTIndex()

```
braid_Int braid_ObjectiveStatusGetTIndex (
    braid_ObjectiveStatus s,
    braid_Int * v1 )
```

14.10.2.35 braid_ObjectiveStatusGetTol()

```
braid_Int braid_ObjectiveStatusGetTol (
    braid_ObjectiveStatus s,
    braid_Real * v1 )
```

14.10.2.36 braid_StepStatusGetIter()

```
braid_Int braid_StepStatusGetIter (
    braid_StepStatus s,
    braid_Int * v1 )
```

14.10.2.37 braid_StepStatusGetLevel()

```
braid_Int braid_StepStatusGetLevel (
    braid_StepStatus s,
    braid_Int * v1 )
```

14.10.2.38 braid_StepStatusGetNLevels()

```
braid_Int braid_StepStatusGetNLevels (
    braid_StepStatus s,
    braid_Int * v1 )
```

14.10.2.39 braid_StepStatusGetNRefine()

```
braid_Int braid_StepStatusGetNRefine (
    braid_StepStatus s,
    braid_Int * v1 )
```

14.10.2.40 braid_StepStatusGetNTPoints()

```
braid_Int braid_StepStatusGetNTPoints (
    braid_StepStatus s,
    braid_Int * v1 )
```

14.10.2.41 braid_StepStatusGetOldFineTolx()

```
braid_Int braid_StepStatusGetOldFineTolx (
    braid_StepStatus s,
    braid_Real * v1 )
```

14.10.2.42 braid_StepStatusGetRNorms()

```
braid_Int braid_StepStatusGetRNorms (
    braid_StepStatus s,
    braid_Int * v1,
    braid_Real * v2 )
```

14.10.2.43 braid_StepStatusGetSingleErrorEstStep()

```
braid_Int braid_StepStatusGetSingleErrorEstStep (
    braid_StepStatus s,
    braid_Real * v1 )
```

14.10.2.44 braid_StepStatusGetT()

```
braid_Int braid_StepStatusGetT (
    braid_StepStatus s,
    braid_Real * v1 )
```

14.10.2.45 braid_StepStatusGetTIndex()

```
braid_Int braid_StepStatusGetTIndex (
    braid_StepStatus s,
    braid_Int * v1 )
```

14.10.2.46 braid_StepStatusGetTol()

```
braid_Int braid_StepStatusGetTol (
    braid_StepStatus s,
    braid_Real * v1 )
```

14.10.2.47 braid_StepStatusGetTstartTstop()

```
braid_Int braid_StepStatusGetTstartTstop (
    braid_StepStatus s,
    braid_Real * v1,
    braid_Real * v2 )
```

14.10.2.48 braid_StepStatusGetTstop()

```
braid_Int braid_StepStatusGetTstop (
    braid_StepStatus s,
    braid_Real * v1 )
```

14.10.2.49 braid_StepStatusSetOldFineTolx()

```
braid_Int braid_StepStatusSetOldFineTolx (
    braid_StepStatus s,
    braid_Real v1 )
```

14.10.2.50 braid_StepStatusSetRFactor()

```
braid_Int braid_StepStatusSetRFactor (
    braid_StepStatus s,
    braid_Real v1 )
```

14.10.2.51 braid_StepStatusSetRSpace()

```
braid_Int braid_StepStatusSetRSpace (
    braid_StepStatus s,
    braid_Real v1 )
```

14.10.2.52 braid_StepStatusSetTightFineTolx()

```
braid_Int braid_StepStatusSetTightFineTolx (
    braid_StepStatus s,
    braid_Real v1 )
```

14.10.2.53 braid_SyncStatusGetAllErrorEst()

```
braid_Int braid_SyncStatusGetAllErrorEst (
    braid_SyncStatus s,
    braid_Real * v1 )
```

14.10.2.54 braid_SyncStatusGetCallingFunction()

```
braid_Int braid_SyncStatusGetCallingFunction (
    braid_SyncStatus s,
    braid_Int * v1 )
```

14.10.2.55 braid_SyncStatusGetDone()

```
braid_Int braid_SyncStatusGetDone (
    braid_SyncStatus s,
    braid_Int * v1 )
```

14.10.2.56 braid_SyncStatusGetIter()

```
braid_Int braid_SyncStatusGetIter (
    braid_SyncStatus s,
    braid_Int * v1 )
```

14.10.2.57 braid_SyncStatusGetLevel()

```
braid_Int braid_SyncStatusGetLevel (
    braid_SyncStatus s,
    braid_Int * v1 )
```

14.10.2.58 braid_SyncStatusGetNLevels()

```
braid_Int braid_SyncStatusGetNLevels (
    braid_SyncStatus s,
    braid_Int * v1 )
```

14.10.2.59 braid_SyncStatusGetNRefine()

```
braid_Int braid_SyncStatusGetNRefine (
    braid_SyncStatus s,
    braid_Int * v1 )
```

14.10.2.60 braid_SyncStatusGetNTPoints()

```
braid_Int braid_SyncStatusGetNTPoints (
    braid_SyncStatus s,
    braid_Int * v1 )
```

14.10.2.61 braid_SyncStatusGetNumErrorEst()

```
braid_Int braid_SyncStatusGetNumErrorEst (
    braid_SyncStatus s,
    braid_Int * v1 )
```

14.10.2.62 braid_SyncStatusGetTimeValues()

```
braid_Int braid_SyncStatusGetTimeValues (
    braid_SyncStatus s,
    braid_Real ** v1,
    braid_Int v2,
    braid_Int v3,
    braid_Int v4 )
```

14.10.2.63 braid_SyncStatusGetTIUL()

```
braid_Int braid_SyncStatusGetTIUL (
    braid_SyncStatus s,
    braid_Int * v1,
    braid_Int * v2,
    braid_Int v3 )
```


14.11 XBraid status macros

Macros

- #define `braid_ASCaller_FInterp` 0
- #define `braid_ASCaller_FRestrict` 1
- #define `braid_ASCaller_FRefine` 2
- #define `braid_ASCaller_FAccess` 3
- #define `braid_ASCaller_FRefine_AfterInitHier` 4
- #define `braid_ASCaller_Drive_TopCycle` 5

14.11.1 Detailed Description

Macros defining Status values that the user can obtain during runtime, which will tell the user where in Braid the current cycle is, e.g. in the `FInterp` function.

14.11.2 Macro Definition Documentation

14.11.2.1 `braid_ASCaller_Drive_TopCycle`

```
#define braid_ASCaller_Drive_TopCycle 5
```

When `CallingFunction` equals 5, Braid is at the top of the cycle

14.11.2.2 `braid_ASCaller_FAccess`

```
#define braid_ASCaller_FAccess 3
```

When `CallingFunction` equals 0, Braid is in `FAccess`

14.11.2.3 `braid_ASCaller_FInterp`

```
#define braid_ASCaller_FInterp 0
```

When `CallingFunction` equals 0, Braid is in `FInterp`

14.11.2.4 `braid_ASCaller_FRefine`

```
#define braid_ASCaller_FRefine 2
```

When `CallingFunction` equals 0, Braid is in `FRefine`

14.11.2.5 `braid_ASCaller_FRefine_AfterInitHier`

```
#define braid_ASCaller_FRefine_AfterInitHier 4
```

When `CallingFunction` equals 4, Braid is inside `FRefine` after the new finest level has been initialized

14.11.2.6 `braid_ASCaller_FRestrict`

```
#define braid_ASCaller_FRestrict 1
```

When `CallingFunction` equals 0, Braid is in `FRestrict`

14.12 XBraid test routines

Functions

- `braid_Int braid_TestInitAccess` (`braid_App` app, `MPI_Comm` comm_x, `FILE *fp`, `braid_Real` t, `braid_PtFcnInit` init, `braid_PtFcnAccess` access, `braid_PtFcnFree` free)
- `braid_Int braid_TestClone` (`braid_App` app, `MPI_Comm` comm_x, `FILE *fp`, `braid_Real` t, `braid_PtFcnInit` init, `braid_PtFcnAccess` access, `braid_PtFcnFree` free, `braid_PtFcnClone` clone)
- `braid_Int braid_TestSum` (`braid_App` app, `MPI_Comm` comm_x, `FILE *fp`, `braid_Real` t, `braid_PtFcnInit` init, `braid_PtFcnAccess` access, `braid_PtFcnFree` free, `braid_PtFcnClone` clone, `braid_PtFcnSum` sum)
- `braid_Int braid_TestSpatialNorm` (`braid_App` app, `MPI_Comm` comm_x, `FILE *fp`, `braid_Real` t, `braid_PtFcnInit` init, `braid_PtFcnFree` free, `braid_PtFcnClone` clone, `braid_PtFcnSum` sum, `braid_PtFcnSpatialNorm` spatialnorm)
- `braid_Int braid_TestBuf` (`braid_App` app, `MPI_Comm` comm_x, `FILE *fp`, `braid_Real` t, `braid_PtFcnInit` init, `braid_PtFcnFree` free, `braid_PtFcnSum` sum, `braid_PtFcnSpatialNorm` spatialnorm, `braid_PtFcnBufSize` bufsize, `braid_PtFcnBufPack` bufpack, `braid_PtFcnBufUnpack` bufunpack)
- `braid_Int braid_TestCoarsenRefine` (`braid_App` app, `MPI_Comm` comm_x, `FILE *fp`, `braid_Real` t, `braid_Real` fdt, `braid_Real` cdt, `braid_PtFcnInit` init, `braid_PtFcnAccess` access, `braid_PtFcnFree` free, `braid_PtFcnClone` clone, `braid_PtFcnSum` sum, `braid_PtFcnSpatialNorm` spatialnorm, `braid_PtFcnSCoarsen` coarsen, `braid_PtFcnSRefine` refine)
- `braid_Int braid_TestResidual` (`braid_App` app, `MPI_Comm` comm_x, `FILE *fp`, `braid_Real` t, `braid_Real` dt, `braid_PtFcnInit` myinit, `braid_PtFcnAccess` myaccess, `braid_PtFcnFree` myfree, `braid_PtFcnClone` clone, `braid_PtFcnSum` sum, `braid_PtFcnSpatialNorm` spatialnorm, `braid_PtFcnResidual` residual, `braid_PtFcnStep` step)
- `braid_Int braid_TestAll` (`braid_App` app, `MPI_Comm` comm_x, `FILE *fp`, `braid_Real` t, `braid_Real` fdt, `braid_Real` cdt, `braid_PtFcnInit` init, `braid_PtFcnFree` free, `braid_PtFcnClone` clone, `braid_PtFcnSum` sum, `braid_PtFcnSpatialNorm` spatialnorm, `braid_PtFcnBufSize` bufsize, `braid_PtFcnBufPack` bufpack, `braid_PtFcnBufUnpack` bufunpack, `braid_PtFcnSCoarsen` coarsen, `braid_PtFcnSRefine` refine, `braid_PtFcnResidual` residual, `braid_PtFcnStep` step)

14.12.1 Detailed Description

These are sanity check routines to help a user test their XBraid code.

14.12.2 Function Documentation

14.12.2.1 `braid_TestAll()`

```
braid_Int braid_TestAll (
    braid_App app,
    MPI_Comm comm_x,
    FILE * fp,
    braid_Real t,
    braid_Real fdt,
    braid_Real cdt,
    braid_PtFcnInit init,
    braid_PtFcnFree free,
    braid_PtFcnClone clone,
    braid_PtFcnSum sum,
```

```

braid_PtFcnSpatialNorm spatialnorm,
braid_PtFcnBufSize bufsize,
braid_PtFcnBufPack bufpack,
braid_PtFcnBufUnpack bufunpack,
braid_PtFcnSCoarsen coarsen,
braid_PtFcnSRefine refine,
braid_PtFcnResidual residual,
braid_PtFcnStep step )

```

Runs all of the individual `braid_Test*` routines

- Returns 0 if the tests fail
- Returns 1 if the tests pass
- Check the log messages to see details of which tests failed.

Parameters

<i>app</i>	User defined App structure
<i>comm_x</i>	Spatial communicator
<i>fp</i>	File pointer (could be stdout or stderr) for log messages
<i>t</i>	Time value to initialize test vectors with
<i>fdt</i>	Fine time step value that you spatially coarsen from
<i>cdt</i>	Coarse time step value that you coarsen to
<i>init</i>	Initialize a <code>braid_Vector</code> on finest temporal grid
<i>free</i>	Free a <code>braid_Vector</code>
<i>clone</i>	Clone a <code>braid_Vector</code>
<i>sum</i>	Compute vector sum of two <code>braid_Vectors</code>
<i>spatialnorm</i>	Compute norm of a <code>braid_Vector</code> , this is a norm only over space
<i>bufsize</i>	Computes size in bytes for one <code>braid_Vector</code> MPI buffer
<i>bufpack</i>	Packs MPI buffer to contain one <code>braid_Vector</code>
<i>bufunpack</i>	Unpacks MPI buffer into a <code>braid_Vector</code>
<i>coarsen</i>	Spatially coarsen a vector. If NULL, test is skipped.
<i>refine</i>	Spatially refine a vector. If NULL, test is skipped.
<i>residual</i>	Compute a residual given two consecutive <code>braid_Vectors</code>
<i>step</i>	Compute a time step with a <code>braid_Vector</code>

14.12.2.2 `braid_TestBuf()`

```

braid_Int braid_TestBuf (
    braid_App app,
    MPI_Comm comm_x,
    FILE * fp,
    braid_Real t,
    braid_PtFcnInit init,

```

```

    braid_PtFcnFree free,
    braid_PtFcnSum sum,
    braid_PtFcnSpatialNorm spatialnorm,
    braid_PtFcnBufSize bufsize,
    braid_PtFcnBufPack bufpack,
    braid_PtFcnBufUnpack bufunpack )

```

Test the BufPack, BufUnpack and BufSize functions.

A vector is initialized at time t , packed into a buffer, then unpacked from a buffer. The unpacked result must equal the original vector.

- Returns 0 if the tests fail
- Returns 1 if the tests pass
- Check the log messages to see details of which tests failed.

Parameters

<i>app</i>	User defined App structure
<i>comm_x</i>	Spatial communicator
<i>fp</i>	File pointer (could be stdout or stderr) for log messages
<i>t</i>	Time value to test Buffer routines (used to initialize the vectors)
<i>init</i>	Initialize a braid_Vector on finest temporal grid
<i>free</i>	Free a braid_Vector
<i>sum</i>	Compute vector sum of two braid_Vectors
<i>spatialnorm</i>	Compute norm of a braid_Vector, this is a norm only over space
<i>bufsize</i>	Computes size in bytes for one braid_Vector MPI buffer
<i>bufpack</i>	Packs MPI buffer to contain one braid_Vector
<i>bufunpack</i>	Unpacks MPI buffer containing one braid_Vector

14.12.2.3 braid_TestClone()

```

braid_Int braid_TestClone (
    braid_App app,
    MPI_Comm comm_x,
    FILE * fp,
    braid_Real t,
    braid_PtFcnInit init,
    braid_PtFcnAccess access,
    braid_PtFcnFree free,
    braid_PtFcnClone clone )

```

Test the clone function.

A vector is initialized at time t , cloned, and both vectors are written. Then both vectors are free-d. The user is to check (via the access function) to see if it is identical.

Parameters

<i>app</i>	User defined App structure
<i>comm</i> ↔ <i>_x</i>	Spatial communicator
<i>fp</i>	File pointer (could be stdout or stderr) for log messages
<i>t</i>	Time value to test clone with (used to initialize the vectors)
<i>init</i>	Initialize a <i>braid_Vector</i> on finest temporal grid
<i>access</i>	Allows access to <i>XBraid</i> and current <i>braid_Vector</i> (can be NULL for no writing)
<i>free</i>	Free a <i>braid_Vector</i>
<i>clone</i>	Clone a <i>braid_Vector</i>

14.12.2.4 *braid_TestCoarsenRefine()*

```

braid_Int braid_TestCoarsenRefine (
    braid_App app,
    MPI_Comm comm_x,
    FILE * fp,
    braid_Real t,
    braid_Real fdt,
    braid_Real cdt,
    braid_PtFcnInit init,
    braid_PtFcnAccess access,
    braid_PtFcnFree free,
    braid_PtFcnClone clone,
    braid_PtFcnSum sum,
    braid_PtFcnSpatialNorm spatialnorm,
    braid_PtFcnSCoarsen coarsen,
    braid_PtFcnSRefine refine )

```

Test the Coarsen and Refine functions.

A vector is initialized at time *t*, and various sanity checks on the spatial coarsening and refinement routines are run.

- Returns 0 if the tests fail
- Returns 1 if the tests pass
- Check the log messages to see details of which tests failed.

Parameters

<i>app</i>	User defined App structure
<i>comm_x</i>	Spatial communicator
<i>fp</i>	File pointer (could be stdout or stderr) for log messages
<i>t</i>	Time value to initialize test vectors
<i>fdt</i>	Fine time step value that you spatially coarsen from
<i>cdt</i>	Coarse time step value that you coarsen to

Parameters

<i>init</i>	Initialize a braid_Vector on finest temporal grid
<i>access</i>	Allows access to XBraid and current braid_Vector (can be NULL for no writing)
<i>free</i>	Free a braid_Vector
<i>clone</i>	Clone a braid_Vector
<i>sum</i>	Compute vector sum of two braid_Vectors
<i>spatialnorm</i>	Compute norm of a braid_Vector, this is a norm only over space
<i>coarsen</i>	Spatially coarsen a vector
<i>refine</i>	Spatially refine a vector

14.12.2.5 braid_TestInitAccess()

```

braid_Int braid_TestInitAccess (
    braid_App app,
    MPI_Comm comm_x,
    FILE * fp,
    braid_Real t,
    braid_PtFcnInit init,
    braid_PtFcnAccess access,
    braid_PtFcnFree free )

```

Test the init, access and free functions.
A vector is initialized at time *t*, written, and then free-d

Parameters

<i>app</i>	User defined App structure
<i>comm</i> _↔ <i>_x</i>	Spatial communicator
<i>fp</i>	File pointer (could be stdout or stderr) for log messages
<i>t</i>	Time value to test init with (used to initialize the vectors)
<i>init</i>	Initialize a braid_Vector on finest temporal grid
<i>access</i>	Allows access to XBraid and current braid_Vector (can be NULL for no writing)
<i>free</i>	Free a braid_Vector

14.12.2.6 braid_TestResidual()

```

braid_Int braid_TestResidual (
    braid_App app,
    MPI_Comm comm_x,
    FILE * fp,
    braid_Real t,

```

```

braid_Real dt,
braid_PtFcnInit myinit,
braid_PtFcnAccess myaccess,
braid_PtFcnFree myfree,
braid_PtFcnClone clone,
braid_PtFcnSum sum,
braid_PtFcnSpatialNorm spatialnorm,
braid_PtFcnResidual residual,
braid_PtFcnStep step )

```

Test compatibility of the Step and Residual functions.

A vector is initialized at time t , step is called with dt , followed by an evaluation of residual, to test the condition $fstop - residual(step(u, fstop), u) \approx 0$

- Check the log messages to determine if test passed. The result should approximately be zero. The more accurate the solution for u is computed in step, the closer the result will be to 0.
- The residual is also written to file

Parameters

<i>app</i>	User defined App structure
<i>comm_x</i>	Spatial communicator
<i>fp</i>	File pointer (could be stdout or stderr) for log messages
<i>t</i>	Time value to initialize test vectors
<i>dt</i>	Time step value to use in step
<i>myinit</i>	Initialize a braid_Vector on finest temporal grid
<i>myaccess</i>	Allows access to XBraid and current braid_Vector (can be NULL for no writing)
<i>myfree</i>	Free a braid_Vector
<i>clone</i>	Clone a braid_Vector
<i>sum</i>	Compute vector sum of two braid_Vectors
<i>spatialnorm</i>	Compute norm of a braid_Vector, this is a norm only over space
<i>residual</i>	Compute a residual given two consecutive braid_Vectors
<i>step</i>	Compute a time step with a braid_Vector

14.12.2.7 braid_TestSpatialNorm()

```

braid_Int braid_TestSpatialNorm (
    braid_App app,
    MPI_Comm comm_x,
    FILE * fp,
    braid_Real t,
    braid_PtFcnInit init,
    braid_PtFcnFree free,
    braid_PtFcnClone clone,
    braid_PtFcnSum sum,
    braid_PtFcnSpatialNorm spatialnorm )

```

Test the `spatialnorm` function.

A vector is initialized at time t and then cloned. Various norm evaluations like $\| 3 v \| / \| v \|$ with known output are then done.

- Returns 0 if the tests fail
- Returns 1 if the tests pass
- Check the log messages to see details of which tests failed.

Parameters

<i>app</i>	User defined App structure
<i>comm_x</i>	Spatial communicator
<i>fp</i>	File pointer (could be stdout or stderr) for log messages
<i>t</i>	Time value to test SpatialNorm with (used to initialize the vectors)
<i>init</i>	Initialize a <code>braid_Vector</code> on finest temporal grid
<i>free</i>	Free a <code>braid_Vector</code>
<i>clone</i>	Clone a <code>braid_Vector</code>
<i>sum</i>	Compute vector sum of two <code>braid_Vectors</code>
<i>spatialnorm</i>	Compute norm of a <code>braid_Vector</code> , this is a norm only over space

14.12.2.8 `braid_TestSum()`

```

braid_Int braid_TestSum (
    braid_App app,
    MPI_Comm comm_x,
    FILE * fp,
    braid_Real t,
    braid_PtFcnInit init,
    braid_PtFcnAccess access,
    braid_PtFcnFree free,
    braid_PtFcnClone clone,
    braid_PtFcnSum sum )

```

Test the sum function.

A vector is initialized at time t , cloned, and then these two vectors are summed a few times, with the results written. The vectors are then free-d. The user is to check (via the access function) that the output matches the sum of the two original vectors.

Parameters

<i>app</i>	User defined App structure
<i>comm_x</i>	Spatial communicator
<i>fp</i>	File pointer (could be stdout or stderr) for log messages
<i>t</i>	Time value to test Sum with (used to initialize the vectors)

Parameters

<i>init</i>	Initialize a <code>braid_Vector</code> on finest temporal grid
<i>access</i>	Allows access to <code>XBraid</code> and current <code>braid_Vector</code> (can be <code>NULL</code> for no writing)
<i>free</i>	Free a <code>braid_Vector</code>
<i>clone</i>	Clone a <code>braid_Vector</code>
<i>sum</i>	Compute vector sum of two <code>braid_Vectors</code>

15 Data Structure Documentation

15.1 `_braid_Action` Struct Reference

Data Fields

- `_braid_Call` `braidCall`
- `braid_Core` `core`
- `braid_Real` `inTime`
- `braid_Real` `outTime`
- `braid_Int` `inTimeldx`
- `braid_Real` `sum_alpha`
- `braid_Real` `sum_beta`
- `braid_Int` `send_recv_rank`
- `braid_Int` `braid_iter`
- `braid_Int` `myid`
- `braid_Int` `level`
- `braid_Int` `nrefine`
- `braid_Int` `gupper`
- `braid_Real` `tol`
- `braid_Int` `messagetype`
- `braid_Int` `size_buffer`

15.1.1 Detailed Description

XBraid Action structure

Holds information for the called user routines

15.1.2 Field Documentation

15.1.2.1 `braid_iter`

`braid_Int` `braid_iter`

iteration number of xBraid

15.1.2.2 `braidCall`

`_braid_Call` `braidCall`

type of the user routine

15.1.2.3 core`braid_Core` core

pointer to braid's core structure

15.1.2.4 gupper`braid_Int` gupper

global size of the fine grid

15.1.2.5 inTime`braid_Real` inTime

time of the input vector

15.1.2.6 inTimeIdx`braid_Int` inTimeIdx

index of time of input vector

15.1.2.7 level`braid_Int` level

current level in Braid

15.1.2.8 messagetype`braid_Int` messagetype

message type, 0: for Step(), 1: for load balancing

15.1.2.9 myid`braid_Int` myid

processors id

15.1.2.10 nrefine`braid_Int` nrefine

number of refinements done

15.1.2.11 `outTime`

`braid_Real` `outTime`

time of the output vector

15.1.2.12 `send_recv_rank`

`braid_Int` `send_recv_rank`

processor rank of sender / receiver in `my_bufpack` / `my_bufunpack`

15.1.2.13 `size_buffer`

`braid_Int` `size_buffer`

if set by user, size of send buffer is "size" bytes

15.1.2.14 `sum_alpha`

`braid_Real` `sum_alpha`

first coefficient of `my_sum`

15.1.2.15 `sum_beta`

`braid_Real` `sum_beta`

second coefficient of `my_sum`

15.1.2.16 `tol`

`braid_Real` `tol`

primal stopping tolerance

The documentation for this struct was generated from the following file:

- [tape.h](#)

15.2 `_braid_CommHandle` Struct Reference

Data Fields

- `braid_Int` `request_type`
- `braid_Int` `num_requests`
- `MPI_Request *` `requests`
- `MPI_Status *` `status`
- `void *` `buffer`
- `braid_BaseVector *` `vector_ptr`

15.2.1 Detailed Description

XBraid comm handle structure

Used for initiating and completing nonblocking communication to pass `braid_BaseVectors` between processors.

15.2.2 Field Documentation

15.2.2.1 `buffer`

```
void* buffer
```

Buffer for message

15.2.2.2 `num_requests`

```
braid_Int num_requests
```

number of active requests for this handle, usually 1

15.2.2.3 `request_type`

```
braid_Int request_type
```

two values: `recv type = 1`, and `send type = 0`

15.2.2.4 `requests`

```
MPI_Request* requests
```

MPI request structure

15.2.2.5 `status`

```
MPI_Status* status
```

MPI status

15.2.2.6 `vector_ptr`

```
braid_BaseVector* vector_ptr
```

`braid_vector` being sent/received

The documentation for this struct was generated from the following file:

- [_braid.h](#)

15.3 `_braid_Core` Struct Reference

Data Fields

- `MPI_Comm comm_world`
- `MPI_Comm comm`
- `braid_Int myid_world`
- `braid_Int myid`
- `braid_Real tstart`
- `braid_Real tstop`
- `braid_Int ntime`
- `braid_App app`
- `braid_PtFcnStep step`
- `braid_PtFcnInit init`
- `braid_PtFcnSInit sinit`
- `braid_PtFcnClone clone`
- `braid_PtFcnSClone sclone`
- `braid_PtFcnFree free`
- `braid_PtFcnSFree sfree`
- `braid_PtFcnSum sum`
- `braid_PtFcnSpatialNorm spatialnorm`
- `braid_PtFcnAccess access`
- `braid_PtFcnBufSize bufsize`
- `braid_PtFcnBufPack bufpack`
- `braid_PtFcnBufUnpack bufunpack`
- `braid_PtFcnResidual residual`
- `braid_PtFcnSCoarsen scoarsen`
- `braid_PtFcnSRefine srefine`
- `braid_PtFcnSync sync`
- `braid_PtFcnTimeGrid tgrid`
- `braid_Int periodic`
- `braid_Int initiali`
- `braid_Int access_level`
- `braid_Int print_level`
- `braid_Int io_level`
- `braid_Int seq_soln`
- `braid_Int max_levels`
- `braid_Int incr_max_levels`
- `braid_Int min_coarse`
- `braid_Real tol`
- `braid_Int rtol`
- `braid_Int * nrels`
- `braid_Int nrdefault`
- `braid_Real * CWts`
- `braid_Real CWt_default`
- `braid_Int * cfactors`
- `braid_Int cfdefault`
- `braid_Int max_iter`
- `braid_Int niter`
- `braid_Int fmg`

- `braid_Int nfmng`
- `braid_Int nfmng_Vcyc`
- `braid_Int warm_restart`
- `braid_Int tnorm`
- `braid_Real * tnorm_a`
- `braid_Real rnorm0`
- `braid_Real * rnorms`
- `braid_PtFcnResidual full_rnorm_res`
- `braid_Real full_rnorm0`
- `braid_Real * full_rnorms`
- `braid_Int storage`
- `braid_Int useshell`
- `braid_Int gupper`
- `braid_Int refine`
- `braid_Int * rfactors`
- `braid_Real ** rdtvalues`
- `braid_Int r_space`
- `braid_Int rstopped`
- `braid_Int nrefine`
- `braid_Int max_refinements`
- `braid_Int tpoints_cutoff`
- `braid_Int skip`
- `braid_Int nlevels`
- `_braid_Grid ** grids`
- `braid_Real localtime`
- `braid_Real globaltime`
- `braid_Int richardson`
- `braid_Int est_error`
- `braid_Int order`
- `braid_Real * dtk`
- `braid_Real * estimate`
- `braid_Optim optim`
- `braid_Int adjoint`
- `braid_Int record`
- `braid_Int obj_only`
- `braid_Int verbose_adj`
- `_braid_Tape * actionTape`
- `_braid_Tape * userVectorTape`
- `_braid_Tape * barTape`
- `braid_PtFcnObjectiveT objectiveT`
- `braid_PtFcnStepDiff step_diff`
- `braid_PtFcnObjectiveTDiff objT_diff`
- `braid_PtFcnResetGradient reset_gradient`
- `braid_PtFcnPostprocessObjective postprocess_obj`
- `braid_PtFcnPostprocessObjective_diff postprocess_obj_diff`
- `braid_Real t`
- `braid_Int idx`
- `braid_Int level`
- `braid_Real rnorm`
- `braid_Int done`
- `braid_Int wrapper_test`

- `braid_Int` `calling_function`
- `braid_Real` `f_tprior`
- `braid_Real` `f_tstop`
- `braid_Real` `c_tprior`
- `braid_Real` `c_tstop`
- `braid_Real` `tnext`
- `braid_Real` `old_fine_tolx`
- `braid_Int` `tight_fine_tolx`
- `braid_Int` `rfactor`
- `braid_Int` `messagetype`
- `braid_Int` `size_buffer`
- `braid_Int` `send_recv_rank`

15.3.1 Detailed Description

The typedef `_braid_Core` struct is a **critical** part of XBraid and is passed to *each* routine in XBraid. It thus allows each routine access to XBraid attributes.

15.3.2 Field Documentation

15.3.2.1 `access`

`braid_PtFcnAccess` `access`

user access function to XBraid and current vector

15.3.2.2 `access_level`

`braid_Int` `access_level`

determines how often to call the user's access routine

15.3.2.3 `actionTape`

`_braid_Tape*` `actionTape`

tape storing the actions while recording

15.3.2.4 `adjoint`

`braid_Int` `adjoint`

determines if adjoint run is performed (1) or not (0)

15.3.2.5 app

`braid_App` app

application data for the user

15.3.2.6 barTape

`_braid_Tape*` barTape

tape storing intermediate AD-bar variables while recording

15.3.2.7 bufpack

`braid_PtFcnBufPack` bufpack

pack a buffer

15.3.2.8 bufsize

`braid_PtFcnBufSize` bufsize

return buffer size

15.3.2.9 bufunpack

`braid_PtFcnBufUnpack` bufunpack

unpack a buffer

15.3.2.10 c_tprior

`braid_Real` c_tprior

time value to the left of tstart on coarse grid

15.3.2.11 c_tstop

`braid_Real` c_tstop

time value to the right of tstart on coarse grid

15.3.2.12 calling_function

`braid_Int` calling_function

from which function are we accessing the vector

15.3.2.13 `cfactors`

`braid_Int*` `cfactors`

coarsening factors

15.3.2.14 `cfdefault`

`braid_Int` `cfdefault`

default coarsening factor

15.3.2.15 `clone`

`braid_PtFcnClone` `clone`

clone a vector

15.3.2.16 `comm`

`MPI_Comm` `comm`

communicator for the time dimension

15.3.2.17 `comm_world`

`MPI_Comm` `comm_world`

15.3.2.18 `CWt_default`

`braid_Real` `CWt_default`

default C-relaxation weight

15.3.2.19 `CWts`

`braid_Real*` `CWts`

C-relaxation weight for each level

15.3.2.20 `done`

`braid_Int` `done`

boolean describing whether XBraid has finished

15.3.2.21 dtk`braid_Real* dtk`

holds value of $\sum_{i} dt_i^k$ for each C-interval

15.3.2.22 est_error`braid_Int est_error`

turns on embedded error estimation, e.g., for refinement

15.3.2.23 estimate`braid_Real* estimate`

holds value of the error estimate at each fine grid point

15.3.2.24 f_tprior`braid_Real f_tprior`

CoarsenRefStatus properties time value to the left of tstart on fine grid

15.3.2.25 f_tstop`braid_Real f_tstop`

time value to the right of tstart on fine grid

15.3.2.26 fmg`braid_Int fmg`

use FMG cycle

15.3.2.27 free`braid_PtFcnFree free`

free up a vector

15.3.2.28 full_rnorm0`braid_Real full_rnorm0`

(optional) initial full residual norm

15.3.2.29 `full_rnorm_res`

`braid_PtFcnResidual` `full_rnorm_res`

(optional) used to compute full residual norm

15.3.2.30 `full_rnorms`

`braid_Real*` `full_rnorms`

(optional) full residual norm history

15.3.2.31 `globaltime`

`braid_Real` `globaltime`

global wall time for `braid_Drive()`

15.3.2.32 `grids`

`_braid_Grid**` `grids`

pointer to temporal grid structures for each level

15.3.2.33 `gupper`

`braid_Int` `gupper`

global size of the fine grid

15.3.2.34 `idx`

`braid_Int` `idx`

time point index value corresponding to `t` on the global time grid

15.3.2.35 `incr_max_levels`

`braid_Int` `incr_max_levels`

After doing refinement, increase the max number of levels by 1 (0=false, 1=true)

15.3.2.36 `init`

`braid_PtFcnInit` `init`

return an initialized `braid_BaseVector`

15.3.2.37 initiali`braid_Int` initiali

initial condition grid index (0: default; -1: periodic)

15.3.2.38 io_level`braid_Int` io_level

determines amount of output printed to files (0,1)

15.3.2.39 level`braid_Int` level

current level in XBraid

15.3.2.40 localtime`braid_Real` localtime

local wall time for `braid_Drive()`

15.3.2.41 max_iter`braid_Int` max_iter

maximum number of multigrid in time iterations

15.3.2.42 max_levels`braid_Int` max_levels

maximum number of temporal grid levels

15.3.2.43 max_refinements`braid_Int` max_refinements

maximum number of refinements

15.3.2.44 messagetype`braid_Int` messagetype

BufferStatus properties message type, 0: for Step(), 1: for load balancing

15.3.2.45 `min_coarse``braid_Int` `min_coarse`

minimum possible coarse grid size

15.3.2.46 `myid``braid_Int` `myid`

my rank in the time communicator

15.3.2.47 `myid_world``braid_Int` `myid_world`

my rank in the world communicator

15.3.2.48 `nfmfg``braid_Int` `nfmfg`

number of fmg cycles to do initially before switching to V-cycles

15.3.2.49 `nfmfg_Vcyc``braid_Int` `nfmfg_Vcyc`

number of V-cycle calls at each level in FMG

15.3.2.50 `niter``braid_Int` `niter`

number of iterations

15.3.2.51 `nlevels``braid_Int` `nlevels`

number of temporal grid levels

15.3.2.52 `nrdefault``braid_Int` `nrdefault`

default number of pre-relaxations

15.3.2.53 nrefine`braid_Int nrefine`

number of refinements done

15.3.2.54 nrels`braid_Int* nrels`

number of pre-relaxations on each level

15.3.2.55 ntime`braid_Int ntime`

initial number of time intervals

15.3.2.56 obj_only`braid_Int obj_only`

determines if adjoint code computes ONLY objective, no gradients.

15.3.2.57 objectiveT`braid_PtFcnObjectiveT objectiveT`

User function: evaluate objective function at time t

15.3.2.58 objT_diff`braid_PtFcnObjectiveTDiff objT_diff`

User function: apply differentiated objective function

15.3.2.59 old_fine_tolx`braid_Real old_fine_tolx`

Allows for storing the previously used fine tolerance from GetSpatialAccuracy

15.3.2.60 optim`braid_Optim optim`

structure that stores optimization variables (objective function, etc.)

15.3.2.61 `order`

`braid_Int` `order`

local order of time integration scheme

15.3.2.62 `periodic`

`braid_Int` `periodic`

determines if periodic

15.3.2.63 `postprocess_obj`

`braid_PtFcnPostprocessObjective` `postprocess_obj`

Optional user function: Modify the time-averaged objective function, e.g. for inverse design problems, adding relaxation term etc.

15.3.2.64 `postprocess_obj_diff`

`braid_PtFcnPostprocessObjective_diff` `postprocess_obj_diff`

Optional user function: Derivative of postprocessing function

15.3.2.65 `print_level`

`braid_Int` `print_level`

determines amount of output printed to screen (0,1,2,3)

15.3.2.66 `r_space`

`braid_Int` `r_space`

spatial refinement flag

15.3.2.67 `rdtvalues`

`braid_Real**` `rdtvalues`

Array of pointers to arrays of dt values for non-uniform refinement

15.3.2.68 `record`

`braid_Int` `record`

determines if actions are recorded to the tape or not. This separate flag from adjoint is needed, because the final `FAccess` call should not be recorded unless `nlevels==1`, but the adjoint flag must be true even if `nlevels==1`.

15.3.2.69 refine`braid_Int refine`

refine in time (refine = 1)

15.3.2.70 reset_gradient`braid_PtFcnResetGradient reset_gradient`

User function: Set the gradient to zero. Is called before each iteration

15.3.2.71 residual`braid_PtFcnResidual residual`

(optional) compute residual

15.3.2.72 rfactor`braid_Int rfactor`

if set by user, allows for subdivision of this interval for better time accuracy

15.3.2.73 rfactors`braid_Int* rfactors`

refinement factors for finest grid (if any)

15.3.2.74 richardson`braid_Int richardson`

Richardson-based error estimation and refinement turns on Richardson extrapolation for accuracy

15.3.2.75 rnorm`braid_Real rnorm`

AccessStatus properties residual norm

15.3.2.76 rnorm0`braid_Real rnorm0`

initial residual norm

15.3.2.77 `rnorms``braid_Real*` `rnorms`

residual norm history

15.3.2.78 `rstopped``braid_Int` `rstopped`refinement stopped at iteration `rstopped`**15.3.2.79 `rtol`**`braid_Int` `rtol`

use relative tolerance

15.3.2.80 `sclone``braid_PtFcnSClone` `sclone`

(optional) clone the shell of a vector

15.3.2.81 `scoarsen``braid_PtFcnSCoarsen` `scoarsen`

(optional) return a spatially coarsened vector

15.3.2.82 `send_recv_rank``braid_Int` `send_recv_rank`**15.3.2.83 `seq_soln`**`braid_Int` `seq_soln`

boolean, controls if the initial guess is from sequential time stepping

15.3.2.84 `sfree``braid_PtFcnSFree` `sfree`

(optional) free up the data of a vector, keep the shell

15.3.2.85 sinit`braid_PtFcnSInit` sinit

(optional) return an initialized shell of `braid_BaseVector`

15.3.2.86 size_buffer`braid_Int` size_buffer

if set by user, send buffer will be "size" bytes in length

15.3.2.87 skip`braid_Int` skip

boolean, controls skipping any work on first down-cycle

15.3.2.88 spatialnorm`braid_PtFcnSpatialNorm` spatialnorm

Compute norm of a `braid_BaseVector`, this is a norm only over space

15.3.2.89 srefine`braid_PtFcnSRefine` srefine

(optional) return a spatially refined vector

15.3.2.90 step`braid_PtFcnStep` step

apply step function

15.3.2.91 step_diff`braid_PtFcnStepDiff` step_diff

User function: apply differentiated step function

15.3.2.92 storage`braid_Int` storage

storage = 0 (C-points), = 1 (all)

15.3.2.93 `sum``braid_PtFcnSum` `sum`

vector sum

15.3.2.94 `sync``braid_PtFcnSync` `sync`

(optional) user access to app once-per-processor

15.3.2.95 `t``braid_Real` `t`

Data elements required for the Status structures Common Status properties current time

15.3.2.96 `tgrid``braid_PtFcnTimeGrid` `tgrid`

(optional) return time point values on level 0

15.3.2.97 `tight_fine_tolx``braid_Int` `tight_fine_tolx`

Boolean, indicating whether the tightest fine tolx has been used, condition for halting

15.3.2.98 `tnext``braid_Real` `tnext`

StepStatus properties time value to evolve towards, time value to the right of tstart

15.3.2.99 `tnorm``braid_Int` `tnorm`

choice of temporal norm

15.3.2.100 `tnorm_a``braid_Real*` `tnorm_a`

local array of residual norms on a proc's interval, used for inf-norm

15.3.2.101 tol`braid_Real tol`

stopping tolerance

15.3.2.102 tpoints_cutoff`braid_Int tpoints_cutoff`

refinements halt after the number of time steps exceed this value

15.3.2.103 tstart`braid_Real tstart`

start time

15.3.2.104 tstop`braid_Real tstop`

stop time

15.3.2.105 userVectorTape`_braid_Tape* userVectorTape`

tape storing primal `braid_vectors` while recording

15.3.2.106 useshell`braid_Int useshell`

activate the shell structure of vectors

15.3.2.107 verbose_adj`braid_Int verbose_adj`

verbosity of the adjoint tape, displays the actions that are pushed / popped to the tape

15.3.2.108 warm_restart`braid_Int warm_restart`

boolean, indicates whether this is a warm restart of an existing `braid_Core`

15.3.2.109 `wrapper_test`

```
braid_Int wrapper_test
```

boolean describing whether this call is only a wrapper test

The documentation for this struct was generated from the following file:

- [_braid.h](#)

15.4 `_braid_Grid` Struct Reference

Data Fields

- [braid_Int](#) `level`
- [braid_Int](#) `ilower`
- [braid_Int](#) `iupper`
- [braid_Int](#) `clower`
- [braid_Int](#) `cupper`
- [braid_Int](#) `gupper`
- [braid_Int](#) `cfactor`
- [braid_Int](#) `ncpoints`
- [braid_Int](#) `nupoints`
- [braid_BaseVector](#) * `ua`
- [braid_Real](#) * `ta`
- [braid_BaseVector](#) * `va`
- [braid_BaseVector](#) * `fa`
- [braid_Int](#) `recv_index`
- [braid_Int](#) `send_index`
- [_braid_CommHandle](#) * `recv_handle`
- [_braid_CommHandle](#) * `send_handle`
- [braid_BaseVector](#) * `ua_alloc`
- [braid_Real](#) * `ta_alloc`
- [braid_BaseVector](#) * `va_alloc`
- [braid_BaseVector](#) * `fa_alloc`

15.4.1 Detailed Description

XBraid Grid structure for a certain time level

Holds all the information for a processor related to the temporal grid at this level.

15.4.2 Field Documentation

15.4.2.1 cfactor

`braid_Int` cfactor

coarsening factor

15.4.2.2 clower

`braid_Int` clower

smallest C point index

15.4.2.3 cupper

`braid_Int` cupper

largest C point index

15.4.2.4 fa

`braid_BaseVector*` fa

rhs vectors f (all points, NULL on level 0)

15.4.2.5 fa_alloc

`braid_BaseVector*` fa_alloc

original memory allocation for fa

15.4.2.6 gupper

`braid_Int` gupper

global size of the grid

15.4.2.7 ilower

`braid_Int` ilower

smallest time index at this level

15.4.2.8 iupper

`braid_Int` iupper

largest time index at this level

15.4.2.9 `level`

`braid_Int` `level`

Level that grid is on

15.4.2.10 `ncpoints`

`braid_Int` `ncpoints`

number of C points

15.4.2.11 `nupoints`

`braid_Int` `nupoints`

number of unknown vector points

15.4.2.12 `recv_handle`

`_braid_CommHandle*` `recv_handle`

Handle for nonblocking receives of `braid_BaseVectors`

15.4.2.13 `recv_index`

`braid_Int` `recv_index`

-1 means no receive

15.4.2.14 `send_handle`

`_braid_CommHandle*` `send_handle`

Handle for nonblocking sends of `braid_BaseVectors`

15.4.2.15 `send_index`

`braid_Int` `send_index`

-1 means no send

15.4.2.16 `ta`

`braid_Real*` `ta`

time values (all points)

15.4.2.17 `ta_alloc`

`braid_Real* ta_alloc`

original memory allocation for `ta`

15.4.2.18 `ua`

`braid_BaseVector* ua`

unknown vectors (C-points at least)

15.4.2.19 `ua_alloc`

`braid_BaseVector* ua_alloc`

original memory allocation for `ua`

15.4.2.20 `va`

`braid_BaseVector* va`

restricted unknown vectors (all points, NULL on level 0)

15.4.2.21 `va_alloc`

`braid_BaseVector* va_alloc`

original memory allocation for `va`

The documentation for this struct was generated from the following file:

- [_braid.h](#)

15.5 `_braid_Status` Struct Reference

Data Fields

- [_braid_Core](#) `core`

15.5.1 Detailed Description

This is the main Status structure, that contains the properties of all the status. The user does not have access to this structure, but only to the derived Status structures. This class is accessed only inside XBraid code.

15.5.2 Field Documentation

15.5.2.1 `core`

`_braid_Core` `core`

The documentation for this struct was generated from the following file:

- [status.h](#)

15.6 `_braid_Tape` Struct Reference

Data Fields

- `int` [size](#)
- `void *` [data_ptr](#)
- `struct _braid_tape_struct *` [next](#)

15.6.1 Detailed Description

C-Implementation of a linked list storing pointers to generic data This structure represents one tape element, holding a pointer to data and a pointer to the next element `int size` holds the number of all elements in the tape

15.6.2 Field Documentation

15.6.2.1 `data_ptr`

`void* data_ptr`

15.6.2.2 `next`

`struct _braid_tape_struct* next`

15.6.2.3 size

```
int size
```

The documentation for this struct was generated from the following file:

- [tape.h](#)

15.7 braid_AccessStatus Struct Reference

Data Fields

- [_braid_Status](#) [status](#)

15.7.1 Detailed Description

AccessStatus structure which defines the status of XBraid at a given instant on some level during a run. The user accesses it through *braid_AccessStatusGet**()* functions. This is just a pointer to the *braid_Status*.

15.7.2 Field Documentation

15.7.2.1 status

```
_braid_Status status
```

The documentation for this struct was generated from the following file:

- [status.h](#)

15.8 braid_BaseVector Struct Reference

Data Fields

- [braid_Vector](#) [userVector](#)
- [braid_VectorBar](#) [bar](#)

15.8.1 Detailed Description

Braid vector used for storage of all state and (if needed) adjoint information. Stores both the user's primal vector (*braid_↔_Vector* type) and the associated bar vector (*braid_VectorBar* type) if the adjoint functionality is being used. If adjoint is not being used, *bar==NULL*.

15.8.2 Field Documentation

15.8.2.1 bar

`braid_VectorBar` bar

holds the bar vector (shared pointer implementation)

15.8.2.2 userVector

`braid_Vector` userVector

holds the users primal vector

The documentation for this struct was generated from the following file:

- [_braid.h](#)

15.9 braid_BufferStatus Struct Reference

Data Fields

- `_braid_Status` [status](#)

15.9.1 Detailed Description

The user's `bufpack`, `bufunpack` and `bufsize` routines will receive a `BufferStatus` structure, which defines the status of XBraid at a given `buf` (un)pack instance. The user accesses it through `braid_BufferStatusGet**()` functions. This is just a pointer to the `braid_Status`.

15.9.2 Field Documentation

15.9.2.1 status

`_braid_Status` status

The documentation for this struct was generated from the following file:

- [status.h](#)

15.10 `braided_CoarsenRefStatus` Struct Reference

Data Fields

- `_braided_Status` [status](#)

15.10.1 Detailed Description

The user `coarsen` and `refine` routines will receive a `CoarsenRefStatus` structure, which defines the status of XBraid at a given instant of coarsening or refinement on some level during a run. The user accesses it through `braided_CoarsenRefStatusGet**()` functions. This is just a pointer to the `braided_Status`.

15.10.2 Field Documentation

15.10.2.1 `status`

```
_braided_Status status
```

The documentation for this struct was generated from the following file:

- [status.h](#)

15.11 `braided_ObjectiveStatus` Struct Reference

Data Fields

- `_braided_Status` [status](#)

15.11.1 Detailed Description

The user's `objectiveT` and `PostprocessObjective` will receive an `ObjectiveStatus` structure, which defines the status of XBraid at a given instance of evaluating the objective function. The user accesses it through `braided_ObjectiveStatusGet**()` functions. This is just a pointer to the `braided_Status`.

15.11.2 Field Documentation

15.11.2.1 status

```
_braid_Status status
```

The documentation for this struct was generated from the following file:

- [status.h](#)

15.12 braid_Optim Struct Reference

Data Fields

- [braid_Real](#) sum_user_obj
- [braid_Real](#) objective
- [braid_Real](#) tstart_obj
- [braid_Real](#) tstop_obj
- [braid_Real](#) f_bar
- [braid_Real](#) rnorm_adj
- [braid_Real](#) rnorm0_adj
- [braid_Real](#) rnorm
- [braid_Real](#) rnorm0
- [braid_Real](#) tol_adj
- [braid_Int](#) rtol_adj
- [braid_Vector](#) * adjoints
- [braid_VectorBar](#) * tapeinput
- void * sendbuffer
- [MPI_Request](#) * request

15.12.1 Detailed Description

Data structure for storing the optimization variables

15.12.2 Field Documentation

15.12.2.1 adjoints

```
braid\_Vector* adjoints
```

vector for the adjoint variables

15.12.2.2 f_bar

```
braid\_Real f_bar
```

contains the seed for tape evaluation

15.12.2.3 objective

`braid_Real` objective

global objective function value

15.12.2.4 request

`MPI_Request*` request

helper: Storing the MPI request of BufUnPackDiff

15.12.2.5 rnorm

`braid_Real` rnorm

norm of the state residual

15.12.2.6 rnorm0

`braid_Real` rnorm0

initial norm of the state residual

15.12.2.7 rnorm0_adj

`braid_Real` rnorm0_adj

initial norm of the adjoint residual

15.12.2.8 rnorm_adj

`braid_Real` rnorm_adj

norm of the adjoint residual

15.12.2.9 rtol_adj

`braid_Int` rtol_adj

flag: use relative tolerance for adjoint

15.12.2.10 sendbuffer

`void*` sendbuffer

helper: Memory for BufUnPackDiff communication

15.12.2.11 `sum_user_obj`

`braid_Real` `sum_user_obj`

sum of user's objective function values over time

15.12.2.12 `tapeinput`

`braid_VectorBar*` `tapeinput`

helper: store pointer to input of one braid iteration

15.12.2.13 `tol_adj`

`braid_Real` `tol_adj`

tolerance of adjoint residual

15.12.2.14 `tstart_obj`

`braid_Real` `tstart_obj`

starting time for evaluating the user's local objective

15.12.2.15 `tstop_obj`

`braid_Real` `tstop_obj`

stopping time for evaluating the user's local objective

The documentation for this struct was generated from the following file:

- [_braid.h](#)

15.13 `braid_StepStatus` Struct Reference

Data Fields

- `_braid_Status` [status](#)

15.13.1 Detailed Description

The user's step routine will receive a `StepStatus` structure, which defines the status of XBraid at the given instant for step evaluation on some level during a run. The user accesses it through `braid_StepStatusGet**()` functions. This is just a pointer to the `braid_Status`.

15.13.2 Field Documentation

15.13.2.1 status

`_braid_Status status`

The documentation for this struct was generated from the following file:

- [status.h](#)

15.14 braid_SyncStatus Struct Reference

Data Fields

- `_braid_Status` [status](#)

15.14.1 Detailed Description

SyncStatus structure which provides the status of XBraid at a given instant on some level during a run. This is vector independent and called once per processor. The user accesses it through *braid_SyncStatusGet**()* functions. This is just a pointer to the `braid_Status`.

15.14.2 Field Documentation

15.14.2.1 status

`_braid_Status status`

The documentation for this struct was generated from the following file:

- [status.h](#)

15.15 braid_VectorBar Struct Reference

Data Fields

- `braid_Vector` [userVector](#)
- `braid_Int` [useCount](#)

15.15.1 Detailed Description

Braid Vector Structures:

There are three vector structures `_braid_VectorBar` Defined below `braid_Vector` Defined in [braid.h](#) `braid_BaseVector` Defined below

The `braid_BaseVector` is the main internal Vector class, which is stored at each time point. It basically wraps the Vector and `braid_VectorBar` (see below). The `braid_VectorBar` is only used if the adjoint capability is used, when it stores adjoint variables. It's basically a smart pointer wrapper around a `braid_Vector`. Note that it is always the `braid_Vector` that's passed to user-routines. Shared pointer implementation for storing the intermediate AD-bar variables while taping. This is essentially the same as a `userVector`, except we need shared pointer capabilities to know when to delete.

15.15.2 Field Documentation

15.15.2.1 useCount

`braid_Int` useCount

counts the number of pointers to this struct

15.15.2.2 userVector

`braid_Vector` userVector

holds the `u_bar` data

The documentation for this struct was generated from the following file:

- [_braid.h](#)

16 File Documentation

16.1 `_braid.h` File Reference

Data Structures

- struct [braid_VectorBar](#)
- struct [braid_BaseVector](#)
- struct [braid_Optim](#)
- struct [_braid_CommHandle](#)
- struct [_braid_Grid](#)
- struct [_braid_Core](#)

Macros

- #define `_braid_Error`(IERR, msg) `_braid_ErrorHandler`(`__FILE__`, `__LINE__`, IERR, msg)
- #define `_braid_ErrorInArg`(IARG, msg) `_braid_Error`(`HYPRE_ERROR_ARG` | `IARG`<<3, msg)
- #define `_braid_TAlloc`(type, count) ((type *)`malloc`((size_t)(sizeof(type) * (count))))
- #define `_braid_CTAlloc`(type, count) ((type *)`calloc`((size_t)(count), (size_t)sizeof(type)))
- #define `_braid_TReAlloc`(ptr, type, count) ((type *)`realloc`((char *)ptr, (size_t)(sizeof(type) * (count))))
- #define `_braid_TFree`(ptr) (`free`((char *)ptr), ptr = NULL)
- #define `_braid_max`(a, b) (((a)<(b)) ? (b) : (a))
- #define `_braid_min`(a, b) (((a)<(b)) ? (a) : (b))
- #define `_braid_isnan`(a) (a != a)
- #define `_braid_SendIndexNull` -2
- #define `_braid_RecvIndexNull` -2
- #define `_braid_MapPeriodic`(index, npoints) (index = ((index)+(npoints)) % (npoints)) /* this also handles negative indexes */
- #define `_braid_CommHandleElt`(handle, elt) ((handle) -> elt)
- #define `_braid_GridElt`(grid, elt) ((grid) -> elt)
- #define `_braid_CoreElt`(core, elt) ((core) -> elt)
- #define `_braid_CoreFcn`(core, fcn) (*(core) -> fcn)
- #define `_braid_MapFineToCoarse`(findex, cfactor, cindex) (cindex = (findex)/(cfactor))
- #define `_braid_MapCoarseToFine`(cindex, cfactor, findex) (findex = (cindex)*(cfactor))
- #define `_braid_IsFPoint`(index, cfactor) ((index)%cfactor)
- #define `_braid_IsCPoint`(index, cfactor) (!_braid_IsFPoint(index, cfactor))
- #define `_braid_NextCPoint`(index, cfactor) (((`braid_Int`)(index)+(cfactor)-1)/(cfactor))*cfactor)
- #define `_braid_PriorCPoint`(index, cfactor) (((`braid_Int`)(index))/(cfactor))*cfactor)

Functions

- void `_braid_ErrorHandler` (const char *filename, `braid_Int` line, `braid_Int` ierr, const char *msg)
- `braid_Int` `_braid_GetBlockDistInterval` (`braid_Int` npoints, `braid_Int` nprocs, `braid_Int` proc, `braid_Int` *ilower_ptr, `braid_Int` *iupper_ptr)
- `braid_Int` `_braid_GetBlockDistProc` (`braid_Int` npoints, `braid_Int` nprocs, `braid_Int` index, `braid_Int` periodic, `braid_Int` *proc_ptr)
- `braid_Int` `_braid_GetDistribution` (`braid_Core` core, `braid_Int` *ilower_ptr, `braid_Int` *iupper_ptr)
- `braid_Int` `_braid_GetProc` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_Int` *proc_ptr)
- `braid_Int` `_braid_CommRecvInit` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` *vector_ptr, `_braid_CommHandle` **handle_ptr)
- `braid_Int` `_braid_CommSendInit` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` vector, `_braid_CommHandle` **handle_ptr)
- `braid_Int` `_braid_CommWait` (`braid_Core` core, `_braid_CommHandle` **handle_ptr)
- `braid_Int` `_braid_UGetIndex` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_Int` *uindex_ptr, `braid_Int` *store_flag_ptr)
- `braid_Int` `_braid_UGetVectorRef` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` *u_ptr)
- `braid_Int` `_braid_USetVectorRef` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` u)
- `braid_Int` `_braid_UGetVector` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` *u_ptr)
- `braid_Int` `_braid_USetVector` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` u, `braid_Int` move)
- `braid_Int` `_braid_UCommInitBasic` (`braid_Core` core, `braid_Int` level, `braid_Int` recv_msg, `braid_Int` send_msg, `braid_Int` send_now)
- `braid_Int` `_braid_UCommInit` (`braid_Core` core, `braid_Int` level)

- `braid_Int_braid_UCommInitF` (`braid_Core` core, `braid_Int` level)
- `braid_Int_braid_UCommWait` (`braid_Core` core, `braid_Int` level)
- `braid_Int_braid_Step` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` ustop, `braid_BaseVector` u)
- `braid_Int_braid_GetUInit` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` u, `braid_BaseVector` *ustop_ptr)
- `braid_Int_braid_Residual` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` ustop, `braid_BaseVector` r)
- `braid_Int_braid_FASResidual` (`braid_Core` core, `braid_Int` level, `braid_Int` index, `braid_BaseVector` ustop, `braid_BaseVector` r)
- `braid_Int_braid_Coarsen` (`braid_Core` core, `braid_Int` level, `braid_Int` f_index, `braid_Int` c_index, `braid_BaseVector` fvector, `braid_BaseVector` *cvector)
- `braid_Int_braid_RefineBasic` (`braid_Core` core, `braid_Int` level, `braid_Int` c_index, `braid_Real` *f_ta, `braid_Real` *c_ta, `braid_BaseVector` cvector, `braid_BaseVector` *fvector)
- `braid_Int_braid_Refine` (`braid_Core` core, `braid_Int` level, `braid_Int` f_index, `braid_Int` c_index, `braid_BaseVector` cvector, `braid_BaseVector` *fvector)
- `braid_Int_braid_FRefineSpace` (`braid_Core` core, `braid_Int` *refined_ptr)
- `braid_Int_braid_GridInit` (`braid_Core` core, `braid_Int` level, `braid_Int` ilower, `braid_Int` iupper, `_braid_Grid` **grid_ptr)
- `braid_Int_braid_GridClean` (`braid_Core` core, `_braid_Grid` *grid)
- `braid_Int_braid_GridDestroy` (`braid_Core` core, `_braid_Grid` *grid)
- `braid_Int_braid_SetRNorm` (`braid_Core` core, `braid_Int` iter, `braid_Real` rnorm)
- `braid_Int_braid_GetRNorm` (`braid_Core` core, `braid_Int` iter, `braid_Real` *rnorm_ptr)
- `braid_Int_braid_SetFullRNorm` (`braid_Core` core, `braid_Int` iter, `braid_Real` rnorm)
- `braid_Int_braid_GetFullRNorm` (`braid_Core` core, `braid_Int` iter, `braid_Real` *rnorm_ptr)
- `braid_Int_braid_ComputeFullRNorm` (`braid_Core` core, `braid_Int` level, `braid_Real` *return_rnorm)
- `braid_Int_braid_PrintSpatialNorms` (`braid_Core` core, `braid_Real` *rnorms, `braid_Int` n)
- `braid_Int_braid_FCRRelax` (`braid_Core` core, `braid_Int` level)
- `braid_Int_braid_FRestrict` (`braid_Core` core, `braid_Int` level)
- `braid_Int_braid_FInterp` (`braid_Core` core, `braid_Int` level)
- `braid_Int_braid_FRefine` (`braid_Core` core, `braid_Int` *refined_ptr)
- `braid_Int_braid_FAccess` (`braid_Core` core, `braid_Int` level, `braid_Int` done)
- `braid_Int_braid_AccessVector` (`braid_Core` core, `braid_AccessStatus` status, `braid_BaseVector` u)
- `braid_Int_braid_Sync` (`braid_Core` core, `braid_SyncStatus` status)
- `braid_Int_braid_InitHierarchy` (`braid_Core` core, `_braid_Grid` *fine_grid, `braid_Int` refined)
- `braid_Int_braid_FinalizeErrorEstimates` (`braid_Core` core, `braid_Real` *estimate, `braid_Int` length)
- `braid_Int_braid_GetDtk` (`braid_Core` core)
- `braid_Int_braid_GetCFactor` (`braid_Core` core, `braid_Int` level, `braid_Int` *cfactor_ptr)
- `braid_Int_braid_InitGuess` (`braid_Core` core, `braid_Int` level)
- `braid_Int_braid_CopyFineToCoarse` (`braid_Core` core)
- `braid_Int_braid_Drive` (`braid_Core` core, `braid_Real` localtime)

Variables

- `braid_Int_braid_error_flag`
- `FILE` * `_braid_printfile`

16.1.1 Detailed Description

Define headers for XBraid internal (developer) routines and XBraid internal structure declarations.

This file contains the headers for XBraid internal (developer) routines and structure declarations.

16.1.2 Macro Definition Documentation

16.1.2.1 `_braid_CommHandleElt`

```
#define _braid_CommHandleElt(  
    handle,  
    elt ) ((handle) -> elt)
```

Accessor for `_braid_CommHandle` attributes

16.1.2.2 `_braid_CoreElt`

```
#define _braid_CoreElt(  
    core,  
    elt ) ( (core) -> elt )
```

Accessor for `_braid_Core` attributes

16.1.2.3 `_braid_CoreFcn`

```
#define _braid_CoreFcn(  
    core,  
    fcn ) (*(core) -> fcn)
```

Accessor for `_braid_Core` functions

16.1.2.4 `_braid_CTAlloc`

```
#define _braid_CTAlloc(  
    type,  
    count ) ( (type *)calloc((size_t)(count), (size_t)sizeof(type)) )
```

Allocation macro

16.1.2.5 `_braid_Error`

```
#define _braid_Error(  
    IERR,  
    msg ) _braid_ErrorHandler(__FILE__, __LINE__, IERR, msg)
```

16.1.2.6 `_braid_ErrorInArg`

```
#define _braid_ErrorInArg(  
    IARG,  
    msg ) _braid_Error(HYPRE_ERROR_ARG | IARG<<3, msg)
```

16.1.2.7 `_braid_GridElt`

```
#define _braid_GridElt(  
    grid,  
    elt ) ((grid) -> elt)
```

Accessor for `_braid_Grid` attributes

16.1.2.8 `_braid_IsCPoint`

```
#define _braid_IsCPoint(  
    index,  
    cfactor ) ( !_braid_IsFPoint(index, cfactor) )
```

Boolean, returns whether a time index is an C-point

16.1.2.9 `_braid_IsFPoint`

```
#define _braid_IsFPoint(  
    index,  
    cfactor ) ( (index)%(cfactor) )
```

Boolean, returns whether a time index is an F-point

16.1.2.10 `_braid_isnan`

```
#define _braid_isnan(  
    a ) (a != a)
```

16.1.2.11 `_braid_MapCoarseToFine`

```
#define _braid_MapCoarseToFine(  
    cindex,  
    cfactor,  
    findex ) ( findex = (cindex)*(cfactor) )
```

Map a coarse time index to a fine time index, assumes a uniform coarsening factor.

16.1.2.12 `_braid_MapFineToCoarse`

```
#define _braid_MapFineToCoarse(  
    findex,  
    cfactor,  
    cindex ) ( cindex = (findex)/(cfactor) )
```

Map a fine time index to a coarse time index, assumes a uniform coarsening factor.

16.1.2.13 `_braid_MapPeriodic`

```
#define _braid_MapPeriodic(  
    index,  
    npoints ) ( index = ((index)+(npoints)) % (npoints) ) /* this also handles negative  
indexes */
```

16.1.2.14 `_braid_max`

```
#define _braid_max(  
    a,  
    b ) ((a)<(b)) ? (b) : (a)
```

16.1.2.15 `_braid_min`

```
#define _braid_min(  
    a,  
    b ) ((a)<(b)) ? (a) : (b)
```

16.1.2.16 `_braid_NextCPoint`

```
#define _braid_NextCPoint(  
    index,  
    cfactor ) ( ((braid_Int) ((index)+(cfactor)-1)/(cfactor))*cfactor )
```

Returns the index for the next C-point to the right of index (inclusive)

16.1.2.17 `_braid_PriorCPoint`

```
#define _braid_PriorCPoint(  
    index,  
    cfactor ) ( ((braid_Int) (index)/(cfactor))*cfactor )
```

Returns the index for the previous C-point to the left of index (inclusive)

16.1.2.18 `_braid_RecvIndexNull`

```
#define _braid_RecvIndexNull -2
```

16.1.2.19 `_braid_SendIndexNull`

```
#define _braid_SendIndexNull -2
```

16.1.2.20 `_braid_TAlloc`

```
#define _braid_TAlloc(  
    type,  
    count ) ( (type *)malloc((size_t)(sizeof(type) * (count))) )
```

Allocation macro

16.1.2.21 `_braid_TFree`

```
#define _braid_TFree(  
    ptr ) ( free((char *)ptr), ptr = NULL )
```

Free memory macro

16.1.2.22 `_braid_TReAlloc`

```
#define _braid_TReAlloc(  
    ptr,  
    type,  
    count ) ( (type *)realloc((char *)ptr, (size_t)(sizeof(type) * (count))) )
```

Re-allocation macro

16.1.3 Function Documentation

16.1.3.1 `_braid_AccessVector()`

```
braid_Int _braid_AccessVector (  
    braid_Core core,  
    braid_AccessStatus status,  
    braid_BaseVector u )
```

Call user's access function in order to give access to XBraid and the current vector. Most commonly, this lets the user write *u* to screen, disk, etc... The vector *u* corresponds to time step *index* on *level*. *status* holds state information about the current XBraid iteration, time value, etc...

16.1.3.2 `_braid_Coarsen()`

```
braid_Int _braid_Coarsen (
    braid_Core core,
    braid_Int level,
    braid_Int f_index,
    braid_Int c_index,
    braid_BaseVector fvector,
    braid_BaseVector * cvector )
```

Coarsen in space on *level* by calling the user's coarsen function. The vector corresponding to the time step index *f_index* on the fine grid is coarsened to the time step index *c_index* on the coarse grid. The output goes in *cvector* and the input vector is *fvector*.

16.1.3.3 `_braid_CommRecvInit()`

```
braid_Int _braid_CommRecvInit (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector * vector_ptr,
    _braid_CommHandle ** handle_ptr )
```

Initialize a receive to go into *vector_ptr* for the given time *index* on *level*. Also return a comm handle *handle_ptr* for querying later, to see if the receive has occurred.

16.1.3.4 `_braid_CommSendInit()`

```
braid_Int _braid_CommSendInit (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector vector,
    _braid_CommHandle ** handle_ptr )
```

Initialize a send of *vector* for the given time *index* on *level*. Also return a comm handle *handle_ptr* for querying later, to see if the send has occurred.

16.1.3.5 `_braid_CommWait()`

```
braid_Int _braid_CommWait (
    braid_Core core,
    _braid_CommHandle ** handle_ptr )
```

Block on the comm handle *handle_ptr* until the MPI operation (send or recv) has completed

16.1.3.6 `_braid_ComputeFullRNorm()`

```
braid_Int _braid_ComputeFullRNorm (
    braid_Core core,
    braid_Int level,
    braid_Real * return_rnorm )
```

Compute full temporal residual norm with user-provided residual routine. Output goes in **return_rnorm*.

16.1.3.7 `_braid_CopyFineToCoarse()`

```
braid_Int _braid_CopyFineToCoarse (
    braid_Core core )
```

Copy the initialized C-points on the fine grid, to all coarse levels. For instance, if a point *k* on level *m* corresponds to point *p* on level 0, then they are equivalent after this function. The only exception is any spatial coarsening the user decides to do. This function allows XBraid to skip all work on the first down cycle and start in FMG style on the coarsest level. Assumes level 0 C-points are initialized.

16.1.3.8 `_braid_Drive()`

```
braid_Int _braid_Drive (
    braid_Core core,
    braid_Real localtime )
```

Main loop for MGRIT

16.1.3.9 `_braid_ErrorHandler()`

```
void _braid_ErrorHandler (
    const char * filename,
    braid_Int line,
    braid_Int ierr,
    const char * msg )
```

16.1.3.10 `_braid_FAccess()`

```
braid_Int _braid_FAccess (
    braid_Core core,
    braid_Int level,
    braid_Int done )
```

Call the user's access function in order to give access to XBraid and the current vector at grid *level* and *iteration *iter*. Most commonly, this lets the user write solutions to screen, disk, etc... The quantity *rnorm* denotes the last computed residual norm, and *done* is a boolean indicating whether XBraid has finished iterating and this is the last Access call.

16.1.3.11 `_braid_FASResidual()`

```
braid_Int _braid_FASResidual (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector ustop,
    braid_BaseVector r )
```

Compute FAS residual = *f* - residual

16.1.3.12 `_braid_FCRelax()`

```
braid_Int _braid_FCRelax (
    braid_Core core,
    braid_Int level )
```

Do nu sweeps of F-then-C relaxation on *level*

16.1.3.13 `_braid_FinalizeErrorEstimates()`

```
braid_Int _braid_FinalizeErrorEstimates (
    braid_Core core,
    braid_Real * estimate,
    braid_Int length )
```

Finalize Richardson error estimates

16.1.3.14 `_braid_FInterp()`

```
braid_Int _braid_FInterp (
    braid_Core core,
    braid_Int level )
```

F-Relax on *level* and interpolate to *level-1*

The output is set in the `braid_Grid` in `core`, so that the vector u on *level* is created by interpolating from *level+1*.

If the user has set spatial refinement, then this user-defined routine is also called.

Parameters

<i>core</i>	<code>braid_Core</code> (<code>_braid_Core</code>) struct
<i>level</i>	interp from level to level+1

16.1.3.15 `_braid_FRefine()`

```
braid_Int _braid_FRefine (
    braid_Core core,
    braid_Int * refined_ptr )
```

Create a new fine grid (level 0) and corresponding grid hierarchy by refining the current fine grid based on user-provided refinement factors. Return the boolean `refined_ptr` to indicate whether grid refinement was actually done. To simplify the algorithm, refinement factors are automatically capped to be no greater than the coarsening factor (for level 0). The grid data is also redistributed to achieve good load balance in the temporal dimension. If the refinement factor is 1 in each time interval, no refinement is done.

16.1.3.16 `_braid_FRefineSpace()`

```

braid_Int _braid_FRefineSpace (
    braid_Core core,
    braid_Int * refined_ptr )

```

Call spatial refinement on all local time steps if `r_space` has been set on the local processor. Returns `refined_ptr == 2` if refinement was completed at any point globally, otherwise returns 0. This is a helper function for `_braid_FRefine()`.

16.1.3.17 `_braid_FRestrict()`

```

braid_Int _braid_FRestrict (
    braid_Core core,
    braid_Int level )

```

F-Relax on *level* and then restrict to *level+1*

The output is set in the `braid_Grid` in `core`, so that the restricted vectors *va* and *fa* will be created, representing *level+1* versions of the unknown and rhs vectors.

If the user has set spatial coarsening, then this user-defined routine is also called.

If *level==0*, then *rnorm_ptr* will contain the residual norm.

Parameters

<i>core</i>	<code>braid_Core</code> (<code>_braid_Core</code>) struct
<i>level</i>	restrict from level to level+1

16.1.3.18 `_braid_GetBlockDistInterval()`

```

braid_Int _braid_GetBlockDistInterval (
    braid_Int npoints,
    braid_Int nprocs,
    braid_Int proc,
    braid_Int * ilower_ptr,
    braid_Int * iupper_ptr )

```

Returns the index interval for *proc* in a blocked data distribution.

16.1.3.19 `_braid_GetBlockDistProc()`

```

braid_Int _braid_GetBlockDistProc (
    braid_Int npoints,
    braid_Int nprocs,
    braid_Int index,
    braid_Int periodic,
    braid_Int * proc_ptr )

```

Returns the processor that owns *index* in a blocked data distribution (returns -1 if *index* is out of range).

16.1.3.20 `_braid_GetCFactor()`

```
braid_Int _braid_GetCFactor (
    braid_Core core,
    braid_Int level,
    braid_Int * cfactor_ptr )
```

Returns the coarsening factor to use on grid *level*.

16.1.3.21 `_braid_GetDistribution()`

```
braid_Int _braid_GetDistribution (
    braid_Core core,
    braid_Int * ilower_ptr,
    braid_Int * iupper_ptr )
```

Returns the index interval for my processor on the finest grid level. For the processor rank calling this function, it returns the smallest and largest time indices (*ilower_ptr* and *iupper_ptr*) that belong to that processor (the indices may be F or C points).

16.1.3.22 `_braid_GetDtk()`

```
braid_Int _braid_GetDtk (
    braid_Core core )
```

Propagate time step information required to compute the Richardson error estimate at each C-point. This can be done at any time, but does require some communication. This fills in *error_factors* at the C points.

16.1.3.23 `_braid_GetFullRNorm()`

```
braid_Int _braid_GetFullRNorm (
    braid_Core core,
    braid_Int iter,
    braid_Real * rnorm_ptr )
```

Same as `GetRNorm`, but gets full residual norm.

16.1.3.24 `_braid_GetProc()`

```
braid_Int _braid_GetProc (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_Int * proc_ptr )
```

Returns the processor number in *proc_ptr* on which the time step *index* lives for the given *level*. Returns -1 if *index* is out of range.

16.1.3.25 `_braid_GetRNorm()`

```
braid_Int _braid_GetRNorm (
    braid_Core core,
    braid_Int iter,
    braid_Real * rnorm_ptr )
```

Get the residual norm for iteration `iter`. If `iter < 0`, get the `rnorm` for the last iteration minus $|\text{iter}|-1$.

16.1.3.26 `_braid_GetUInit()`

```
braid_Int _braid_GetUInit (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector u,
    braid_BaseVector * ustop_ptr )
```

Return an initial guess in `ustop_ptr` to use in the step routine for implicit schemes. The value returned depends on the storage options used. If the return value is NULL, no initial guess is available.

16.1.3.27 `_braid_GridClean()`

```
braid_Int _braid_GridClean (
    braid_Core core,
    _braid_Grid * grid )
```

Destroy the vectors on `grid`

16.1.3.28 `_braid_GridDestroy()`

```
braid_Int _braid_GridDestroy (
    braid_Core core,
    _braid_Grid * grid )
```

Destroy `grid`

16.1.3.29 `_braid_GridInit()`

```
braid_Int _braid_GridInit (
    braid_Core core,
    braid_Int level,
    braid_Int ilower,
    braid_Int iupper,
    _braid_Grid ** grid_ptr )
```

Create a new grid object `grid_ptr` with level indicator `level`. Arguments `ilower` and `iupper` correspond to the lower and upper time index values for this processor on this grid.

16.1.3.30 `_braid_InitGuess()`

```
braid_Int _braid_InitGuess (
    braid_Core core,
    braid_Int level )
```

Set initial guess on *level*. Only C-pts are initialized on level 0, otherwise stored values are initialized based on restricted fine-grid values.

16.1.3.31 `_braid_InitHierarchy()`

```
braid_Int _braid_InitHierarchy (
    braid_Core core,
    _braid_Grid * fine_grid,
    braid_Int refined )
```

Initialize grid hierarchy with *fine_grid* serving as the finest grid. Boolean *refined* indicates whether *fine_grid* was created by refining a coarser grid (in the `FRefine()` routine), which has implications on how to define CF-intervals.

16.1.3.32 `_braid_PrintSpatialNorms()`

```
braid_Int _braid_PrintSpatialNorms (
    braid_Core core,
    braid_Real * rnorms,
    braid_Int n )
```

Print out the residual norm for every C-point. Processor 0 gathers all the *rnorms* and prints them in order through a `gatherv` operator

16.1.3.33 `_braid_Refine()`

```
braid_Int _braid_Refine (
    braid_Core core,
    braid_Int level,
    braid_Int f_index,
    braid_Int c_index,
    braid_BaseVector cvector,
    braid_BaseVector * fvector )
```

Refine in space on *level* by calling the user's refine function. The vector corresponding to the time step index *c_index* on the coarse grid is refined to the time step index *f_index* on the fine grid. The output goes in *fvector* and the input vector is *cvector*.

16.1.3.34 `_braid_RefineBasic()`

```
braid_Int _braid_RefineBasic (
    braid_Core core,
    braid_Int level,
    braid_Int c_index,
    braid_Real * f_ta,
    braid_Real * c_ta,
    braid_BaseVector cvector,
    braid_BaseVector * fvector )
```

Refine in space (basic routine)

16.1.3.35 `_braid_Residual()`

```
braid_Int _braid_Residual (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector ustop,
    braid_BaseVector r )
```

Compute residual r

16.1.3.36 `_braid_SetFullRNorm()`

```
braid_Int _braid_SetFullRNorm (
    braid_Core core,
    braid_Int iter,
    braid_Real rnorm )
```

Same as `SetRNorm`, but sets full residual norm.

16.1.3.37 `_braid_SetRNorm()`

```
braid_Int _braid_SetRNorm (
    braid_Core core,
    braid_Int iter,
    braid_Real rnorm )
```

Set the residual norm for iteration `iter`. If `iter < 0`, set the `rnorm` for the last iteration minus $|\text{iter}|-1$. Also set the initial residual norm.

16.1.3.38 `_braid_Step()`

```
braid_Int _braid_Step (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector ustop,
    braid_BaseVector u )
```

Integrate one time step at time step `index` to time step `index+1`.

16.1.3.39 `_braid_Sync()`

```
braid_Int _braid_Sync (
    braid_Core core,
    braid_SyncStatus status )
```

Call user's sync function in order to give access to XBraid and the user's app. This is called once-per-processor at various points in XBraid in order to allow the user to perform any book-keeping operations. `status` provides state information about the current XBraid status and processor.

16.1.3.40 `_braid_UCommInit()`

```
braid_Int _braid_UCommInit (
    braid_Core core,
    braid_Int level )
```

This routine initiates communication under the assumption that work will be done on all intervals (F or C) on *level*. It posts a receive for the point to the left of *ilower* (regardless whether *ilower* is F or C), and it posts a send of *iupper* if *iupper* is a C point.

16.1.3.41 `_braid_UCommInitBasic()`

```
braid_Int _braid_UCommInitBasic (
    braid_Core core,
    braid_Int level,
    braid_Int recv_msg,
    braid_Int send_msg,
    braid_Int send_now )
```

Basic communication (from the left, to the right). Arguments *recv_msg* and *send_msg* are booleans that indicate whether or not to initiate a receive from the left and a send to the right respectively. Argument *send_now* indicates that the send should be initiated immediately.

16.1.3.42 `_braid_UCommInitF()`

```
braid_Int _braid_UCommInitF (
    braid_Core core,
    braid_Int level )
```

This routine initiates communication under the assumption that work will be done on only F-pt intervals on *level*. It only posts a receive for the point to the left of *ilower* if *ilower* is an F point, and it posts a send of *iupper* if *iupper* is a C point.

16.1.3.43 `_braid_UCommWait()`

```
braid_Int _braid_UCommWait (
    braid_Core core,
    braid_Int level )
```

Finish up communication. On *level*, wait on both the *recv* and *send* handles at this level.

16.1.3.44 `_braid_UGetIndex()`

```
braid_Int _braid_UGetIndex (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_Int * uindex_ptr,
    braid_Int * store_flag_ptr )
```

Returns an index into the local u-vector for grid *level* at point *index*, and information on the storage status of the point. If nothing is stored at that point, *uindex* = -1 and *store_flag* = -2. If only the shell is stored *store_flag* = -1, and if the whole u-vector is stored, *store_flag* = 0.

16.1.3.45 `_braid_UGetVector()`

```
braid_Int _braid_UGetVector (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector * u_ptr )
```

Returns a copy of the u-vector on grid *level* at point *index*. If *index* is my "receive index" (as set by `UCommlnit()`, for example), the u-vector will be received from a neighbor processor. If the u-vector is not stored, NULL is returned.

16.1.3.46 `_braid_UGetVectorRef()`

```
braid_Int _braid_UGetVectorRef (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector * u_ptr )
```

Returns a reference to the local u-vector on grid *level* at point *index*. If the u-vector is not stored, returns NULL.

16.1.3.47 `_braid_USetVector()`

```
braid_Int _braid_USetVector (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector u,
    braid_Int move )
```

Stores the u-vector on grid *level* at point *index*. If *index* is my "send index", a send is initiated to a neighbor processor. If *move* is true, the u-vector is moved into core storage instead of copied. If the u-vector is not stored, nothing is done.

16.1.3.48 `_braid_USetVectorRef()`

```
braid_Int _braid_USetVectorRef (
    braid_Core core,
    braid_Int level,
    braid_Int index,
    braid_BaseVector u )
```

Stores a reference to the local u-vector on grid *level* at point *index*. If the u-vector is not stored, nothing is done.

16.1.4 Variable Documentation

16.1.4.1 `_braid_error_flag`

```
braid_Int _braid_error_flag
```

This is the global XBraid error flag. If it is ever nonzero, an error has occurred.

16.1.4.2 `_braid_printfile`

```
FILE* _braid_printfile
```

This is the print file for redirecting stdout for all XBraid screen output

16.2 `adjoint.h` File Reference

Functions

- `braid_Int _braid_VectorBarCopy` (`braid_VectorBar` bar, `braid_VectorBar *bar_ptr`)
- `braid_Int _braid_VectorBarDelete` (`braid_Core` core, `braid_VectorBar` bar)
- `braid_Int _braid_OptimDestroy` (`braid_Core` core)
- `braid_Int _braid_UpdateAdjoint` (`braid_Core` core, `braid_Real *rnorm_adj_ptr`)
- `braid_Int _braid_SetRNormAdjoint` (`braid_Core` core, `braid_Int` iter, `braid_Real` rnorm_adj)
- `braid_Int _braid_AddToObjective` (`braid_Core` core, `braid_BaseVector` u, `braid_ObjectiveStatus` ostatus)
- `braid_Int _braid_EvalObjective` (`braid_Core` core)
- `braid_Int _braid_EvalObjective_diff` (`braid_Core` core)
- `braid_Int _braid_InitAdjointVars` (`braid_Core` core, `_braid_Grid *fine_grid`)
- `braid_Int _braid_AdjointFeatureCheck` (`braid_Core` core)

16.2.1 Detailed Description

Define internal XBraid headers for the adjoint feature.

This file contains the internal XBraid headers for the adjoint feature, e.g., the functions to wrap and call the users objective function, and allocate adjoint (bar) variables.

16.2.2 Function Documentation

16.2.2.1 `_braid_AddToObjective()`

```
braid_Int _braid_AddToObjective (
    braid_Core core,
    braid_BaseVector u,
    braid_ObjectiveStatus ostatus )
```

Evaluate the user's local objective function at time t and add it to the time-averaged objective function

16.2.2.2 `_braid_AdjointFeatureCheck()`

```
braid_Int _braid_AdjointFeatureCheck (
    braid_Core core )
```

Sanity check for non-supported adjoint features

16.2.2.3 `_braid_EvalObjective()`

```
braid_Int _braid_EvalObjective (
    braid_Core core )
```

Evaluate the objective function: MPI_Allreduce the time average and postprocess the objective

16.2.2.4 `_braid_EvalObjective_diff()`

```
braid_Int _braid_EvalObjective_diff (
    braid_Core core )
```

Differentiated objective function

16.2.2.5 `_braid_InitAdjointVars()`

```
braid_Int _braid_InitAdjointVars (
    braid_Core core,
    _braid_Grid * fine_grid )
```

Allocate and initialize the adjoint variables

16.2.2.6 `_braid_OptimDestroy()`

```
braid_Int _braid_OptimDestroy (
    braid_Core core )
```

Free memory of the optimization structure

16.2.2.7 `_braid_SetRNormAdjoint()`

```
braid_Int _braid_SetRNormAdjoint (
    braid_Core core,
    braid_Int iter,
    braid_Real rnorm_adj )
```

Set adjoint residual norm

16.2.2.8 `_braid_UpdateAdjoint()`

```
braid_Int _braid_UpdateAdjoint (
    braid_Core core,
    braid_Real * rnorm_adj_ptr )
```

Update the adjoint variables and compute adjoint residual norm Returns the tnorm of adjoint residual

16.2.2.9 `_braid_VectorBarCopy()`

```
braid_Int _braid_VectorBarCopy (
    braid_VectorBar bar,
    braid_VectorBar * bar_ptr )
```

Shallow copy a `braid_VectorBar` shared pointer, `bar_ptr` is set to `bar` and the `useCount` is incremented by one.

16.2.2.10 `_braid_VectorBarDelete()`

```
braid_Int _braid_VectorBarDelete (
    braid_Core core,
    braid_VectorBar bar )
```

Reduce the `useCount` of a `braid_VectorBar` shared pointer Free the pointer memory if `useCount` is zero.

16.3 `base.h` File Reference

Functions

- `braid_Int _braid_BaseStep` (`braid_Core` core, `braid_App` app, `braid_BaseVector` ustop, `braid_BaseVector` fstop, `braid_BaseVector` u, `braid_Int` level, `braid_StepStatus` status)
- `braid_Int _braid_BaseInit` (`braid_Core` core, `braid_App` app, `braid_Real` t, `braid_BaseVector` *u_ptr)
- `braid_Int _braid_BaseClone` (`braid_Core` core, `braid_App` app, `braid_BaseVector` u, `braid_BaseVector` *v_ptr)
- `braid_Int _braid_BaseFree` (`braid_Core` core, `braid_App` app, `braid_BaseVector` u)
- `braid_Int _braid_BaseSum` (`braid_Core` core, `braid_App` app, `braid_Real` alpha, `braid_BaseVector` x, `braid_Real` beta, `braid_BaseVector` y)
- `braid_Int _braid_BaseSpatialNorm` (`braid_Core` core, `braid_App` app, `braid_BaseVector` u, `braid_Real` *norm_ptr)
- `braid_Int _braid_BaseAccess` (`braid_Core` core, `braid_App` app, `braid_BaseVector` u, `braid_AccessStatus` status)
- `braid_Int _braid_BaseSync` (`braid_Core` core, `braid_App` app, `braid_SyncStatus` status)
- `braid_Int _braid_BaseBufSize` (`braid_Core` core, `braid_App` app, `braid_Int` *size_ptr, `braid_BufferStatus` status)
- `braid_Int _braid_BaseBufPack` (`braid_Core` core, `braid_App` app, `braid_BaseVector` u, `void` *buffer, `braid_Buffer`←
Status status)
- `braid_Int _braid_BaseBufUnpack` (`braid_Core` core, `braid_App` app, `void` *buffer, `braid_BaseVector` *u_ptr, `braid_BufferStatus` status)
- `braid_Int _braid_BaseObjectiveT` (`braid_Core` core, `braid_App` app, `braid_BaseVector` u, `braid_ObjectiveStatus` ostatus, `braid_Real` *objT_ptr)
- `braid_Int _braid_BaseResidual` (`braid_Core` core, `braid_App` app, `braid_BaseVector` ustop, `braid_BaseVector` r, `braid_StepStatus` status)
- `braid_Int _braid_BaseFullResidual` (`braid_Core` core, `braid_App` app, `braid_BaseVector` r, `braid_BaseVector` u, `braid_StepStatus` status)
- `braid_Int _braid_BaseSCoarsen` (`braid_Core` core, `braid_App` app, `braid_BaseVector` fu, `braid_BaseVector` *cu←
_ptr, `braid_CoarsenRefStatus` status)
- `braid_Int _braid_BaseSRefine` (`braid_Core` core, `braid_App` app, `braid_BaseVector` cu, `braid_BaseVector` *fu_ptr, `braid_CoarsenRefStatus` status)
- `braid_Int _braid_BaseSInit` (`braid_Core` core, `braid_App` app, `braid_Real` t, `braid_BaseVector` *u_ptr)
- `braid_Int _braid_BaseSClone` (`braid_Core` core, `braid_App` app, `braid_BaseVector` u, `braid_BaseVector` *v_ptr)
- `braid_Int _braid_BaseSFree` (`braid_Core` core, `braid_App` app, `braid_BaseVector` u)
- `braid_Int _braid_BaseTimeGrid` (`braid_Core` core, `braid_App` app, `braid_Real` *ta, `braid_Int` *ilower, `braid_Int` *iupper)

- [braid_Int_braid_BaseStep_diff](#) ([_braid_Action](#) *action)
- [braid_Int_braid_BaseClone_diff](#) ([_braid_Action](#) *action)
- [braid_Int_braid_BaseSum_diff](#) ([_braid_Action](#) *action)
- [braid_Int_braid_BaseObjectiveT_diff](#) ([_braid_Action](#) *action)
- [braid_Int_braid_BaseBufPack_diff](#) ([_braid_Action](#) *action)
- [braid_Int_braid_BaseBufUnpack_diff](#) ([_braid_Action](#) *action)
- [braid_Int_braid_BaseInit_diff](#) ([_braid_Action](#) *action)

16.3.1 Detailed Description

Define XBraid internal headers for wrapper routines of user-defined functions.

The XBraid internal headers defined here wrap the user-defined routines. If this is a normal XBraid run (i.e., no adjoint), then the wrappers serve no function, and just call the user's routines. If this is an XBraid_Adjoint run, then these routines record themselves to the action tape and push state and bar vectors to the primal and the bar tape, respectively. These vectors are then later popped from the tape and passed to the user *diff* routines in order to compute the differentiated actions. This is a form of automatic differentiation to compute the adjoint cycle.

16.3.2 Function Documentation

16.3.2.1 [_braid_BaseAccess\(\)](#)

```
braid_Int _braid_BaseAccess (
    braid_Core core,
    braid_App app,
    braid_BaseVector u,
    braid_AccessStatus status )
```

This calls the user's Access routine. If (adjoint): also record the action

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>u</i>	vector to be accessed
<i>status</i>	can be queried for info like the current XBraid Iteration

16.3.2.2 [_braid_BaseBufPack\(\)](#)

```
braid_Int _braid_BaseBufPack (
    braid_Core core,
    braid_App app,
```

```

    braid_BaseVector u,
    void * buffer,
    braid_BufferStatus status )

```

This calls the user's BufPack routine. If (adjoint): also record the action, and push to the bar tape.

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>u</i>	vector to pack into buffer
<i>buffer</i>	output, MPI buffer containing u
<i>status</i>	can be queried for info about the message

16.3.2.3 _braid_BaseBufPack_diff()

```

braid_Int _braid_BaseBufPack_diff (
    _braid_Action * action )

```

This pops the bar vector from the tape, and then performs the differentiated BufPack action using that vector as input: MPI_Recv(utmp) ubar += utmp

Parameters

<i>action</i>	_braid_Action structure, holds information about the primal XBraid action
---------------	---

16.3.2.4 _braid_BaseBufSize()

```

braid_Int _braid_BaseBufSize (
    braid_Core core,
    braid_App app,
    braid_Int * size_ptr,
    braid_BufferStatus status )

```

This calls the user's BufSize routine. If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>size_ptr</i>	upper bound on vector size in bytes
<i>status</i>	can be queried for info about the message type

16.3.2.5 `_braid_BaseBufUnpack()`

```
braid_Int _braid_BaseBufUnpack (
    braid_Core core,
    braid_App app,
    void * buffer,
    braid_BaseVector * u_ptr,
    braid_BufferStatus status )
```

This calls the user's BufUnPack routine. If (adjoint): also record the action, initialize the bar vector with zero and push it to the bar tape.

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>buffer</i>	MPI Buffer to unpack and place in u_ptr
<i>u_ptr</i>	output, braid_Vector containing buffer's data
<i>status</i>	can be queried for info about the message type

16.3.2.6 `_braid_BaseBufUnpack_diff()`

```
braid_Int _braid_BaseBufUnpack_diff (
    _braid_Action * action )
```

This pops the bar vector from the tape, and then performs the differentiated BufUnPack action using that vector as input: `MPI_Send(ubar); ubar = 0.0`

Parameters

<i>action</i>	<code>_braid_Action</code> structure, holds information about the primal XBraid action
---------------	--

16.3.2.7 `_braid_BaseClone()`

```
braid_Int _braid_BaseClone (
    braid_Core core,
    braid_App app,
    braid_BaseVector u,
    braid_BaseVector * v_ptr )
```

This initializes a `braid_BaseVector` and calls the user's clone routine. If (adjoint): also record the action, initialize a `barVector` with zero and push to the bar tape

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>u</i>	vector to clone
<i>v_ptr</i>	output, newly allocated and cloned vector

16.3.2.8 _braid_BaseClone_diff()

```
braid_Int _braid_BaseClone_diff (
    _braid_Action * action )
```

This pops bar vectors from the tape, and then performs the differentiated clone action using those vectors as input: $u_{bar} += v_{bar}$ $v_{bar} = 0.0$

Parameters

<i>action</i>	_braid_Action structure, holds information about the primal XBraid action
---------------	---

16.3.2.9 _braid_BaseFree()

```
braid_Int _braid_BaseFree (
    braid_Core core,
    braid_App app,
    braid_BaseVector u )
```

This calls the user's free routine. If (adjoint): also record the action, and free the bar vector.

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>u</i>	vector to free

16.3.2.10 _braid_BaseFullResidual()

```
braid_Int _braid_BaseFullResidual (
    braid_Core core,
    braid_App app,
    braid_BaseVector r,
```

```

    braid_BaseVector u,
    braid_StepStatus status )

```

This calls the user's FullResidual routine (full_rnorm_res). If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>r</i>	output, residual at <i>tstop</i>
<i>u</i>	input, <i>u</i> vector at <i>tstop</i>
<i>status</i>	braid_Status structure (pointer to the core)

16.3.2.11 _braid_BaseInit()

```

braid_Int _braid_BaseInit (
    braid_Core core,
    braid_App app,
    braid_Real t,
    braid_BaseVector * u_ptr )

```

This initializes a braid_BaseVector and calls the user's init routine. If (adjoint): also record the action, initialize barVector with zero and push to the bar tape.

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>t</i>	current time value for <i>u_ptr</i>
<i>u_ptr</i>	output, newly allocated and initialized vector

16.3.2.12 _braid_BaseInit_diff()

```

braid_Int _braid_BaseInit_diff (
    _braid_Action * action )

```

This pops the bar vector from the tape, and then call's the user's differentiated init routine (init_diff) using that vector as input. Note: init_diff is optional for the user.

Parameters

<i>action</i>	_braid_Action structure, holds information about the primal XBraid action
---------------	---

16.3.2.13 `_braid_BaseObjectiveT()`

```

braid_Int _braid_BaseObjectiveT (
    braid_Core core,
    braid_App app,
    braid_BaseVector u,
    braid_ObjectiveStatus ostatus,
    braid_Real * objT_ptr )

```

If (adjoint): This calls the user's ObjectiveT routine, records the action, and pushes to the state and bar tapes.

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>u</i>	input, state vector at current time
<i>ostatus</i>	status structure for querying time, index, etc.
<i>objT_ptr</i>	output, objective function value at current time

16.3.2.14 `_braid_BaseObjectiveT_diff()`

```

braid_Int _braid_BaseObjectiveT_diff (
    _braid_Action * action )

```

This pops state and bar vectors from the tape, and then calls the user's differentiated ObjectiveT routine (`objT_diff`) using those vectors as input: $\text{ubar} = (d(\text{objectiveT})/d(u))^T * \text{f_bar}$

Parameters

<i>action</i>	<code>_braid_Action</code> structure, holds information about the primal XBraid action
---------------	--

16.3.2.15 `_braid_BaseResidual()`

```

braid_Int _braid_BaseResidual (
    braid_Core core,
    braid_App app,
    braid_BaseVector ustop,
    braid_BaseVector r,
    braid_StepStatus status )

```

This calls the user's Residual routine. If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>ustop</i>	input, <i>u</i> vector at <i>tstop</i>
<i>r</i>	output, residual at <i>tstop</i> (at input, equals <i>u</i> at <i>tstart</i>)
<i>status</i>	braid_Status structure (pointer to the core)

16.3.2.16 _braid_BaseSClone()

```
braid_Int _braid_BaseSClone (
    braid_Core core,
    braid_App app,
    braid_BaseVector u,
    braid_BaseVector * v_ptr )
```

This clones a shell baseVector and call's the user's SClone routine. If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>u</i>	vector to clone
<i>v_ptr</i>	output, newly allocated and cloned vector shell

16.3.2.17 _braid_BaseSCoarsen()

```
braid_Int _braid_BaseSCoarsen (
    braid_Core core,
    braid_App app,
    braid_BaseVector fu,
    braid_BaseVector * cu_ptr,
    braid_CoarsenRefStatus status )
```

This initializes a baseVector and calls the user's SCoarsen routine. If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>fu</i>	braid_BaseVector to refine
<i>cu_ptr</i>	output, refined vector
<i>status</i>	braid_Status structure (pointer to the core)

16.3.2.18 _braid_BaseSFree()

```
braid_Int _braid_BaseSFree (
    braid_Core core,
    braid_App app,
    braid_BaseVector u )
```

Call the user's shell free (SFree) routine. If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>u</i>	vector to free (keeping the shell)

16.3.2.19 _braid_BaseSInit()

```
braid_Int _braid_BaseSInit (
    braid_Core core,
    braid_App app,
    braid_Real t,
    braid_BaseVector * u_ptr )
```

This initializes a shell baseVector and call's the user's Sinit routine. If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>t</i>	time value for <i>u_ptr</i>
<i>u_ptr</i>	output, newly allocated and initialized vector shell

16.3.2.20 _braid_BaseSpatialNorm()

```
braid_Int _braid_BaseSpatialNorm (
    braid_Core core,
    braid_App app,
    braid_BaseVector u,
    braid_Real * norm_ptr )
```

This calls the user's SpatialNorm routine. If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>u</i>	vector to norm
<i>norm_ptr</i>	output, norm of braid_Vector (this is a spatial norm)

16.3.2.21 _braid_BaseSRefine()

```
braid_Int _braid_BaseSRefine (
    braid_Core core,
    braid_App app,
    braid_BaseVector cu,
    braid_BaseVector * fu_ptr,
    braid_CoarsenRefStatus status )
```

This initializes a baseVector and calls the user's SRefine routine. If (adjoint): nothing

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure
<i>cu</i>	braid_BaseVector to refine
<i>fu_ptr</i>	output, refined vector
<i>status</i>	braid_Status structure (pointer to the core)

16.3.2.22 _braid_BaseStep()

```
braid_Int _braid_BaseStep (
    braid_Core core,
    braid_App app,
    braid_BaseVector ustop,
    braid_BaseVector fstop,
    braid_BaseVector u,
    braid_Int level,
    braid_StepStatus status )
```

This calls the user's step routine. If (adjoint): also record the action, and push state and bar vector to primal and bar tapes. braid_Status structure (pointer to the core)

Parameters

<i>core</i>	braid_Core structure
<i>app</i>	user-defined _braid_App structure

Parameters

<i>ustop</i>	input, <i>u</i> vector at <i>tstop</i>
<i>fstop</i>	input, right-hand-side at <i>tstop</i>
<i>u</i>	input/output, initially <i>u</i> vector at <i>tstart</i> , upon exit, <i>u</i> vector at <i>tstop</i>
<i>level</i>	current time grid level

16.3.2.23 `_braid_BaseStep_diff()`

```
braid_Int _braid_BaseStep_diff (
    _braid_Action * action )
```

This pops state and bar vectors from the tape, and then calls the user's differentiated step routine (`step_diff`) using those vectors as input. $\text{ubar} = (d(\text{step})/d(u))^T * \text{ubar}$

Parameters

<i>action</i>	<code>_braid_Action</code> structure, holds information about the primal XBraid action
---------------	--

16.3.2.24 `_braid_BaseSum()`

```
braid_Int _braid_BaseSum (
    braid_Core core,
    braid_App app,
    braid_Real alpha,
    braid_BaseVector x,
    braid_Real beta,
    braid_BaseVector y )
```

This calls the user's sum routine. If (adjoint): also record the action, and push to the bar tape.

Parameters

<i>core</i>	<code>braid_Core</code> structure
<i>app</i>	user-defined <code>_braid_App</code> structure
<i>alpha</i>	scalar for AXPY
<i>x</i>	vector for AXPY
<i>beta</i>	scalar for AXPY
<i>y</i>	output and vector for AXPY

16.3.2.25 `_braid_BaseSum_diff()`

```
braid_Int _braid_BaseSum_diff (
    _braid_Action * action )
```

This pops bar vectors from the tape, and then performs the differentiated sum action using those vectors as input: $xbar += alpha * ybar$ $ybar = beta * ybar$

Parameters

<i>action</i>	<code>_braid_Action</code> structure, holds information about the primal XBraid action
---------------	--

16.3.2.26 `_braid_BaseSync()`

```
braid_Int _braid_BaseSync (
    braid_Core core,
    braid_App app,
    braid_SyncStatus status )
```

This calls the user's Sync routine. If (adjoint): nothing

Parameters

<i>core</i>	<code>braid_Core</code> structure
<i>app</i>	user-defined <code>_braid_App</code> structure
<i>status</i>	can be queried for info like the current XBraid Iteration

16.3.2.27 `_braid_BaseTimeGrid()`

```
braid_Int _braid_BaseTimeGrid (
    braid_Core core,
    braid_App app,
    braid_Real * ta,
    braid_Int * ilower,
    braid_Int * iupper )
```

This calls the user's TimeGrid routine, which allows the user to explicitly define the initial time grid. If (adjoint): nothing

Parameters

<i>core</i>	<code>braid_Core</code> structure
<i>app</i>	user-defined <code>_braid_App</code> structure
<i>ta</i>	temporal grid on level 0 (slice per processor)
<i>ilower</i>	lower time index value for this processor
<i>iupper</i>	upper time index value for this processor

16.4 braid.h File Reference

Macros

- #define `braid_FMANGLE` 1
- #define `braid_Fortran_SpatialCoarsen` 0
- #define `braid_Fortran_Residual` 1
- #define `braid_Fortran_TimeGrid` 1
- #define `braid_Fortran_Sync` 1
- #define `braid_INVALID_RNORM` -1
- #define `braid_ERROR_GENERIC` 1 /* generic error */
- #define `braid_ERROR_MEMORY` 2 /* unable to allocate memory */
- #define `braid_ERROR_ARG` 4 /* argument error */
- #define `braid_RAND_MAX` 32768

Typedefs

- typedef struct `_braid_App_struct` * `braid_App`
- typedef struct `_braid_Vector_struct` * `braid_Vector`
- typedef `braid_Int`(* `braid_PtFcnStep`) (`braid_App` app, `braid_Vector` ustop, `braid_Vector` fstop, `braid_Vector` u, `braid_StepStatus` status)
- typedef `braid_Int`(* `braid_PtFcnInit`) (`braid_App` app, `braid_Real` t, `braid_Vector` *u_ptr)
- typedef `braid_Int`(* `braid_PtFcnClone`) (`braid_App` app, `braid_Vector` u, `braid_Vector` *v_ptr)
- typedef `braid_Int`(* `braid_PtFcnFree`) (`braid_App` app, `braid_Vector` u)
- typedef `braid_Int`(* `braid_PtFcnSum`) (`braid_App` app, `braid_Real` alpha, `braid_Vector` x, `braid_Real` beta, `braid_←_Vector` y)
- typedef `braid_Int`(* `braid_PtFcnSpatialNorm`) (`braid_App` app, `braid_Vector` u, `braid_Real` *norm_ptr)
- typedef `braid_Int`(* `braid_PtFcnAccess`) (`braid_App` app, `braid_Vector` u, `braid_AccessStatus` status)
- typedef `braid_Int`(* `braid_PtFcnSync`) (`braid_App` app, `braid_SyncStatus` status)
- typedef `braid_Int`(* `braid_PtFcnBufSize`) (`braid_App` app, `braid_Int` *size_ptr, `braid_BufferStatus` status)
- typedef `braid_Int`(* `braid_PtFcnBufPack`) (`braid_App` app, `braid_Vector` u, void *buffer, `braid_BufferStatus` status)
- typedef `braid_Int`(* `braid_PtFcnBufUnpack`) (`braid_App` app, void *buffer, `braid_Vector` *u_ptr, `braid_BufferStatus` status)
- typedef `braid_Int`(* `braid_PtFcnResidual`) (`braid_App` app, `braid_Vector` ustop, `braid_Vector` r, `braid_StepStatus` status)
- typedef `braid_Int`(* `braid_PtFcnSCoarsen`) (`braid_App` app, `braid_Vector` fu, `braid_Vector` *cu_ptr, `braid_←_CoarsenRefStatus` status)
- typedef `braid_Int`(* `braid_PtFcnSRefine`) (`braid_App` app, `braid_Vector` cu, `braid_Vector` *fu_ptr, `braid_←_CoarsenRefStatus` status)
- typedef `braid_Int`(* `braid_PtFcnSInit`) (`braid_App` app, `braid_Real` t, `braid_Vector` *u_ptr)
- typedef `braid_Int`(* `braid_PtFcnSClone`) (`braid_App` app, `braid_Vector` u, `braid_Vector` *v_ptr)
- typedef `braid_Int`(* `braid_PtFcnSFree`) (`braid_App` app, `braid_Vector` u)
- typedef `braid_Int`(* `braid_PtFcnTimeGrid`) (`braid_App` app, `braid_Real` *ta, `braid_Int` *ilower, `braid_Int` *iupper)
- typedef `braid_Int`(* `braid_PtFcnObjectiveT`) (`braid_App` app, `braid_Vector` u, `braid_ObjectiveStatus` ostatus, `braid_Real` *objectiveT_ptr)
- typedef `braid_Int`(* `braid_PtFcnObjectiveTDiff`) (`braid_App` app, `braid_Vector` u, `braid_Vector` u_bar, `braid_Real` F_bar, `braid_ObjectiveStatus` ostatus)
- typedef `braid_Int`(* `braid_PtFcnPostprocessObjective`) (`braid_App` app, `braid_Real` sum_obj, `braid_Real` *postprocess_ptr)
- typedef `braid_Int`(* `braid_PtFcnPostprocessObjective_diff`) (`braid_App` app, `braid_Real` sum_obj, `braid_Real` *F_←_bar_ptr)
- typedef `braid_Int`(* `braid_PtFcnStepDiff`) (`braid_App` app, `braid_Vector` ustop, `braid_Vector` u, `braid_Vector` ustop_bar, `braid_Vector` u_bar, `braid_StepStatus` status)
- typedef `braid_Int`(* `braid_PtFcnResetGradient`) (`braid_App` app)
- typedef struct `_braid_Core_struct` * `braid_Core`

Functions

- [braid_Int braid_Init](#) (MPI_Comm comm_world, MPI_Comm comm, [braid_Real tstart](#), [braid_Real tstop](#), [braid_Int ntime](#), [braid_App app](#), [braid_PtFcnStep step](#), [braid_PtFcnInit init](#), [braid_PtFcnClone clone](#), [braid_PtFcnFree free](#), [braid_PtFcnSum sum](#), [braid_PtFcnSpatialNorm spatialnorm](#), [braid_PtFcnAccess access](#), [braid_PtFcnBufSize bufsize](#), [braid_PtFcnBufPack bufpack](#), [braid_PtFcnBufUnpack bufunpack](#), [braid_Core *core_ptr](#))
- [braid_Int braid_Drive](#) ([braid_Core core](#))
- [braid_Int braid_Destroy](#) ([braid_Core core](#))
- [braid_Int braid_PrintStats](#) ([braid_Core core](#))
- [braid_Int braid_WriteConvHistory](#) ([braid_Core core](#), const char *filename)
- [braid_Int braid_SetMaxLevels](#) ([braid_Core core](#), [braid_Int max_levels](#))
- [braid_Int braid_SetIncrMaxLevels](#) ([braid_Core core](#))
- [braid_Int braid_SetSkip](#) ([braid_Core core](#), [braid_Int skip](#))
- [braid_Int braid_SetRefine](#) ([braid_Core core](#), [braid_Int refine](#))
- [braid_Int braid_SetMaxRefinements](#) ([braid_Core core](#), [braid_Int max_refinements](#))
- [braid_Int braid_SetTPointsCutoff](#) ([braid_Core core](#), [braid_Int tpoints_cutoff](#))
- [braid_Int braid_SetMinCoarse](#) ([braid_Core core](#), [braid_Int min_coarse](#))
- [braid_Int braid_SetAbsTol](#) ([braid_Core core](#), [braid_Real atol](#))
- [braid_Int braid_SetRelTol](#) ([braid_Core core](#), [braid_Real rtol](#))
- [braid_Int braid_SetNRelax](#) ([braid_Core core](#), [braid_Int level](#), [braid_Int nrelax](#))
- [braid_Int braid_SetCRelaxWt](#) ([braid_Core core](#), [braid_Int level](#), [braid_Real Cwt](#))
- [braid_Int braid_SetCFactor](#) ([braid_Core core](#), [braid_Int level](#), [braid_Int cfactor](#))
- [braid_Int braid_SetMaxIter](#) ([braid_Core core](#), [braid_Int max_iter](#))
- [braid_Int braid_SetFMG](#) ([braid_Core core](#))
- [braid_Int braid_SetNFMG](#) ([braid_Core core](#), [braid_Int k](#))
- [braid_Int braid_SetNFMGVcyc](#) ([braid_Core core](#), [braid_Int nfmfg_Vcyc](#))
- [braid_Int braid_SetStorage](#) ([braid_Core core](#), [braid_Int storage](#))
- [braid_Int braid_SetTemporalNorm](#) ([braid_Core core](#), [braid_Int tnorm](#))
- [braid_Int braid_SetResidual](#) ([braid_Core core](#), [braid_PtFcnResidual residual](#))
- [braid_Int braid_SetFullRNormRes](#) ([braid_Core core](#), [braid_PtFcnResidual residual](#))
- [braid_Int braid_SetTimeGrid](#) ([braid_Core core](#), [braid_PtFcnTimeGrid tgrid](#))
- [braid_Int braid_SetPeriodic](#) ([braid_Core core](#), [braid_Int periodic](#))
- [braid_Int braid_SetSpatialCoarsen](#) ([braid_Core core](#), [braid_PtFcnSCoarsen scoarsen](#))
- [braid_Int braid_SetSpatialRefine](#) ([braid_Core core](#), [braid_PtFcnSRefine srefine](#))
- [braid_Int braid_SetSync](#) ([braid_Core core](#), [braid_PtFcnSync sync](#))
- [braid_Int braid_SetPrintLevel](#) ([braid_Core core](#), [braid_Int print_level](#))
- [braid_Int braid_SetFileIOLevel](#) ([braid_Core core](#), [braid_Int io_level](#))
- [braid_Int braid_SetPrintFile](#) ([braid_Core core](#), const char *printfile_name)
- [braid_Int braid_SetDefaultPrintFile](#) ([braid_Core core](#))
- [braid_Int braid_SetAccessLevel](#) ([braid_Core core](#), [braid_Int access_level](#))
- [braid_Int braid_SplitCommworld](#) (const MPI_Comm *comm_world, [braid_Int px](#), MPI_Comm *comm_x, MPI_Comm *comm_t)
- [braid_Int braid_SetShell](#) ([braid_Core core](#), [braid_PtFcnSInit sinit](#), [braid_PtFcnSClone sclone](#), [braid_PtFcnSFree sfree](#))
- [braid_Int braid_GetNumIter](#) ([braid_Core core](#), [braid_Int *niter_ptr](#))
- [braid_Int braid_GetRNorms](#) ([braid_Core core](#), [braid_Int *nrequest_ptr](#), [braid_Real *rnorms](#))
- [braid_Int braid_GetNLevels](#) ([braid_Core core](#), [braid_Int *nlevels_ptr](#))
- [braid_Int braid_GetSpatialAccuracy](#) ([braid_StepStatus status](#), [braid_Real loose_tol](#), [braid_Real tight_tol](#), [braid_Real *tol_ptr](#))
- [braid_Int braid_SetSeqSoln](#) ([braid_Core core](#), [braid_Int seq_soln](#))
- [braid_Int braid_GetMyID](#) ([braid_Core core](#), [braid_Int *myid_ptr](#))

- `braid_Int braid_Rand` (void)
- `braid_Int braid_InitAdjoint` (`braid_PtFcnObjectiveT` objectiveT, `braid_PtFcnObjectiveTDiff` objectiveT_diff, `braid_PtFcnStepDiff` step_diff, `braid_PtFcnResetGradient` reset_gradient, `braid_Core` *core_ptr)
- `braid_Int braid_SetTStartObjective` (`braid_Core` core, `braid_Real` tstart_obj)
- `braid_Int braid_SetTStopObjective` (`braid_Core` core, `braid_Real` tstop_obj)
- `braid_Int braid_SetPostprocessObjective` (`braid_Core` core, `braid_PtFcnPostprocessObjective` post_fcn)
- `braid_Int braid_SetPostprocessObjective_diff` (`braid_Core` core, `braid_PtFcnPostprocessObjective_diff` post_fcn_diff)
- `braid_Int braid_SetAbsTolAdjoint` (`braid_Core` core, `braid_Real` tol_adj)
- `braid_Int braid_SetRelTolAdjoint` (`braid_Core` core, `braid_Real` rtol_adj)
- `braid_Int braid_SetObjectiveOnly` (`braid_Core` core, `braid_Int` boolean)
- `braid_Int braid_GetObjective` (`braid_Core` core, `braid_Real` *objective_ptr)
- `braid_Int braid_GetRNormAdjoint` (`braid_Core` core, `braid_Real` *rnorm_adj)
- `braid_Int braid_SetRichardsonEstimation` (`braid_Core` core, `braid_Int` est_error, `braid_Int` richardson, `braid_Int` local_order)

16.4.1 Detailed Description

Define headers for user-interface routines.

This file contains user-routines used to allow the user to initialize, run and get and set options for a XBraid solver.

16.5 braid_defs.h File Reference

Macros

- `#define braid_Int_Max` INT_MAX;
- `#define braid_Int_Min` INT_MIN;
- `#define braid_MPI_REAL` MPI_DOUBLE
- `#define braid_MPI_INT` MPI_INT

Typedefs

- `typedef int braid_Int`
- `typedef double braid_Real`

16.5.1 Detailed Description

Definitions of braid types, error flags, etc...

16.5.2 Macro Definition Documentation

16.5.2.1 braid_Int_Max

```
#define braid_Int_Max INT_MAX;
```

16.5.2.2 braid_Int_Min

```
#define braid_Int_Min INT_MIN;
```

16.5.2.3 braid_MPI_INT

```
#define braid_MPI_INT MPI_INT
```

16.5.2.4 braid_MPI_REAL

```
#define braid_MPI_REAL MPI_DOUBLE
```

16.5.3 Typedef Documentation

16.5.3.1 braid_Int

```
typedef int braid_Int
```

Defines integer type

16.5.3.2 braid_Real

```
typedef double braid_Real
```

Defines floating point type

16.6 braid_status.h File Reference

Macros

- #define [ACCESSOR_HEADER_GET1](#)(stype, param, vtype1) [braid_Int](#) [braid_##stype##StatusGet##param](#)([braid_↵_##stype##Status](#) s, [braid_##vtype1](#) *v1);
- #define [ACCESSOR_HEADER_GET1_IN3](#)(stype, param, vtype1, vtype2, vtype3, vtype4) [braid_Int](#) [braid_↵_##stype##StatusGet##param](#)([braid_##stype##Status](#) s, [braid_##vtype1](#) *v1, [braid_##vtype2](#) v2, [braid_##vtype3](#) v3, [braid_##vtype4](#) v4);
- #define [ACCESSOR_HEADER_GET2](#)(stype, param, vtype1, vtype2) [braid_Int](#) [braid_##stype##Status↵Get##param](#)([braid_##stype##Status](#) s, [braid_##vtype1](#) *v1, [braid_##vtype2](#) *v2);
- #define [ACCESSOR_HEADER_GET2_IN1](#)(stype, param, vtype1, vtype2, vtype3) [braid_Int](#) [braid_↵_##stype##StatusGet##param](#)([braid_##stype##Status](#) s, [braid_##vtype1](#) *v1, [braid_##vtype2](#) *v2, [braid_↵_##vtype3](#) v3);
- #define [ACCESSOR_HEADER_GET3](#)(stype, param, vtype1, vtype2, vtype3) [braid_Int](#) [braid_##stype##Status↵Get##param](#)([braid_##stype##Status](#) s, [braid_##vtype1](#) *v1, [braid_##vtype2](#) *v2, [braid_##vtype3](#) *v3);
- #define [ACCESSOR_HEADER_GET4](#)(stype, param, vtype1, vtype2, vtype3, vtype4) [braid_Int](#) [braid_↵_##stype##StatusGet##param](#)([braid_##stype##Status](#) s, [braid_##vtype1](#) *v1, [braid_##vtype2](#) *v2, [braid_↵_##vtype3](#) *v3, [braid_##vtype4](#) *v4);
- #define [ACCESSOR_HEADER_GET5](#)(stype, param, vtype1, vtype2, vtype3, vtype4, vtype5) [braid_Int](#) [braid_↵_##stype##StatusGet##param](#)([braid_##stype##Status](#) s, [braid_##vtype1](#) *v1, [braid_##vtype2](#) *v2, [braid_↵_##vtype3](#) *v3, [braid_##vtype4](#) *v4, [braid_##vtype5](#) *v5);
- #define [ACCESSOR_HEADER_SET1](#)(stype, param, vtype1) [braid_Int](#) [braid_##stype##StatusSet##param](#)([braid_↵_##stype##Status](#) s, [braid_##vtype1](#) v1);
- #define [braid_ASCaller_FInterp](#) 0
- #define [braid_ASCaller_FRestrict](#) 1
- #define [braid_ASCaller_FRefine](#) 2
- #define [braid_ASCaller_FAccess](#) 3
- #define [braid_ASCaller_FRefine_AfterInitHier](#) 4
- #define [braid_ASCaller_Drive_TopCycle](#) 5

Functions

- [braid_Int](#) [braid_StatusGetT](#) ([braid_Status](#) status, [braid_Real](#) *t_ptr)
- [braid_Int](#) [braid_StatusGetTIndex](#) ([braid_Status](#) status, [braid_Int](#) *idx_ptr)
- [braid_Int](#) [braid_StatusGetIter](#) ([braid_Status](#) status, [braid_Int](#) *iter_ptr)
- [braid_Int](#) [braid_StatusGetLevel](#) ([braid_Status](#) status, [braid_Int](#) *level_ptr)
- [braid_Int](#) [braid_StatusGetNLevels](#) ([braid_Status](#) status, [braid_Int](#) *nlevels_ptr)
- [braid_Int](#) [braid_StatusGetNRefine](#) ([braid_Status](#) status, [braid_Int](#) *nrefine_ptr)
- [braid_Int](#) [braid_StatusGetNTPoints](#) ([braid_Status](#) status, [braid_Int](#) *ntpoints_ptr)
- [braid_Int](#) [braid_StatusGetResidual](#) ([braid_Status](#) status, [braid_Real](#) *rnorm_ptr)
- [braid_Int](#) [braid_StatusGetDone](#) ([braid_Status](#) status, [braid_Int](#) *done_ptr)
- [braid_Int](#) [braid_StatusGetTIUL](#) ([braid_Status](#) status, [braid_Int](#) *iloc_upper, [braid_Int](#) *iloc_lower, [braid_Int](#) level)
- [braid_Int](#) [braid_StatusGetTimeValues](#) ([braid_Status](#) status, [braid_Real](#) **tvalues_ptr, [braid_Int](#) i_upper, [braid_Int](#) i_lower, [braid_Int](#) level)
- [braid_Int](#) [braid_StatusGetTILD](#) ([braid_Status](#) status, [braid_Real](#) *t_ptr, [braid_Int](#) *iter_ptr, [braid_Int](#) *level_ptr, [braid_Int](#) *done_ptr)
- [braid_Int](#) [braid_StatusGetWrapperTest](#) ([braid_Status](#) status, [braid_Int](#) *wtest_ptr)
- [braid_Int](#) [braid_StatusGetCallingFunction](#) ([braid_Status](#) status, [braid_Int](#) *cfunction_ptr)
- [braid_Int](#) [braid_StatusGetCTprior](#) ([braid_Status](#) status, [braid_Real](#) *ctprior_ptr)

- [braid_Int braid_StatusGetCTstop](#) (braid_Status status, [braid_Real *ctstop_ptr](#))
- [braid_Int braid_StatusGetFTPrior](#) (braid_Status status, [braid_Real *ftprior_ptr](#))
- [braid_Int braid_StatusGetFTstop](#) (braid_Status status, [braid_Real *ftstop_ptr](#))
- [braid_Int braid_StatusGetTpriorTstop](#) (braid_Status status, [braid_Real *t_ptr](#), [braid_Real *ftprior_ptr](#), [braid_Real *ftstop_ptr](#), [braid_Real *ctprior_ptr](#), [braid_Real *ctstop_ptr](#))
- [braid_Int braid_StatusGetTstop](#) (braid_Status status, [braid_Real *tstop_ptr](#))
- [braid_Int braid_StatusGetTstartTstop](#) (braid_Status status, [braid_Real *tstart_ptr](#), [braid_Real *tstop_ptr](#))
- [braid_Int braid_StatusGetTol](#) (braid_Status status, [braid_Real *tol_ptr](#))
- [braid_Int braid_StatusGetRNorms](#) (braid_Status status, [braid_Int *nrequest_ptr](#), [braid_Real *rnorms_ptr](#))
- [braid_Int braid_StatusGetOldFineTolx](#) (braid_Status status, [braid_Real *old_fine_tolx_ptr](#))
- [braid_Int braid_StatusSetOldFineTolx](#) (braid_Status status, [braid_Real old_fine_tolx](#))
- [braid_Int braid_StatusSetTightFineTolx](#) (braid_Status status, [braid_Real tight_fine_tolx](#))
- [braid_Int braid_StatusSetRFactor](#) (braid_Status status, [braid_Real rfactor](#))
- [braid_Int braid_StatusSetRefinementDtValues](#) (braid_Status status, [braid_Real rfactor](#), [braid_Real *dtarray](#))
- [braid_Int braid_StatusSetRSpace](#) (braid_Status status, [braid_Real r_space](#))
- [braid_Int braid_StatusGetMessageType](#) (braid_Status status, [braid_Int *messagetype_ptr](#))
- [braid_Int braid_StatusSetSize](#) (braid_Status status, [braid_Real size](#))
- [braid_Int braid_StatusGetSingleErrorEstStep](#) (braid_Status status, [braid_Real *estimate](#))
- [braid_Int braid_StatusGetSingleErrorEstAccess](#) (braid_Status status, [braid_Real *estimate](#))
- [braid_Int braid_StatusGetNumErrorEst](#) (braid_Status status, [braid_Int *npoints](#))
- [braid_Int braid_StatusGetAllErrorEst](#) (braid_Status status, [braid_Real *error_est](#))
- [braid_Int braid_AccessStatusGetT](#) (braid_AccessStatus s, [braid_Real *v1](#))
- [braid_Int braid_AccessStatusGetTIndex](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetIter](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetLevel](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetNLevels](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetNRefine](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetNTPoints](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetResidual](#) (braid_AccessStatus s, [braid_Real *v1](#))
- [braid_Int braid_AccessStatusGetDone](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetTILD](#) (braid_AccessStatus s, [braid_Real *v1](#), [braid_Int *v2](#), [braid_Int *v3](#), [braid_Int *v4](#))
- [braid_Int braid_AccessStatusGetWrapperTest](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetCallingFunction](#) (braid_AccessStatus s, [braid_Int *v1](#))
- [braid_Int braid_AccessStatusGetSingleErrorEstAccess](#) (braid_AccessStatus s, [braid_Real *v1](#))
- [braid_Int braid_SyncStatusGetTIUL](#) (braid_SyncStatus s, [braid_Int *v1](#), [braid_Int *v2](#), [braid_Int v3](#))
- [braid_Int braid_SyncStatusGetTimeValues](#) (braid_SyncStatus s, [braid_Real **v1](#), [braid_Int v2](#), [braid_Int v3](#), [braid_Int v4](#))
- [braid_Int braid_SyncStatusGetIter](#) (braid_SyncStatus s, [braid_Int *v1](#))
- [braid_Int braid_SyncStatusGetLevel](#) (braid_SyncStatus s, [braid_Int *v1](#))
- [braid_Int braid_SyncStatusGetNLevels](#) (braid_SyncStatus s, [braid_Int *v1](#))
- [braid_Int braid_SyncStatusGetNRefine](#) (braid_SyncStatus s, [braid_Int *v1](#))
- [braid_Int braid_SyncStatusGetNTPoints](#) (braid_SyncStatus s, [braid_Int *v1](#))
- [braid_Int braid_SyncStatusGetDone](#) (braid_SyncStatus s, [braid_Int *v1](#))
- [braid_Int braid_SyncStatusGetCallingFunction](#) (braid_SyncStatus s, [braid_Int *v1](#))
- [braid_Int braid_SyncStatusGetNumErrorEst](#) (braid_SyncStatus s, [braid_Int *v1](#))
- [braid_Int braid_SyncStatusGetAllErrorEst](#) (braid_SyncStatus s, [braid_Real *v1](#))
- [braid_Int braid_CoarsenRefStatusGetT](#) (braid_CoarsenRefStatus s, [braid_Real *v1](#))
- [braid_Int braid_CoarsenRefStatusGetTIndex](#) (braid_CoarsenRefStatus s, [braid_Int *v1](#))
- [braid_Int braid_CoarsenRefStatusGetIter](#) (braid_CoarsenRefStatus s, [braid_Int *v1](#))
- [braid_Int braid_CoarsenRefStatusGetLevel](#) (braid_CoarsenRefStatus s, [braid_Int *v1](#))

- [braid_Int braid_CoarsenRefStatusGetNLevels](#) (braid_CoarsenRefStatus s, [braid_Int *v1](#))
- [braid_Int braid_CoarsenRefStatusGetNRefine](#) (braid_CoarsenRefStatus s, [braid_Int *v1](#))
- [braid_Int braid_CoarsenRefStatusGetNTPoints](#) (braid_CoarsenRefStatus s, [braid_Int *v1](#))
- [braid_Int braid_CoarsenRefStatusGetCTprior](#) (braid_CoarsenRefStatus s, [braid_Real *v1](#))
- [braid_Int braid_CoarsenRefStatusGetCTstop](#) (braid_CoarsenRefStatus s, [braid_Real *v1](#))
- [braid_Int braid_CoarsenRefStatusGetFTprior](#) (braid_CoarsenRefStatus s, [braid_Real *v1](#))
- [braid_Int braid_CoarsenRefStatusGetFTstop](#) (braid_CoarsenRefStatus s, [braid_Real *v1](#))
- [braid_Int braid_CoarsenRefStatusGetTpriorTstop](#) (braid_CoarsenRefStatus s, [braid_Real *v1](#), [braid_Real *v2](#), [braid_Real *v3](#), [braid_Real *v4](#), [braid_Real *v5](#))
- [braid_Int braid_StepStatusGetT](#) (braid_StepStatus s, [braid_Real *v1](#))
- [braid_Int braid_StepStatusGetTIndex](#) (braid_StepStatus s, [braid_Int *v1](#))
- [braid_Int braid_StepStatusGetTIter](#) (braid_StepStatus s, [braid_Int *v1](#))
- [braid_Int braid_StepStatusGetLevel](#) (braid_StepStatus s, [braid_Int *v1](#))
- [braid_Int braid_StepStatusGetNLevels](#) (braid_StepStatus s, [braid_Int *v1](#))
- [braid_Int braid_StepStatusGetNRefine](#) (braid_StepStatus s, [braid_Int *v1](#))
- [braid_Int braid_StepStatusGetNTPoints](#) (braid_StepStatus s, [braid_Int *v1](#))
- [braid_Int braid_StepStatusGetTstop](#) (braid_StepStatus s, [braid_Real *v1](#))
- [braid_Int braid_StepStatusGetTstartTstop](#) (braid_StepStatus s, [braid_Real *v1](#), [braid_Real *v2](#))
- [braid_Int braid_StepStatusGetTol](#) (braid_StepStatus s, [braid_Real *v1](#))
- [braid_Int braid_StepStatusGetRNorms](#) (braid_StepStatus s, [braid_Int *v1](#), [braid_Real *v2](#))
- [braid_Int braid_StepStatusGetOldFineTolx](#) (braid_StepStatus s, [braid_Real *v1](#))
- [braid_Int braid_StepStatusSetOldFineTolx](#) (braid_StepStatus s, [braid_Real v1](#))
- [braid_Int braid_StepStatusSetTightFineTolx](#) (braid_StepStatus s, [braid_Real v1](#))
- [braid_Int braid_StepStatusSetRFactor](#) (braid_StepStatus s, [braid_Real v1](#))
- [braid_Int braid_StepStatusSetRSpace](#) (braid_StepStatus s, [braid_Real v1](#))
- [braid_Int braid_StepStatusGetSingleErrorEstStep](#) (braid_StepStatus s, [braid_Real *v1](#))
- [braid_Int braid_BufferStatusGetMessageType](#) (braid_BufferStatus s, [braid_Int *v1](#))
- [braid_Int braid_BufferStatusSetSize](#) (braid_BufferStatus s, [braid_Real v1](#))
- [braid_Int braid_ObjectiveStatusGetT](#) (braid_ObjectiveStatus s, [braid_Real *v1](#))
- [braid_Int braid_ObjectiveStatusGetTIndex](#) (braid_ObjectiveStatus s, [braid_Int *v1](#))
- [braid_Int braid_ObjectiveStatusGetTIter](#) (braid_ObjectiveStatus s, [braid_Int *v1](#))
- [braid_Int braid_ObjectiveStatusGetLevel](#) (braid_ObjectiveStatus s, [braid_Int *v1](#))
- [braid_Int braid_ObjectiveStatusGetNLevels](#) (braid_ObjectiveStatus s, [braid_Int *v1](#))
- [braid_Int braid_ObjectiveStatusGetNRefine](#) (braid_ObjectiveStatus s, [braid_Int *v1](#))
- [braid_Int braid_ObjectiveStatusGetNTPoints](#) (braid_ObjectiveStatus s, [braid_Int *v1](#))
- [braid_Int braid_ObjectiveStatusGetTol](#) (braid_ObjectiveStatus s, [braid_Real *v1](#))

16.6.1 Detailed Description

Define headers for the user-interface with the XBraid status structures, allowing the user to get/set status structure values.

16.6.2 Macro Definition Documentation

16.6.2.1 ACCESSOR_HEADER_GET1

```
#define ACCESSOR_HEADER_GET1(  
    stype,  
    param,  
    vtype1 ) braid_Int braid_##stype##StatusGet##param(braid_##stype##Status s, braid_↔  
##vtype1 *v1);
```

Macros allowing for auto-generation of 'inherited' StatusGet functions

16.6.2.2 ACCESSOR_HEADER_GET1_IN3

```
#define ACCESSOR_HEADER_GET1_IN3(  
    stype,  
    param,  
    vtype1,  
    vtype2,  
    vtype3,  
    vtype4 ) braid_Int braid_##stype##StatusGet##param(braid_##stype##Status s, braid_↔  
##vtype1 *v1, braid_##vtype2 v2, braid_##vtype3 v3, braid_##vtype4 v4);
```

16.6.2.3 ACCESSOR_HEADER_GET2

```
#define ACCESSOR_HEADER_GET2(  
    stype,  
    param,  
    vtype1,  
    vtype2 ) braid_Int braid_##stype##StatusGet##param(braid_##stype##Status s, braid_↔  
##vtype1 *v1, braid_##vtype2 *v2);
```

16.6.2.4 ACCESSOR_HEADER_GET2_IN1

```
#define ACCESSOR_HEADER_GET2_IN1(  
    stype,  
    param,  
    vtype1,  
    vtype2,  
    vtype3 ) braid_Int braid_##stype##StatusGet##param(braid_##stype##Status s, braid_↔  
##vtype1 *v1, braid_##vtype2 *v2, braid_##vtype3 v3);
```

16.6.2.5 ACCESSOR_HEADER_GET3

```
#define ACCESSOR_HEADER_GET3(  
    stype,  
    param,  
    vtype1,  
    vtype2,  
    vtype3 ) braid_Int braid_##stype##StatusGet##param(braid_##stype##Status s, braid_↔  
##vtype1 *v1, braid_##vtype2 *v2, braid_##vtype3 *v3);
```


16.6.2.6 ACCESSOR_HEADER_GET4

```
#define ACCESSOR_HEADER_GET4(
    stype,
    param,
    vtype1,
    vtype2,
    vtype3,
    vtype4 ) braid_Int braid_##stype##StatusGet##param(braid_##stype##Status s, braid_↔
##vtype1 *v1, braid_##vtype2 *v2, braid_##vtype3 *v3, braid_##vtype4 *v4);
```

16.6.2.7 ACCESSOR_HEADER_GET5

```
#define ACCESSOR_HEADER_GET5(
    stype,
    param,
    vtype1,
    vtype2,
    vtype3,
    vtype4,
    vtype5 ) braid_Int braid_##stype##StatusGet##param(braid_##stype##Status s, braid_↔
##vtype1 *v1, braid_##vtype2 *v2, braid_##vtype3 *v3, braid_##vtype4 *v4, braid_##vtype5 *v5);
```

16.6.2.8 ACCESSOR_HEADER_SET1

```
#define ACCESSOR_HEADER_SET1(
    stype,
    param,
    vtype1 ) braid_Int braid_##stype##StatusSet##param(braid_##stype##Status s, braid_↔
##vtype1 v1);
```

16.7 braid_test.h File Reference

Functions

- [braid_Int braid_TestInitAccess](#) ([braid_App](#) app, [MPI_Comm](#) comm_x, [FILE](#) *fp, [braid_Real](#) t, [braid_PtFcnInit](#) init, [braid_PtFcnAccess](#) access, [braid_PtFcnFree](#) free)
- [braid_Int braid_TestClone](#) ([braid_App](#) app, [MPI_Comm](#) comm_x, [FILE](#) *fp, [braid_Real](#) t, [braid_PtFcnInit](#) init, [braid_PtFcnAccess](#) access, [braid_PtFcnFree](#) free, [braid_PtFcnClone](#) clone)
- [braid_Int braid_TestSum](#) ([braid_App](#) app, [MPI_Comm](#) comm_x, [FILE](#) *fp, [braid_Real](#) t, [braid_PtFcnInit](#) init, [braid_PtFcnAccess](#) access, [braid_PtFcnFree](#) free, [braid_PtFcnClone](#) clone, [braid_PtFcnSum](#) sum)
- [braid_Int braid_TestSpatialNorm](#) ([braid_App](#) app, [MPI_Comm](#) comm_x, [FILE](#) *fp, [braid_Real](#) t, [braid_PtFcnInit](#) init, [braid_PtFcnFree](#) free, [braid_PtFcnClone](#) clone, [braid_PtFcnSum](#) sum, [braid_PtFcnSpatialNorm](#) spatialnorm)
- [braid_Int braid_TestBuf](#) ([braid_App](#) app, [MPI_Comm](#) comm_x, [FILE](#) *fp, [braid_Real](#) t, [braid_PtFcnInit](#) init, [braid_PtFcnFree](#) free, [braid_PtFcnSum](#) sum, [braid_PtFcnSpatialNorm](#) spatialnorm, [braid_PtFcnBufSize](#) bufsize, [braid_PtFcnBufPack](#) bufpack, [braid_PtFcnBufUnpack](#) bufunpack)

- [braid_Int braid_TestCoarsenRefine](#) ([braid_App](#) app, [MPI_Comm](#) comm_x, [FILE](#) *fp, [braid_Real](#) t, [braid_Real](#) fdt, [braid_Real](#) cdt, [braid_PtFcnInit](#) init, [braid_PtFcnAccess](#) access, [braid_PtFcnFree](#) free, [braid_PtFcnClone](#) clone, [braid_PtFcnSum](#) sum, [braid_PtFcnSpatialNorm](#) spatialnorm, [braid_PtFcnSCoarsen](#) coarsen, [braid_PtFcnSRefine](#) refine)
- [braid_Int braid_TestResidual](#) ([braid_App](#) app, [MPI_Comm](#) comm_x, [FILE](#) *fp, [braid_Real](#) t, [braid_Real](#) dt, [braid_PtFcnInit](#) myinit, [braid_PtFcnAccess](#) myaccess, [braid_PtFcnFree](#) myfree, [braid_PtFcnClone](#) clone, [braid_PtFcnSum](#) sum, [braid_PtFcnSpatialNorm](#) spatialnorm, [braid_PtFcnResidual](#) residual, [braid_PtFcnStep](#) step)
- [braid_Int braid_TestAll](#) ([braid_App](#) app, [MPI_Comm](#) comm_x, [FILE](#) *fp, [braid_Real](#) t, [braid_Real](#) fdt, [braid_Real](#) cdt, [braid_PtFcnInit](#) init, [braid_PtFcnFree](#) free, [braid_PtFcnClone](#) clone, [braid_PtFcnSum](#) sum, [braid_PtFcnSpatialNorm](#) spatialnorm, [braid_PtFcnBufSize](#) bufsize, [braid_PtFcnBufPack](#) bufpack, [braid_PtFcnBufUnpack](#) bufunpack, [braid_PtFcnSCoarsen](#) coarsen, [braid_PtFcnSRefine](#) refine, [braid_PtFcnResidual](#) residual, [braid_PtFcnStep](#) step)

16.7.1 Detailed Description

Define headers for XBraid user-test routines.

This file contains headers for the user to test their XBraid wrapper routines one-by-one.

16.8 mpistubs.h File Reference

16.8.1 Detailed Description

XBraid internal headers to define fake MPI stubs. This ultimately allows the user to generate purely serial codes without MPI.

16.9 status.h File Reference

Data Structures

- struct [_braid_Status](#)
- struct [braid_AccessStatus](#)
- struct [braid_SyncStatus](#)
- struct [braid_StepStatus](#)
- struct [braid_CoarsenRefStatus](#)
- struct [braid_BufferStatus](#)
- struct [braid_ObjectiveStatus](#)

Macros

- `#define _braid_StatusElt(status, elt) (((braid_Core)status) -> elt)`

Functions

- [braid_Int _braid_StatusDestroy](#) (braid_Status status)
- [braid_Int _braid_AccessStatusInit](#) (braid_Real t, braid_Int idx, braid_Real rnorm, braid_Int iter, braid_Int level, braid_Int nrefine, braid_Int gupper, braid_Int done, braid_Int wrapper_test, braid_Int calling_function, braid_↔ AccessStatus status)
- [braid_Int _braid_SyncStatusInit](#) (braid_Int iter, braid_Int level, braid_Int nrefine, braid_Int gupper, braid_Int done, braid_Int calling_function, braid_SyncStatus status)
- [braid_Int _braid_CoarsenRefStatusInit](#) (braid_Real tstart, braid_Real f_tprior, braid_Real f_tstop, braid_Real c_↔ tprior, braid_Real c_tstop, braid_Int level, braid_Int nrefine, braid_Int gupper, braid_Int c_index, braid_Coarsen↔ RefStatus status)
- [braid_Int _braid_StepStatusInit](#) (braid_Real tstart, braid_Real tstop, braid_Int idx, braid_Real tol, braid_Int iter, braid_Int level, braid_Int nrefine, braid_Int gupper, braid_StepStatus status)
- [braid_Int _braid_BufferStatusInit](#) (braid_Int messagetype, braid_Int size, braid_BufferStatus status)
- [braid_Int _braid_ObjectiveStatusInit](#) (braid_Real tstart, braid_Int idx, braid_Int iter, braid_Int level, braid_Int nrefine, braid_Int gupper, braid_ObjectiveStatus status)

16.9.1 Detailed Description

Define the XBraid internal headers for the XBraid status structure routines, and define the status structures themselves.

16.9.2 Macro Definition Documentation

16.9.2.1 _braid_StatusElt

```
#define _braid_StatusElt(
    status,
    elt ) ( ((braid_Core)status) -> elt )
```

16.9.3 Function Documentation

16.9.3.1 _braid_AccessStatusInit()

```
braid_Int _braid_AccessStatusInit (
    braid_Real t,
    braid_Int idx,
    braid_Real rnorm,
    braid_Int iter,
    braid_Int level,
    braid_Int nrefine,
    braid_Int gupper,
    braid_Int done,
    braid_Int wrapper_test,
    braid_Int calling_function,
    braid_AccessStatus status )
```

Initialize a braid_AccessStatus structure

Parameters

<i>t</i>	current time
<i>idx</i>	time point index value corresponding to <i>t</i> on the global time grid
<i>rnorm</i>	current residual norm in XBraid
<i>iter</i>	current iteration in XBraid
<i>level</i>	current level in XBraid
<i>nrefine</i>	number of refinements done
<i>gupper</i>	global size of the fine grid
<i>done</i>	boolean describing whether XBraid has finished
<i>wrapper_test</i>	boolean describing whether this call is only a wrapper test
<i>calling_function</i>	from which function are we accessing the vector
<i>status</i>	structure to initialize

16.9.3.2 `_braid_BufferStatusInit()`

```
braid_Int _braid_BufferStatusInit (
    braid_Int messagetype,
    braid_Int size,
    braid_BufferStatus status )
```

Initialize a `braid_BufferStatus` structure

Parameters

<i>messagetype</i>	message type, 0: for Step(), 1: for load balancing
<i>size</i>	if set by user, size of send buffer is "size" bytes
<i>status</i>	structure to initialize

16.9.3.3 `_braid_CoarsenRefStatusInit()`

```
braid_Int _braid_CoarsenRefStatusInit (
    braid_Real tstart,
    braid_Real f_tprior,
    braid_Real f_tstop,
    braid_Real c_tprior,
    braid_Real c_tstop,
    braid_Int level,
    braid_Int nrefine,
    braid_Int gupper,
    braid_Int c_index,
    braid_CoarsenRefStatus status )
```

Initialize a `braid_CoarsenRefStatus` structure

Parameters

<i>tstart</i>	time value for current vector
<i>f_tprior</i>	time value to the left of tstart on fine grid
<i>f_tstop</i>	time value to the right of tstart on fine grid
<i>c_tprior</i>	time value to the left of tstart on coarse grid
<i>c_tstop</i>	time value to the right of tstart on coarse grid
<i>level</i>	current fine level in XBraid
<i>nrefine</i>	number of refinements done
<i>gupper</i>	global size of the fine grid
<i>c_index</i>	coarse time index refining from
<i>status</i>	structure to initialize

16.9.3.4 `_braid_ObjectiveStatusInit()`

```

braid_Int _braid_ObjectiveStatusInit (
    braid_Real tstart,
    braid_Int idx,
    braid_Int iter,
    braid_Int level,
    braid_Int nrefine,
    braid_Int gupper,
    braid_ObjectiveStatus status )

```

Initialize a `braid_ObjectiveStatus` structure

16.9.3.5 `_braid_StatusDestroy()`

```

braid_Int _braid_StatusDestroy (
    braid_Status status )

```

16.9.3.6 `_braid_StepStatusInit()`

```

braid_Int _braid_StepStatusInit (
    braid_Real tstart,
    braid_Real tstop,
    braid_Int idx,
    braid_Real tol,
    braid_Int iter,
    braid_Int level,
    braid_Int nrefine,
    braid_Int gupper,
    braid_StepStatus status )

```

Initialize a `braid_StepStatus` structure

Parameters

<i>tstart</i>	current time value
<i>tstop</i>	time value to evolve towards, time value to the right of <i>tstart</i>
<i>idx</i>	time point index value corresponding to <i>tstart</i> on the global time grid
<i>tol</i>	Current XBraid stopping tolerance
<i>iter</i>	Current XBraid iteration (also equal to length of <i>rnorms</i>)
<i>level</i>	current level in XBraid
<i>nrefine</i>	number of refinements done
<i>gupper</i>	global size of the fine grid
<i>status</i>	structure to initialize

16.9.3.7 `_braid_SyncStatusInit()`

```

braid_Int _braid_SyncStatusInit (
    braid_Int iter,
    braid_Int level,
    braid_Int nrefine,
    braid_Int gupper,
    braid_Int done,
    braid_Int calling_function,
    braid_SyncStatus status )

```

Initialize a `braid_SyncStatus` structure

Parameters

<i>iter</i>	current iteration in XBraid
<i>level</i>	current level in XBraid
<i>nrefine</i>	number of refinements done
<i>gupper</i>	global size of the fine grid
<i>done</i>	boolean describing whether XBraid has finished
<i>calling_function</i>	from which function are we accessing braid
<i>status</i>	structure to initialize

16.10 `tape.h` File Reference

Data Structures

- struct [_braid_Tape](#)
- struct [_braid_Action](#)

Enumerations

- enum `_braid_Call` {
`STEP = 1, INIT = 2, CLONE = 3, FREE = 4,`
`SUM = 5, BUFPACK = 6, BUFUNPACK = 7, ACCESS = 8,`
`OBJECTIVET = 9 }`

Functions

- `braid_Int _braid_TapeInit (_braid_Tape *head)`
- `_braid_Tape * _braid_TapePush (_braid_Tape *head, void *ptr)`
- `_braid_Tape * _braid_TapePop (_braid_Tape *head)`
- `braid_Int _braid_TapeIsEmpty (_braid_Tape *head)`
- `braid_Int _braid_TapeGetSize (_braid_Tape *head)`
- `braid_Int _braid_TapeDisplayBackwards (braid_Core core, _braid_Tape *head, void(*fctptr)(braid_Core core, void *data_ptr))`
- `braid_Int _braid_TapeEvaluate (braid_Core core)`
- `braid_Int _braid_DiffCall (_braid_Action *action)`
- `braid_Int _braid_TapeSetSeed (braid_Core core)`
- `braid_Int _braid_TapeResetInput (braid_Core core)`
- `const char * _braid_CallGetName (_braid_Call call)`

16.10.1 Detailed Description

Define the XBraid internal headers for the action-tape routines (linked list for AD)

16.10.2 Enumeration Type Documentation

16.10.2.1 `_braid_Call`

```
enum _braid_Call
```

Enumerator for identifying performed action

Enumerator

STEP	
INIT	
CLONE	
FREE	
SUM	
BUFPACK	
BUFUNPACK	
ACCESS	
OBJECTIVET	

16.10.3 Function Documentation

16.10.3.1 `_braid_CallGetName()`

```
const char* _braid_CallGetName (
    _braid_Call call )
```

Return the name of a `_braid_Call` (action name)

16.10.3.2 `_braid_DiffCall()`

```
braid_Int _braid_DiffCall (
    _braid_Action * action )
```

Call differentiated action

16.10.3.3 `_braid_TapeDisplayBackwards()`

```
braid_Int _braid_TapeDisplayBackwards (
    braid_Core core,
    _braid_Tape * head,
    void(*) (braid_Core core, void *data_ptr) fctptr )
```

Display the tape in reverse order, calls the display function at each element Input: - pointer to the braid core

- pointer to the display function

16.10.3.4 `_braid_TapeEvaluate()`

```
braid_Int _braid_TapeEvaluate (
    braid_Core core )
```

Evaluate the action tape in reverse order. This will clear the action tape! Input: - pointer to the braid core

- pointer to the head of the action tape

16.10.3.5 `_braid_TapeGetSize()`

```
braid_Int _braid_TapeGetSize (
    _braid_Tape * head )
```

Returns the number of elements in the tape

16.10.3.6 `_braid_TapeInit()`

```
braid_Int _braid_TapeInit (
    _braid_Tape * head )
```

Initialize the tape Set head to NULL

16.10.3.7 `_braid_TapeIsEmpty()`

```
braid_Int _braid_TapeIsEmpty (
    _braid_Tape * head )
```

Test if tape is empty return 1 if tape is empty, otherwise returns 0

16.10.3.8 `_braid_TapePop()`

```
_braid_Tape* _braid_TapePop (
    _braid_Tape * head )
```

Pop an element from the tape Return pointer to head

16.10.3.9 `_braid_TapePush()`

```
_braid_Tape* _braid_TapePush (
    _braid_Tape * head,
    void * ptr )
```

Push data on the tape Return pointer to head

16.10.3.10 `_braid_TapeResetInput()`

```
braid_Int _braid_TapeResetInput (
    braid_Core core )
```

Set the pointers in tapeinput to the input of an xbraid iteration (ua).

16.10.3.11 `_braid_TapeSetSeed()`

```
braid_Int _braid_TapeSetSeed (
    braid_Core core )
```

Set the adjoint seed for tape evaluation, i.e., set $u \rightarrow \bar{}$ at stored points on level 0 to the values contained in `core->optim->adjoints`

16.11 util.h File Reference

Functions

- [braid_Int _braid_ProjectInterval](#) ([braid_Int](#) ilower, [braid_Int](#) iupper, [braid_Int](#) index, [braid_Int](#) stride, [braid_Int](#) *pilower, [braid_Int](#) *piupper)
- [braid_Int _braid_GetInterval](#) ([braid_Core](#) core, [braid_Int](#) level, [braid_Int](#) interval_index, [braid_Int](#) *flo_ptr, [braid_Int](#) *fhi_ptr, [braid_Int](#) *ci_ptr)
- [braid_Int _braid_SetVerbosity](#) ([braid_Core](#) core, [braid_Int](#) verbose_adj)
- [braid_Int _braid_printf](#) (const char *format,...)
- [braid_Int _braid_ParPrintfFlush](#) (FILE *file, [braid_Int](#) myid, const char *message,...)
- [braid_Int _braid_Max](#) ([braid_Real](#) *array, [braid_Int](#) size, [braid_Real](#) *max_val)
- [braid_Int _braid_GetNEntries](#) ([braid_Real](#) *_array, [braid_Int](#) array_len, [braid_Int](#) *k_ptr, [braid_Real](#) *array)

16.11.1 Detailed Description

Define XBraid internal headers for utility routines.

This file contains the headers for utility routines. Essentially, if a routine does not take `braid_Core` (or other XBraid specific structs) as an argument, then it's a utility routine.

16.11.2 Function Documentation

16.11.2.1 `_braid_GetInterval()`

```
braid_Int _braid_GetInterval (
    braid_Core core,
    braid_Int level,
    braid_Int interval_index,
    braid_Int * flo_ptr,
    braid_Int * fhi_ptr,
    braid_Int * ci_ptr )
```

Retrieve the time step indices at this *level* corresponding to a local FC interval given by *interval_index*. Argument *ci_ptr* is the time step index for the C-pt and *flo_ptr* and *fhi_ptr* are the smallest and largest F-pt indices in this interval. The C-pt is always to the right of the F-interval, but neither a C-pt or an F-interval are guaranteed. If the *ci_ptr* returns a -1, there is no C-pt. If the *flo_ptr* is greater than the *fhi_ptr*, there is no F-interval.

16.11.2.2 `_braid_GetNEntries()`

```
braid_Int _braid_GetNEntries (
    braid_Real *_array,
    braid_Int array_len,
    braid_Int * k_ptr,
    braid_Real * array )
```

Copy *k* entries from **_array** into *array*. If *k* is negative, return the last *k* entries. If positive, return the first *k* entries. Upon exit, *k* holds the number of residuals actually returned (in the case that $|k| > \text{array_len}$.)

If no entries are copied, $k=0$, $\text{array}[0] = -1.0$

16.11.2.3 `_braid_Max()`

```
braid_Int _braid_Max (
    braid_Real * array,
    braid_Int size,
    braid_Real * max_val )
```

This function finds the maximum value in a `braid_Real` array

16.11.2.4 `_braid_ParPrintfFlush()`

```
braid_Int _braid_ParPrintfFlush (
    FILE * file,
    braid_Int myid,
    const char * message,
    ... )
```

This is a function that allows for "sane" printing of information in parallel. Currently, only `myid = 0` prints, but this can be updated as needs change.

The string *message* is printed and can be multiple parameters in the standard * C-format, like
`message = '%1.2e is a format string', 1.24`

16.11.2.5 `_braid_printf()`

```
braid_Int _braid_printf (
    const char * format,
    ... )
```

If set, print to `_braid_printfile` and then flush. Else print to standard out.

The string *format* can be multiple parameters in the standard * C-format, like
`format = '%1.2e is a format string', 1.24`

16.11.2.6 `_braid_ProjectInterval()`

```
braid_Int _braid_ProjectInterval (
    braid_Int ilower,
    braid_Int iupper,
    braid_Int index,
    braid_Int stride,
    braid_Int * pilower,
    braid_Int * piupper )
```

Project an interval onto a strided index space that contains the index 'index' and has stride 'stride'. An empty projection is represented by `ilower > iupper`.

16.11.2.7 `_braid_SetVerbosity()`

```
braid_Int _braid_SetVerbosity (
    braid_Core core,
    braid_Int verbose_adj )
```

Switch for displaying the XBraid actions. Used for debugging only.

Index

- [_braid.h, 155](#)
 - [_braid_AccessVector, 161](#)
 - [_braid_CTAlloc, 158](#)
 - [_braid_Coarsen, 161](#)
 - [_braid_CommHandleElt, 158](#)
 - [_braid_CommRecvInit, 162](#)
 - [_braid_CommSendInit, 162](#)
 - [_braid_CommWait, 162](#)
 - [_braid_ComputeFullIRNorm, 162](#)
 - [_braid_CopyFineToCoarse, 162](#)
 - [_braid_CoreElt, 158](#)
 - [_braid_CoreFcn, 158](#)
 - [_braid_Drive, 163](#)
 - [_braid_Error, 158](#)
 - [_braid_ErrorHandler, 163](#)
 - [_braid_ErrorInArg, 158](#)
 - [_braid_FASResidual, 163](#)
 - [_braid_FAccess, 163](#)
 - [_braid_FCRelax, 163](#)
 - [_braid_FInterp, 164](#)
 - [_braid_FRefine, 164](#)
 - [_braid_FRefineSpace, 164](#)
 - [_braid_FRestrict, 165](#)
 - [_braid_FinalizeErrorEstimates, 164](#)
 - [_braid_GetBlockDistInterval, 165](#)
 - [_braid_GetBlockDistProc, 165](#)
 - [_braid_GetCFactor, 165](#)
 - [_braid_GetDistribution, 166](#)
 - [_braid_GetDtk, 166](#)
 - [_braid_GetFullIRNorm, 166](#)
 - [_braid_GetProc, 166](#)
 - [_braid_GetRNorm, 166](#)
 - [_braid_GetUInit, 167](#)
 - [_braid_GridClean, 167](#)
 - [_braid_GridDestroy, 167](#)
 - [_braid_GridElt, 158](#)
 - [_braid_GridInit, 167](#)
 - [_braid_InitGuess, 167](#)
 - [_braid_InitHierarchy, 168](#)
 - [_braid_IsCPoint, 159](#)
 - [_braid_IsFPoint, 159](#)
 - [_braid_MapCoarseToFine, 159](#)
 - [_braid_MapFineToCoarse, 159](#)
 - [_braid_MapPeriodic, 159](#)
 - [_braid_NextCPoint, 160](#)
 - [_braid_PrintSpatialNorms, 168](#)
 - [_braid_PriorCPoint, 160](#)
 - [_braid_RecvIndexNull, 160](#)
 - [_braid_Refine, 168](#)
 - [_braid_RefineBasic, 168](#)
 - [_braid_Residual, 168](#)
 - [_braid_SendIndexNull, 160](#)
 - [_braid_SetFullIRNorm, 169](#)
 - [_braid_SetRNorm, 169](#)
 - [_braid_Step, 169](#)
 - [_braid_Sync, 169](#)
 - [_braid_TAlloc, 161](#)
 - [_braid_TFree, 161](#)
 - [_braid_TReAlloc, 161](#)
 - [_braid_UCommInit, 169](#)
 - [_braid_UCommInitF, 170](#)
 - [_braid_UCommInitBasic, 170](#)
 - [_braid_UCommWait, 170](#)
 - [_braid_UGetIndex, 170](#)
 - [_braid_UGetVector, 170](#)
 - [_braid_UGetVectorRef, 171](#)
 - [_braid_USetVector, 171](#)
 - [_braid_USetVectorRef, 171](#)
 - [_braid_error_flag, 171](#)
 - [_braid_isnan, 159](#)
 - [_braid_max, 160](#)
 - [_braid_min, 160](#)
 - [_braid_printfile, 172](#)
- [_braid_AccessStatusInit](#)
 - [status.h, 196](#)
- [_braid_AccessStatus_struct](#)
 - [status, 148](#)
- [_braid_AccessVector](#)
 - [_braid.h, 161](#)
- [_braid_Action, 123](#)
 - [braid_iter, 123](#)
 - [braidCall, 123](#)
 - [core, 123](#)
 - [gupper, 124](#)
 - [inTime, 124](#)
 - [inTimeldx, 124](#)
 - [level, 124](#)
 - [messagetype, 124](#)
 - [myid, 124](#)
 - [nrefine, 124](#)
 - [outTime, 124](#)
 - [send_recv_rank, 125](#)
 - [size_buffer, 125](#)
 - [sum_alpha, 125](#)
 - [sum_beta, 125](#)
 - [tol, 125](#)
- [_braid_AddToObjective](#)
 - [adjoint.h, 172](#)
- [_braid_AdjointFeatureCheck](#)
 - [adjoint.h, 172](#)
- [_braid_BaseAccess](#)
 - [base.h, 175](#)

_braid_BaseBufPack
 base.h, 175
 _braid_BaseBufPack_diff
 base.h, 176
 _braid_BaseBufSize
 base.h, 176
 _braid_BaseBufUnpack
 base.h, 177
 _braid_BaseBufUnpack_diff
 base.h, 177
 _braid_BaseClone
 base.h, 177
 _braid_BaseClone_diff
 base.h, 178
 _braid_BaseFree
 base.h, 178
 _braid_BaseFullResidual
 base.h, 178
 _braid_BaseInit
 base.h, 179
 _braid_BaseInit_diff
 base.h, 179
 _braid_BaseObjectiveT
 base.h, 180
 _braid_BaseObjectiveT_diff
 base.h, 180
 _braid_BaseResidual
 base.h, 180
 _braid_BaseSClone
 base.h, 181
 _braid_BaseSCoarsen
 base.h, 181
 _braid_BaseSFree
 base.h, 182
 _braid_BaseSInit
 base.h, 182
 _braid_BaseSRefine
 base.h, 183
 _braid_BaseSpatialNorm
 base.h, 182
 _braid_BaseStep
 base.h, 183
 _braid_BaseStep_diff
 base.h, 184
 _braid_BaseSum
 base.h, 184
 _braid_BaseSum_diff
 base.h, 184
 _braid_BaseSync
 base.h, 185
 _braid_BaseTimeGrid
 base.h, 185
 _braid_BaseVector_struct
 bar, 149
 userVector, 149
 _braid_BufferStatusInit
 status.h, 197
 _braid_BufferStatus_struct
 status, 149
 _braid_CTAlloc
 _braid.h, 158
 _braid_Call
 tape.h, 200
 _braid_CallGetName
 tape.h, 201
 _braid_Coarsen
 _braid.h, 161
 _braid_CoarsenRefStatusInit
 status.h, 197
 _braid_CoarsenRefStatus_struct
 status, 150
 _braid_CommHandle, 125
 buffer, 126
 num_requests, 126
 request_type, 126
 requests, 126
 status, 126
 vector_ptr, 126
 _braid_CommHandleElt
 _braid.h, 158
 _braid_CommRecvInit
 _braid.h, 162
 _braid_CommSendInit
 _braid.h, 162
 _braid_CommWait
 _braid.h, 162
 _braid_ComputeFullIRNorm
 _braid.h, 162
 _braid_CopyFineToCoarse
 _braid.h, 162
 _braid_Core, 127
 access, 129
 access_level, 129
 actionTape, 129
 adjoint, 129
 app, 129
 barTape, 130
 bufpack, 130
 bufsize, 130
 bufunpack, 130
 c_tprior, 130
 c_tstop, 130
 CWt_default, 131
 CWts, 131
 calling_function, 130
 cfactors, 130
 cfdefault, 131
 clone, 131

comm, 131
 comm_world, 131
 done, 131
 dtk, 131
 est_error, 132
 estimate, 132
 f_tprior, 132
 f_tstop, 132
 fmg, 132
 free, 132
 full_rnorm0, 132
 full_rnorm_res, 132
 full_rnorms, 133
 globaltime, 133
 grids, 133
 gupper, 133
 idx, 133
 incr_max_levels, 133
 init, 133
 initiali, 133
 io_level, 134
 level, 134
 localtime, 134
 max_iter, 134
 max_levels, 134
 max_refinements, 134
 messagetype, 134
 min_coarse, 134
 myid, 135
 myid_world, 135
 nfmg, 135
 nfmg_Vcyc, 135
 niter, 135
 nlevels, 135
 nrdefault, 135
 nrefine, 135
 nrels, 136
 ntime, 136
 obj_only, 136
 objT_diff, 136
 objectiveT, 136
 old_fine_tolx, 136
 optim, 136
 order, 136
 periodic, 137
 postprocess_obj, 137
 postprocess_obj_diff, 137
 print_level, 137
 r_space, 137
 rdtvalues, 137
 record, 137
 refine, 137
 reset_gradient, 138
 residual, 138
 rfactor, 138
 rfactors, 138
 richardson, 138
 rnorm, 138
 rnorm0, 138
 rnorms, 138
 rstopped, 139
 rtol, 139
 sclone, 139
 scoarsen, 139
 send_recv_rank, 139
 seq_soln, 139
 sfree, 139
 sinit, 139
 size_buffer, 140
 skip, 140
 spatialnorm, 140
 srefine, 140
 step, 140
 step_diff, 140
 storage, 140
 sum, 140
 sync, 141
 t, 141
 tgrid, 141
 tight_fine_tolx, 141
 tnext, 141
 tnorm, 141
 tnorm_a, 141
 tol, 141
 tpoints_cutoff, 142
 tstart, 142
 tstop, 142
 userVectorTape, 142
 useshell, 142
 verbose_adj, 142
 warm_restart, 142
 wrapper_test, 142
 _braid_CoreElt
 _braid.h, 158
 _braid_CoreFcn
 _braid.h, 158
 _braid_DiffCall
 tape.h, 201
 _braid_Drive
 _braid.h, 163
 _braid_Error
 _braid.h, 158
 _braid_ErrorHandler
 _braid.h, 163
 _braid_ErrorInArg
 _braid.h, 158
 _braid_EvalObjective
 adjoint.h, 173

_braid_EvalObjective_diff
 adjoint.h, 173
 _braid_FASResidual
 _braid.h, 163
 _braid_FAccess
 _braid.h, 163
 _braid_FCRelax
 _braid.h, 163
 _braid_FInterp
 _braid.h, 164
 _braid_FRefine
 _braid.h, 164
 _braid_FRefineSpace
 _braid.h, 164
 _braid_FRestrict
 _braid.h, 165
 _braid_FinalizeErrorEstimates
 _braid.h, 164
 _braid_GetBlockDistInterval
 _braid.h, 165
 _braid_GetBlockDistProc
 _braid.h, 165
 _braid_GetCFactor
 _braid.h, 165
 _braid_GetDistribution
 _braid.h, 166
 _braid_GetDtk
 _braid.h, 166
 _braid_GetFullRNorm
 _braid.h, 166
 _braid_GetInterval
 util.h, 203
 _braid_GetNEntries
 util.h, 203
 _braid_GetProc
 _braid.h, 166
 _braid_GetRNorm
 _braid.h, 166
 _braid_GetUInit
 _braid.h, 167
 _braid_Grid, 143
 cfactor, 143
 clower, 144
 cupper, 144
 fa, 144
 fa_alloc, 144
 gupper, 144
 ilower, 144
 iupper, 144
 level, 144
 ncpoints, 145
 nupoints, 145
 recv_handle, 145
 recv_index, 145
 send_handle, 145
 send_index, 145
 ta, 145
 ta_alloc, 145
 ua, 146
 ua_alloc, 146
 va, 146
 va_alloc, 146
 _braid_GridClean
 _braid.h, 167
 _braid_GridDestroy
 _braid.h, 167
 _braid_GridElt
 _braid.h, 158
 _braid_GridInit
 _braid.h, 167
 _braid_InitAdjointVars
 adjoint.h, 173
 _braid_InitGuess
 _braid.h, 167
 _braid_InitHierarchy
 _braid.h, 168
 _braid_IsCPoint
 _braid.h, 159
 _braid_IsFPoint
 _braid.h, 159
 _braid_MapCoarseToFine
 _braid.h, 159
 _braid_MapFineToCoarse
 _braid.h, 159
 _braid_MapPeriodic
 _braid.h, 159
 _braid_Max
 util.h, 203
 _braid_NextCPoint
 _braid.h, 160
 _braid_ObjectiveStatusInit
 status.h, 198
 _braid_ObjectiveStatus_struct
 status, 150
 _braid_OptimDestroy
 adjoint.h, 173
 _braid_Optimization_struct
 adjoints, 151
 f_bar, 151
 objective, 151
 request, 152
 rnorm, 152
 rnorm0, 152
 rnorm0_adj, 152
 rnorm_adj, 152
 rtol_adj, 152
 sendbuffer, 152
 sum_user_obj, 152

- tapeinput, 153
- tol_adj, 153
- tstart_obj, 153
- tstop_obj, 153
- _braid_ParFprintfFlush
 - util.h, 204
- _braid_PrintSpatialNorms
 - _braid.h, 168
- _braid_PriorCPoint
 - _braid.h, 160
- _braid_ProjectInterval
 - util.h, 204
- _braid_RecvIndexNull
 - _braid.h, 160
- _braid_Refine
 - _braid.h, 168
- _braid_RefineBasic
 - _braid.h, 168
- _braid_Residual
 - _braid.h, 168
- _braid_SendIndexNull
 - _braid.h, 160
- _braid_SetFullRNorm
 - _braid.h, 169
- _braid_SetRNorm
 - _braid.h, 169
- _braid_SetRNormAdjoint
 - adjoint.h, 173
- _braid_SetVerbosity
 - util.h, 204
- _braid_Status, 146
- _braid_StatusDestroy
 - status.h, 198
- _braid_StatusElt
 - status.h, 196
- _braid_Status_struct
 - core, 147
- _braid_Step
 - _braid.h, 169
- _braid_StepStatusInit
 - status.h, 198
- _braid_StepStatus_struct
 - status, 154
- _braid_Sync
 - _braid.h, 169
- _braid_SyncStatusInit
 - status.h, 199
- _braid_SyncStatus_struct
 - status, 154
- _braid_TAlloc
 - _braid.h, 161
- _braid_TFree
 - _braid.h, 161
- _braid_TReAlloc
 - _braid.h, 161
- _braid_Tape, 147
 - data_ptr, 147
 - next, 147
 - size, 147
- _braid_TapeDisplayBackwards
 - tape.h, 201
- _braid_TapeEvaluate
 - tape.h, 201
- _braid_TapeGetSize
 - tape.h, 201
- _braid_TapeInit
 - tape.h, 201
- _braid_TapeIsEmpty
 - tape.h, 202
- _braid_TapePop
 - tape.h, 202
- _braid_TapePush
 - tape.h, 202
- _braid_TapeResetInput
 - tape.h, 202
- _braid_TapeSetSeed
 - tape.h, 202
- _braid_UCommInit
 - _braid.h, 169
- _braid_UCommInitF
 - _braid.h, 170
- _braid_UCommInitBasic
 - _braid.h, 170
- _braid_UCommWait
 - _braid.h, 170
- _braid_UGetIndex
 - _braid.h, 170
- _braid_UGetVector
 - _braid.h, 170
- _braid_UGetVectorRef
 - _braid.h, 171
- _braid_USetVector
 - _braid.h, 171
- _braid_USetVectorRef
 - _braid.h, 171
- _braid_UpdateAdjoint
 - adjoint.h, 173
- _braid_VectorBarCopy
 - adjoint.h, 173
- _braid_VectorBarDelete
 - adjoint.h, 174
- _braid_VectorBar_struct
 - useCount, 155
 - userVector, 155
- _braid_error_flag
 - _braid.h, 171
- _braid_isnan
 - _braid.h, 159

- `_braid_max`
- `_braid.h`, 160
- `_braid_min`
- `_braid.h`, 160
- `_braid_printf`
- `util.h`, 204
- `_braid_printfile`
- `_braid.h`, 172
- `ACCESSOR_HEADER_GET1`
- `braid_status.h`, 192
- `ACCESSOR_HEADER_GET1_IN3`
- `braid_status.h`, 193
- `ACCESSOR_HEADER_GET2`
- `braid_status.h`, 193
- `ACCESSOR_HEADER_GET2_IN1`
- `braid_status.h`, 193
- `ACCESSOR_HEADER_GET3`
- `braid_status.h`, 193
- `ACCESSOR_HEADER_GET4`
- `braid_status.h`, 193
- `ACCESSOR_HEADER_GET5`
- `braid_status.h`, 194
- `ACCESSOR_HEADER_SET1`
- `braid_status.h`, 194
- `access`
- `_braid_Core`, 129
- `access_level`
- `_braid_Core`, 129
- `actionTape`
- `_braid_Core`, 129
- `adjoint`
- `_braid_Core`, 129
- `adjoint.h`, 172
- `_braid_AddToObjective`, 172
- `_braid_AdjointFeatureCheck`, 172
- `_braid_EvalObjective`, 173
- `_braid_EvalObjective_diff`, 173
- `_braid_InitAdjointVars`, 173
- `_braid_OptimDestroy`, 173
- `_braid_SetRNormAdjoint`, 173
- `_braid_UpdateAdjoint`, 173
- `_braid_VectorBarCopy`, 173
- `_braid_VectorBarDelete`, 174
- `adjoints`
- `_braid_Optimization_struct`, 151
- `app`
- `_braid_Core`, 129
- `bar`
- `_braid_BaseVector_struct`, 149
- `barTape`
- `_braid_Core`, 130
- `base.h`, 174
- `_braid_BaseAccess`, 175
- `_braid_BaseBufPack`, 175
- `_braid_BaseBufPack_diff`, 176
- `_braid_BaseBufSize`, 176
- `_braid_BaseBufUnpack`, 177
- `_braid_BaseBufUnpack_diff`, 177
- `_braid_BaseClone`, 177
- `_braid_BaseClone_diff`, 178
- `_braid_BaseFree`, 178
- `_braid_BaseFullResidual`, 178
- `_braid_BaseInit`, 179
- `_braid_BaseInit_diff`, 179
- `_braid_BaseObjectiveT`, 180
- `_braid_BaseObjectiveT_diff`, 180
- `_braid_BaseResidual`, 180
- `_braid_BaseSClone`, 181
- `_braid_BaseSCoarsen`, 181
- `_braid_BaseSFree`, 182
- `_braid_BaseSInit`, 182
- `_braid_BaseSRefine`, 183
- `_braid_BaseSpatialNorm`, 182
- `_braid_BaseStep`, 183
- `_braid_BaseStep_diff`, 184
- `_braid_BaseSum`, 184
- `_braid_BaseSum_diff`, 184
- `_braid_BaseSync`, 185
- `_braid_BaseTimeGrid`, 185
- `braid.h`, 186
- `braid_ASCaller_Drive_TopCycle`
- XBraid status macros, 114
- `braid_ASCaller_FAccess`
- XBraid status macros, 114
- `braid_ASCaller_FInterp`
- XBraid status macros, 114
- `braid_ASCaller_FRefine`
- XBraid status macros, 114
- `braid_ASCaller_FRefine_AfterInitHier`
- XBraid status macros, 114
- `braid_ASCaller_FRestrict`
- XBraid status macros, 114
- `braid_AccessStatus`, 148
- `braid_AccessStatusGetCallingFunction`
- Inherited XBraid status routines, 103
- `braid_AccessStatusGetDone`
- Inherited XBraid status routines, 103
- `braid_AccessStatusGetIter`
- Inherited XBraid status routines, 103
- `braid_AccessStatusGetLevel`
- Inherited XBraid status routines, 104
- `braid_AccessStatusGetNLevels`
- Inherited XBraid status routines, 104
- `braid_AccessStatusGetNRefine`
- Inherited XBraid status routines, 104
- `braid_AccessStatusGetNTPoints`
- Inherited XBraid status routines, 104

- braided_AccessStatusGetResidual
 - Inherited XBraid status routines, [104](#)
- braided_AccessStatusGetSingleErrorEstAccess
 - Inherited XBraid status routines, [104](#)
- braided_AccessStatusGetTILD
 - Inherited XBraid status routines, [105](#)
- braided_AccessStatusGetTIndex
 - Inherited XBraid status routines, [105](#)
- braided_AccessStatusGetWrapperTest
 - Inherited XBraid status routines, [105](#)
- braided_AccessStatusGetT
 - Inherited XBraid status routines, [105](#)
- braided_App
 - User-written routines, [55](#)
- braided_BaseVector, [148](#)
- braided_BufferStatus, [149](#)
- braided_BufferStatusGetMessageType
 - Inherited XBraid status routines, [105](#)
- braided_BufferStatusSetSize
 - Inherited XBraid status routines, [105](#)
- braided_CoarsenRefStatus, [150](#)
- braided_CoarsenRefStatusGetCTprior
 - Inherited XBraid status routines, [106](#)
- braided_CoarsenRefStatusGetCTstop
 - Inherited XBraid status routines, [106](#)
- braided_CoarsenRefStatusGetFTprior
 - Inherited XBraid status routines, [106](#)
- braided_CoarsenRefStatusGetFTstop
 - Inherited XBraid status routines, [106](#)
- braided_CoarsenRefStatusGetIter
 - Inherited XBraid status routines, [106](#)
- braided_CoarsenRefStatusGetLevel
 - Inherited XBraid status routines, [106](#)
- braided_CoarsenRefStatusGetNLevels
 - Inherited XBraid status routines, [107](#)
- braided_CoarsenRefStatusGetNRefine
 - Inherited XBraid status routines, [107](#)
- braided_CoarsenRefStatusGetNTPoints
 - Inherited XBraid status routines, [107](#)
- braided_CoarsenRefStatusGetTIndex
 - Inherited XBraid status routines, [107](#)
- braided_CoarsenRefStatusGetTpriorTstop
 - Inherited XBraid status routines, [107](#)
- braided_CoarsenRefStatusGetT
 - Inherited XBraid status routines, [107](#)
- braided_Core
 - General Interface routines, [64](#)
- braided_Destroy
 - General Interface routines, [64](#)
- braided_Drive
 - General Interface routines, [65](#)
- braided_ERROR_ARG
 - Error Codes, [54](#)
- braided_ERROR_GENERIC
 - Error Codes, [54](#)
- braided_ERROR_MEMORY
 - Error Codes, [54](#)
- braided_FMANGLE
 - Fortran 90 interface options, [53](#)
- braided_Fortran_Residual
 - Fortran 90 interface options, [53](#)
- braided_Fortran_SpatialCoarsen
 - Fortran 90 interface options, [53](#)
- braided_Fortran_Sync
 - Fortran 90 interface options, [53](#)
- braided_Fortran_TimeGrid
 - Fortran 90 interface options, [53](#)
- braided_GetMyID
 - General Interface routines, [65](#)
- braided_GetNLevels
 - General Interface routines, [65](#)
- braided_GetNumIter
 - General Interface routines, [66](#)
- braided_GetObjective
 - Interface routines for XBraid_Adjoint, [82](#)
- braided_GetRNormAdjoint
 - Interface routines for XBraid_Adjoint, [82](#)
- braided_GetRNorms
 - General Interface routines, [66](#)
- braided_GetSpatialAccuracy
 - General Interface routines, [66](#)
- braided_INVALID_RNORM
 - Error Codes, [54](#)
- braided_Init
 - General Interface routines, [67](#)
- braided_InitAdjoint
 - Interface routines for XBraid_Adjoint, [83](#)
- braided_Int
 - braided_defs.h, [189](#)
- braided_Int_Max
 - braided_defs.h, [188](#)
- braided_Int_Min
 - braided_defs.h, [189](#)
- braided_MPI_INT
 - braided_defs.h, [189](#)
- braided_MPI_REAL
 - braided_defs.h, [189](#)
- braided_ObjectiveStatus, [150](#)
- braided_ObjectiveStatusGetIter
 - Inherited XBraid status routines, [108](#)
- braided_ObjectiveStatusGetLevel
 - Inherited XBraid status routines, [108](#)
- braided_ObjectiveStatusGetNLevels
 - Inherited XBraid status routines, [108](#)
- braided_ObjectiveStatusGetNRefine
 - Inherited XBraid status routines, [108](#)
- braided_ObjectiveStatusGetNTPoints
 - Inherited XBraid status routines, [108](#)

- braid_ObjectiveStatusGetTIndex
 - Inherited XBraid status routines, [109](#)
- braid_ObjectiveStatusGetTol
 - Inherited XBraid status routines, [109](#)
- braid_ObjectiveStatusGetT
 - Inherited XBraid status routines, [108](#)
- braid_Optim, [151](#)
- braid_PrintStats
 - General Interface routines, [68](#)
- braid_PtFcnAccess
 - User-written routines, [56](#)
- braid_PtFcnBufPack
 - User-written routines, [56](#)
- braid_PtFcnBufSize
 - User-written routines, [56](#)
- braid_PtFcnBufUnpack
 - User-written routines, [56](#)
- braid_PtFcnClone
 - User-written routines, [56](#)
- braid_PtFcnFree
 - User-written routines, [57](#)
- braid_PtFcnInit
 - User-written routines, [57](#)
- braid_PtFcnObjectiveTDiff
 - User-written routines for XBraid_Adjoint, [60](#)
- braid_PtFcnObjectiveT
 - User-written routines for XBraid_Adjoint, [60](#)
- braid_PtFcnPostprocessObjective
 - User-written routines for XBraid_Adjoint, [60](#)
- braid_PtFcnPostprocessObjective_diff
 - User-written routines for XBraid_Adjoint, [61](#)
- braid_PtFcnResetGradient
 - User-written routines for XBraid_Adjoint, [61](#)
- braid_PtFcnResidual
 - User-written routines, [57](#)
- braid_PtFcnSClone
 - User-written routines, [57](#)
- braid_PtFcnSCoarsen
 - User-written routines, [57](#)
- braid_PtFcnSFree
 - User-written routines, [57](#)
- braid_PtFcnSInit
 - User-written routines, [58](#)
- braid_PtFcnSRefine
 - User-written routines, [58](#)
- braid_PtFcnSpatialNorm
 - User-written routines, [58](#)
- braid_PtFcnStep
 - User-written routines, [58](#)
- braid_PtFcnStepDiff
 - User-written routines for XBraid_Adjoint, [61](#)
- braid_PtFcnSum
 - User-written routines, [58](#)
- braid_PtFcnSync
 - User-written routines, [59](#)
- braid_PtFcnTimeGrid
 - User-written routines, [59](#)
- braid_RAND_MAX
 - General Interface routines, [64](#)
- braid_Rand
 - General Interface routines, [68](#)
- braid_Real
 - braid_defs.h, [189](#)
- braid_SetAbsTol
 - General Interface routines, [68](#)
- braid_SetAbsTolAdjoint
 - Interface routines for XBraid_Adjoint, [83](#)
- braid_SetAccessLevel
 - General Interface routines, [70](#)
- braid_SetCFactor
 - General Interface routines, [70](#)
- braid_SetCRelaxWt
 - General Interface routines, [71](#)
- braid_SetDefaultPrintFile
 - General Interface routines, [71](#)
- braid_SetFMG
 - General Interface routines, [72](#)
- braid_SetFileIOLevel
 - General Interface routines, [71](#)
- braid_SetFullIRNormRes
 - General Interface routines, [72](#)
- braid_SetIncrMaxLevels
 - General Interface routines, [72](#)
- braid_SetMaxIter
 - General Interface routines, [72](#)
- braid_SetMaxLevels
 - General Interface routines, [73](#)
- braid_SetMaxRefinements
 - General Interface routines, [73](#)
- braid_SetMinCoarse
 - General Interface routines, [73](#)
- braid_SetNFMGVcyc
 - General Interface routines, [74](#)
- braid_SetNFMG
 - General Interface routines, [74](#)
- braid_SetNRelax
 - General Interface routines, [74](#)
- braid_SetObjectiveOnly
 - Interface routines for XBraid_Adjoint, [84](#)
- braid_SetPeriodic
 - General Interface routines, [75](#)
- braid_SetPostprocessObjective
 - Interface routines for XBraid_Adjoint, [84](#)
- braid_SetPostprocessObjective_diff
 - Interface routines for XBraid_Adjoint, [84](#)
- braid_SetPrintFile
 - General Interface routines, [75](#)
- braid_SetPrintLevel

- General Interface routines, 75
- braid_SetRefine
 - General Interface routines, 76
- braid_SetRelTol
 - General Interface routines, 76
- braid_SetRelTolAdjoint
 - Interface routines for XBraid_Adjoint, 85
- braid_SetResidual
 - General Interface routines, 76
- braid_SetRichardsonEstimation
 - Interface routines for XBraid_Adjoint, 85
- braid_SetSeqSoln
 - General Interface routines, 77
- braid_SetShell
 - General Interface routines, 77
- braid_SetSkip
 - General Interface routines, 78
- braid_SetSpatialCoarsen
 - General Interface routines, 78
- braid_SetSpatialRefine
 - General Interface routines, 78
- braid_SetStorage
 - General Interface routines, 79
- braid_SetSync
 - General Interface routines, 79
- braid_SetTPointsCutoff
 - General Interface routines, 80
- braid_SetTStartObjective
 - Interface routines for XBraid_Adjoint, 85
- braid_SetTStopObjective
 - Interface routines for XBraid_Adjoint, 86
- braid_SetTemporalNorm
 - General Interface routines, 79
- braid_SetTimeGrid
 - General Interface routines, 80
- braid_SplitCommworld
 - General Interface routines, 81
- braid_StatusGetAllErrorEst
 - XBraid status routines, 89
- braid_StatusGetCTprior
 - XBraid status routines, 89
- braid_StatusGetCTstop
 - XBraid status routines, 90
- braid_StatusGetCallingFunction
 - XBraid status routines, 89
- braid_StatusGetDone
 - XBraid status routines, 90
- braid_StatusGetFTprior
 - XBraid status routines, 90
- braid_StatusGetFTstop
 - XBraid status routines, 91
- braid_StatusGetIter
 - XBraid status routines, 91
- braid_StatusGetLevel
 - XBraid status routines, 91
- braid_StatusGetMessageType
 - XBraid status routines, 92
- braid_StatusGetNLevels
 - XBraid status routines, 92
- braid_StatusGetNRefine
 - XBraid status routines, 92
- braid_StatusGetNTPoints
 - XBraid status routines, 93
- braid_StatusGetNumErrorEst
 - XBraid status routines, 93
- braid_StatusGetOldFineTolx
 - XBraid status routines, 93
- braid_StatusGetRNorms
 - XBraid status routines, 94
- braid_StatusGetResidual
 - XBraid status routines, 94
- braid_StatusGetSingleErrorEstAccess
 - XBraid status routines, 94
- braid_StatusGetSingleErrorEstStep
 - XBraid status routines, 95
- braid_StatusGetTILD
 - XBraid status routines, 95
- braid_StatusGetTIUL
 - XBraid status routines, 97
- braid_StatusGetTIndex
 - XBraid status routines, 96
- braid_StatusGetTimeValues
 - XBraid status routines, 96
- braid_StatusGetTol
 - XBraid status routines, 97
- braid_StatusGetTpriorTstop
 - XBraid status routines, 98
- braid_StatusGetTstartTstop
 - XBraid status routines, 98
- braid_StatusGetTstop
 - XBraid status routines, 98
- braid_StatusGetWrapperTest
 - XBraid status routines, 99
- braid_StatusGetT
 - XBraid status routines, 95
- braid_StatusSetOldFineTolx
 - XBraid status routines, 99
- braid_StatusSetRFactor
 - XBraid status routines, 100
- braid_StatusSetRSpace
 - XBraid status routines, 100
- braid_StatusSetRefinementDtValues
 - XBraid status routines, 99
- braid_StatusSetSize
 - XBraid status routines, 101
- braid_StatusSetTightFineTolx
 - XBraid status routines, 101
- braid_StepStatus, 153

- braid_StepStatusGetIter
 - Inherited XBraid status routines, [109](#)
- braid_StepStatusGetLevel
 - Inherited XBraid status routines, [109](#)
- braid_StepStatusGetNLevels
 - Inherited XBraid status routines, [109](#)
- braid_StepStatusGetNRefine
 - Inherited XBraid status routines, [109](#)
- braid_StepStatusGetNTPoints
 - Inherited XBraid status routines, [110](#)
- braid_StepStatusGetOldFineTolx
 - Inherited XBraid status routines, [110](#)
- braid_StepStatusGetRNorms
 - Inherited XBraid status routines, [110](#)
- braid_StepStatusGetSingleErrorEstStep
 - Inherited XBraid status routines, [110](#)
- braid_StepStatusGetTIndex
 - Inherited XBraid status routines, [110](#)
- braid_StepStatusGetTol
 - Inherited XBraid status routines, [111](#)
- braid_StepStatusGetTstartTstop
 - Inherited XBraid status routines, [111](#)
- braid_StepStatusGetTstop
 - Inherited XBraid status routines, [111](#)
- braid_StepStatusGetT
 - Inherited XBraid status routines, [110](#)
- braid_StepStatusSetOldFineTolx
 - Inherited XBraid status routines, [111](#)
- braid_StepStatusSetRFactor
 - Inherited XBraid status routines, [111](#)
- braid_StepStatusSetRSpace
 - Inherited XBraid status routines, [111](#)
- braid_StepStatusSetTightFineTolx
 - Inherited XBraid status routines, [112](#)
- braid_SyncStatus, [154](#)
- braid_SyncStatusGetAllErrorEst
 - Inherited XBraid status routines, [112](#)
- braid_SyncStatusGetCallingFunction
 - Inherited XBraid status routines, [112](#)
- braid_SyncStatusGetDone
 - Inherited XBraid status routines, [112](#)
- braid_SyncStatusGetIter
 - Inherited XBraid status routines, [112](#)
- braid_SyncStatusGetLevel
 - Inherited XBraid status routines, [112](#)
- braid_SyncStatusGetNLevels
 - Inherited XBraid status routines, [113](#)
- braid_SyncStatusGetNRefine
 - Inherited XBraid status routines, [113](#)
- braid_SyncStatusGetNTPoints
 - Inherited XBraid status routines, [113](#)
- braid_SyncStatusGetNumErrorEst
 - Inherited XBraid status routines, [113](#)
- braid_SyncStatusGetTIUL
 - Inherited XBraid status routines, [113](#)
- braid_TestAll
 - XBraid test routines, [115](#)
- braid_TestBuf
 - XBraid test routines, [116](#)
- braid_TestClone
 - XBraid test routines, [117](#)
- braid_TestCoarsenRefine
 - XBraid test routines, [118](#)
- braid_TestInitAccess
 - XBraid test routines, [119](#)
- braid_TestResidual
 - XBraid test routines, [119](#)
- braid_TestSpatialNorm
 - XBraid test routines, [120](#)
- braid_TestSum
 - XBraid test routines, [121](#)
- braid_Vector
 - User-written routines, [59](#)
- braid_VectorBar, [154](#)
- braid_WriteConvHistory
 - General Interface routines, [81](#)
- braid_defs.h, [188](#)
 - braid_Int, [189](#)
 - braid_Int_Max, [188](#)
 - braid_Int_Min, [189](#)
 - braid_MPI_INT, [189](#)
 - braid_MPI_REAL, [189](#)
 - braid_Real, [189](#)
- braid_iter
 - _braid_Action, [123](#)
- braid_status.h, [190](#)
 - ACCESSOR_HEADER_GET1, [192](#)
 - ACCESSOR_HEADER_GET1_IN3, [193](#)
 - ACCESSOR_HEADER_GET2, [193](#)
 - ACCESSOR_HEADER_GET2_IN1, [193](#)
 - ACCESSOR_HEADER_GET3, [193](#)
 - ACCESSOR_HEADER_GET4, [193](#)
 - ACCESSOR_HEADER_GET5, [194](#)
 - ACCESSOR_HEADER_SET1, [194](#)
- braid_test.h, [194](#)
- braidCall
 - _braid_Action, [123](#)
- buffer
 - _braid_CommHandle, [126](#)
- bufpack
 - _braid_Core, [130](#)
- bufsize
 - _braid_Core, [130](#)
- bufunpack
 - _braid_Core, [130](#)

- c_tprior
 - _braid_Core, 130
- c_tstop
 - _braid_Core, 130
- CWt_default
 - _braid_Core, 131
- CWts
 - _braid_Core, 131
- calling_function
 - _braid_Core, 130
- cfactor
 - _braid_Grid, 143
- cfactors
 - _braid_Core, 130
- cfdefault
 - _braid_Core, 131
- clone
 - _braid_Core, 131
- clower
 - _braid_Grid, 144
- comm
 - _braid_Core, 131
- comm_world
 - _braid_Core, 131
- core
 - _braid_Action, 123
 - _braid_Status_struct, 147
- cupper
 - _braid_Grid, 144
- data_ptr
 - _braid_Tape, 147
- done
 - _braid_Core, 131
- dtk
 - _braid_Core, 131
- Error Codes, 54
 - braid_ERROR_ARG, 54
 - braid_ERROR_GENERIC, 54
 - braid_ERROR_MEMORY, 54
 - braid_INVALID_RNORM, 54
- est_error
 - _braid_Core, 132
- estimate
 - _braid_Core, 132
- f_bar
 - _braid_Optimization_struct, 151
- f_tprior
 - _braid_Core, 132
- f_tstop
 - _braid_Core, 132
- fa
 - _braid_Grid, 144
- fa_alloc
 - _braid_Grid, 144
- fmg
 - _braid_Core, 132
- Fortran 90 interface options, 52
 - braid_FMANGLE, 53
 - braid_Fortran_Residual, 53
 - braid_Fortran_SpatialCoarsen, 53
 - braid_Fortran_Sync, 53
 - braid_Fortran_TimeGrid, 53
- free
 - _braid_Core, 132
- full_rnorm0
 - _braid_Core, 132
- full_rnorm_res
 - _braid_Core, 132
- full_rnorms
 - _braid_Core, 133
- General Interface routines, 63
 - braid_Core, 64
 - braid_Destroy, 64
 - braid_Drive, 65
 - braid_GetMyID, 65
 - braid_GetNLevels, 65
 - braid_GetNumIter, 66
 - braid_GetRNorms, 66
 - braid_GetSpatialAccuracy, 66
 - braid_Init, 67
 - braid_PrintStats, 68
 - braid_RAND_MAX, 64
 - braid_Rand, 68
 - braid_SetAbsTol, 68
 - braid_SetAccessLevel, 70
 - braid_SetCFactor, 70
 - braid_SetCRelaxWt, 71
 - braid_SetDefaultPrintFile, 71
 - braid_SetFMG, 72
 - braid_SetFileIOLevel, 71
 - braid_SetFullRNormRes, 72
 - braid_SetIncrMaxLevels, 72
 - braid_SetMaxIter, 72
 - braid_SetMaxLevels, 73
 - braid_SetMaxRefinements, 73
 - braid_SetMinCoarse, 73
 - braid_SetNFMGVcyc, 74
 - braid_SetNFMG, 74
 - braid_SetNRelax, 74
 - braid_SetPeriodic, 75
 - braid_SetPrintFile, 75
 - braid_SetPrintLevel, 75
 - braid_SetRefine, 76
 - braid_SetRelTol, 76
 - braid_SetResidual, 76

- braid_SetSeqSoln, 77
- braid_SetShell, 77
- braid_SetSkip, 78
- braid_SetSpatialCoarsen, 78
- braid_SetSpatialRefine, 78
- braid_SetStorage, 79
- braid_SetSync, 79
- braid_SetTPointsCutoff, 80
- braid_SetTemporalNorm, 79
- braid_SetTimeGrid, 80
- braid_SplitCommworld, 81
- braid_WriteConvHistory, 81
- globaltime
 - _braid_Core, 133
- grids
 - _braid_Core, 133
- gupper
 - _braid_Action, 124
 - _braid_Core, 133
 - _braid_Grid, 144
- idx
 - _braid_Core, 133
- ilower
 - _braid_Grid, 144
- inTime
 - _braid_Action, 124
- inTimeIdx
 - _braid_Action, 124
- incr_max_levels
 - _braid_Core, 133
- Inherited XBraid status routines, 102
 - braid_AccessStatusGetCallingFunction, 103
 - braid_AccessStatusGetDone, 103
 - braid_AccessStatusGetIter, 103
 - braid_AccessStatusGetLevel, 104
 - braid_AccessStatusGetNLevels, 104
 - braid_AccessStatusGetNRefine, 104
 - braid_AccessStatusGetNTPoints, 104
 - braid_AccessStatusGetResidual, 104
 - braid_AccessStatusGetSingleErrorEstAccess, 104
 - braid_AccessStatusGetTILD, 105
 - braid_AccessStatusGetTIndex, 105
 - braid_AccessStatusGetWrapperTest, 105
 - braid_AccessStatusGetT, 105
 - braid_BufferStatusGetMessageType, 105
 - braid_BufferStatusSetSize, 105
 - braid_CoarsenRefStatusGetCTprior, 106
 - braid_CoarsenRefStatusGetCTstop, 106
 - braid_CoarsenRefStatusGetFTprior, 106
 - braid_CoarsenRefStatusGetFTstop, 106
 - braid_CoarsenRefStatusGetIter, 106
 - braid_CoarsenRefStatusGetLevel, 106
 - braid_CoarsenRefStatusGetNLevels, 107
 - braid_CoarsenRefStatusGetNRefine, 107
 - braid_CoarsenRefStatusGetNTPoints, 107
 - braid_CoarsenRefStatusGetTIndex, 107
 - braid_CoarsenRefStatusGetTpriorTstop, 107
 - braid_CoarsenRefStatusGetT, 107
 - braid_ObjectiveStatusGetIter, 108
 - braid_ObjectiveStatusGetLevel, 108
 - braid_ObjectiveStatusGetNLevels, 108
 - braid_ObjectiveStatusGetNRefine, 108
 - braid_ObjectiveStatusGetNTPoints, 108
 - braid_ObjectiveStatusGetTIndex, 109
 - braid_ObjectiveStatusGetTol, 109
 - braid_ObjectiveStatusGetT, 108
 - braid_StepStatusGetIter, 109
 - braid_StepStatusGetLevel, 109
 - braid_StepStatusGetNLevels, 109
 - braid_StepStatusGetNRefine, 109
 - braid_StepStatusGetNTPoints, 110
 - braid_StepStatusGetOldFineTolx, 110
 - braid_StepStatusGetRNorms, 110
 - braid_StepStatusGetSingleErrorEstStep, 110
 - braid_StepStatusGetTIndex, 110
 - braid_StepStatusGetTol, 111
 - braid_StepStatusGetTstartTstop, 111
 - braid_StepStatusGetTstop, 111
 - braid_StepStatusGetT, 110
 - braid_StepStatusSetOldFineTolx, 111
 - braid_StepStatusSetRFactor, 111
 - braid_StepStatusSetRSpace, 111
 - braid_StepStatusSetTightFineTolx, 112
 - braid_SyncStatusGetAllErrorEst, 112
 - braid_SyncStatusGetCallingFunction, 112
 - braid_SyncStatusGetDone, 112
 - braid_SyncStatusGetIter, 112
 - braid_SyncStatusGetLevel, 112
 - braid_SyncStatusGetNLevels, 113
 - braid_SyncStatusGetNRefine, 113
 - braid_SyncStatusGetNTPoints, 113
 - braid_SyncStatusGetNumErrorEst, 113
 - braid_SyncStatusGetTIUL, 113
 - braid_SyncStatusGetTimeValues, 113
- init
 - _braid_Core, 133
- initiali
 - _braid_Core, 133
- Interface routines for XBraid_Adjoint, 82
 - braid_GetObjective, 82
 - braid_GetRNormAdjoint, 82
 - braid_InitAdjoint, 83
 - braid_SetAbsTolAdjoint, 83
 - braid_SetObjectiveOnly, 84
 - braid_SetPostprocessObjective, 84
 - braid_SetPostprocessObjective_diff, 84
 - braid_SetRelTolAdjoint, 85

braid_SetRichardsonEstimation, 85
 braid_SetTStartObjective, 85
 braid_SetTStopObjective, 86
 io_level
 _braid_Core, 134
 iupper
 _braid_Grid, 144
 level
 _braid_Action, 124
 _braid_Core, 134
 _braid_Grid, 144
 localtime
 _braid_Core, 134
 max_iter
 _braid_Core, 134
 max_levels
 _braid_Core, 134
 max_refinements
 _braid_Core, 134
 messagetype
 _braid_Action, 124
 _braid_Core, 134
 min_coarse
 _braid_Core, 134
 mpistubs.h, 195
 myid
 _braid_Action, 124
 _braid_Core, 135
 myid_world
 _braid_Core, 135
 ncpoints
 _braid_Grid, 145
 next
 _braid_Tape, 147
 nfmfg
 _braid_Core, 135
 nfmfg_Vcyc
 _braid_Core, 135
 niter
 _braid_Core, 135
 nlevels
 _braid_Core, 135
 nrdefault
 _braid_Core, 135
 nrefine
 _braid_Action, 124
 _braid_Core, 135
 nrels
 _braid_Core, 136
 ntime
 _braid_Core, 136
 num_requests
 _braid_CommHandle, 126
 _braid_Grid, 145
 obj_only
 _braid_Core, 136
 objT_diff
 _braid_Core, 136
 objective
 _braid_Optimization_struct, 151
 objectiveT
 _braid_Core, 136
 old_fine_tolx
 _braid_Core, 136
 optim
 _braid_Core, 136
 order
 _braid_Core, 136
 outTime
 _braid_Action, 124
 periodic
 _braid_Core, 137
 postprocess_obj
 _braid_Core, 137
 postprocess_obj_diff
 _braid_Core, 137
 print_level
 _braid_Core, 137
 r_space
 _braid_Core, 137
 rdtvalues
 _braid_Core, 137
 record
 _braid_Core, 137
 recv_handle
 _braid_Grid, 145
 recv_index
 _braid_Grid, 145
 refine
 _braid_Core, 137
 request
 _braid_Optimization_struct, 152
 request_type
 _braid_CommHandle, 126
 requests
 _braid_CommHandle, 126
 reset_gradient
 _braid_Core, 138
 residual
 _braid_Core, 138
 rfactor
 _braid_Core, 138
 rfactors

- [_braid_Core](#), 138
- richardson
 - [_braid_Core](#), 138
- rnorm
 - [_braid_Core](#), 138
 - [_braid_Optimization_struct](#), 152
- rnorm0
 - [_braid_Core](#), 138
 - [_braid_Optimization_struct](#), 152
- rnorm0_adj
 - [_braid_Optimization_struct](#), 152
- rnorm_adj
 - [_braid_Optimization_struct](#), 152
- rnorms
 - [_braid_Core](#), 138
- rstopped
 - [_braid_Core](#), 139
- rtol
 - [_braid_Core](#), 139
- rtol_adj
 - [_braid_Optimization_struct](#), 152
- sclone
 - [_braid_Core](#), 139
- scoarsen
 - [_braid_Core](#), 139
- send_handle
 - [_braid_Grid](#), 145
- send_index
 - [_braid_Grid](#), 145
- send_recv_rank
 - [_braid_Action](#), 125
 - [_braid_Core](#), 139
- sendbuffer
 - [_braid_Optimization_struct](#), 152
- seq_soln
 - [_braid_Core](#), 139
- sfree
 - [_braid_Core](#), 139
- sinit
 - [_braid_Core](#), 139
- size
 - [_braid_Tape](#), 147
- size_buffer
 - [_braid_Action](#), 125
 - [_braid_Core](#), 140
- skip
 - [_braid_Core](#), 140
- spatialnorm
 - [_braid_Core](#), 140
- srefine
 - [_braid_Core](#), 140
- status
 - [_braid_AccessStatus_struct](#), 148
 - [_braid_BufferStatus_struct](#), 149
 - [_braid_CoarsenRefStatus_struct](#), 150
 - [_braid_CommHandle](#), 126
 - [_braid_ObjectiveStatus_struct](#), 150
 - [_braid_StepStatus_struct](#), 154
 - [_braid_SyncStatus_struct](#), 154
- status.h, 195
 - [_braid_AccessStatusInit](#), 196
 - [_braid_BufferStatusInit](#), 197
 - [_braid_CoarsenRefStatusInit](#), 197
 - [_braid_ObjectiveStatusInit](#), 198
 - [_braid_StatusDestroy](#), 198
 - [_braid_StatusElt](#), 196
 - [_braid_StepStatusInit](#), 198
 - [_braid_SyncStatusInit](#), 199
- step
 - [_braid_Core](#), 140
- step_diff
 - [_braid_Core](#), 140
- storage
 - [_braid_Core](#), 140
- sum
 - [_braid_Core](#), 140
- sum_alpha
 - [_braid_Action](#), 125
- sum_beta
 - [_braid_Action](#), 125
- sum_user_obj
 - [_braid_Optimization_struct](#), 152
- sync
 - [_braid_Core](#), 141
- t
 - [_braid_Core](#), 141
- ta
 - [_braid_Grid](#), 145
- ta_alloc
 - [_braid_Grid](#), 145
- tape.h, 199
 - [_braid_Call](#), 200
 - [_braid_CallGetName](#), 201
 - [_braid_DiffCall](#), 201
 - [_braid_TapeDisplayBackwards](#), 201
 - [_braid_TapeEvaluate](#), 201
 - [_braid_TapeGetSize](#), 201
 - [_braid_TapeInit](#), 201
 - [_braid_TapeIsEmpty](#), 202
 - [_braid_TapePop](#), 202
 - [_braid_TapePush](#), 202
 - [_braid_TapeResetInput](#), 202
 - [_braid_TapeSetSeed](#), 202
- tapeinput
 - [_braid_Optimization_struct](#), 153
- tgrid

- _braid_Core, 141
- tight_fine_tolx
 - _braid_Core, 141
- tnext
 - _braid_Core, 141
- tnorm
 - _braid_Core, 141
- tnorm_a
 - _braid_Core, 141
- tol
 - _braid_Action, 125
 - _braid_Core, 141
- tol_adj
 - _braid_Optimization_struct, 153
- tpoints_cutoff
 - _braid_Core, 142
- tstart
 - _braid_Core, 142
- tstart_obj
 - _braid_Optimization_struct, 153
- tstop
 - _braid_Core, 142
- tstop_obj
 - _braid_Optimization_struct, 153
- ua
 - _braid_Grid, 146
- ua_alloc
 - _braid_Grid, 146
- useCount
 - _braid_VectorBar_struct, 155
- User interface routines, 62
- User-written routines, 55
 - braid_App, 55
 - braid_PtFcnAccess, 56
 - braid_PtFcnBufPack, 56
 - braid_PtFcnBufSize, 56
 - braid_PtFcnBufUnpack, 56
 - braid_PtFcnClone, 56
 - braid_PtFcnFree, 57
 - braid_PtFcnInit, 57
 - braid_PtFcnResidual, 57
 - braid_PtFcnSClone, 57
 - braid_PtFcnSCoarsen, 57
 - braid_PtFcnSFree, 57
 - braid_PtFcnSInit, 58
 - braid_PtFcnSRefine, 58
 - braid_PtFcnSpatialNorm, 58
 - braid_PtFcnStep, 58
 - braid_PtFcnSum, 58
 - braid_PtFcnSync, 59
 - braid_PtFcnTimeGrid, 59
 - braid_Vector, 59
- User-written routines for XBraid_Adjoint, 60
 - braid_PtFcnObjectiveTDiff, 60
 - braid_PtFcnObjectiveT, 60
 - braid_PtFcnPostprocessObjective, 60
 - braid_PtFcnPostprocessObjective_diff, 61
 - braid_PtFcnResetGradient, 61
 - braid_PtFcnStepDiff, 61
- userVector
 - _braid_BaseVector_struct, 149
 - _braid_VectorBar_struct, 155
- userVectorTape
 - _braid_Core, 142
- useshell
 - _braid_Core, 142
- util.h, 203
 - _braid_GetInterval, 203
 - _braid_GetNEntries, 203
 - _braid_Max, 203
 - _braid_ParFprintfFlush, 204
 - _braid_ProjectInterval, 204
 - _braid_SetVerbosity, 204
 - _braid_printf, 204
- va
 - _braid_Grid, 146
- va_alloc
 - _braid_Grid, 146
- vector_ptr
 - _braid_CommHandle, 126
- verbose_adj
 - _braid_Core, 142
- warm_restart
 - _braid_Core, 142
- wrapper_test
 - _braid_Core, 142
- XBraid status macros, 114
 - braid_ASCaller_Drive_TopCycle, 114
 - braid_ASCaller_FAccess, 114
 - braid_ASCaller_FInterp, 114
 - braid_ASCaller_FRefine, 114
 - braid_ASCaller_FRefine_AfterInitHier, 114
 - braid_ASCaller_FRestrict, 114
- XBraid status routines, 88
 - braid_StatusGetAllErrorEst, 89
 - braid_StatusGetCTprior, 89
 - braid_StatusGetCTstop, 90
 - braid_StatusGetCallingFunction, 89
 - braid_StatusGetDone, 90
 - braid_StatusGetFTPrior, 90
 - braid_StatusGetFTstop, 91
 - braid_StatusGetIter, 91
 - braid_StatusGetLevel, 91
 - braid_StatusGetMessageType, 92
 - braid_StatusGetNLevels, 92

- [braid_StatusGetNRefine](#), 92
- [braid_StatusGetNTPoints](#), 93
- [braid_StatusGetNumErrorEst](#), 93
- [braid_StatusGetOldFineTolx](#), 93
- [braid_StatusGetRNorms](#), 94
- [braid_StatusGetResidual](#), 94
- [braid_StatusGetSingleErrorEstAccess](#), 94
- [braid_StatusGetSingleErrorEstStep](#), 95
- [braid_StatusGetTILD](#), 95
- [braid_StatusGetTIUL](#), 97
- [braid_StatusGetTIndex](#), 96
- [braid_StatusGetTimeValues](#), 96
- [braid_StatusGetTol](#), 97
- [braid_StatusGetTpriorTstop](#), 98
- [braid_StatusGetTstartTstop](#), 98
- [braid_StatusGetTstop](#), 98
- [braid_StatusGetWrapperTest](#), 99
- [braid_StatusGetT](#), 95
- [braid_StatusSetOldFineTolx](#), 99
- [braid_StatusSetRFactor](#), 100
- [braid_StatusSetRSpace](#), 100
- [braid_StatusSetRefinementDtValues](#), 99
- [braid_StatusSetSize](#), 101
- [braid_StatusSetTightFineTolx](#), 101

[XBraid status structures](#), 87

[XBraid test routines](#), 115

- [braid_TestAll](#), 115
- [braid_TestBuf](#), 116
- [braid_TestClone](#), 117
- [braid_TestCoarsenRefine](#), 118
- [braid_TestInitAccess](#), 119
- [braid_TestResidual](#), 119
- [braid_TestSpatialNorm](#), 120
- [braid_TestSum](#), 121