

Abstract Locale Operations

ECMA 402

Zibi Braniecki (Mozilla)

Eric Ferraiuolo (Yahoo)

Caridy Patiño (SalesForce)

Intl.getCanonicalLocales(locales)

Usage:

```
Intl.getCanonicalLocales([Symbol.for("foo")]); // throw TypeError  
Intl.getCanonicalLocales(""); // throw RangeError  
Intl.getCanonicalLocales("EN-US"); // ["en-US"]  
Intl.getCanonicalLocales("EN-US", "FR"); // ["en-US", "fr"]  
Intl.getCanonicalLocales(["es-us-miami"]); // ["en-US-Miami"]
```

Note: relies on CanonicalizeLocaleList , which is an existing abstract operation in 402 2nd Edition.

`Intl.getParentLocales(locale)`

"zh-Hant-MO"



"zh-Hant"

"zh-Hant-MO"



"zh-Hant-HK"



"zh-Hant"

Intl.getParentLocales(locale)

Usage:

```
Intl.getParentLocales(null);          // throw SyntaxError  
Intl.getParentLocales("");          // throw RangeError  
Intl.getParentLocales("en-US");      // ["en-US", "en"]  
Intl.getParentLocales("zh-Hant-MO");  // ["zh-Hant-MO", "zh-Hant-HK", "zh-Hant"]
```

Note: will relies on the same abstract operation used by `ResolveLocale` abstract operations in 402 2nd Edition.

Intl.resolveLocaleInfo(locales[, options])

Usage:

```
Intl.resolveLocaleInfo(null);           // throw TypeError
Intl.resolveLocaleInfo("");            // throw RangeError
Intl.resolveLocaleInfo("EN-US");        // { locale: "en-US", direction: "ltr", ... }
Intl.resolveLocaleInfo("ar");           // { locale: "ar", direction: "rtl", ... }
Intl.resolveLocaleInfo("en-US-Miami");   // { locale: "en-US", direction: "ltr", ... }
```

Intl.resolveLocaleInfo(locales[, options])

```
let el = document.getElementById("container");
el.dir = Intl.resolveLocaleInfo(navigator.languages).direction;
```